
PyLops

Dec 21, 2021

Getting started:

1	Terminology	3
2	Implementation	5
3	History	7
	Bibliography	265
	Index	267

This Python library is inspired by the MATLAB [Spot – A Linear-Operator Toolbox](#) project.

Linear operators and inverse problems are at the core of many of the most used algorithms in signal processing, image processing, and remote sensing. When dealing with small-scale problems, the Python numerical scientific libraries [numpy](#) and [scipy](#) allow to perform most of the underlying matrix operations (e.g., computation of matrix-vector products and manipulation of matrices) in a simple and expressive way.

Many useful operators, however, do not lend themselves to an explicit matrix representation when used to solve large-scale problems. PyLops operators, on the other hand, still represent a matrix and can be treated in a similar way, but do not rely on the explicit creation of a dense (or sparse) matrix itself. Conversely, the forward and adjoint operators are represented by small pieces of codes that mimic the effect of the matrix on a vector or another matrix.

Luckily, many iterative methods (e.g. `cg`, `lsqr`) do not need to know the individual entries of a matrix to solve a linear system. Such solvers only require the computation of forward and adjoint matrix-vector products as done for any of the PyLops operators.

Here is a simple example showing how a dense first-order first derivative operator can be created, applied and inverted using `numpy/scipy` commands:

```
import numpy as np
from scipy.linalg import lstsq

nx = 7
x = np.arange(nx) - (nx-1)/2

D = np.diag(0.5*np.ones(nx-1), k=1) - \
    np.diag(0.5*np.ones(nx-1), k=-1)
D[0] = D[-1] = 0 # take away edge effects

# y = Dx
y = np.dot(D, x)
# x = D'y
xadj = np.dot(D.T, y)
# xinv = D^-1 y
xinv = lstsq(D, y)[0]
```

and similarly using PyLops commands:

```
from pylops import FirstDerivative

nx = 7
x = range(-(nx // 2), nx // 2 + (1 if nx % 2 else 0))

Dlop = FirstDerivative(nx, dtype='float64')

# y = Dx
y = Dlop*x
# x = D'y
xadj = Dlop.H*y
# xinv = D^-1 y
xinv = Dlop / y
```

Note how this second approach does not require creating a dense matrix, reducing both the memory load and the computational cost of applying a derivative to an input vector `x`. Moreover, the code becomes even more compact and expressive than in the previous case letting the user focus on the formulation of equations of the forward problem to be solved by inversion.

CHAPTER 1

Terminology

A common *terminology* is used within the entire documentation of PyLops. Every linear operator and its application to a model will be referred to as **forward model (or operation)**

$$\mathbf{y} = \mathbf{A}\mathbf{x}$$

while its application to a data is referred to as **adjoint modelling (or operation)**

$$\mathbf{x} = \mathbf{A}^H \mathbf{y}$$

where \mathbf{x} is called *model* and \mathbf{y} is called *data*. The *operator* $\mathbf{A} : \mathbb{F}^m \rightarrow \mathbb{F}^n$ effectively maps a vector of size m in the *model space* to a vector of size n in the *data space*, conversely the *adjoint operator* $\mathbf{A}^H : \mathbb{F}^n \rightarrow \mathbb{F}^m$ maps a vector of size n in the *data space* to a vector of size m in the *model space*. As linear operators mimics the effect a matrix on a vector we can also loosely refer to m as the number of *columns* and n as the number of *rows* of the operator.

Ultimately, solving an inverse problems accounts to removing the effect of \mathbf{A} from the data \mathbf{y} to retrieve the model \mathbf{x} .

For a more detailed description of the concepts of linear operators, adjoints and inverse problems in general, you can head over to one of Jon Claerbout's books such as [Basic Earth Imaging](#).

Implementation

PyLops is build on top of the `scipy` class `scipy.sparse.linalg.LinearOperator`.

This class allows in fact for the creation of objects (or interfaces) for matrix-vector and matrix-matrix products that can ultimately be used to solve any inverse problem of the form $\mathbf{y} = \mathbf{Ax}$.

As explained in the `scipy LinearOperator` official documentation, to construct a `scipy.sparse.linalg.LinearOperator`, a user is required to pass appropriate callables to the constructor of this class, or subclass it. More specifically one of the methods `_matvec` and `_matmat` must be implemented for the *forward operator* and one of the methods `_rmatvec` or `_adjoint` may be implemented to apply the *Hermitian adjoint*. The attributes/properties `shape` (pair of integers) and `dtype` (may be None) must also be provided during `__init__` of this class.

Any linear operator developed within the PyLops library follows this philosophy. As explained more in details in *Implementing new operators* section, a linear operator is created by subclassing the `scipy.sparse.linalg.LinearOperator` class and `_matvec` and `_rmatvec` are implemented.

PyLops was initially written by [Equinor](#). It is a flexible and scalable python library for large-scale optimization with linear operators that can be tailored to our needs, and as contribution to the free software community. Since June 2021, PyLops is a [NUMFOCUS](#) Affiliated Project.

3.1 Installation

The PyLops project strives to create a library that is easy to install in any environment and has a very limited number of dependencies. However, since *Python2* will retire soon, we have decided to only focus on a *Python3* implementation. If you are still using *Python2*, hurry up!

For this reason you will need **Python 3.6 or greater** to get started.

3.1.1 Dependencies

Our mandatory dependencies are limited to:

- [numpy](#)
- [scipy](#)

We advise using the [Anaconda Python distribution](#) to ensure that these dependencies are installed via the `Conda` package manager. This is not just a pure stylistic choice but comes with some *hidden* advantages, such as the linking to `Intel MKL` library (i.e., a highly optimized BLAS library created by Intel).

If you simply want to use PyLops for teaching purposes or for small-scale examples, this should not really affect you. However, if you are interested in getting better code performance, read carefully the [Advanced installation](#) page.

3.1.2 Optional dependencies

PyLops's optional dependencies refer to those dependencies that we do not include in our `requirements.txt` and `environment.yml` files and thus are not strictly needed nor installed directly as part of a standar installation (see

below for details)

However, we sometimes implement additional back-ends (referred to as `engine` in the code) for some of our operators in order to improve their performance. To do so, we rely on third-party libraries. Those libraries are generally added to the list of our optional dependencies. If you are not after code performance, you may simply stick to the mandatory dependencies and `pylops` will ensure to always fallback to one of those for any linear operator.

If you are instead after code performance, take a look at the *Optional dependencies* section in the [Advanced installation](#) page.

3.1.3 Step-by-step installation for users

Python environment

Activate your Python environment, and simply type the following command in your terminal to install the PyPi distribution:

```
>> pip install pylops
```

If using Conda, you can also install our conda-forge distribution via:

```
>> conda install -c conda-forge pylops
```

Note that using the `conda-forge` distribution is recommended as all the dependencies (both mandatory and optional) will be correctly installed for you, while only mandatory dependencies are installed using the `pip` distribution.

Alternatively, to access the latest source from github:

```
>> pip install git+https://git@github.com/PyLops/pylops.git@master
```

or just clone the repository

```
>> git clone https://github.com/PyLops/pylops.git
```


or download the zip file from the repository (green button in the top right corner of the main github repo page) and install `PyLops` from terminal using the command:

```
>> make install
```

Docker

If you want to try `PyLops` but do not have Python in your local machine, you can use our [Docker](#) image instead.

After installing Docker in your computer, type the following command in your terminal (note that this will take some time the first time you type it as you will download and install the docker image):

```
>> docker run -it -v /path/to/local/folder:/home/jupyter/notebook -p 8888:8888 mrava87/pylops:notebook
```

This will give you an address that you can put in your browser and will open a jupyter-notebook environment with `PyLops` and other basic Python libraries installed. Here `/path/to/local/folder` is the absolute path of a local folder on your computer where you will create a notebook (or containing notebooks that you want to continue working on). Note that anything you do to the notebook(s) will be saved in your local folder.

A larger image with Conda distribution is also available. Simply use `conda_notebook` instead of `notebook` in the previous command.

3.1.4 Step-by-step installation for developers

Fork and clone the repository by executing the following in your terminal:

```
>> git clone https://github.com/your_name_here/pylops.git
```

The first time you clone the repository run the following command:

```
>> make dev-install
```

If you prefer to build a new Conda environment just for PyLops, run the following command:

```
>> make dev-install_conda
```

To ensure that everything has been setup correctly, run tests:

```
>> make tests
```

Make sure no tests fail, this guarantees that the installation has been successful.

If using Conda environment, always remember to activate the conda environment every time you open a new *bash* shell by typing:

```
>> source activate pylops
```

3.2 Advanced installation

In this section we discuss some *important details* regarding code performance when using PyLops.

To get the most out of PyLops operators in terms of speed you will need to follow these guidelines as much as possible or ensure that the Python libraries used by PyLops are efficiently installed (e.g., allow multithreading) in your system.

3.2.1 Dependencies

PyLops relies on the [numpy](#) and [scipy](#) libraries and being able to link these to the most performant [BLAS](#) will ensure optimal performance of PyLops when using only *required dependencies*.

As already mentioned in the [Installation](#) page, we strongly encourage using the [Anaconda Python distribution](#) as [numpy](#) and [scipy](#) will be automatically linked to the Intel MKL library, which is per today the most performant library for basic linear algebra operations (if you don't believe it, take a read at this [blog post](#)).

The best way to understand which BLAS library is currently linked to your [numpy](#) and [scipy](#) libraries is to run the following commands in `ipython`:

```
import numpy as np
import scipy as sp
print(np.__config__.show())
print(sp.__config__.show())
```

You should be able to understand if your [numpy](#) and [scipy](#) are linked to Intel MKL or something else.

Note: Unfortunately, PyLops is so far only shipped with [PyPI](#), meaning that if you have not already installed [numpy](#) and [scipy](#) in your environment they will be installed as part of the installation process of the *pylops* library, all of those using `pip`. This comes with the disadvantage that [numpy](#) and [scipy](#) are linked to OpenBlas instead of Intel MKL, leading to a loss of performance. To prevent this, we suggest the following strategy:

- create conda environment, e.g. `conda create -n envname python=3.6.4 numpy scipy`
 - install pylops using `pip install pylops`
-

Finally, it is always important to make sure that your environment variable `OMP_NUM_THREADS` is correctly set to the maximum number of threads you would like to use in your code. If that is not the case *numpy* and *scipy* will underutilize your hardware even if linked to a performant BLAS library.

For example, first set `OMP_NUM_THREADS=1` (single-threaded) in your terminal:

```
>> export OMP_NUM_THREADS=1
```

and run the following code in python:

```
import os
import numpy as np
from timeit import timeit

size = 4096
A = np.random.random((size, size)),
B = np.random.random((size, size))
print('Time with %s threads: %f s' \
      %(os.environ.get('OMP_NUM_THREADS'),
        timeit(lambda: np.dot(A, B), number=4)))
```

Subsequently set `OMP_NUM_THREADS=2`, or any higher number of threads available in your hardware (multi-threaded):

```
>> export OMP_NUM_THREADS=2
```

and run the same python code. By both looking at your processes (e.g. using `top`) and at the python print statement you should see a speed-up in the second case.

Alternatively, you could set the `OMP_NUM_THREADS` variable directly inside your script using `os.environ['OMP_NUM_THREADS']=str(2)`. Moreover, note that when using Intel MKL you can alternatively set the `MKL_NUM_THREADS` instead of `OMP_NUM_THREADS`: this could be useful if your code runs other parallel processes which you can control independently from the Intel MKL ones using `OMP_NUM_THREADS`.

Note: Always remember to set `OMP_NUM_THREADS` (or `MKL_NUM_THREADS`) in your environment when using PyLops

3.2.2 Optional dependencies

To avoid increasing the number of *required* dependencies, which may lead to conflicts with other libraries that you have in your system, we have decided to build some of the additional features of PyLops in such a way that if an *optional* dependency is not present in your python environment, a safe fallback to one of the required dependencies will be enforced.

When available in your system, we recommend using the Conda package manager and install all the mandatory and optional dependencies of PyLops at once using the command:

```
>> conda install -c conda-forge pylops
```

in this case all dependencies will be installed from their conda distributions.

Alternatively, from version 1.4.0 optional dependencies can also be installed as part of the pip installation via:

```
>> pip install pylops[advanced]
```

Dependencies are however installed from their PyPI wheels.

An exception is however represented by `cupy`. This library is NOT installed automatically. Users interested to accelerate their computations with the aid of GPUs should install it prior to installing `pylops` (see below for more details).

numba

Although we always strive to write code for forward and adjoint operators that takes advantage of the perks of `numpy` and `scipy` (e.g., broadcasting, `ufunc`), in some case we may end up using for loops that may lead to poor performance. In those cases we may decide to implement alternative (optional) back-ends in `numba`.

In this case a user can simply switch from the native, always available implementation to the `numba` implementation by simply providing the following additional input parameter to the operator `engine='numba'`. This is for example the case in the `pylops.signalprocessing.Radon2D`.

If interested to use `numba` backend from `conda`, you will need to manually install it:

```
>> conda install numba
```

Finally, it is also advised to install the additional package `icc_rt`.

```
>> conda install -c numba icc_rt
```

or `pip` equivalent. Similarly to Intel MKL, you need to set the environment variable `NUMBA_NUM_THREADS` to tell `numba` how many threads to use. If this variable is not present in your environment, `numba` code will be compiled with `parallel=False`.

fft routines

Two different *engines* are provided by the `pylops.signalprocessing.FFT` operator for `fft` and `ifft` routines in the forward and adjoint modes: `engine='numpy'` (default) and `engine='fftw'`.

The first engine comes as default as `numpy` is part of the dependencies of `PyLops` and automatically installed when `PyLops` is installed if not already available in your Python distribution.

The second engine implements the well-known `FFTW` via the python wrapper `pyfftw.FFTW`. This optimized `fft` tends to outperform the one from `numpy` in many cases, however it has not been inserted in the mandatory requirements of `PyLops`, meaning that when installing `PyLops` with `pip`, `pyfftw.FFTW` will *not* be installed automatically.

Again, if interested to use `FFTW` backend from `conda`, you will need to manually install it:

```
>> conda install -c conda-forge pyfftw
```

or `pip` equivalent.

skfmm

This library is used to compute traveltime tables with the fast-marching method in the initialization of the `pylops.waveeqprocessing.Demigration` operator when choosing `mode == 'eikonal'`.

As this may not be of interest for many users, this library has not been inserted in the mandatory requirements of `PyLops`. If interested to use `skfmm`, you will need to manually install it:

```
>> conda install -c conda-forge scikit-fmm
```

or pip equivalent.

spgl1

This library is used to solve sparsity-promoting BP, BPDN, and LASSO problems in `pylops.optimization.sparsity.SPGL1` solver.

If interested to use `spgl1`, you can manually install it:

```
>> pip install spgl1
```

pywt

This library is used to implement the Wavelet operators.

If interested to use `pywt`, you can manually install it:

```
>> conda install pywavelets
```

or pip equivalent.

Note: If you are a developer, all the above optional dependencies can also be installed automatically by cloning the repository and installing `pylops` via `make dev-install` or `make dev-install_conda`.

3.2.3 Optional Dependencies (GPU)

cupy

This library is used as a drop-in replacement to `numpy` for GPU-accelerated computations. Since many different versions of `cupy` exist (based on the CUDA drivers of the GPU), users must install `cupy` prior to installing `pylops`. PyLops will automatically check if `cupy` is installed and in that case use it any time the input vector passed to an operator is of `cupy` type. Users can however disable this option even if `cupy` is installed. For more details of GPU-accelerated PyLops read the [GPU support](#) section.

cusignal

This library is used as a drop-in replacement to `scipy.signal` for GPU-accelerated computations. Similar to `cupy`, users must install `cusignal` prior to installing `pylops`. PyLops will automatically check if `cusignal` is installed and in that case use it any time the input vector passed to an operator is of `cusignal` type. Users can however disable this option even if `cupy` is installed. For more details of GPU-accelerated PyLops read the [GPU support](#) section.

3.3 GPU support

From `v1.12.0`, PyLops supports computations on GPUs powered by `cupy` and `cusignal`.

Note: For this to work, ensure to have installed `cupy-cudaXX>=8.1.0` and `cusignal>=0.16.0`. If neither `cupy` nor `cusignal` is installed, `pylops` will work just fine using its CPU backend. Note, however, that setting the environment variable `CUPY_PYLOPS` (or `CUSIGNAL_PYLOPS`) to 0 will force `pylops` not to use the `cupy` backend. This can be also used if a previous version of `cupy` or `cusignal` is installed in your system, otherwise you will get an error when importing `pylops`.

Apart from a few exceptions, all operators and solvers in PyLops can seamlessly work with `numpy` arrays on CPU as well as with `cupy` arrays on GPU. Users do simply need to consistently create operators and provide data vectors to the solvers - e.g., when using `pylops.MatrixMult` the input matrix must be a `cupy` array if the data provided to a solver is a `cupy` array.

`pylops.LinearOperator` methods that are currently not available for GPU computations are:

- `eigs`, `cond`, and `tosparse`, and `estimate_spectral_norm`

Operators that are currently not available for GPU computations are:

- `pylops.Spread`
- `pylops.signalprocessing.Radon2D`
- `pylops.signalprocessing.Radon3D`
- `pylops.signalprocessing.DWT`
- `pylops.signalprocessing.DWT2D`
- `pylops.signalprocessing.Seislet`
- `pylops.waveeqprocessing.Demigration`
- `pylops.waveeqprocessing.LSM`

Solvers that are currently not available for GPU computations are:

- `pylops.optimization.sparsity.SPGL1`

3.3.1 Example

Finally, let's briefly look at an example. First we write a code snippet using `numpy` arrays which PyLops will run on your CPU:

```
ny, nx = 400, 400
G = np.random.normal(0,1,(ny, nx)).astype(np.float32)
x = np.ones(nx, dtype=np.float32)

Gop = MatrixMult(G, dtype='float32')
y = Gop * x
xest = Gop / y
```

Now we write a code snippet using `cupy` arrays which PyLops will run on your GPU:

```
ny, nx = 400, 400
G = cp.random.normal(0,1,(ny, nx)).astype(np.float32)
x = cp.ones(nx, dtype=np.float32)

Gop = MatrixMult(G, dtype='float32')
y = Gop * x
xest = Gop / y
```

The code is almost unchanged apart from the fact that we now use `cupy` arrays, PyLops will figure this out! For more examples head over to these [notebooks](#).

3.4 Extensions

PyLops brings to users the power of linear operators in a simple and easy to use programming interface.

While very powerful on its own, this library is further extended to take advantage of more advanced computational resources, either in terms of **multiple-node clusters** or **GPUs**. Moreover, some independent small libraries are created to use third party softwares that cannot be included as dependencies to our main library for licensing issues but may be useful for academic purposes.

Spin-off projects that aim at extending the capabilities of PyLops are:

- [PyLops-GPU](#)
- [PyLops-Distributed](#)
- [curvelops](#)

3.5 Tutorials

3.5.1 01. The LinearOperator

This first tutorial is aimed at easing the use of the PyLops library for both new users and developers.

Since PyLops heavily relies on the use of the `scipy.sparse.linalg.LinearOperator` class of `scipy`, we will start by looking at how to initialize a linear operator as well as different ways to apply the forward and adjoint operations. Finally we will investigate various *special methods*, also called *magic methods* (i.e., methods with the double underscores at the beginning and the end) that have been implemented for such a class and will allow summing, subtracting, chaining, etc. multiple operators in a very easy and expressive way.

Let's start by defining a simple operator that applies element-wise multiplication of the model with a vector `d` in forward mode and element-wise multiplication of the data with the same vector `d` in adjoint mode. This operator is present in PyLops under the name of `pylops.Diagonal` and its implementation is discussed in more details in the [Implementing new operators](#) page.

```
import timeit
import matplotlib.pyplot as plt
import numpy as np
import pylops

n = 10
d = np.arange(n) + 1.
x = np.ones(n)
Dop = pylops.Diagonal(d)
```

First of all we apply the operator in the forward mode. This can be done in four different ways:

- `_matvec`: directly applies the method implemented for forward mode
- `matvec`: performs some checks before and after applying `_matvec`
- `*`: operator used to map the special method `__matmul__` which checks whether the input `x` is a vector or matrix and applies `_matvec` or `_matmul` accordingly.
- `@`: operator used to map the special method `__mul__` which performs like the `*` operator

We will time these 4 different executions and see how using `_matvec` (or `matvec`) will result in the faster computation. It is thus advised to use `*` (or `@`) in examples when expressivity has priority but prefer `_matvec` (or `matvec`) for efficient implementations.

```
# setup command
cmd_setup = """\
import numpy as np
import pylops
n = 10
d = np.arange(n) + 1.
x = np.ones(n)
Dop = pylops.Diagonal(d)
DopH = Dop.H
"""

# _matvec
cmd1 = 'Dop._matvec(x) '


# matvec
cmd2 = 'Dop.matvec(x) '

# @
cmd3 = 'Dop@x'

# *
cmd4 = 'Dop*x'

# timing
t1 = 1.e3 * np.array(timeit.repeat(cmd1, setup=cmd_setup,
                                   number=500, repeat=5))
t2 = 1.e3 * np.array(timeit.repeat(cmd2, setup=cmd_setup,
                                   number=500, repeat=5))
t3 = 1.e3 * np.array(timeit.repeat(cmd3, setup=cmd_setup,
                                   number=500, repeat=5))
t4 = 1.e3 * np.array(timeit.repeat(cmd4, setup=cmd_setup,
                                   number=500, repeat=5))

plt.figure(figsize=(7, 2))
plt.plot(t1, 'k', label='_matvec')
plt.plot(t2, 'r', label='matvec')
plt.plot(t3, 'g', label='@')
plt.plot(t4, 'b', label='*')
plt.axis('tight')
plt.legend();
```



Out:

```
<matplotlib.legend.Legend object at 0x7fc20ad23080>
```

Similarly we now consider the adjoint mode. This can be done in three different ways:

- `_rmatvec`: directly applies the method implemented for adjoint mode
- `rmatvec`: performs some checks before and after applying `_rmatvec`
- `.H*`: first applies the adjoint `.H` which creates a new `scipy.sparse.linalg._CustomLinearOperator` where `_matvec` and `_rmatvec` are swapped and then applies the new `_matvec`.

Once again, after timing these 3 different executions we can see how using `_rmatvec` (or `rmatvec`) will result in the faster computation while `.H*` is very inefficient and slow. Note that if the adjoint has to be applied multiple times it is at least advised to create the adjoint operator by applying `.H` only once upfront. Not surprisingly, the linear solvers in `scipy` as well as in `PyLops` actually use `matvec` and `rmatvec` when dealing with linear operators.

```
# _rmatvec
cmd1 = 'Dop._rmatvec(x) '


# rmatvec
cmd2 = 'Dop.rmatvec(x) '

# .H* (pre-computed H)
cmd3 = 'Dop.H*x'

# .H*
cmd4 = 'Dop.H*x'

# timing
t1 = 1.e3 * np.array(timeit.repeat(cmd1, setup=cmd_setup,
                                   number=500, repeat=5))
t2 = 1.e3 * np.array(timeit.repeat(cmd2, setup=cmd_setup,
                                   number=500, repeat=5))
t3 = 1.e3 * np.array(timeit.repeat(cmd3, setup=cmd_setup,
                                   number=500, repeat=5))
t4 = 1.e3 * np.array(timeit.repeat(cmd4, setup=cmd_setup,
                                   number=500, repeat=5))

plt.figure(figsize=(7, 2))
plt.plot(t1, 'k', label='_rmatvec')
plt.plot(t2, 'r', label='rmatvec')
plt.plot(t3, 'g', label='.H* (pre-computed H)')
plt.plot(t4, 'b', label='.H*')
plt.axis('tight')
plt.legend();
```



Out:

```
<matplotlib.legend.Legend object at 0x7fc21377bf60>
```

Just to reiterate once again, it is advised to call `matvec` and `rmatvec` unless PyLops linear operators are used for teaching purposes.

We now go through some other *methods* and *special methods* that are implemented in `scipy.sparse.linalg.LinearOperator` (and `pylops.LinearOperator`):

- `Op1+Op2`: maps the special method `__add__` and performs summation between two operators and returns a `pylops.LinearOperator`
- `-Op`: maps the special method `__neg__` and performs negation of an operators and returns a `pylops.LinearOperator`
- `Op1-Op2`: maps the special method `__sub__` and performs summation between two operators and returns a `pylops.LinearOperator`
- `Op1**N`: maps the special method `__pow__` and performs exponentiation of an operator and returns a `pylops.LinearOperator`
- `Op/y` (and `Op.div(y)`): maps the special method `__truediv__` and performs inversion of an operator
- `Op.eigs()`: estimates the eigenvalues of the operator
- `Op.cond()`: estimates the condition number of the operator
- `Op.conj()`: create complex conjugate operator

```
# +
print(Dop + Dop)

# -
print(-Dop)
print(Dop - 0.5 * Dop)

# **
print(Dop ** 3)

#* and /
y = Dop * x
print(Dop/y)

# eigs
print(Dop.eigs(neigs=3))

# cond
print(Dop.cond())

# conj
print(Dop.conj())
```

Out:

```
<10x10 LinearOperator with dtype=float64>
<10x10 LinearOperator with dtype=float64>
<10x10 LinearOperator with dtype=float64>
<10x10 LinearOperator with dtype=float64>
[1. 1. 1. 1. 1. 1. 1. 1. 1. 1.]
[10.+0.j 9.+0.j 8.+0.j]
```

(continues on next page)

(continued from previous page)

```
(9.9999999999999986+0j)
<10x10 _ConjLinearOperator with dtype=float64>
```

To understand the effect of `conj` we need to look into a problem with an operator in the complex domain. Let's create again our `pylops.Diagonal` operator but this time we populate it with complex numbers. We will see that the action of the operator and its complex conjugate is different even if the model is real.

```
n = 5
d = 1j*(np.arange(n) + 1.)
x = np.ones(n)
Dop = pylops.Diagonal(d)

print('y = Dx = ', Dop*x)
print('y = conj(D)x = ', Dop.conj()*x)
```


Out:

```
y = Dx = [0.+1.j 0.+2.j 0.+3.j 0.+4.j 0.+5.j]
y = conj(D)x = [0.-1.j 0.-2.j 0.-3.j 0.-4.j 0.-5.j]
```

At this point, the concept of linear operator may sound abstract. The convenience method `pylops.LinearOperator.todense` can be used to create the equivalent dense matrix of any operator. In this case for example we expect to see a diagonal matrix with `d` values along the main diagonal

```
D = Dop.todense()

plt.figure(figsize=(5, 5))
plt.imshow(np.abs(D))
plt.title('Dense representation of Diagonal operator')
plt.axis('tight')
plt.colorbar()
```



Out:

```
<matplotlib.colorbar.Colorbar object at 0x7fc20b677780>
```


Finally it is worth reiterating that if two linear operators are combined by means of the algebraical operations shown above, the resulting operator is still a `pylops.LinearOperator` operator. This means that we can still apply any of the methods implemented in the original scipy class definition like `*`, as well as those in our class definition like `/`

```
Dop1 = Dop - Dop.conj()

y = Dop1 * x
print('x = (Dop - conj(Dop))/y = ', Dop1 / y)

D1 = Dop1.todense()

plt.figure(figsize=(5, 5))
plt.imshow(np.abs(D1))
plt.title(r'Dense representation of  $|D + D^*|$ ')
plt.axis('tight')
plt.colorbar()
```



Out:

```
x = (Dop - conj(Dop))/y = [1.+0.j 1.+0.j 1.+0.j 1.+0.j 1.+0.j]
<matplotlib.colorbar.Colorbar object at 0x7fc20ad54a58>
```

This first tutorial is completed. You have seen the basic operations that can be performed using `scipy.sparse.linalg.LinearOperator` and our overload of such a class `pylops.LinearOperator` and you should be able to get started combining various PyLops operators and solving your own inverse problems.

Total running time of the script: (0 minutes 0.629 seconds)

3.5.2 02. The Dot-Test

One of the most important aspect of writing a *Linear operator* is to be able to verify that the code implemented in *forward mode* and the code implemented in *adjoint mode* are effectively adjoint to each other. If this is the case, your Linear operator will successfully pass the so-called **dot-test**. Refer to the *Notes* section of `pylops.utils.dottest` for a more detailed description.

In this example, I will show you how to use the dot-test for a variety of operator when model and data are either real or complex numbers.


```
# pylint: disable=C0103
import numpy as np
import matplotlib.pyplot as plt
import matplotlib.gridspec as pltgs

import pylops
from pylops.utils import dottest

plt.close('all')
```

Let's start with something very simple. We will make a `pylops.MatrixMult` operator and verify that its implementation passes the dot-test. For this time, we will do this step-by-step, replicating what happens in the `pylops.utils.dottest` routine.

```
N, M = 5, 3
Mat = np.arange(N*M).reshape(N, M)
Op = pylops.MatrixMult(Mat)

v = np.random.randn(N)
u = np.random.randn(M)

# Op * u
y = Op.matvec(u)
# Op' * v
x = Op.rmatvec(v)

yy = np.dot(y, v) # (Op * u)' * v
xx = np.dot(u, x) # u' * (Op' * v)

print('Dot-test %e' % np.abs((yy - xx) / ((yy + xx + 1e-15) / 2)))
```

Out:

```
Dot-test 1.366060e-16
```

And here is a visual interpretation of what a dot-test is

```
gs = pltgs.GridSpec(1, 9)
fig = plt.figure(figsize=(7, 3))
ax = plt.subplot(gs[0, 0:2])
ax.imshow(Op.A, cmap='rainbow')
ax.set_title(r'$Op$', size=20, fontweight='bold')
ax.set_xticks(np.arange(M-1)+0.5)
ax.set_yticks(np.arange(N-1)+0.5)
ax.grid(linewidth=3, color='white')
ax.xaxis.set_ticklabels([])
ax.yaxis.set_ticklabels([])
ax.axis('tight')
ax = plt.subplot(gs[0, 2])
ax.imshow(u[:, np.newaxis], cmap='rainbow')
ax.set_title(r'$u^{T}$', size=20, fontweight='bold')
ax.set_xticks([])
ax.set_yticks(np.arange(M-1)+0.5)
ax.grid(linewidth=3, color='white')
ax.xaxis.set_ticklabels([])
ax.yaxis.set_ticklabels([])
ax.axis('tight')
```


(continues on next page)

(continued from previous page)

```

ax = plt.subplot(gs[0, 3])
ax.imshow(v[:, np.newaxis], cmap='rainbow')
ax.set_title(r'$v$', size=20, fontweight='bold')
ax.set_xticks([])
ax.set_yticks(np.arange(N-1)+0.5)
ax.grid(linewidth=3, color='white')
ax.xaxis.set_ticklabels([])
ax.yaxis.set_ticklabels([])
ax = plt.subplot(gs[0, 4])
ax.text(0.35, 0.5, '=', horizontalalignment='center',
        verticalalignment='center', size=40, fontweight='bold')
ax.axis('off')
ax = plt.subplot(gs[0, 5])
ax.imshow(u[:, np.newaxis].T, cmap='rainbow')
ax.set_title(r'$u^T$', size=20, fontweight='bold')
ax.set_xticks(np.arange(M-1)+0.5)
ax.set_yticks([])
ax.grid(linewidth=3, color='white')
ax.xaxis.set_ticklabels([])
ax.yaxis.set_ticklabels([])
ax = plt.subplot(gs[0, 6:8])
ax.imshow(Op.A.T, cmap='rainbow')
ax.set_title(r'$Op^T$', size=20, fontweight='bold')
ax.set_xticks(np.arange(N-1)+0.5)
ax.set_yticks(np.arange(M-1)+0.5)
ax.grid(linewidth=3, color='white')
ax.xaxis.set_ticklabels([])
ax.yaxis.set_ticklabels([])
ax.axis('tight')
ax = plt.subplot(gs[0, 8])
ax.imshow(v[:, np.newaxis], cmap='rainbow')
ax.set_title(r'$v$', size=20, fontweight='bold')
ax.set_xticks([])
ax.set_yticks(np.arange(N-1)+0.5)
ax.grid(linewidth=3, color='white')
ax.xaxis.set_ticklabels([])
ax.yaxis.set_ticklabels([])

```



Out:

```
[Text(0, 0.5, ''), Text(0, 1.5, ''), Text(0, 2.5, ''), Text(0, 3.5, '')]
```

From now on, we can simply use the `pylops.utils.dottest` implementation of the dot-test and pass the operator we would like to validate, its size in the model and data spaces and optionally the tolerance we will be accepting for the dot-test to be considered successful. Finally we need to specify if our data or/and model vectors contain complex numbers using the `complexflag` parameter. While the dot-test will return `True` when successful and `False` otherwise, we can also ask to print its outcome putting the `verb` parameters to `True`.

```
N = 10
d = np.arange(N)
Dop = pylops.Diagonal(d)

dottest(Dop, N, N, tol=1e-6, complexflag=0, verb=True)
```

Out:

```
Dot test passed, v^T(Opu)=-6.919654 - u^T(Op^Tv)=-6.919654

True
```

We move now to a more complicated operator, the `pylops.signalprocessing.FFT` operator. We use once again the `pylops.utils.dottest` to verify its implementation and since we are dealing with a transform that can be applied to both real and complex array, we try different combinations using the `complexflag` input.

```
dt = 0.005
nt = 100
nfft = 2**10

FFTop = pylops.signalprocessing.FFT(dims=(nt,), nfft=nfft,
                                     sampling=dt, dtype=np.complex128)
dottest(FFTop, nfft, nt, complexflag=2, verb=True)
dottest(FFTop, nfft, nt, complexflag=3, verb=True)
```

Out:

```
Dot test passed, v^T(Opu)=-17.139104+3.828834i - u^T(Op^Tv)=-17.139104+3.828834i
Dot test passed, v^T(Opu)=11.420800-3.688151i - u^T(Op^Tv)=11.420800-3.688151i

True
```

Total running time of the script: (0 minutes 0.259 seconds)

3.5.3 03. Solvers

This tutorial will guide you through the `pylops.optimization` module and show how to use various solvers that are included in the PyLops library.

The main idea here is to provide the user of PyLops with very high-level functionalities to quickly and easily set up and solve complex systems of linear equations as well as include regularization and/or preconditioning terms (all of those constructed by means of PyLops linear operators).

To make this tutorial more interesting, we will present a real life problem and show how the choice of the solver and regularization/preconditioning terms is vital in many circumstances to successfully retrieve an estimate of the model. The problem that we are going to consider is generally referred to as the *data reconstruction* problem and aims at

reconstructing a regularly sampled signal of size M from N randomly selected samples:

$$\mathbf{y} = \mathbf{R}\mathbf{x}$$

where the restriction operator \mathbf{R} that selects the M elements from \mathbf{x} at random locations is implemented using `pylops.Restriction`, and

$$\mathbf{y} = [y_1, y_2, \dots, y_N]^T, \quad \mathbf{x} = [x_1, x_2, \dots, x_M]^T,$$

with $M \gg N$.

```
# pylint: disable=C0103
import numpy as np
import matplotlib.pyplot as plt

import pylops

plt.close('all')
np.random.seed(10)
```


Let's first create the data in the frequency domain. The data is composed by the superposition of 3 sinusoids with different frequencies.

```
# Signal creation in frequency domain
ifreqs = [41, 25, 66]
amps = [1., 1., 1.]
N = 200
nfft = 2**11
dt = 0.004
t = np.arange(N)*dt
f = np.fft.rfftfreq(nfft, dt)

FFTop = 10*pylops.signalprocessing.FFT(N, nfft=nfft, real=True)

X = np.zeros(nfft//2+1, dtype='complex128')
X[ifreqs] = amps
x = FFTop.H*X

fig, axs = plt.subplots(2, 1, figsize=(12, 8))
axs[0].plot(f, np.abs(X), 'k', LineWidth=2)
axs[0].set_xlim(0, 30)
axs[0].set_title('Data(frequency domain)')
axs[1].plot(t, x, 'k', LineWidth=2)
axs[1].set_title('Data(time domain)')
axs[1].axis('tight')
```



Out:

```
(-0.0398, 0.8358000000000001, -0.7554257721191237, 1.4249324045744862)
```

We now define the locations at which the signal will be sampled.


```
# subsampling locations
perc_subsampling = 0.2
Nsub = int(np.round(N*perc_subsampling))

iava = np.sort(np.random.permutation(np.arange(N))[:Nsub])

# Create restriction operator
Rop = pylops.Restriction(N, iava, dtype='float64')

y = Rop*x
ymask = Rop.mask(x)

# Visualize data
fig = plt.figure(figsize=(12, 4))
plt.plot(t, x, 'k', lw=3)
plt.plot(t, x, '.k', ms=20, label='all samples')
plt.plot(t, ymask, '.g', ms=15, label='available samples')
plt.legend()
plt.title('Data restriction')
```



Out:

```
Text(0.5, 1.0, 'Data restriction')
```

To start let's consider the simplest 'solver', i.e., *least-square inversion without regularization*. We aim here to minimize the following cost function:

$$J = ||\mathbf{y} - \mathbf{R}\mathbf{x}||_2^2$$

Depending on the choice of the operator \mathbf{R} , such problem can be solved using explicit matrix solvers as well as iterative solvers. In this case we will be using the latter approach (more specifically the scipy implementation of the *LSQR* solver - i.e., `scipy.sparse.linalg.lsqr`) as we do not want to explicitly create and invert a matrix. In most cases this will be the only viable approach as most of the large-scale optimization problems that we are interested to solve using PyLops do not lend naturally to the creation and inversion of explicit matrices.

This first solver can be very easily implemented using the `/` for PyLops operators, which will automatically call the `scipy.sparse.linalg.lsqr` with some default parameters.

```
xinv = Rop / y
```

We can also use `pylops.optimization.leastsquares.RegularizedInversion` (without regularization term for now) and customize our solvers using kwargs.

```
xinv = \
    pylops.optimization.leastsquares.RegularizedInversion(Rop, [], y,
                                                         **dict(damp=0,
                                                                iter_lim=10,
                                                                show=1))
```

Out:

```
LSQR               Least-squares solution of  Ax = b
The matrix A has 40 rows and 200 columns
damp = 0.0000000000000000e+00    calc_var =          0
atol = 1.00e-08                  conlim = 1.00e+08
btol = 1.00e-08                  iter_lim =        10
```

Itn	x[0]	rlnorm	r2norm	Compatible	LS	Norm A	Cond A
0	0.000000e+00	3.759e+00	3.759e+00	1.0e+00	2.7e-01		
1	0.000000e+00	0.000e+00	0.000e+00	0.0e+00	0.0e+00	0.0e+00	0.0e+00

(continues on next page)

(continued from previous page)

```

LSQR finished
Ax - b is small enough, given atol, btol

istop =          1    rlnorm = 0.0e+00    anorm = 0.0e+00    arnorm = 0.0e+00
itn    =          1    r2norm = 0.0e+00    acond = 0.0e+00    xnorm  = 3.8e+00

```

Finally we can select a different starting guess from the null vector

```

xinv_fromx0 = \
    pylops.optimization.leastsquares.RegularizedInversion(Rop, [], y,
                                                           x0=np.ones(N),
                                                           **dict(damp=0,
                                                                iter_lim=10,
                                                                show=0))

```

The cost function above can be also expanded in terms of its *normal equations*

$$\mathbf{x}_{ne} = (\mathbf{R}^T \mathbf{R})^{-1} \mathbf{R}^T \mathbf{y}$$

The method `pylops.optimization.leastsquares.NormalEquationsInversion` implements such system of equations explicitly and solves them using an iterative scheme suitable for square matrices (i.e., $M = N$).

While this approach may seem not very useful, we will soon see how regularization terms could be easily added to the normal equations using this method.

```

xne = pylops.optimization.leastsquares.NormalEquationsInversion(Rop, [], y)


```

Let's now visualize the different inversion results

```

fig = plt.figure(figsize=(12, 4))
plt.plot(t, x, 'k', lw=2, label='original')
plt.plot(t, xinv, 'b', ms=10, label='inversion')
plt.plot(t, xinv_fromx0, '--r', ms=10, label='inversion from x0')
plt.plot(t, xne, '--g', ms=10, label='normal equations')
plt.legend()
plt.title('Data reconstruction without regularization')

```



Out:

```
Text(0.5, 1.0, 'Data reconstruction without regularization')
```

Regularization

You may have noticed that none of the inversion has been successful in recovering the original signal. This is a clear indication that the problem we are trying to solve is highly ill-posed and requires some prior knowledge from the user.

We will now see how to add prior information to the inverse process in the form of regularization (or preconditioning). This can be done in two different ways

- regularization via `pylops.optimization.leastsquares.NormalEquationsInversion` or `pylops.optimization.leastsquares.RegularizedInversion`
- preconditioning via `pylops.optimization.leastsquares.PreconditionedInversion`

Let's start by regularizing the normal equations using a second derivative operator

$$\mathbf{x} = (\mathbf{R}^T \mathbf{R} + \epsilon_{\nabla}^2 \nabla^T \nabla)^{-1} \mathbf{R}^T \mathbf{y}$$

```
# Create regularization operator
D2op = pylops.SecondDerivative(N, dims=None, dtype='float64')

# Regularized inversion
epsR = np.sqrt(0.1)
epsI = np.sqrt(1e-4)

xne = \
    pylops.optimization.leastsquares.NormalEquationsInversion(Rop, [D2op], y,
                                                                epsI=epsI,
                                                                epsRs=[epsR],
                                                                returninfo=False,
                                                                **dict(maxiter=50))
```

Note that in case we have access to a fast implementation for the chain of forward and adjoint for the regularization operator (i.e., $\nabla^T \nabla$), we can modify our call to `pylops.optimization.leastsquares.NormalEquationsInversion` as follows:

```
ND2op = pylops.MatrixMult((D2op.H * D2op).tospars()) # mimic fast D^T D

xne1 = \
    pylops.optimization.leastsquares.NormalEquationsInversion(Rop, [], y,
                                                                NRegs=[ND2op],
                                                                epsI=epsI,
                                                                epsNRs=[epsR],
                                                                returninfo=False,
                                                                **dict(maxiter=50))
```

We can do the same while using `pylops.optimization.leastsquares.RegularizedInversion` which solves the following augmented problem

$$\begin{bmatrix} \mathbf{R} \\ \epsilon_{\nabla} \nabla \end{bmatrix} \mathbf{x} = \begin{bmatrix} \mathbf{y} \\ 0 \end{bmatrix}$$


```
xreg = \
    pylops.optimization.leastsquares.RegularizedInversion(Rop, [D2op], y,
                                                         epsRs=[np.sqrt(0.1)],
                                                         returninfo=False,
                                                         **dict(damp=np.sqrt(1e-4),
                                                                iter_lim=50,
                                                                show=0))
```

We can also write a preconditioned problem, whose cost function is

$$J = ||\mathbf{y} - \mathbf{R}\mathbf{P}\mathbf{p}||_2^2$$

where \mathbf{P} is the preconditioned operator, \mathbf{p} is the projected model in the preconditioned space, and $\mathbf{x} = \mathbf{P}\mathbf{p}$ is the model in the original model space we want to solve for. Note that a preconditioned problem converges much faster to its solution than its corresponding regularized problem. This can be done using the routine `pylops.optimization.leastsquares.PreconditionedInversion`.


```
# Create regularization operator
Sop = pylops.Smoothing1D(nsmooth=11, dims=[N], dtype='float64')

# Invert for interpolated signal
xprec = \
    pylops.optimization.leastsquares.PreconditionedInversion(Rop, Sop, y,
                                                            returninfo=False,
                                                            **dict(damp=np.sqrt(1e-
↪9),
                                                                iter_lim=20,
                                                                show=0))
```

Let's finally visualize these solutions

```
# sphinx_gallery_thumbnail_number=4
fig = plt.figure(figsize=(12, 4))
plt.plot(t[iava], y, '.k', ms=20, label='available samples')
plt.plot(t, x, 'k', lw=3, label='original')
plt.plot(t, xne, 'b', lw=3, label='normal equations')
plt.plot(t, xnel, '--c', lw=3, label='normal equations (with direct D^T D)')
plt.plot(t, xreg, '-.r', lw=3, label='regularized')
plt.plot(t, xprec, '--g', lw=3, label='preconditioned equations')
plt.legend()
plt.title('Data reconstruction with regularization')

subax = fig.add_axes([0.7, 0.2, 0.15, 0.6])
subax.plot(t[iava], y, '.k', ms=20)
subax.plot(t, x, 'k', lw=3)
subax.plot(t, xne, 'b', lw=3)
subax.plot(t, xnel, '--c', lw=3)
subax.plot(t, xreg, '-.r', lw=3)
subax.plot(t, xprec, '--g', lw=3)
subax.set_xlim(0.05, 0.3)
```



Out:

```
(0.05, 0.3)
```

Much better estimates! We have seen here how regularization and/or preconditioning can be vital to successfully solve some ill-posed inverse problems.

We have however so far only considered solvers that can include additional norm-2 regularization terms. A very active area of research is that of *sparsity-promoting* solvers (also sometimes referred to as *compressive sensing*): the regularization term added to the cost function to minimize has norm- p ($p \leq 1$) and the problem is generally recasted by considering the model to be sparse in some domain. We can follow this philosophy as our signal to invert was actually created as superposition of 3 sinusoids (i.e., three spikes in the Fourier domain). Our new cost function is:

$$J_1 = \|y - \mathbf{R}\mathbf{F}\mathbf{p}\|_2^2 + \epsilon \|\mathbf{p}\|_1$$

where \mathbf{F} is the FFT operator. We will thus use the `pylops.optimization.sparsity.ISTA` and `pylops.optimization.sparsity.FISTA` solvers to estimate our input signal.

```
pista, niteri, costi = \
    pylops.optimization.sparsity.ISTA(Rop*FFTop.H, y, niter=1000,
                                     eps=0.1, tol=1e-7, returninfo=True)

xista = FFTop.H*pista

pfista, niterf, costf = \
    pylops.optimization.sparsity.FISTA(Rop*FFTop.H, y, niter=1000,
                                       eps=0.1, tol=1e-7, returninfo=True)

xfista = FFTop.H*pfista

fig, axs = plt.subplots(2, 1, figsize=(12, 8))
fig.suptitle('Data reconstruction with sparsity', fontsize=14,
             fontweight='bold', y=0.9)
axs[0].plot(f, np.abs(X), 'k', lw=3)
axs[0].plot(f, np.abs(pista), '--r', lw=3)
axs[0].plot(f, np.abs(pfista), '--g', lw=3)
axs[0].set_xlim(0, 30)
axs[0].set_title('Frequency domain')
axs[1].plot(t[iava], y, '.k', ms=20, label='available samples')
axs[1].plot(t, x, 'k', lw=3, label='original')
axs[1].plot(t, xista, '--r', lw=3, label='ISTA')
axs[1].plot(t, xfista, '--g', lw=3, label='FISTA')
axs[1].set_title('Time domain')
```

(continues on next page)

(continued from previous page)


```

axs[1].axis('tight')
axs[1].legend()
plt.tight_layout()
plt.subplots_adjust(top=0.8)

fig, ax = plt.subplots(1, 1, figsize=(12, 3))
ax.semilogy(costi, 'r', lw=2, label='ISTA')
ax.semilogy(costf, 'g', lw=2, label='FISTA')
ax.set_title('Cost functions', size=15, fontweight='bold')
ax.set_xlabel('Iteration')
ax.legend()
ax.grid(True)
plt.tight_layout()

```

Data reconstruction with sparsity



As you can see, changing parametrization of the model and imposing sparsity in the Fourier domain has given an extra improvement to our ability of recovering the underlying densely sampled input signal. Moreover, FISTA converges much faster than ISTA as expected and should be preferred when using sparse solvers.

Finally we consider a slightly different cost function (note that in this case we try to solve a constrained problem):

$$J_1 = \|\mathbf{p}\|_1 \quad \text{subj.to} \quad \|\mathbf{y} - \mathbf{R}\mathbf{F}\mathbf{p}\|$$


A very popular solver to solve such kind of cost function is called *spgl1* and can be accessed via *pylops.optimization.sparsity.SPGL1*.

```
xspgl1, pspgl1, info = \
    pylops.optimization.sparsity.SPGL1(Rop, y, FFTop, tau=3, iter_lim=200)

fig, axs = plt.subplots(2, 1, figsize=(12, 8))
fig.suptitle('Data reconstruction with SPGL1', fontsize=14,
             fontweight='bold', y=0.9)
axs[0].plot(f, np.abs(X), 'k', lw=3)
axs[0].plot(f, np.abs(pspgl1), '--m', lw=3)
axs[0].set_xlim(0, 30)
axs[0].set_title('Frequency domain')
axs[1].plot(t[iava], y, '.k', ms=20, label='available samples')
axs[1].plot(t, x, 'k', lw=3, label='original')
axs[1].plot(t, xspgl1, '--m', lw=3, label='SPGL1')
axs[1].set_title('Time domain')
axs[1].axis('tight')
axs[1].legend()
plt.tight_layout()
plt.subplots_adjust(top=0.8)

fig, ax = plt.subplots(1, 1, figsize=(12, 3))
ax.semilogy(info['rnorm2'], 'k', lw=2, label='ISTA')
ax.set_title('Cost functions', size=15, fontweight='bold')
ax.set_xlabel('Iteration')
ax.legend()
ax.grid(True)
plt.tight_layout()
```

Data reconstruction with SPGL1



Total running time of the script: (0 minutes 3.421 seconds)

3.5.4 04. Bayesian Inversion

This tutorial focuses on Bayesian inversion, a special type of inverse problem that aims at incorporating prior information in terms of model and data probabilities in the inversion process.

In this case we will be dealing with the same problem that we discussed in [03. Solvers](#), but instead of defining ad-hoc regularization or preconditioning terms we parametrize and model our input signal in the frequency domain in a probabilistic fashion: the central frequency, amplitude and phase of the three sinusoids have gaussian distributions as follows:

$$X(f) = \sum_{i=1}^3 a_i e^{j\phi_i} \delta(f - f_i)$$

where $f_i \sim N(f_{0,i}, \sigma_{f,i})$, $a_i \sim N(a_{0,i}, \sigma_{a,i})$, and $\phi_i \sim N(\phi_{0,i}, \sigma_{\phi,i})$.

Based on the above definition, we construct some prior models in the frequency domain, convert each of them to the time domain and use such an ensemble to estimate the prior mean $\mu_{\mathbf{x}}$ and model covariance $\mathbf{C}_{\mathbf{x}}$.

We then create our data by sampling the true signal at certain locations and solve the reconstruction problem within a Bayesian framework. Since we are assuming gaussianity in our priors, the equation to obtain the posterior mean can be derived analytically:

$$\mathbf{x} = \mathbf{x}_0 + \mathbf{C}_x \mathbf{R}^T (\mathbf{R} \mathbf{C}_x \mathbf{R}^T + \mathbf{C}_y)^{-1} (\mathbf{y} - \mathbf{R} \mathbf{x}_0)$$

```
# sphinx_gallery_thumbnail_number = 2
import numpy as np
import matplotlib.pyplot as plt
import pylops

from scipy.sparse.linalg import lsqr

plt.close('all')
np.random.seed(10)
```

Let's start by creating our true model and prior realizations

```
def prior_realization(f0, a0, phi0, sigmaf, sigmaa, sigmaphi, dt, nt, nfft):
    """Create realization from prior mean and std for amplitude, frequency and
    phase
    """
    f = np.fft.rfftfreq(nfft, dt)
    df = f[1] - f[0]
    ifreqs = [int(np.random.normal(f, sigma)/df)
               for f, sigma in zip(f0, sigmaf)]
    amps = [np.random.normal(a, sigma) for a, sigma in zip(a0, sigmaa)]
    phis = [np.random.normal(phi, sigma) for phi, sigma in zip(phi0, sigmaphi)]

    # input signal in frequency domain
    X = np.zeros(nfft//2+1, dtype='complex128')
    X[ifreqs] = np.array(amps).squeeze() * \
        np.exp(1j * np.deg2rad(np.array(phis))).squeeze()

    # input signal in time domain
    FFTop = pylops.signalprocessing.FFT(nt, nfft=nfft, real=True)
    x = FFTop.H*X
    return x

# Priors
nreals = 100
f0 = [5, 3, 8]
sigmaf = [0.5, 1., 0.6]
a0 = [1., 1., 1.]
sigmaa = [0.1, 0.5, 0.6]
phi0 = [-90., 0., 0.]
sigmaphi = [0.1, 0.2, 0.4]
sigmad = 1e-2

# Prior models
nt = 200
nfft = 2**11
dt = 0.004
t = np.arange(nt)*dt
xs = \
    np.array([prior_realization(f0, a0, phi0, sigmaf,
```

(continues on next page)

(continued from previous page)

```

                                sigmaa, sigmaphi, dt, nt, nfft)
    for _ in range(nreals)])

# True model (taken as one possible realization)
x = prior_realization(f0, a0, phi0, [0, 0, 0], [0, 0, 0],
                     [0, 0, 0], dt, nt, nfft)

```

We have now a set of prior models in time domain. We can easily use sample statistics to estimate the prior mean and covariance. For the covariance, we perform a second step where we average values around the main diagonal for each row and find a smooth, compact filter that we use to define a convolution linear operator that mimics the action of the covariance matrix on a vector

```


x0 = np.average(xs, axis=0)
Cm = ((xs - x0).T @ (xs - x0))/nreals


N = 30 # lenght of decorrelation
diags = np.array([Cm[i, i-N:i+N+1] for i in range(N, nt-N)])
diag_ave = np.average(diags, axis=0)
diag_ave *= np.hamming(2*N+1) # add a taper at the end to avoid edge effects

fig, ax = plt.subplots(1, 1, figsize=(12, 4))
ax.plot(t, xs.T, 'r', lw=1)
ax.plot(t, x0, 'g', lw=4)
ax.plot(t, x, 'k', lw=4)
ax.set_title('Prior realizations and mean')
ax.set_xlim(0, 0.8)

fig, (ax1, ax2) = plt.subplots(1, 2, figsize=(10, 4))
im = ax1.imshow(Cm, interpolation='nearest', cmap='seismic',
                extent=(t[0], t[-1], t[-1], t[0]))
ax1.set_title(r"$\mathbf{C}_m^{\text{prior}}$")
ax1.axis('tight')
ax2.plot(np.arange(-N, N + 1) * dt, diags.T, '--r', lw=1)
ax2.plot(np.arange(-N, N + 1) * dt, diag_ave, 'k', lw=4)
ax2.set_title("Averaged covariance 'filter'")

```





Out:

```
Text(0.5, 1.0, "Averaged covariance 'filter'")
```

Let's define now the sampling operator as well as create our covariance matrices in terms of linear operators. This may not be strictly necessary here but shows how even Bayesian-type of inversion can very easily scale to large model and data spaces.

```
# Sampling operator
perc_subsampling = 0.2
ntsub = int(np.round(nt*perc_subsampling))
iava = np.sort(np.random.permutation(np.arange(nt))[:ntsub])
iava[-1] = nt-1 # assume we have the last sample to avoid instability
Rop = pylops.Restriction(nt, iava, dtype='float64')

# Covariance operators
Cm_op = \
    pylops.signalprocessing.Convolve1D(nt, diag_ave, offset=N)
Cd_op = sigmad**2 * pylops.Identity(ntsub)
```

We model now our data and add noise that respects our prior definition

```
n = np.random.normal(0, sigmad, nt)
y = Rop * x
yn = Rop * (x + n)
ymask = Rop.mask(x)
ynmask = Rop.mask(x + n)
```

First we apply the Bayesian inversion equation


```
xbayes = x0 + Cm_op * Rop.H * (lsqr(Rop * Cm_op * Rop.H + Cd_op,
                                     yn - Rop*x0, iter_lim=400)[0])

# Visualize
fig, ax = plt.subplots(1, 1, figsize=(12, 5))
ax.plot(t, x, 'k', lw=6, label='true')
ax.plot(t, ymask, '.k', ms=25, label='available samples')
ax.plot(t, ynmask, '.r', ms=25, label='available noisy samples')
ax.plot(t, xbayes, 'r', lw=3, label='bayesian inverse')
ax.legend()
```

(continues on next page)

(continued from previous page)

```
ax.set_title('Signal')
ax.set_xlim(0, 0.8)
```



Out:

```
(0.0, 0.8)
```

So far we have been able to estimate our posterior mean. What about its uncertainties (i.e., posterior covariance)?



In real-life applications it is very difficult (if not impossible) to directly compute the posterior covariance matrix. It is much more useful to create a set of models that sample the posterior probability. We can do that by solving our problem several times using different prior realizations as starting guesses:

```
xpost = [x0 + Cm_op * Rop.H * (lsqr(Rop * Cm_op * Rop.H + Cd_op, yn - Rop * x0, iter_
→lim=400)[0])
        for x0 in xs[:30]]
xpost = np.array(xpost)

x0post = np.average(xpost, axis=0)
Cm_post = ((xpost - x0post).T @ (xpost - x0post)) / nreals

# Visualize
fig, ax = plt.subplots(1, 1, figsize=(12, 5))
ax.plot(t, x, 'k', lw=6, label='true')
ax.plot(t, xpost.T, '--r', lw=1)
ax.plot(t, x0post, 'r', lw=3, label='bayesian inverse')
ax.plot(t, ymask, '.k', ms=25, label='available samples')
ax.plot(t, ynmask, '.r', ms=25, label='available noisy samples')
ax.legend()
ax.set_title('Signal')
ax.set_xlim(0, 0.8)

fig, ax = plt.subplots(1, 1, figsize=(5, 4))
im = ax.imshow(Cm_post, interpolation='nearest', cmap='seismic',
               extent=(t[0], t[-1], t[-1], t[0]))
ax.set_title(r"$\mathbf{C}_m^{\text{posterior}}$")
ax.axis('tight')
```



Out:

```
(0.0, 0.796, 0.796, 0.0)
```

Note that here we have been able to compute a sample posterior covariance from its estimated samples. By displaying it we can see how both the overall variances and the correlation between different parameters have become narrower compared to their prior counterparts.

Total running time of the script: (0 minutes 1.588 seconds)

3.5.5 05. Image deblurring

Deblurring is the process of removing blurring effects from images, caused for example by defocus aberration or motion blur.

In forward mode, such blurring effect is typically modelled as a 2-dimensional convolution between the so-called *point spread function* and a target sharp input image, where the sharp input image (which has to be recovered) is unknown and the point-spread function can be either known or unknown.

In this tutorial, an example of 2d blurring and deblurring will be shown using the `pylops.signalprocessing.Convolve2D` operator assuming knowledge of the point-spread function.

```
import numpy as np
import matplotlib.pyplot as plt
import pylops
```

Let's start by importing a 2d image and defining the blurring operator


```
im = np.load('../testdata/python.npy')[::5, ::5, 0]

Nz, Nx = im.shape

# Blurring gaussian operator
nh = [15, 25]
hz = np.exp(-0.1*np.linspace(-(nh[0]//2), nh[0]//2, nh[0])**2)
hx = np.exp(-0.03*np.linspace(-(nh[1]//2), nh[1]//2, nh[1])**2)
hz /= np.trapz(hz) # normalize the integral to 1
hx /= np.trapz(hx) # normalize the integral to 1
h = hz[:, np.newaxis] * hx[np.newaxis, :]

fig, ax = plt.subplots(1, 1, figsize=(5, 3))
him = ax.imshow(h)
ax.set_title('Blurring operator')
fig.colorbar(him, ax=ax)
ax.axis('tight')

Cop = pylops.signalprocessing.Convolve2D(Nz * Nx, h=h,
                                         offset=(nh[0] // 2,
                                                  nh[1] // 2),
                                         dims=(Nz, Nx), dtype='float32')
```



We first apply the blurring operator to the sharp image. We then try to recover the sharp input image by inverting the convolution operator from the blurred image. Note that when we perform inversion without any regularization, the deblurred image will show some ringing due to the instabilities of the inverse process. Using a L1 solver with a DWT preconditioner or TV regularization allows to recover sharper contrasts.

```
imblur = Cop * im.flatten()

imdeblur = \
    pylops.optimization.leastsquares.NormalEquationsInversion(Cop, None,
                                                              imblur,
                                                              maxiter=50)

Wop = pylops.signalprocessing.DWT2D((Nz, Nx), wavelet='haar', level=3)
Dop = [pylops.FirstDerivative(Nz * Nx, dims=(Nz, Nx), dir=0, edge=False),
       pylops.FirstDerivative(Nz * Nx, dims=(Nz, Nx), dir=1, edge=False)]
DWop = Dop + [Wop, ]

imdeblurfista = \
    pylops.optimization.sparsity.FISTA(Cop * Wop.H, imblur, eps=1e-1,
                                       niter=100)[0]
imdeblurfista = Wop.H * imdeblurfista

imdeblurtv = \
    pylops.optimization.sparsity.SplitBregman(Cop, Dop, imblur.flatten(),
                                              niter_outer=10, niter_inner=5,
                                              mu=1.5, epsRL1s=[2e0, 2e0],
                                              tol=1e-4, tau=1., show=False,
                                              ** dict(iter_lim=5, damp=1e-4))[0]

imdeblurtv1 = \
    pylops.optimization.sparsity.SplitBregman(Cop, DWop,
                                              imblur.flatten(),
                                              niter_outer=10, niter_inner=5,
                                              mu=1.5, epsRL1s=[1e0, 1e0, 1e0],
                                              tol=1e-4, tau=1., show=False,
                                              ** dict(iter_lim=5, damp=1e-4))[0]
```


(continues on next page)

(continued from previous page)

```
# Reshape images
imblur = imblur.reshape((Nz, Nx))
imdeblur = imdeblur.reshape((Nz, Nx))
imdeblurfista = imdeblurfista.reshape((Nz, Nx))
imdeblurtv = imdeblurtv.reshape((Nz, Nx))
imdeblurtv1 = imdeblurtv1.reshape((Nz, Nx))
```

Finally we visualize the original, blurred, and recovered images.

```
# sphinx_gallery_thumbnail_number = 2
fig = plt.figure(figsize=(12, 6))
fig.suptitle('Deblurring', fontsize=14, fontweight='bold', y=0.95)
ax1 = plt.subplot2grid((2, 5), (0, 0))
ax2 = plt.subplot2grid((2, 5), (0, 1))
ax3 = plt.subplot2grid((2, 5), (0, 2))
ax4 = plt.subplot2grid((2, 5), (1, 0))
ax5 = plt.subplot2grid((2, 5), (1, 1))
ax6 = plt.subplot2grid((2, 5), (1, 2))
ax7 = plt.subplot2grid((2, 5), (0, 3), colspan=2)
ax8 = plt.subplot2grid((2, 5), (1, 3), colspan=2)
ax1.imshow(im, cmap='viridis', vmin=0, vmax=250)
ax1.axis('tight')
ax1.set_title('Original')
ax2.imshow(imblur, cmap='viridis', vmin=0, vmax=250)
ax2.axis('tight')
ax2.set_title('Blurred')
ax3.imshow(imdeblur, cmap='viridis', vmin=0, vmax=250)
ax3.axis('tight')
ax3.set_title('Deblurred')
ax4.imshow(imdeblurfista, cmap='viridis', vmin=0, vmax=250)
ax4.axis('tight')
ax4.set_title('FISTA deblurred')
ax5.imshow(imdeblurtv, cmap='viridis', vmin=0, vmax=250)
ax5.axis('tight')
ax5.set_title('TV deblurred')
ax6.imshow(imdeblurtv1, cmap='viridis', vmin=0, vmax=250)
ax6.axis('tight')
ax6.set_title('TV+Haar deblurred')
ax7.plot(im[Nz//2], 'k')
ax7.plot(imblur[Nz//2], '--r')
ax7.plot(imdeblur[Nz//2], '--b')
ax7.plot(imdeblurfista[Nz//2], '--g')
ax7.plot(imdeblurtv[Nz//2], '--m')
ax7.plot(imdeblurtv1[Nz//2], '--y')
ax7.axis('tight')
ax7.set_title('Horizontal section')
ax8.plot(im[:, Nx//2], 'k', label='Original')
ax8.plot(imblur[:, Nx//2], '--r', label='Blurred')
ax8.plot(imdeblur[:, Nx//2], '--b', label='Deblurred')
ax8.plot(imdeblurfista[:, Nx//2], '--g', label='FISTA deblurred')
ax8.plot(imdeblurtv[:, Nx//2], '--m', label='TV deblurred')
ax8.plot(imdeblurtv1[:, Nx//2], '--y', label='TV+Haar deblurred')
ax8.axis('tight')
ax8.set_title('Vertical section')
ax8.legend(loc=5, fontsize='small')
plt.tight_layout()
plt.subplots_adjust(top=0.8)
```



Total running time of the script: (0 minutes 7.118 seconds)

3.5.6 06. 2D Interpolation

In the mathematical field of numerical analysis, interpolation is the problem of constructing new data points within the range of a discrete set of known data points. In signal and image processing, the data may be recorded at irregular locations and it is often required to *regularize* the data into a regular grid.

In this tutorial, an example of 2d interpolation of an image is carried out using a combination of PyLops operators (`pylops.Restriction` and `pylops.Laplacian`) and the `pylops.optimization` module.

Mathematically speaking, if we want to interpolate a signal using the theory of inverse problems, we can define the following forward problem:

$$\mathbf{y} = \mathbf{R}\mathbf{x}$$

where the restriction operator \mathbf{R} selects M elements from the regularly sampled signal \mathbf{x} at random locations. The input and output signals are:

$$\mathbf{y} = [y_1, y_2, \dots, y_N]^T, \quad \mathbf{x} = [x_1, x_2, \dots, x_M]^T,$$

with $M \gg N$.

```
import numpy as np
import matplotlib.pyplot as plt
import pylops

plt.close('all')
np.random.seed(0)
```

To start we import a 2d image and define our restriction operator to irregularly and randomly sample the image for 30% of the entire grid

```

im = np.load('../testdata/python.npy')[:, :, 0]

Nz, Nx = im.shape
N = Nz * Nx

# Subsample signal
perc_subsampling = 0.2

Nsub2d = int(np.round(N*perc_subsampling))
iava = np.sort(np.random.permutation(np.arange(N))[:Nsub2d])

# Create operators and data
Rop = pylops.Restriction(N, iava, dtype='float64')
D2op = pylops.Laplacian((Nz, Nx), weights=(1, 1), dtype='float64')

x = im.flatten()
y = Rop * x
y1 = Rop.mask(x)

```

We will now use two different routines from our optimization toolbox to estimate our original image in the regular grid.

```

xcg_reg_lop = \
    pylops.optimization.leastsquares.NormalEquationsInversion(Rop, [D2op], y,
                                                              epsRs=[np.sqrt(0.1)],
                                                              returninfo=False,
                                                              **dict(maxiter=200))

# Invert for interpolated signal, lsqr
xlsqr_reg_lop, istop, itn, rlnorm, r2norm = \
    pylops.optimization.leastsquares.RegularizedInversion(Rop, [D2op], y,
                                                          epsRs=[np.sqrt(0.1)],
                                                          returninfo=True,
                                                          **dict(damp=0,
                                                              iter_lim=200,
                                                              show=0))

# Reshape estimated images
im_sampled = y1.reshape((Nz, Nx))
im_rec_lap_cg = xcg_reg_lop.reshape((Nz, Nx))
im_rec_lap_lsqr = xlsqr_reg_lop.reshape((Nz, Nx))

```

Finally we visualize the original image, the reconstructed images and their error

```

fig, axs = plt.subplots(1, 4, figsize=(12, 4))
fig.suptitle('Data reconstruction - normal eqs', fontsize=14,
             fontweight='bold', y=0.95)
axs[0].imshow(im, cmap='viridis', vmin=0, vmax=250)
axs[0].axis('tight')
axs[0].set_title('Original')
axs[1].imshow(im_sampled, cmap='viridis', vmin=0, vmax=250)
axs[1].axis('tight')
axs[1].set_title('Sampled')
axs[2].imshow(im_rec_lap_cg, cmap='viridis', vmin=0, vmax=250)
axs[2].axis('tight')
axs[2].set_title('2D Regularization')
axs[3].imshow(im - im_rec_lap_cg, cmap='gray', vmin=-80, vmax=80)

```

(continues on next page)


(continued from previous page)

```

axs[3].axis('tight')
axs[3].set_title('2D Regularization Error')
plt.tight_layout()
plt.subplots_adjust(top=0.8)

fig, axs = plt.subplots(1, 4, figsize=(12, 4))
fig.suptitle('Data reconstruction - regularized eqs', fontsize=14,
             fontweight='bold', y=0.95)
axs[0].imshow(im, cmap='viridis', vmin=0, vmax=250)
axs[0].axis('tight')
axs[0].set_title('Original')
axs[1].imshow(im_sampled, cmap='viridis', vmin=0, vmax=250)
axs[1].axis('tight')
axs[1].set_title('Sampled')
axs[2].imshow(im_rec_lap_lsqr, cmap='viridis', vmin=0, vmax=250)
axs[2].axis('tight')
axs[2].set_title('2D Regularization')
axs[3].imshow(im - im_rec_lap_lsqr, cmap='gray', vmin=-80, vmax=80)
axs[3].axis('tight')
axs[3].set_title('2D Regularization Error')
plt.tight_layout()
plt.subplots_adjust(top=0.8)

```



Total running time of the script: (0 minutes 14.312 seconds)

3.5.7 07. Post-stack inversion

Estimating subsurface properties from band-limited seismic data represents an important task for geophysical subsurface characterization.

In this tutorial, the `pylops.avo.poststack.PoststackLinearModelling` operator is used for modelling of both 1d and 2d synthetic post-stack seismic data from a profile or 2d model of the subsurface acoustic impedance.

$$d(t, \theta = 0) = \frac{1}{2} w(t) * \frac{d \ln(AI(t))}{dt}$$

where $AI(t)$ is the acoustic impedance profile and $w(t)$ is the time domain seismic wavelet. In compact form:

$$\mathbf{d} = \mathbf{W} \mathbf{D} \mathbf{a_i}$$

where \mathbf{W} is a convolution operator, \mathbf{D} is a first derivative operator, and $\mathbf{a_i}$ is the input model. Subsequently the acoustic impedance model is estimated via the `pylops.avo.poststack.PoststackInversion` module. A two-steps inversion strategy is finally presented to deal with the case of noisy data.

```
# sphinx_gallery_thumbnail_number = 4
import numpy as np
import matplotlib.pyplot as plt
from scipy.signal import filtfilt

import pylops
from pylops.utils.wavelets import ricker

plt.close('all')
np.random.seed(10)
```

Let's start with a 1d example. A synthetic profile of acoustic impedance is created and data is modelled using both the dense and linear operator version of `pylops.avo.poststack.PoststackLinearModelling` operator.

```
# model
nt0 = 301
dt0 = 0.004
t0 = np.arange(nt0)*dt0
vp = 1200 + np.arange(nt0) + \
    filtfilt(np.ones(5)/5., 1, np.random.normal(0, 80, nt0))
rho = 1000 + vp + \
    filtfilt(np.ones(5)/5., 1, np.random.normal(0, 30, nt0))
vp[131:] += 500
rho[131:] += 100
m = np.log(vp*rho)

# smooth model
nsmooth = 100
mback = filtfilt(np.ones(nsmooth)/float(nsmooth), 1, m)

# wavelet
ntwav = 41
wav, twav, wavc = ricker(t0[:ntwav//2+1], 20)

# dense operator
PPop_dense = \
    pylops.avo.poststack.PoststackLinearModelling(wav / 2, nt0=nt0, explicit=True)

# lop operator
```

(continues on next page)

(continued from previous page)

```

PPop = pylops.avo.poststack.PoststackLinearModelling(wav / 2, nt0=nt0)

# data
d_dense = PPop_dense*m.flatten()
d = PPop*m

# add noise
dn_dense = d_dense + np.random.normal(0, 2e-2, d_dense.shape)

```

We can now estimate the acoustic profile from band-limited data using either the dense operator or linear operator.

```


# solve dense
minv_dense = \
    pylops.avo.poststack.PoststackInversion(d, wav / 2, m0=mback, explicit=True,
                                             simultaneous=False)[0]

# solve lop
minv = \
    pylops.avo.poststack.PoststackInversion(d_dense, wav / 2, m0=mback,
                                             explicit=False,
                                             simultaneous=False,
                                             **dict(iter_lim=2000))[0]

# solve noisy
mn = \
    pylops.avo.poststack.PoststackInversion(dn_dense, wav / 2, m0=mback,
                                             explicit=True,
                                             epsR=1e0, **dict(damp=1e-1))[0]

fig, axs = plt.subplots(1, 2, figsize=(6, 7), sharey=True)
axs[0].plot(d_dense, t0, 'k', lw=4, label='Dense')
axs[0].plot(d, t0, '--r', lw=2, label='Lop')
axs[0].plot(dn_dense, t0, '-.g', lw=2, label='Noisy')
axs[0].set_title('Data')
axs[0].invert_yaxis()
axs[0].axis('tight')
axs[0].legend(loc=1)
axs[1].plot(m, t0, 'k', lw=4, label='True')
axs[1].plot(mback, t0, '--b', lw=4, label='Back')
axs[1].plot(minv_dense, t0, '--m', lw=2, label='Inv Dense')
axs[1].plot(minv, t0, '--r', lw=2, label='Inv Lop')
axs[1].plot(mn, t0, '--g', lw=2, label='Inv Noisy')
axs[1].set_title('Model')
axs[1].axis('tight')
axs[1].legend(loc=1)

```



Out:

```
<matplotlib.legend.Legend object at 0x7fc20a9bd518>
```

We see how inverting a dense matrix is in this case faster than solving for the linear operator (a good estimate of the model is in fact obtained only after 2000 iterations of lsqr). Nevertheless, having a linear operator is useful when we deal with larger dimensions (2d or 3d) and we want to couple our modelling operator with different types of spatial regularizations or preconditioning.

Before we move onto a 2d example, let's consider the case of non-stationary wavelet and see how we can easily use the same routines in this case

```

# wavelet
ntwav = 41
f0s = np.flip(np.arange(nt0) * 0.05 + 3)
wavs = np.array([ricker(t0[:ntwav], f0)[0] for f0 in f0s])
wavc = np.argmax(wavs[0])

plt.figure(figsize=(5, 4))
plt.imshow(wavs.T, cmap='gray', extent=(t0[0], t0[-1], t0[ntwav], -t0[ntwav]))
plt.xlabel('t')
plt.title('Wavelets')
plt.axis('tight')


# operator
PPop = \
    pylops.avo.poststack.PoststackLinearModelling(wavs / 2, nt0=nt0, explicit=True)


# data
d = PPop * m

# solve
minv = \
    pylops.avo.poststack.PoststackInversion(d, wavs / 2, m0=mback, explicit=True,
                                             **dict(cond=1e-10))[0]

fig, axs = plt.subplots(1, 2, figsize=(6, 7), sharey=True)
axs[0].plot(d, t0, 'k', lw=4)
axs[0].set_title('Data')
axs[0].invert_yaxis()
axs[0].axis('tight')
axs[1].plot(m, t0, 'k', lw=4, label='True')
axs[1].plot(mback, t0, '--b', lw=4, label='Back')
axs[1].plot(minv, t0, '--r', lw=2, label='Inv')
axs[1].set_title('Model')
axs[1].axis('tight')
axs[1].legend(loc=1)

```





Out:

```
<matplotlib.legend.Legend object at 0x7fc20ac5eb38>
```

We move now to a 2d example. First of all the model is loaded and data generated.

```
# model
inputfile = '../testdata/avo/poststack_model.npz'

model = np.load(inputfile)
m = np.log(model['model'][:, :, :3])
```

(continues on next page)

(continued from previous page)

```

x, z = model['x'][:, :3]/1000., model['z']/1000.
nx, nz = len(x), len(z)

# smooth model
nsmoothz, nsmoothx = 60, 50
mback = filtfilt(np.ones(nsmoothz)/float(nsmoothz), 1, m, axis=0)
mback = filtfilt(np.ones(nsmoothx)/float(nsmoothx), 1, mback, axis=1)

# dense operator
PPop_dense = \
    pylops.avopoststack.PoststackLinearModelling(wav / 2, nt0=nz,
                                                  spatdims=nx, explicit=True)

# lop operator
PPop = pylops.avopoststack.PoststackLinearModelling(wav / 2, nt0=nz,
                                                  spatdims=nx)

# data
d = (PPop_dense * m.flatten()).reshape(nz, nx)
n = np.random.normal(0, 1e-1, d.shape)
dn = d + n

```

Finally we perform 4 different inversions:

- trace-by-trace inversion with explicit solver and dense operator with noise-free data
- trace-by-trace inversion with explicit solver and dense operator with noisy data
- multi-trace regularized inversion with iterative solver and linear operator using the result of trace-by-trace inversion as starting guess

$$J = \|\Delta \mathbf{d} - \mathbf{W} \Delta \mathbf{a}\|_2 + \epsilon_{\nabla}^2 \|\nabla \mathbf{a}\|_2$$

where $\Delta \mathbf{d} = \mathbf{d} - \mathbf{W} \mathbf{A} \mathbf{I}_0$ is the residual data

- multi-trace blocky inversion with iterative solver and linear operator

```

# dense inversion with noise-free data
minv_dense = \
    pylops.avopoststack.PoststackInversion(d, wav / 2, m0=mback,
                                           explicit=True,
                                           simultaneous=False)[0]

# dense inversion with noisy data
minv_dense_noisy = \
    pylops.avopoststack.PoststackInversion(dn, wav / 2, m0=mback,
                                           explicit=True, epsI=4e-2,
                                           simultaneous=False)[0]

# spatially regularized lop inversion with noisy data
minv_lop_reg = \
    pylops.avopoststack.PoststackInversion(dn, wav / 2, m0=minv_dense_noisy,
                                           explicit=False, epsR=5e1,
                                           **dict(damp=np.sqrt(1e-4),
                                                  iter_lim=80))[0]

# blockiness promoting inversion with noisy data
minv_lop_blocky = \

```

(continues on next page)

(continued from previous page)

```

pylops.avo.poststack.PoststackInversion(dn, wav / 2, m0=mback,
                                         explicit=False,
                                         epsR=[0.4], epsRL1=[0.1],
                                         **dict(mu=0.1,
                                                niter_outer=5,
                                                niter_inner=10,
                                                iter_lim=5, damp=1e-3))[0]

fig, axs = plt.subplots(2, 4, figsize=(15, 9))
axs[0][0].imshow(d, cmap='gray',
                 extent=(x[0], x[-1], z[-1], z[0]),
                 vmin=-0.4, vmax=0.4)
axs[0][0].set_title('Data')
axs[0][0].axis('tight')
axs[0][1].imshow(dn, cmap='gray',
                 extent=(x[0], x[-1], z[-1], z[0]),
                 vmin=-0.4, vmax=0.4)
axs[0][1].set_title('Noisy Data')
axs[0][1].axis('tight')
axs[0][2].imshow(m, cmap='gist_rainbow',
                 extent=(x[0], x[-1], z[-1], z[0]),
                 vmin=m.min(), vmax=m.max())
axs[0][2].set_title('Model')
axs[0][2].axis('tight')
axs[0][3].imshow(mback, cmap='gist_rainbow',
                 extent=(x[0], x[-1], z[-1], z[0]),
                 vmin=m.min(), vmax=m.max())
axs[0][3].set_title('Smooth Model')
axs[0][3].axis('tight')
axs[1][0].imshow(minv_dense, cmap='gist_rainbow',
                 extent=(x[0], x[-1], z[-1], z[0]),
                 vmin=m.min(), vmax=m.max())
axs[1][0].set_title('Noise-free Inversion')
axs[1][0].axis('tight')
axs[1][1].imshow(minv_dense_noisy, cmap='gist_rainbow',
                 extent=(x[0], x[-1], z[-1], z[0]),
                 vmin=m.min(), vmax=m.max())
axs[1][1].set_title('Trace-by-trace Noisy Inversion')
axs[1][1].axis('tight')
axs[1][2].imshow(minv_lop_reg, cmap='gist_rainbow',
                 extent=(x[0], x[-1], z[-1], z[0]),
                 vmin=m.min(), vmax=m.max())
axs[1][2].set_title('Regularized Noisy Inversion - lop ')
axs[1][2].axis('tight')
axs[1][3].imshow(minv_lop_blocky, cmap='gist_rainbow',
                 extent=(x[0], x[-1], z[-1], z[0]),
                 vmin=m.min(), vmax=m.max())
axs[1][3].set_title('Blocky Noisy Inversion - lop ')
axs[1][3].axis('tight')

fig, ax = plt.subplots(1, 1, figsize=(3, 7))
ax.plot(m[:, nx//2], z, 'k', lw=4, label='True')
ax.plot(mback[:, nx//2], z, '--r', lw=4, label='Back')
ax.plot(minv_dense[:, nx//2], z, '--b', lw=2, label='Inv Dense')
ax.plot(minv_dense_noisy[:, nx//2], z, '--m', lw=2, label='Inv Dense noisy')
ax.plot(minv_lop_reg[:, nx//2], z, '--g', lw=2, label='Inv Lop regularized')
ax.plot(minv_lop_blocky[:, nx//2], z, '--y', lw=2, label='Inv Lop blocky')

```


(continues on next page)


(continued from previous page)

```

ax.set_title('Model')
ax.invert_yaxis()
ax.axis('tight')
ax.legend()
plt.tight_layout()

```





That's almost it. If you wonder how this can be applied to real data, head over to the following [notebook](#) where the open-source [segymio](#) library is used alongside `pylops` to create an end-to-end open-source seismic inversion workflow with SEG-Y input data.

Total running time of the script: (0 minutes 13.802 seconds)

3.5.8 08. Pre-stack (AVO) inversion

Pre-stack inversion represents one step beyond post-stack inversion in that not only the profile of acoustic impedance can be inferred from seismic data, rather a set of elastic parameters is estimated from pre-stack data (i.e., angle gathers) using the information contained in the so-called AVO (amplitude versus offset) response. Such elastic parameters

represent vital information for more sophisticated geophysical subsurface characterization than it would be possible to achieve working with post-stack seismic data.

In this tutorial, the `pylops.avo.prestack.PrestackLinearModelling` operator is used for modelling of both 1d and 2d synthetic pre-stack seismic data using 1d profiles or 2d models of different subsurface elastic parameters (P-wave velocity, S-wave velocity, and density) as input.

$$d(t, \theta) = w(t) * \sum_{i=1}^N G_i(t, \theta) \frac{d \ln(m_i(t))}{dt}$$

where $\mathbf{m}(t) = [V_P(t), V_S(t), \rho(t)]$ is a vector containing three elastic parameters at time t , $G_i(t, \theta)$ are the coefficients of the AVO parametrization used to model pre-stack data and $w(t)$ is the time domain seismic wavelet. In compact form:

$$\mathbf{d} = \mathbf{WGDm}$$

where \mathbf{W} is a convolution operator, \mathbf{G} is the AVO modelling operator, \mathbf{D} is a block-diagonal derivative operator, and \mathbf{m} is the input model. Subsequently the elastic parameters are estimated via the `pylops.avo.prestack.PrestackInversion` module. Once again, a two-steps inversion strategy can also be used to deal with the case of noisy data.

```
import numpy as np
import matplotlib.pyplot as plt
from scipy.signal import filtfilt

import pylops
from pylops.utils.wavelets import ricker

plt.close('all')
np.random.seed(0)
```

Let's start with a 1d example. A synthetic profile of acoustic impedance is created and data is modelled using both the dense and linear operator version of `pylops.avo.prestack.PrestackLinearModelling` operator

```
# sphinx_gallery_thumbnail_number = 5

# model
nt0 = 301
dt0 = 0.004

t0 = np.arange(nt0)*dt0
vp = 1200 + np.arange(nt0) + \
    filtfilt(np.ones(5)/5., 1, np.random.normal(0, 80, nt0))
vs = 600 + vp/2 + \
    filtfilt(np.ones(5)/5., 1, np.random.normal(0, 20, nt0))
rho = 1000 + vp + \
    filtfilt(np.ones(5)/5., 1, np.random.normal(0, 30, nt0))
vp[131:] += 500
vs[131:] += 200
rho[131:] += 100
vsvp = 0.5
m = np.stack((np.log(vp), np.log(vs), np.log(rho)), axis=1)

# background model
nsmooth = 50
mback = filtfilt(np.ones(nsmooth)/float(nsmooth), 1, m, axis=0)
```

(continues on next page)

(continued from previous page)

```

# angles
ntheta = 21
thetamin, thetamax = 0, 40
theta = np.linspace(thetamin, thetamax, ntheta)

# wavelet
ntwav = 41
wav = ricker(t0[:ntwav//2+1], 15)[0]

# lop
PPop = \
    pylops.avo.prestack.PrestackLinearModelling(wav, theta,
                                                  vsvp=vsvp, nt0=nt0,
                                                  linearization='akirich')

# dense
PPop_dense = \
    pylops.avo.prestack.PrestackLinearModelling(wav, theta,
                                                  vsvp=vsvp, nt0=nt0,
                                                  linearization='akirich',
                                                  explicit=True)

# data lop
dPP = PPop * m.flatten()
dPP = dPP.reshape(nt0, ntheta)

# data dense
dPP_dense = PPop_dense * m.T.flatten()
dPP_dense = dPP_dense.reshape(ntheta, nt0).T

# noisy data
dPPn_dense = dPP_dense + np.random.normal(0, 1e-2, dPP_dense.shape)

```

We can now invert our data and retrieve elastic profiles for both noise-free and noisy data using `pylops.avo.prestack.PrestackInversion`.

```

# dense
minv_dense, dPP_dense_res = \
    pylops.avo.prestack.PrestackInversion(dPP_dense, theta, wav, m0=mback,
                                          linearization='akirich',
                                          explicit=True, returnres=True,
                                          **dict(cond=1e-10))

# lop
minv, dPP_res = \
    pylops.avo.prestack.PrestackInversion(dPP, theta, wav, m0=mback,
                                          linearization='akirich',
                                          explicit=False, returnres=True,
                                          **dict(damp=1e-10, iter_lim=2000))

# dense noisy
minv_dense_noise, dPPn_dense_res = \
    pylops.avo.prestack.PrestackInversion(dPPn_dense, theta, wav, m0=mback,
                                          linearization='akirich',
                                          explicit=True,
                                          returnres=True, **dict(cond=1e-1))

```

(continues on next page)

(continued from previous page)

```
# lop noisy (with vertical smoothing)
minv_noise, dPPn_res = \
    pylops.avo.prestack.PrestackInversion(dPPn_dense, theta, wav, m0=mback,
                                          linearization='akirich',
                                          explicit=False,
                                          epsR=5e-1, returnres=True,
                                          **dict(damp=1e-1, iter_lim=100))
```

The data, inverted models and residuals are now displayed.

```
# data and model
fig, (axd, axdn, axvp, axvs, axrho) = \
    plt.subplots(1, 5, figsize=(8, 5), sharey=True)
axd.imshow(dPP_dense, cmap='gray',
           extent=(theta[0], theta[-1], t0[-1], t0[0]),
           vmin=-np.abs(dPP_dense).max(), vmax=np.abs(dPP_dense).max())
axd.set_title('Data')
axd.axis('tight')
axdn.imshow(dPPn_dense, cmap='gray',
           extent=(theta[0], theta[-1], t0[-1], t0[0]),
           vmin=-np.abs(dPPn_dense).max(), vmax=np.abs(dPPn_dense).max())
axdn.set_title('Noisy Data')
axdn.axis('tight')
axvp.plot(vp, t0, 'k', lw=4, label='True')
axvp.plot(np.exp(mback[:, 0]), t0, '--r', lw=4, label='Back')
axvp.plot(np.exp(minv_dense[:, 0]), t0, '--b', lw=2, label='Inv Dense')
axvp.plot(np.exp(minv[:, 0]), t0, '--m', lw=2, label='Inv Lop')
axvp.plot(np.exp(minv_dense_noise[:, 0]), t0, '--c', lw=2, label='Noisy Dense')
axvp.plot(np.exp(minv_noise[:, 0]), t0, '--g', lw=2, label='Noisy Lop')
axvp.set_title(r'$V\_P$')
axvs.plot(vs, t0, 'k', lw=4, label='True')
axvs.plot(np.exp(mback[:, 1]), t0, '--r', lw=4, label='Back')
axvs.plot(np.exp(minv_dense[:, 1]), t0, '--b', lw=2, label='Inv Dense')
axvs.plot(np.exp(minv[:, 1]), t0, '--m', lw=2, label='Inv Lop')
axvs.plot(np.exp(minv_dense_noise[:, 1]), t0, '--c', lw=2, label='Noisy Dense')
axvs.plot(np.exp(minv_noise[:, 1]), t0, '--g', lw=2, label='Noisy Lop')
axvs.set_title(r'$V\_S$')
axrho.plot(rho, t0, 'k', lw=4, label='True')
axrho.plot(np.exp(mback[:, 2]), t0, '--r', lw=4, label='Back')
axrho.plot(np.exp(minv_dense[:, 2]), t0, '--b', lw=2, label='Inv Dense')
axrho.plot(np.exp(minv[:, 2]), t0, '--m', lw=2, label='Inv Lop')
axrho.plot(np.exp(minv_dense_noise[:, 2]),
           t0, '--c', lw=2, label='Noisy Dense')
axrho.plot(np.exp(minv_noise[:, 2]), t0, '--g', lw=2, label='Noisy Lop')
axrho.set_title(r'$\rho$')
axrho.legend(loc='center left', bbox_to_anchor=(1, 0.5))
axd.axis('tight')
plt.tight_layout()

# residuals
fig, axs = plt.subplots(1, 4, figsize=(8, 5), sharey=True)
fig.suptitle('Residuals', fontsize=14,
            fontweight='bold', y=0.95)
im = axs[0].imshow(dPP_dense_res, cmap='gray',
                  extent=(theta[0], theta[-1], t0[-1], t0[0]),
                  vmin=-0.1, vmax=0.1)
```


(continues on next page)


(continued from previous page)

```

axs[0].set_title('Dense')
axs[0].set_xlabel(r'$\theta$')
axs[0].set_ylabel('t[s]')
axs[0].axis('tight')
axs[1].imshow(dPP_res, cmap='gray',
              extent=(theta[0], theta[-1], t0[-1], t0[0]),
              vmin=-0.1, vmax=0.1)
axs[1].set_title('Lop')
axs[1].set_xlabel(r'$\theta$')
axs[1].axis('tight')
axs[2].imshow(dPPn_dense_res, cmap='gray',
              extent=(theta[0], theta[-1], t0[-1], t0[0]),
              vmin=-0.1, vmax=0.1)
axs[2].set_title('Noisy Dense')
axs[2].set_xlabel(r'$\theta$')
axs[2].axis('tight')
axs[3].imshow(dPPn_res, cmap='gray',
              extent=(theta[0], theta[-1], t0[-1], t0[0]),
              vmin=-0.1, vmax=0.1)
axs[3].set_title('Noisy Lop')
axs[3].set_xlabel(r'$\theta$')
axs[3].axis('tight')
plt.tight_layout()
plt.subplots_adjust(top=0.85)

```





Finally before moving to the 2d example, we consider the case when both PP and PS data are available. A joint PP-PS inversion can be easily solved as follows.

```
PSop = \
    pylops.avo.prestack.PrestackLinearModelling(2 * wav, theta,
                                                vsvp=vsvp, nt0=nt0,
                                                linearization='ps')

PPPSop = pylops.VStack((PPop, PSop))

# data
dPPPS = PPPSop * m.flatten()
dPPPS = dPPPS.reshape(2, nt0, ntheta)

dPPPSn = dPPPS + np.random.normal(0, 1e-2, dPPPS.shape)

# Invert
minvPPSP, dPPPS_res = \
    pylops.avo.prestack.PrestackInversion(dPPPS, theta,
                                          [wav, 2 * wav], m0=mback,
                                          linearization=['fatti', 'ps'],
                                          epsR=5e-1, returnres=True,
                                          **dict(damp=1e-1, iter_lim=100))

# Data and model
fig, (axd, axdn, axvp, axvs, axrho) = \
    plt.subplots(1, 5, figsize=(8, 5), sharey=True)
axd.imshow(dPPPSn[0], cmap='gray',
           extent=(theta[0], theta[-1], t0[-1], t0[0]),
           vmin=-np.abs(dPPPSn[0]).max(), vmax=np.abs(dPPPSn[0]).max())
axd.set_title('PP Data')
axd.axis('tight')
axdn.imshow(dPPPSn[1], cmap='gray',
```


(continues on next page)

(continued from previous page)

```

        extent=(theta[0], theta[-1], t0[-1], t0[0]),
        vmin=-np.abs(dPPPSn[1]).max(), vmax=np.abs(dPPPSn[1]).max())
axdn.set_title('PS Data')
axdn.axis('tight')
axvp.plot(vp, t0, 'k', lw=4, label='True')
axvp.plot(np.exp(mback[:, 0]), t0, '--r', lw=4, label='Back')
axvp.plot(np.exp(minv_noise[:, 0]), t0, '--g', lw=2, label='PP')
axvp.plot(np.exp(minvPPSP[:, 0]), t0, '--b', lw=2, label='PP+PS')
axvp.set_title(r'$V_P$')
axvs.plot(vs, t0, 'k', lw=4, label='True')
axvs.plot(np.exp(mback[:, 1]), t0, '--r', lw=4, label='Back')
axvs.plot(np.exp(minv_noise[:, 1]), t0, '--g', lw=2, label='PP')
axvs.plot(np.exp(minvPPSP[:, 1]), t0, '--b', lw=2, label='PP+PS')
axvs.set_title(r'$V_S$')
axrho.plot(rho, t0, 'k', lw=4, label='True')
axrho.plot(np.exp(mback[:, 2]), t0, '--r', lw=4, label='Back')
axrho.plot(np.exp(minv_noise[:, 2]), t0, '--g', lw=2, label='PP')
axrho.plot(np.exp(minvPPSP[:, 2]), t0, '--b', lw=2, label='PP+PS')
axrho.set_title(r'$\rho$')
axrho.legend(loc='center left', bbox_to_anchor=(1, 0.5))
axd.axis('tight')
plt.tight_layout()

```



We move now to a 2d example. First of all the model is loaded and data generated.

```

# model
inputfile = '../testdata/avo/poststack_model.npz'

model = np.load(inputfile)

```

(continues on next page)

(continued from previous page)

```

x, z = model['x'][:, :6]/1000., model['z'][:300]/1000.
nx, nz = len(x), len(z)
m = 1000*model['model'][:300, :6]

mvp = m.copy()
mvs = m/2
mrho = m/3+300
m = np.log(np.stack((mvp, mvs, mrho), axis=1))

# smooth model
nsmoothz, nsmoothx = 30, 25
mback = filtfilt(np.ones(nsmoothz)/float(nsmoothz), 1, m, axis=0)
mback = filtfilt(np.ones(nsmoothx)/float(nsmoothx), 1, mback, axis=2)

# dense operator
PPop_dense = \
    pylops.avoprestack.PrestackLinearModelling(wav, theta, vsvp=vsvp,
                                                nt0=nz, spatdims=(nx, ),
                                                linearization='akirich',
                                                explicit=True)

# lop operator
PPop = pylops.avoprestack.PrestackLinearModelling(wav, theta, vsvp=vsvp,
                                                nt0=nz, spatdims=(nx, ),
                                                linearization='akirich')

# data
dPP = PPop_dense*m.swapaxes(0, 1).flatten()
dPP = dPP.reshape(ntheta, nz, nx).swapaxes(0, 1)
dPPn = dPP + np.random.normal(0, 5e-2, dPP.shape)

```

Finally we perform the same 4 different inversions as in the post-stack tutorial (see [07. Post-stack inversion](#) for more details).

```

# dense inversion with noise-free data
minv_dense = \
    pylops.avoprestack.PrestackInversion(dPP, theta, wav, m0=mback,
                                         explicit=True,
                                         simultaneous=False)

# dense inversion with noisy data
minv_dense_noisy = \
    pylops.avoprestack.PrestackInversion(dPPn, theta, wav, m0=mback,
                                         explicit=True, epsI=4e-2,
                                         simultaneous=False)

# spatially regularized lop inversion with noisy data
minv_lop_reg = \
    pylops.avoprestack.PrestackInversion(dPPn, theta, wav,
                                         m0=minv_dense_noisy,
                                         explicit=False, epsR=1e1,
                                         **dict(damp=np.sqrt(1e-4),
                                                iter_lim=20))

# blockiness promoting inversion with noisy data
minv_blocky = \

```

(continues on next page)

(continued from previous page)

```

pylops.avo.prestack.PrestackInversion(dPPn, theta, wav,
                                       m0=mback,
                                       explicit=False,
                                       epsR=0.4, epsRL1=0.1,
                                       **dict(mu=0.1,
                                              niter_outer=3,
                                              niter_inner=3,
                                              iter_lim=5, damp=1e-3))

```

Let's now visualize the inverted elastic parameters for the different scenarios

```

def plotmodel(axes, m, x, z, vmin, vmax,
              params=('VP', 'VS', 'Rho'),
              cmap='gist_rainbow', title=None):
    """Quick visualization of model
    """
    for ip, param in enumerate(params):
        axes[ip].imshow(m[:, ip],
                       extent=(x[0], x[-1], z[-1], z[0]),
                       vmin=vmin, vmax=vmax, cmap=cmap)
        axes[ip].set_title('%s - %s' % (param, title))
        axes[ip].axis('tight')
    plt.setp(axes[1].get_yticklabels(), visible=False)
    plt.setp(axes[2].get_yticklabels(), visible=False)

# data
fig = plt.figure(figsize=(8, 9))
ax1 = plt.subplot2grid((2, 3), (0, 0), colspan=3)
ax2 = plt.subplot2grid((2, 3), (1, 0))
ax3 = plt.subplot2grid((2, 3), (1, 1), sharey=ax2)
ax4 = plt.subplot2grid((2, 3), (1, 2), sharey=ax2)
ax1.imshow(dPP[:, 0], cmap='gray',
           extent=(x[0], x[-1], z[-1], z[0]),
           vmin=-0.4, vmax=0.4)
ax1.vlines([x[nx//5], x[nx//2], x[4*nx//5]], ymin=z[0], ymax=z[-1],
           colors='w', linestyle='--')
ax1.set_xlabel('x [km]')
ax1.set_ylabel('z [km]')
ax1.set_title(r'Stack ($\theta=0$)')
ax1.axis('tight')
ax2.imshow(dPP[:, :, nx//5], cmap='gray',
           extent=(theta[0], theta[-1], z[-1], z[0]),
           vmin=-0.4, vmax=0.4)
ax2.set_xlabel(r'$\theta$')
ax2.set_ylabel('z [km]')
ax2.set_title(r'Gather (x=%2f)' % x[nx//5])
ax2.axis('tight')
ax3.imshow(dPP[:, :, nx//2], cmap='gray',
           extent=(theta[0], theta[-1], z[-1], z[0]),
           vmin=-0.4, vmax=0.4)
ax3.set_xlabel(r'$\theta$')
ax3.set_title(r'Gather (x=%2f)' % x[nx//2])
ax3.axis('tight')
ax4.imshow(dPP[:, :, 4*nx//5], cmap='gray',
           extent=(theta[0], theta[-1], z[-1], z[0]),
           vmin=-0.4, vmax=0.4)
ax4.set_xlabel(r'$\theta$')

```

(continues on next page)

(continued from previous page)

```

ax4.set_title(r'Gather (x=%.2f)' % x[4*nx//5])
ax4.axis('tight')
plt.setp(ax3.get_yticklabels(), visible=False)
plt.setp(ax4.get_yticklabels(), visible=False)

# noisy data
fig = plt.figure(figsize=(8, 9))
ax1 = plt.subplot2grid((2, 3), (0, 0), colspan=3)
ax2 = plt.subplot2grid((2, 3), (1, 0))
ax3 = plt.subplot2grid((2, 3), (1, 1), sharey=ax2)
ax4 = plt.subplot2grid((2, 3), (1, 2), sharey=ax2)
ax1.imshow(dPPn[:, 0], cmap='gray',
            extent=(x[0], x[-1], z[-1], z[0]),
            vmin=-0.4, vmax=0.4)
ax1.vlines([x[nx//5], x[nx//2], x[4*nx//5]], ymin=z[0], ymax=z[-1],
            colors='w', linestyle='--')
ax1.set_xlabel('x [km]')
ax1.set_ylabel('z [km]')
ax1.set_title(r'Noisy Stack ($\theta=0$)')
ax1.axis('tight')
ax2.imshow(dPPn[:, :, nx//5], cmap='gray',
            extent=(theta[0], theta[-1], z[-1], z[0]),
            vmin=-0.4, vmax=0.4)
ax2.set_xlabel(r'$\theta$')
ax2.set_ylabel('z [km]')
ax2.set_title(r'Gather (x=%.2f)' % x[nx//5])
ax2.axis('tight')
ax3.imshow(dPPn[:, :, nx//2], cmap='gray',
            extent=(theta[0], theta[-1], z[-1], z[0]),
            vmin=-0.4, vmax=0.4)
ax3.set_title(r'Gather (x=%.2f)' % x[nx//2])
ax3.set_xlabel(r'$\theta$')
ax3.axis('tight')
ax4.imshow(dPPn[:, :, 4*nx//5], cmap='gray',
            extent=(theta[0], theta[-1], z[-1], z[0]),
            vmin=-0.4, vmax=0.4)
ax4.set_xlabel(r'$\theta$')
ax4.set_title(r'Gather (x=%.2f)' % x[4*nx//5])
ax4.axis('tight')
plt.setp(ax3.get_yticklabels(), visible=False)
plt.setp(ax4.get_yticklabels(), visible=False)

# inverted models
fig, axs = plt.subplots(6, 3, figsize=(8, 19))
fig.suptitle('Model', fontsize=12, fontweight='bold', y=0.95)
plotmodel(axs[0], m, x, z, m.min(),
           m.max(), title='True')
plotmodel(axs[1], mback, x, z, m.min(),
           m.max(), title='Back')
plotmodel(axs[2], minv_dense, x, z,
           m.min(), m.max(), title='Dense')
plotmodel(axs[3], minv_dense_noisy, x, z,
           m.min(), m.max(), title='Dense noisy')
plotmodel(axs[4], minv_lop_reg, x, z,
           m.min(), m.max(), title='Lop regularized')
plotmodel(axs[5], minv_blocky, x, z,
           m.min(), m.max(), title='Lop blocky')


```

(continues on next page)


(continued from previous page)

```
plt.tight_layout()
plt.subplots_adjust(top=0.92)


fig, axs = plt.subplots(1, 3, figsize=(8, 7))
for ip, param in enumerate(['VP', 'VS', 'Rho']):
    axs[ip].plot(m[:, ip, nx//2], z, 'k', lw=4, label='True')
    axs[ip].plot(mback[:, ip, nx//2], z, '--r', lw=4, label='Back')
    axs[ip].plot(minv_dense[:, ip, nx//2], z, '--b', lw=2, label='Inv Dense')
    axs[ip].plot(minv_dense_noisy[:, ip, nx//2], z, '--m', lw=2,
                 label='Inv Dense noisy')
    axs[ip].plot(minv_lop_reg[:, ip, nx//2], z, '--g', lw=2,
                 label='Inv Lop regularized')
    axs[ip].plot(minv_blocky[:, ip, nx // 2], z, '--y', lw=2,
                 label='Inv Lop blocky')
    axs[ip].set_title(param)
    axs[ip].invert_yaxis()
axs[2].legend(loc=8, fontsize='small')
```




•



•





Out:


```
<matplotlib.legend.Legend object at 0x7fc20a390390>
```

While the background model `m0` has been provided in all the examples so far, it is worth showing that the module `pylops.avo.prestack.PrestackInversion` can also produce so-called relative elastic parameters (i.e., variations from an average medium property) when the background model `m0` is not available.

```
dminv = \
    pylops.avo.prestack.PrestackInversion(dPP, theta, wav, m0=None,
                                          explicit=True,
                                          simultaneous=False)

fig, axs = plt.subplots(1, 3, figsize=(8, 3))
plotmodel(axs, dminv, x, z, -dminv.max(), dminv.max(),
          cmap='seismic', title='relative')

fig, axs = plt.subplots(1, 3, figsize=(8, 7))
for ip, param in enumerate(['VP', 'VS', 'Rho']):
    axs[ip].plot(dminv[:, ip, nx//2], z, 'k', lw=2)
    axs[ip].set_title(param)
    axs[ip].invert_yaxis()
```

Total running time of the script: (0 minutes 33.164 seconds)

3.5.9 09. Multi-Dimensional Deconvolution

This example shows how to set-up and run the `pylops.waveeqprocessing.MDD` inversion using synthetic data.

```

import warnings
import numpy as np
import matplotlib.pyplot as plt
import pylops

from pylops.utils.tapers import taper3d
from pylops.utils.wavelets import ricker
from pylops.utils.seismicevents import makeaxis, hyperbolic2d

warnings.filterwarnings('ignore')
plt.close('all')

# sphinx_gallery_thumbnail_number = 5

```

Let's start by creating a set of hyperbolic events to be used as our MDC kernel

```

# Input parameters
par = {'ox':-150, 'dx':10, 'nx':31,
       'oy':-250, 'dy':10, 'ny':51,
       'ot':0, 'dt':0.004, 'nt':300,
       'f0': 20, 'nfmax': 200}

t0_m = [0.2]
vrms_m = [700.]
amp_m = [1.]

t0_G = [0.2, 0.5, 0.7]
vrms_G = [800., 1200., 1500.]
amp_G = [1., 0.6, 0.5]

# Taper
tap = taper3d(par['nt'], [par['ny'], par['nx']],
              (5, 5), tapertype='hanning')

# Create axis
t, t2, x, y = makeaxis(par)

# Create wavelet
wav = ricker(t[:41], f0=par['f0'])[0]

# Generate model
m, mwav = hyperbolic2d(x, t, t0_m, vrms_m, amp_m, wav)

# Generate operator
G, Gwav = np.zeros((par['ny'], par['nx'], par['nt'])), \
          np.zeros((par['ny'], par['nx'], par['nt']))
for iy, y0 in enumerate(y):
    G[iy], Gwav[iy] = hyperbolic2d(x-y0, t, t0_G, vrms_G, amp_G, wav)
G, Gwav = G*tap, Gwav*tap

# Add negative part to data and model
m = np.concatenate((np.zeros((par['nx'], par['nt']-1)), m), axis=-1)
mwav = np.concatenate((np.zeros((par['nx'], par['nt']-1)), mwav), axis=-1)
Gwav2 = np.concatenate((np.zeros((par['ny'], par['nx'], par['nt']-1)), Gwav),
                       axis=-1)

# Define MDC linear operator

```

(continues on next page)

(continued from previous page)

```

Gwav_fft = np.fft.rfft(Gwav2, 2*par['nt']-1, axis=-1)
Gwav_fft = Gwav_fft[..., :par['nfmax']]

MDCop = pylops.waveeqprocessing.MDC(Gwav_fft, nt=2 * par['nt']-1, nv=1,
                                     dt=0.004, dr=1., dtype='float32')

# Create data
d = MDCop*m.flatten()
d = d.reshape(par['ny'], 2*par['nt']-1)

```



Let's display what we have so far: operator, input model, and data

```


fig, axs = plt.subplots(1, 2, figsize=(8, 6))
axs[0].imshow(Gwav2[int(par['ny']/2)].T, aspect='auto',
               interpolation='nearest', cmap='gray',
               vmin=-np.abs(Gwav2.max()), vmax=np.abs(Gwav2.max()),
               extent=(x.min(), x.max(), t2.max(), t2.min()))
axs[0].set_title('G - inline view', fontsize=15)
axs[0].set_xlabel(r'$x_R$')
axs[1].set_ylabel(r'$t$')
axs[1].imshow(Gwav2[:, int(par['nx']/2)].T, aspect='auto',
               interpolation='nearest', cmap='gray',
               vmin=-np.abs(Gwav2.max()), vmax=np.abs(Gwav2.max()),
               extent=(y.min(), y.max(), t2.max(), t2.min()))
axs[1].set_title('G - inline view', fontsize=15)
axs[1].set_xlabel(r'$x_{SS}$')
axs[1].set_ylabel(r'$t$')
fig.tight_layout()

fig, axs = plt.subplots(1, 2, figsize=(8, 6))
axs[0].imshow(mwav.T, aspect='auto', interpolation='nearest', cmap='gray',
               vmin=-np.abs(mwav.max()), vmax=np.abs(mwav.max()),
               extent=(x.min(), x.max(), t2.max(), t2.min()))
axs[0].set_title(r'$m$', fontsize=15)
axs[0].set_xlabel(r'$x_R$')
axs[1].set_ylabel(r'$t$')
axs[1].imshow(d.T, aspect='auto', interpolation='nearest', cmap='gray',
               vmin=-np.abs(d.max()), vmax=np.abs(d.max()),
               extent=(x.min(), x.max(), t2.max(), t2.min()))
axs[1].set_title(r'$d$', fontsize=15)
axs[1].set_xlabel(r'$x_{SS}$')
axs[1].set_ylabel(r'$t$')
fig.tight_layout()

```



•



We are now ready to feed our operator to `pylops.waveeqprocessing.MDD` and invert back for our input model

```
minv, madj, psfinv, psfadj = \
    pylops.waveeqprocessing.MDD(Gwav, d[:, par['nt'] - 1:],
                                dt=par['dt'], dr=par['dx'],
                                nfmax=par['nfmax'], wav=wav,
                                twosided=True, add_negative=True,
                                adjoint=True, psf=True,
                                dtype='complex64', dottest=False,
                                **dict(damp=1e-4, iter_lim=20, show=0))

fig = plt.figure(figsize=(8, 6))
ax1 = plt.subplot2grid((1, 5), (0, 0), colspan=2)
ax2 = plt.subplot2grid((1, 5), (0, 2), colspan=2)
ax3 = plt.subplot2grid((1, 5), (0, 4))
ax1.imshow(madj.T, aspect='auto', interpolation='nearest', cmap='gray',
            vmin=-np.abs(madj.max()), vmax=np.abs(madj.max()),
            extent=(x.min(), x.max(), t2.max(), t2.min()))
ax1.set_title('Adjoint m', fontsize=15)
ax1.set_xlabel(r'$x_V$')
axs[1].set_ylabel(r'$t$')
ax2.imshow(minv.T, aspect='auto', interpolation='nearest', cmap='gray',
            vmin=-np.abs(minv.max()), vmax=np.abs(minv.max()),
            extent=(x.min(), x.max(), t2.max(), t2.min()))
ax2.set_title('Inverted m', fontsize=15)
ax2.set_xlabel(r'$x_V$')
axs[1].set_ylabel(r'$t$')
```

(continues on next page)


(continued from previous page)


```

ax3.plot(madj[int(par['nx']/2)]/np.abs(madj[int(par['nx']/2))).max(),
         t2, 'r', lw=5)
ax3.plot(minv[int(par['nx']/2)]/np.abs(minv[int(par['nx']/2))).max(),
         t2, 'k', lw=3)
ax3.set_ylim([t2[-1], t2[0]])
fig.tight_layout()

fig, axs = plt.subplots(1, 2, figsize=(8, 6))
axs[0].imshow(psfinv[int(par['nx']/2)].T,
              aspect='auto', interpolation='nearest',
              vmin=-np.abs(psfinv.max()), vmax=np.abs(psfinv.max()),
              cmap='gray', extent=(x.min(), x.max(), t2.max(), t2.min()))
axs[0].set_title('Inverted psf - inline view', fontsize=15)
axs[0].set_xlabel(r'$x_V$')
axs[1].set_ylabel(r'$t$')
axs[1].imshow(psfinv[:, int(par['nx']/2)].T,
              aspect='auto', interpolation='nearest',
              vmin=-np.abs(psfinv.max()), vmax=np.abs(psfinv.max()),
              cmap='gray', extent=(y.min(), y.max(), t2.max(), t2.min()))
axs[1].set_title('Inverted psf - xline view', fontsize=15)
axs[1].set_xlabel(r'$x_V$')
axs[1].set_ylabel(r'$t$')
fig.tight_layout()

```





We repeat the same procedure but this time we will add a preconditioning by means of `causality_precond` parameter, which enforces the inverted model to be zero in the negative part of the time axis (as expected by theory). This preconditioning will have the effect of speeding up the convergence of the iterative solver and thus reduce the computation time of the deconvolution

```
minvprec = pyllops.waveeqprocessing.MDD(Gwav, d[:, par['nt'] - 1:],
                                         dt=par['dt'], dr=par['dx'],
                                         nfmax=par['nfmax'], wav=wav,
                                         twosided=True, add_negative=True,
                                         adjoint=False, psf=False,
                                         causality_precond=True,
                                         dtype='complex64',
                                         dottest=False,
                                         **dict(damp=1e-4, iter_lim=50, show=0))

fig = plt.figure(figsize=(8, 6))
ax1 = plt.subplot2grid((1, 5), (0, 0), colspan=2)
ax2 = plt.subplot2grid((1, 5), (0, 2), colspan=2)
ax3 = plt.subplot2grid((1, 5), (0, 4))
ax1.imshow(madj.T, aspect='auto', interpolation='nearest', cmap='gray',
           vmin=-np.abs(madj.max()), vmax=np.abs(madj.max()),
           extent=(x.min(), x.max(), t2.max(), t2.min()))
ax1.set_title('Adjoint m', fontsize=15)
ax1.set_xlabel(r'$x_V$')
axs[1].set_ylabel(r'$t$')
ax2.imshow(minvprec.T, aspect='auto', interpolation='nearest', cmap='gray',
           vmin=-np.abs(minvprec.max()), vmax=np.abs(minvprec.max()),
```


(continues on next page)

(continued from previous page)

```

        extent=(x.min(), x.max(), t2.max(), t2.min()))
ax2.set_title('Inverted m', fontsize=15)
ax2.set_xlabel(r'$x_V$')
axs[1].set_ylabel(r'$t$')
ax3.plot(madj[int(par['nx']/2)]/np.abs(madj[int(par['nx']/2)]).max(),
         t2, 'r', lw=5)
ax3.plot(minvprec[int(par['nx']/2)]/np.abs(minv[int(par['nx']/2)]).max(),
         t2, 'k', lw=3)
ax3.set_ylim([t2[-1], t2[0]])
fig.tight_layout()

```



Total running time of the script: (0 minutes 10.041 seconds)

3.5.10 10. Marchenko redatuming by inversion

This example shows how to set-up and run the `pylops.waveeqprocessing.Marchenko` inversion using synthetic data.

```

# sphinx_gallery_thumbnail_number = 5
# pylint: disable=C0103
import warnings
import numpy as np
import matplotlib.pyplot as plt

```

(continues on next page)

(continued from previous page)

```

from scipy.signal import convolve
from pylops.waveeqprocessing import Marchenko

warnings.filterwarnings('ignore')
plt.close('all')

```

Let's start by defining some input parameters and loading the test data

```

# Input parameters
inputfile = '../testdata/marchenko/input.npz'

vel = 2400.0          # velocity
toff = 0.045         # direct arrival time shift
nsmooth = 10         # time window smoothing
nfmax = 1000         # max frequency for MDC (#samples)
niter = 10           # iterations

inputdata = np.load(inputfile)

# Receivers
r = inputdata['r']
nr = r.shape[1]
dr = r[0, 1]-r[0, 0]

# Sources
s = inputdata['s']
ns = s.shape[1]
ds = s[0, 1]-s[0, 0]

# Virtual points
vs = inputdata['vs']

# Density model
rho = inputdata['rho']
z, x = inputdata['z'], inputdata['x']

# Reflection data (R[s, r, t]) and subsurface fields
R = inputdata['R'][:, :, :-100]
R = np.swapaxes(R, 0, 1) # just because of how the data was saved

Gsub = inputdata['Gsub'][:-100]
G0sub = inputdata['G0sub'][:-100]
wav = inputdata['wav']
wav_c = np.argmax(wav)

t = inputdata['t'][:-100]
ot, dt, nt = t[0], t[1]-t[0], len(t)

Gsub = np.apply_along_axis(convolve, 0, Gsub, wav, mode='full')
Gsub = Gsub[wav_c:][:nt]
G0sub = np.apply_along_axis(convolve, 0, G0sub, wav, mode='full')
G0sub = G0sub[wav_c:][:nt]

plt.figure(figsize=(10, 5))
plt.imshow(rho, cmap='gray', extent=(x[0], x[-1], z[-1], z[0]))
plt.scatter(s[0, 5::10], s[1, 5::10], marker='*', s=150, c='r', edgecolors='k')

```



(continues on next page)


(continued from previous page)

```
plt.scatter(r[0, ::10], r[1, ::10], marker='v', s=150, c='b', edgecolors='k')
plt.scatter(vs[0], vs[1], marker='.', s=250, c='m', edgecolors='k')
plt.axis('tight')
plt.xlabel('x [m]')
plt.ylabel('y [m]')
plt.title('Model and Geometry')
plt.xlim(x[0], x[-1])
```

```
fig, axs = plt.subplots(1, 3, sharey=True, figsize=(12, 7))
axs[0].imshow(R[0].T, cmap='gray', vmin=-1e-2, vmax=1e-2,
              extent=(r[0, 0], r[0, -1], t[-1], t[0]))
axs[0].set_title('R shot=0')
axs[0].set_xlabel(r'$x_{R}$')
axs[0].set_ylabel(r'$t$')
axs[0].axis('tight')
axs[0].set_ylim(1.5, 0)
axs[1].imshow(R[ns//2].T, cmap='gray', vmin=-1e-2, vmax=1e-2,
              extent=(r[0, 0], r[0, -1], t[-1], t[0]))
axs[1].set_title('R shot=%d' %(ns//2))
axs[1].set_xlabel(r'$x_{R}$')
axs[1].set_ylabel(r'$t$')
axs[1].axis('tight')
axs[1].set_ylim(1.5, 0)
axs[2].imshow(R[-1].T, cmap='gray', vmin=-1e-2, vmax=1e-2,
              extent=(r[0, 0], r[0, -1], t[-1], t[0]))
axs[2].set_title('R shot=%d' %ns)
axs[2].set_xlabel(r'$x_{R}$')
axs[2].axis('tight')
axs[2].set_ylim(1.5, 0)
fig.tight_layout()
```

```
fig, axs = plt.subplots(1, 2, sharey=True, figsize=(8, 6))
axs[0].imshow(Gsub, cmap='gray', vmin=-1e6, vmax=1e6,
              extent=(r[0, 0], r[0, -1], t[-1], t[0]))
axs[0].set_title('G')
axs[0].set_xlabel(r'$x_{R}$')
axs[0].set_ylabel(r'$t$')
axs[0].axis('tight')
axs[0].set_ylim(1.5, 0)
axs[1].imshow(G0sub, cmap='gray', vmin=-1e6, vmax=1e6,
              extent=(r[0, 0], r[0, -1], t[-1], t[0]))
axs[1].set_title('G0')
axs[1].set_xlabel(r'$x_{R}$')
axs[1].set_ylabel(r'$t$')
axs[1].axis('tight')
axs[1].set_ylim(1.5, 0)
fig.tight_layout()
```





Let's now create an object of the `pylops.waveeqprocessing.Marchenko` class and apply redatuming for a single subsurface point vs.

```
# direct arrival window
trav = np.sqrt((vs[0]-r[0])**2+(vs[1]-r[1])**2)/vel

MarchenkoWM = Marchenko(R, dt=dt, dr=dr, nfmax=nfmax, wav=wav,
                        toff=toff, nsmooth=nsmooth)

fl_inv_minus, fl_inv_plus, p0_minus, g_inv_minus, g_inv_plus = \
    MarchenkoWM.apply_onepoint(trav, G0=G0sub.T, rtm=True, greens=True,
                              dottest=True, **dict(iter_lim=niter, show=True))
g_inv_tot = g_inv_minus + g_inv_plus
```

Out:

```
Dot test passed, v^T(Opu)=405.165096 - u^T(Op^Tv)=405.165096
Dot test passed, v^T(Opu)=172.065076 - u^T(Op^Tv)=172.065076
```

```
LSQR          Least-squares solution of  Ax = b
The matrix A has 282598 rows and 282598 columns
damp = 0.0000000000000000e+00   calc_var =      0
atol = 1.00e-08                 conlim = 1.00e+08
btol = 1.00e-08                 iter_lim =     10
```

Itn	x[0]	rlnorm	r2norm	Compatible	LS	Norm A	Cond A
0	0.000000e+00	3.134e+07	3.134e+07	1.0e+00	3.3e-08		

(continues on next page)

(continued from previous page)

1	0.000000e+00	1.374e+07	1.374e+07	4.4e-01	9.3e-01	1.1e+00	1.0e+00
2	0.000000e+00	7.770e+06	7.770e+06	2.5e-01	3.9e-01	1.8e+00	2.2e+00
3	0.000000e+00	5.750e+06	5.750e+06	1.8e-01	3.3e-01	2.1e+00	3.4e+00
4	0.000000e+00	3.930e+06	3.930e+06	1.3e-01	3.4e-01	2.5e+00	5.1e+00
5	0.000000e+00	3.042e+06	3.042e+06	9.7e-02	2.6e-01	2.9e+00	6.8e+00
6	0.000000e+00	2.423e+06	2.423e+06	7.7e-02	2.2e-01	3.3e+00	8.6e+00
7	0.000000e+00	1.675e+06	1.675e+06	5.3e-02	2.5e-01	3.6e+00	1.1e+01
8	0.000000e+00	1.248e+06	1.248e+06	4.0e-02	2.0e-01	3.9e+00	1.3e+01
9	0.000000e+00	1.004e+06	1.004e+06	3.2e-02	1.5e-01	4.2e+00	1.4e+01
10	0.000000e+00	7.762e+05	7.762e+05	2.5e-02	1.8e-01	4.4e+00	1.6e+01

LSQR finished

The iteration limit has been reached

```

istop =      7    rlnorm = 7.8e+05    anorm = 4.4e+00    arnorm = 6.1e+05
itn    =     10    r2norm = 7.8e+05    acond = 1.6e+01    xnorm  = 3.6e+07

```

We can now compare the result of Marchenko redatuming via LSQR with standard redatuming

```

fig, axs = plt.subplots(1, 3, sharey=True, figsize=(12, 7))
axs[0].imshow(p0_minus.T, cmap='gray', vmin=-5e5, vmax=5e5,
               extent=(r[0, 0], r[0, -1], t[-1], -t[-1]))
axs[0].set_title(r'$p_0^-$')
axs[0].set_xlabel(r'$x_R$')
axs[0].set_ylabel(r'$t$')
axs[0].axis('tight')
axs[0].set_ylim(1.2, 0)
axs[1].imshow(g_inv_minus.T, cmap='gray', vmin=-5e5, vmax=5e5,
               extent=(r[0, 0], r[0, -1], t[-1], -t[-1]))
axs[1].set_title(r'$g^-$')
axs[1].set_xlabel(r'$x_R$')
axs[1].set_ylabel(r'$t$')
axs[1].axis('tight')
axs[1].set_ylim(1.2, 0)
axs[2].imshow(g_inv_plus.T, cmap='gray', vmin=-5e5, vmax=5e5,
               extent=(r[0, 0], r[0, -1], t[-1], -t[-1]))
axs[2].set_title(r'$g^+$')
axs[2].set_xlabel(r'$x_R$')
axs[2].set_ylabel(r'$t$')
axs[2].axis('tight')
axs[2].set_ylim(1.2, 0)
fig.tight_layout()

```

```

fig = plt.figure(figsize=(12, 7))
ax1 = plt.subplot2grid((1, 5), (0, 0), colspan=2)
ax2 = plt.subplot2grid((1, 5), (0, 2), colspan=2)
ax3 = plt.subplot2grid((1, 5), (0, 4))
ax1.imshow(Gsub, cmap='gray', vmin=-5e5, vmax=5e5,
            extent=(r[0, 0], r[0, -1], t[-1], t[0]))
ax1.set_title(r'$G_{\{true\}}$')
axs[0].set_xlabel(r'$x_R$')
axs[0].set_ylabel(r'$t$')
ax1.axis('tight')
ax1.set_ylim(1.2, 0)
ax2.imshow(g_inv_tot.T, cmap='gray', vmin=-5e5, vmax=5e5,
            extent=(r[0, 0], r[0, -1], t[-1], -t[-1]))
ax2.set_title(r'$G_{\{est\}}$')

```


(continues on next page)

(continued from previous page)

```

axs[1].set_xlabel(r'$x_R$')
axs[1].set_ylabel(r'$t$')
ax2.axis('tight')
ax2.set_ylim(1.2, 0)
ax3.plot(Gsub[:, nr//2]/Gsub.max(), t, 'r', lw=5)
ax3.plot(g_inv_tot[nr//2, nt-1:]/g_inv_tot.max(), t, 'k', lw=3)
ax3.set_ylim(1.2, 0)
fig.tight_layout()

```



Note that Marchenko redatuming can also be applied simultaneously to multiple subsurface points. Use `pylops.waveeqprocessing.Marchenko.apply_multiplepoints` instead of `pylops.waveeqprocessing.Marchenko.apply_onepoint`.

Total running time of the script: (0 minutes 8.081 seconds)

3.5.11 11. Radon filtering

In this example we will be taking advantage of the `pylops.signalprocessing.Radon2D` operator to perform filtering of unwanted events from a seismic data. For those of you not familiar with seismic data, let's imagine that we have a data composed of a certain number of flat events and a parabolic event, we are after a transform that allows us to separate such an event from the others and filter it out. Those of you with a geophysics background may immediately realize this is the case of seismic angle (or offset) gathers after migration and those events with parabolic moveout are generally residual multiples that we would like to suppress prior to performing further analysis of our data.

The Radon transform is actually a very good transform to perform such a separation. We can thus devise a simple workflow that takes our data as input, applies a Radon transform, filters some of the events out and goes back to the original domain.

```
import numpy as np
import matplotlib.pyplot as plt

import pylops
from pylops.utils.wavelets import ricker

plt.close('all')
np.random.seed(0)
```

Let's first create a data composed on 3 linear events and a parabolic event.

```
par = {'ox':0, 'dx':2, 'nx':121,
       'ot':0, 'dt':0.004, 'nt':100,
       'f0': 30}

# linear events
v = 1500
t0 = [0.1, 0.2, 0.3]
theta = [0, 0, 0]
amp = [1., -2, 0.5]

# parabolic event
tp0 = [0.13]
px = [0]
pxx = [5e-7]
ampp = [0.7]

# create axis
taxis, taxis2, xaxis, yaxis = pylops.utils.seismicevents.makeaxis(par)

# create wavelet
wav = ricker(taxis[:41], f0=par['f0'])[0]

# generate model
y = pylops.utils.seismicevents.linear2d(xaxis, taxis, v, t0,
                                         theta, amp, wav)[1] + \
    pylops.utils.seismicevents.parabolic2d(xaxis, taxis, tp0,
                                           px, pxx, ampp, wav)[1]
```

We can now create the `pylops.signalprocessing.Radon2D` operator. We also apply its adjoint to the data to obtain a representation of those 3 linear events overlapping to a parabolic event in the Radon domain. Similarly, we feed the operator to a sparse solver like `pylops.optimization.sparsity.FISTA` to obtain a sparse representation of the data in the Radon domain. At this point we try to filter out the unwanted event. We can see how this is much easier for the sparse transform as each event has a much more compact representation in the Radon domain than for the adjoint transform.

```
# radon operator
npx = 61
pxmax = 5e-4
px = np.linspace(-pxmax, pxmax, npx)

Rop = pylops.signalprocessing.Radon2D(taxis, xaxis, px, kind='linear',
                                      interp='nearest', centeredh=False,
                                      dtype='float64')

# adjoint Radon transform
xadj = Rop.H * y.flatten()
xadj = xadj.reshape(npx, par['nt'])

# sparse Radon transform
xinv, niter, cost = \
    pylops.optimization.sparsity.FISTA(Rop, y.flatten(), 15,
                                       eps=1e1, returninfo=True)
xinv = xinv.reshape(npx, par['nt'])

# filtering
xfilt = np.zeros_like(xadj)
xfilt[npx//2-3:npx//2+4] = xadj[npx//2-3:npx//2+4]

yfilt = Rop * xfilt.flatten()
yfilt = yfilt.reshape(par['nx'], par['nt'])

# filtering on sparse transform
xinvfilt = np.zeros_like(xinv)
xinvfilt[npx//2-3:npx//2+4] = xinv[npx//2-3:npx//2+4]

yinvfilt = Rop * xinvfilt.flatten()
yinvfilt = yinvfilt.reshape(par['nx'], par['nt'])
```

Finally we visualize our results.

```
fig, axs = plt.subplots(1, 5, sharey=True, figsize=(12, 5))
axs[0].imshow(y.T, cmap='gray',
              vmin=-np.abs(y).max(), vmax=np.abs(y).max(),
              extent=(xaxis[0], xaxis[-1], taxis[-1], taxis[0]))
axs[0].set_title('Data')
axs[0].axis('tight')
axs[1].imshow(xadj.T, cmap='gray',
              vmin=-np.abs(xadj).max(), vmax=np.abs(xadj).max(),
              extent=(px[0], px[-1], taxis[-1], taxis[0]))
axs[1].axvline(px[npx//2-3], color='r', linestyle='--')
axs[1].axvline(px[npx//2+3], color='r', linestyle='--')
axs[1].set_title('Radon')
axs[1].axis('tight')
axs[2].imshow(yfilt.T, cmap='gray',
              vmin=-np.abs(yfilt).max(), vmax=np.abs(yfilt).max(),
              extent=(xaxis[0], xaxis[-1], taxis[-1], taxis[0]))
```


(continues on next page)

(continued from previous page)

```

axs[2].set_title('Filtered data')
axs[2].axis('tight')
axs[3].imshow(xinv.T, cmap='gray',
              vmin=-np.abs(xinv).max(), vmax=np.abs(xinv).max(),
              extent=(px[0], px[-1], taxis[-1], taxis[0]))
axs[3].axvline(px[np $\times$ //2-3], color='r', linestyle='--')
axs[3].axvline(px[np $\times$ //2+3], color='r', linestyle='--')
axs[3].set_title('Sparse Radon')
axs[3].axis('tight')
axs[4].imshow(yinvfilt.T, cmap='gray',
              vmin=-np.abs(y).max(), vmax=np.abs(y).max(),
              extent=(xaxis[0], xaxis[-1], taxis[-1], taxis[0]))
axs[4].set_title('Sparse filtered data')
axs[4].axis('tight')

```



Out:

```
(0.0, 240.0, 0.396, 0.0)
```

As expected, the Radon domain is a suitable domain for this type of filtering and the sparse transform improves the ability to filter out parabolic events with small curvature.

On the other hand, it is important to note that we have not been able to correctly preserve the amplitudes of each event. This is because the sparse Radon transform can only identify a sparsest response that explain the data within a certain threshold. For this reason a more suitable approach for preserving amplitudes could be to apply a parabolic Radon transform with the aim of reconstructing only the unwanted event and apply an adaptive subtraction between the input data and the reconstructed unwanted event.

Total running time of the script: (0 minutes 24.264 seconds)

3.5.12 12. Seismic regularization

The problem of *seismic data regularization* (or interpolation) is a very simple one to write, yet ill-posed and very hard to solve.

The forward modelling operator is a simple `pylops.Restriction` operator which is applied along the spatial

direction(s).

$$\mathbf{y} = \mathbf{R}\mathbf{x}$$

Here $\mathbf{y} = [\mathbf{y}_{R1}^T, \mathbf{y}_{R2}^T, \dots, \mathbf{y}_{RNT}^T]^T$ where each vector \mathbf{y}_{Ri} contains all time samples recorded in the seismic data at the specific receiver R_i . Similarly, $\mathbf{x} = [\mathbf{x}_{r1}^T, \mathbf{x}_{r2}^T, \dots, \mathbf{x}_{rM}^T]$, contains all traces at the regularly and finely sampled receiver locations r_i .

By inverting such an equation we can create a regularized data with densely and regularly spatial direction(s).

```
import numpy as np
import matplotlib.pyplot as plt
from scipy.signal import convolve

import pylops
from pylops.utils.wavelets import ricker
from pylops.utils.seismicevents import makeaxis, linear2d

np.random.seed(0)
plt.close('all')
```

Let's start by creating a very simple 2d data composed of 3 linear events input parameters

```
par = {'ox':0, 'dx':2, 'nx':70,
       'ot':0, 'dt':0.004, 'nt':80,
       'f0': 20}

v = 1500
t0_m = [0.1, 0.2, 0.28]
theta_m = [0, 30, -80]
phi_m = [0]
amp_m = [1., -2, 0.5]

# axis
taxis, t2, xaxis, y = makeaxis(par)

# wavelet
wav = ricker(taxis[:41], f0=par['f0'])[0]

# model
_, x = linear2d(xaxis, taxis, v, t0_m, theta_m, amp_m, wav)
```

We can now define the spatial locations along which the data has been sampled. In this specific example we will assume that we have access only to 40% of the 'original' locations.

```
perc_subsampling = 0.6
nxsub = int(np.round(par['nx']*perc_subsampling))

iava = np.sort(np.random.permutation(np.arange(par['nx']))[:nxsub])

# restriction operator
Rop = pylops.Restriction(par['nx']*par['nt'],
                          iava, dims=(par['nx'], par['nt']),
                          dir=0, dtype='float64')

# data
y = Rop*x.ravel()
y = y.reshape(nxsub, par['nt'])
```

(continues on next page)

(continued from previous page)


```

# mask
ymask = Rop.mask(x.flatten())

# inverse
xinv = Rop / y.ravel()
xinv = xinv.reshape(par['nx'], par['nt'])

fig, axs = plt.subplots(1, 2, sharey=True, figsize=(5, 4))
axs[0].imshow(x.T, cmap='gray', vmin=-2, vmax=2,
               extent=(xaxis[0], xaxis[-1], taxis[-1], taxis[0]))
axs[0].set_title('Model')
axs[0].axis('tight')
axs[1].imshow(ymask.T, cmap='gray', vmin=-2, vmax=2,
               extent=(xaxis[0], xaxis[-1], taxis[-1], taxis[0]))
axs[1].set_title('Masked model')
axs[1].axis('tight')

```



Out:

```
(0.0, 138.0, 0.316, 0.0)
```

As we can see, inverting the restriction operator is not possible without adding any prior information into the inverse problem. In the following we will consider two possible routes:

- regularized inversion with second derivative along the spatial axis

$$J = \|y - \mathbf{R}\mathbf{x}\|_2 + \epsilon_{\nabla}^2 \|\nabla \mathbf{x}\|_2$$

- sparsity-promoting inversion with `pylops.FFT2` operator used as sparsifying transform

$$J = ||\mathbf{y} - \mathbf{R}\mathbf{F}^H \mathbf{x}||_2 + \epsilon ||\mathbf{F}^H \mathbf{x}||_1$$

```
# smooth inversion
D2op = pylops.SecondDerivative(par['nx']*par['nt'],
                               dims=(par['nx'], par['nt']),
                               dir=0, dtype='float64')

xsmooth, _, _ = \
    pylops.waveeqprocessing.SeismicInterpolation(y, par['nx'], iava,
                                                  kind='spatial',
                                                  **dict(epsRs=[np.sqrt(0.1)],
                                                         damp=np.sqrt(1e-4),
                                                         iter_lim=50, show=0))

# sparse inversion with FFT2
nfft = 2**8
FFTop = pylops.signalprocessing.FFT2D(dims=[par['nx'], par['nt']],
                                       nffts=[nfft, nfft],
                                       sampling=[par['dx'], par['dt']])

X = FFTop*x.flatten()
X = np.reshape(X, (nfft, nfft))

x11, X11, cost = \
    pylops.waveeqprocessing.SeismicInterpolation(y, par['nx'], iava, kind='fk',
                                                  nffts=(nfft, nfft),
                                                  sampling=(par['dx'],
                                                            par['dt']),
                                                  **dict(niter=50, eps=1e-1,
                                                         returninfo=True))

fig, axs = plt.subplots(1, 4, sharey=True, figsize=(13, 4))
axs[0].imshow(x.T, cmap='gray', vmin=-2, vmax=2,
              extent=(xaxis[0], xaxis[-1], taxis[-1], taxis[0]))
axs[0].set_title('Model')
axs[0].axis('tight')
axs[1].imshow(ymask.T, cmap='gray', vmin=-2, vmax=2,
              extent=(xaxis[0], xaxis[-1], taxis[-1], taxis[0]))
axs[1].set_title('Masked model')
axs[1].axis('tight')
axs[2].imshow(xsmooth.T, cmap='gray', vmin=-2, vmax=2,
              extent=(xaxis[0], xaxis[-1], taxis[-1], taxis[0]))
axs[2].set_title('Smoothed model')
axs[2].axis('tight')
axs[3].imshow(x11.T, cmap='gray', vmin=-2, vmax=2,
              extent=(xaxis[0], xaxis[-1], taxis[-1], taxis[0]))
axs[3].set_title('L1 model')
axs[3].axis('tight')

fig, axs = plt.subplots(1, 3, figsize=(10, 2))
axs[0].imshow(np.fft.fftshift(np.abs(X[:, :nfft//2-1]), axes=0).T,
              extent=(np.fft.fftshift(FFTop.f1)[0],
                      np.fft.fftshift(FFTop.f1)[-1],
                      FFTop.f2[nfft // 2 - 1], FFTop.f2[0]))
axs[0].set_title('Model in f-k domain')
axs[0].axis('tight')
```


(continues on next page)

(continued from previous page)

```

axs[0].set_xlim(-0.1, 0.1)
axs[0].set_ylim(50, 0)
axs[1].imshow(np.fft.fftshift(np.abs(Xl1[:, :nfft // 2 - 1])), axes=0).T,
               extent=(np.fft.fftshift(FFTop.f1)[0],
                       np.fft.fftshift(FFTop.f1)[-1],
                       FFTop.f2[nfft // 2 - 1], FFTop.f2[0],))
axs[1].set_title('Reconstructed model in f-k domain')
axs[1].axis('tight')
axs[1].set_xlim(-0.1, 0.1)
axs[1].set_ylim(50, 0)
axs[2].plot(cost, 'k', lw=3)
axs[2].set_title('FISTA convergence')

```



Out:

```
Text(0.5, 1.0, 'FISTA convergence')
```

We see how adding prior information to the inversion can help improving the estimate of the regularized seismic data. Nevertheless, in both cases the reconstructed data is not perfect. A better sparsifying transform could in fact be chosen here to be the linear `pylops.signalprocessing.Radon2D` transform in spite of the `pylops.FFT2` transform.

```

npx = 40
pxmax = 1e-3
px = np.linspace(-pxmax, pxmax, npx)
Radop = pylops.signalprocessing.Radon2D(taxis, xaxis, px, engine='numba')

RRop = Rop*Radop

# adjoint
Xadj_fromx = Radop.H*x.flatten()
Xadj_fromx = Xadj_fromx.reshape(npx, par['nt'])

Xadj = RRop.H*y.flatten()

```

(continues on next page)

(continued from previous page)


```

Xadj = Xadj.reshape(npx, par['nt'])

# L1 inverse
x11, X11, cost = \
    pylops.waveeqprocessing.SeismicInterpolation(y, par['nx'], iava,
                                                  kind='radon-linear',
                                                  spataxis=xaxis,
                                                  taxis=taxis, paxis=px,
                                                  centeredh=True,
                                                  **dict(niter=50, eps=1e-1,
                                                         returninfo=True))

fig, axs = plt.subplots(2, 3, sharey=True, figsize=(12, 7))
axs[0][0].imshow(x.T, cmap='gray', vmin=-2, vmax=2,
                 extent=(xaxis[0], xaxis[-1], taxis[-1], taxis[0]))
axs[0][0].set_title('Data', fontsize=12)
axs[0][0].axis('tight')
axs[0][1].imshow(ymask.T, cmap='gray', vmin=-2, vmax=2,
                 extent=(xaxis[0], xaxis[-1], taxis[-1], taxis[0]))
axs[0][1].set_title('Masked data', fontsize=12)
axs[0][1].axis('tight')
axs[0][2].imshow(x11.T, cmap='gray', vmin=-2, vmax=2,
                 extent=(xaxis[0], xaxis[-1], taxis[-1], taxis[0]))
axs[0][2].set_title('Reconstructed data', fontsize=12)
axs[0][2].axis('tight')
axs[1][0].imshow(Xadj_fromx.T, cmap='gray', vmin=-70, vmax=70,
                 extent=(px[0], px[-1], taxis[-1], taxis[0]))
axs[1][0].set_title('Adj. Radon on data', fontsize=12)
axs[1][0].axis('tight')
axs[1][1].imshow(Xadj.T, cmap='gray', vmin=-50, vmax=50,
                 extent=(px[0], px[-1], taxis[-1], taxis[0]))
axs[1][1].set_title('Adj. Radon on subsampled data', fontsize=12)
axs[1][1].axis('tight')
axs[1][2].imshow(X11.T, cmap='gray', vmin=-0.2, vmax=0.2,
                 extent=(px[0], px[-1], taxis[-1], taxis[0]))
axs[1][2].set_title('Inverse Radon on subsampled data', fontsize=12)
axs[1][2].axis('tight')

```



Out:

```
(-0.001, 0.001, 0.316, 0.0)
```

Finally, let's take now a more realistic dataset. We will use once again the linear `pylops.signalprocessing.Radon2D` transform but we will take advantage of the `pylops.signalprocessing.Sliding2D` operator to perform such a transform locally instead of globally to the entire dataset.

```
inputfile = '../testdata/marchenko/input.npz'
inputdata = np.load(inputfile)

x = inputdata['R'][50, :, ::2]
x = x/np.abs(x).max()
taxis, xaxis = inputdata['t'][:, ::2], inputdata['r'][0]

par = {}
par['nx'], par['nt'] = x.shape
par['dx'] = inputdata['r'][0, 1] - inputdata['r'][0, 0]
par['dt'] = inputdata['t'][1] - inputdata['t'][0]

# add wavelet
wav = inputdata['wav'][:, ::2]
wav_c = np.argmax(wav)
x = np.apply_along_axis(convolve, 1, x, wav, mode='full')
x = x[:, wav_c:][:, :par['nt']]

# gain
gain = np.tile((taxis**2)[:, np.newaxis], (1, par['nx'])).T
x = x*gain

# subsampling locations
perc_subsampling = 0.5
```

(continues on next page)

(continued from previous page)

```

Nsub = int(np.round(par['nx']*perc_subsampling))
iava = np.sort(np.random.permutation(np.arange(par['nx']))[:Nsub])

# restriction operator
Rop = pylops.Restriction(par['nx']*par['nt'], iava,
                        dims=(par['nx'], par['nt']),
                        dir=0, dtype='float64')

y = Rop*x.flatten()
xadj = Rop.H*y.flatten()

y = y.reshape(Nsub, par['nt'])
xadj = xadj.reshape(par['nx'], par['nt'])

# apply mask
ymask = Rop.mask(x.flatten())

# sliding windows with radon transform
dx = par['dx']
nwins = 4
nwin = 27
nover = 3
npx = 31
pxmax = 5e-4
px = np.linspace(-pxmax, pxmax, npy)
dimsd = x.shape
dims = (nwins*npx, dimsd[1])

Op = \
    pylops.signalprocessing.Radon2D(taxis, np.linspace(-par['dx']*nwin//2,
                                                    par['dx']*nwin//2,
                                                    nwin),
                                   px, centeredh=True, kind='linear',
                                   engine='numba')
Slidop = pylops.signalprocessing.Sliding2D(Op, dims, dimsd, nwin, nover,
                                           tapertype='cosine', design=True)

# adjoint
RSop = Rop*Slidop

Xadj_fromx = Slidop.H*x.flatten()
Xadj_fromx = Xadj_fromx.reshape(npx*nwins, par['nt'])

Xadj = RSop.H*y.flatten()
Xadj = Xadj.reshape(npx*nwins, par['nt'])

# inverse
xll, Xll, _ = \
    pylops.waveeqprocessing.SeismicInterpolation(y, par['nx'], iava,
                                                  kind='sliding',
                                                  spataxis=xaxis,
                                                  taxis=taxis, paxis=px,
                                                  nwins=nwins, nwin=nwin,
                                                  nover=nover,
                                                  **dict(niter=50, eps=1e-2))

fig, axs = plt.subplots(2, 3, sharey=True, figsize=(12, 14))

```


(continues on next page)

(continued from previous page)

```

axs[0][0].imshow(x.T, cmap='gray', vmin=-0.1, vmax=0.1,
                  extent=(xaxis[0], xaxis[-1], taxis[-1], taxis[0]))
axs[0][0].set_title('Data')
axs[0][0].axis('tight')
axs[0][1].imshow(ymask.T, cmap='gray', vmin=-0.1, vmax=0.1,
                  extent=(xaxis[0], xaxis[-1], taxis[-1], taxis[0]))
axs[0][1].set_title('Masked data')
axs[0][1].axis('tight')
axs[0][2].imshow(xl1.T, cmap='gray', vmin=-0.1, vmax=0.1,
                  extent=(xaxis[0], xaxis[-1], taxis[-1], taxis[0]))
axs[0][2].set_title('Reconstructed data')
axs[0][2].axis('tight')
axs[1][0].imshow(Xadj_fromx.T, cmap='gray', vmin=-1, vmax=1,
                  extent=(px[0], px[-1], taxis[-1], taxis[0]))
axs[1][0].set_title('Adjoint Radon on data')
axs[1][0].axis('tight')
axs[1][1].imshow(Xadj.T, cmap='gray', vmin=-0.6, vmax=0.6,
                  extent=(px[0], px[-1], taxis[-1], taxis[0]))
axs[1][1].set_title('Adjoint Radon on subsampled data')
axs[1][1].axis('tight')
axs[1][2].imshow(Xl1.T, cmap='gray', vmin=-0.03, vmax=0.03,
                  extent=(px[0], px[-1], taxis[-1], taxis[0]))
axs[1][2].set_title('Inverse Radon on subsampled data')
axs[1][2].axis('tight')

```



Out:

```
(-0.0005, 0.0005, 1.995, 0.0)
```

As expected the linear `pylops.signalprocessing.Radon2D` is able to locally explain events in the input data and leads to a satisfactory recovery. Note that increasing the number of iterations and sliding windows can further refine the result, especially the accuracy of weak events, as shown in this companion [notebook](#).

Total running time of the script: (0 minutes 8.062 seconds)

3.5.13 13. Deghosting

Single-component seismic data can be decomposed in their up- and down-going constituents in a model driven fashion. This task can be achieved by defining an f-k propagator (or ghost model) and solving an inverse problem as described in `pylops.waveeqprocessing.Deghosting`.

```
# sphinx_gallery_thumbnail_number = 3
import numpy as np
import matplotlib.pyplot as plt
from scipy.sparse.linalg import lsqr

import pylops

np.random.seed(0)
plt.close('all')
```

Let's start by loading the input dataset and geometry

```
inputfile = '../testdata/updown/input.npz'
inputdata = np.load(inputfile)

vel_sep = 2400.0 # velocity at separation level
clip = 1e-1 # plotting clip

# Receivers
r = inputdata['r']
nr = r.shape[1]
dr = r[0, 1]-r[0, 0]

# Sources
s = inputdata['s']

# Model
rho = inputdata['rho']

# Axes
t = inputdata['t']
nt, dt = len(t), t[1]-t[0]
x, z = inputdata['x'], inputdata['z']
dx, dz = x[1] - x[0], z[1] - z[0]

# Data
p = inputdata['p'].T
p /= p.max()

fig = plt.figure(figsize=(9, 4))
ax1 = plt.subplot2grid((1, 5), (0, 0), colspan=4)
ax2 = plt.subplot2grid((1, 5), (0, 4))
ax1.imshow(rho, cmap='gray', extent=(x[0], x[-1], z[-1], z[0]))
ax1.scatter(r[0, ::5], r[1, ::5], marker='v', s=150, c='b', edgecolors='k')
ax1.scatter(s[0], s[1], marker='*', s=250, c='r', edgecolors='k')
ax1.axis('tight')
ax1.set_xlabel('x [m]')
ax1.set_ylabel('y [m]')
```


(continues on next page)

(continued from previous page)

```

ax1.set_title('Model and Geometry')
ax1.set_xlim(x[0], x[-1])
ax1.set_ylim(z[-1], z[0])
ax2.plot(rho[:, len(x)//2], z, 'k', lw=2)
ax2.set_ylim(z[-1], z[0])
ax2.set_yticks([])

```



Out:

```
[ ]
```

To be able to deghost the input dataset, we need to remove its direct arrival. In this example we will create a mask based on the analytical traveltimes of the direct arrival.

```

direct = np.sqrt(np.sum((s[:, np.newaxis]-r)**2, axis=0))/vel_sep

# Window
off = 0.035
direct_off = direct + off
win = np.zeros((nt, nr))
iwin = np.round(direct_off/dt).astype(np.int)
for i in range(nr):
    win[iwin[i]:, i] = 1


fig, axs = plt.subplots(1, 2, sharey=True, figsize=(8, 7))
axs[0].imshow(p.T, cmap='gray', vmin=-clip*np.abs(p).max(),
              vmax=clip*np.abs(p).max(),
              extent=(r[0, 0], r[0, -1], t[-1], t[0]))
axs[0].plot(r[0], direct_off, 'r', lw=2)
axs[0].set_title(r'$P$')
axs[0].axis('tight')
axs[1].imshow(win * p.T, cmap='gray', vmin=-clip*np.abs(p).max(),
              vmax=clip*np.abs(p).max(),
              extent=(r[0, 0], r[0, -1], t[-1], t[0]))
axs[1].set_title(r'Windowed $P$')
axs[1].axis('tight')

```

(continues on next page)

(continued from previous page)

```
axs[1].set_ylim(1, 0)
```



Out:

```
(1.0, 0.0)
```

We can now perform deghosting

```
pup, pdown = \
    pylops.waveeqprocessing.Deghosting(p.T, nt, nr, dt, dr, vel_sep,
                                       r[1, 0] + dz, win=win,
                                       npad=5, ntaper=11, solver=lsqr,
                                       dottest=False, dtype='complex128',
                                       **dict(damp=1e-10, iter_lim=60))

fig, axs = plt.subplots(1, 3, sharey=True, figsize=(12, 7))
axs[0].imshow(p.T, cmap='gray', vmin=-clip * np.abs(p).max(),
              vmax=clip * np.abs(p).max(),
              extent=(r[0, 0], r[0, -1], t[-1], t[0]))
```

(continues on next page)

(continued from previous page)


```

axs[0].set_title(r'$P$')
axs[0].axis('tight')
axs[1].imshow(pup, cmap='gray', vmin=-clip * np.abs(p).max(),
              vmax=clip * np.abs(p).max(),
              extent=(r[0, 0], r[0, -1], t[-1], t[0]))
axs[1].set_title(r'$P^-$')
axs[1].axis('tight')
axs[2].imshow(pdown, cmap='gray', vmin=-clip * np.abs(p).max(),
              vmax=clip * np.abs(p).max(),
              extent=(r[0, 0], r[0, -1], t[-1], t[0]))
axs[2].set_title(r'$P^+$')
axs[2].axis('tight')
axs[2].set_ylim(1, 0)


plt.figure(figsize=(14, 3))
plt.plot(t, p[nr // 2], 'k', lw=2, label=r'$p$')
plt.plot(t, pup[:, nr // 2], 'r', lw=2, label=r'$p^-$')
plt.xlim(0, t[200])
plt.ylim(-0.2, 0.2)
plt.legend()

plt.figure(figsize=(14, 3))
plt.plot(t, pdown[:, nr // 2], 'b', lw=2, label=r'$p^+$')
plt.plot(t, pup[:, nr // 2], 'r', lw=2, label=r'$p^-$')
plt.xlim(0, t[200])
plt.ylim(-0.2, 0.2)
plt.legend()

```



•



Out:

```
<matplotlib.legend.Legend object at 0x7fc20ab9cef0>
```

To see more examples head over to the following notebook: [notebook1](#).

Total running time of the script: (0 minutes 6.572 seconds)

3.5.14 14. Seismic wavefield decomposition

Multi-component seismic data can be decomposed in their up- and down-going constituents in a purely data driven fashion. This task can be accurately achieved by linearly combining the input pressure and particle velocity data in the frequency-wavenumber described in details in *pylops.waveeqprocessing.UpDownComposition2D* and *pylops.waveeqprocessing.WavefieldDecomposition*.

In this tutorial we will consider a simple synthetic data composed of six events (three up-going and three down-going). We will first combine them to create pressure and particle velocity data and then show how we can retrieve their directional constituents both by directly combining the input data as well as by setting an inverse problem. The latter approach results vital in case of spatial aliasing, as applying simple scaled summation in the frequency-wavenumber would result in sub-optimal decomposition due to the superposition of different frequency-wavenumber pairs at some (aliased) locations.

```
import numpy as np
import matplotlib.pyplot as plt
from scipy.signal import filtfilt

import pylops
from pylops.utils.wavelets import ricker
from pylops.utils.seismicevents import makeaxis, hyperbolic2d

np.random.seed(0)
plt.close('all')
```

Let's first the input up- and down-going wavefields

```
par = {'ox':-220, 'dx':5, 'nx':89,
       'ot':0, 'dt':0.004, 'nt':200,
       'f0': 40}
```

(continues on next page)

(continued from previous page)

```

t0_plus = np.array([0.2, 0.5, 0.7])
t0_minus = t0_plus + 0.04
vrms = np.array([1400., 1500., 2000.])
amp = np.array([1., -0.6, 0.5])
vel_sep = 1000.0 # velocity at separation level
rho_sep = 1000.0 # density at separation level

# Create axis
t, t2, x, y = makeaxis(par)

# Create wavelet
wav = ricker(t[:41], f0=par['f0'])[0]

# Create data
_, p_minus = hyperbolic2d(x, t, t0_minus, vrms, amp, wav)
_, p_plus = hyperbolic2d(x, t, t0_plus, vrms, amp, wav)

```

We can now combine them to create pressure and particle velocity data

```

critical = 1.1
ntaper = 51
nfft = 2**10

# 2d fft operator
FFTop = pylops.signalprocessing.FFT2D(dims=[par['nx'], par['nt']],
                                       nffts=[nfft, nfft],
                                       sampling=[par['dx'], par['dt']])

# obliquity factor
[Kx, F] = np.meshgrid(FFTop.f1, FFFTop.f2, indexing='ij')
k = F/vel_sep
Kz = np.sqrt((k**2 - Kx**2).astype(np.complex))
Kz[np.isnan(Kz)] = 0
OBL = rho_sep*(np.abs(F)/Kz)
OBL[Kz == 0] = 0

mask = np.abs(Kx) < critical*np.abs(F)/vel_sep
OBL *= mask
OBL = filtfilt(np.ones(ntaper)/float(ntaper), 1, OBL, axis=0)
OBL = filtfilt(np.ones(ntaper)/float(ntaper), 1, OBL, axis=1)

# composition operator
UPop = \
    pylops.waveeqprocessing.UpDownComposition2D(par['nt'], par['nx'],
                                                par['dt'], par['dx'],
                                                rho_sep, vel_sep,
                                                nffts=(nfft, nfft),
                                                critical=critical*100.,
                                                ntaper=ntaper,
                                                dtype='complex128')

# wavefield modelling
d = UPop * np.concatenate((p_plus.flatten(), p_minus.flatten())).flatten()
d = np.real(d.reshape(2*par['nx'], par['nt']))
p, vz = d[:, par['nx']], d[par['nx']:]

```

(continues on next page)

(continued from previous page)


```

# obliquity scaled vz
VZ = FFTop * vz.flatten()
VZ = VZ.reshape(nfft, nfft)

VZ_obl = OBL * VZ
vz_obl = FFTop.H*VZ_obl.flatten()
vz_obl = np.real(vz_obl.reshape(par['nx'], par['nt']))

fig, axs = plt.subplots(1, 4, figsize=(10, 5))
axs[0].imshow(p.T, aspect='auto', vmin=-1, vmax=1,
               interpolation='nearest', cmap='gray',
               extent=(x.min(), x.max(), t.max(), t.min()))
axs[0].set_title(r'$p$', fontsize=15)
axs[0].set_xlabel('x')
axs[0].set_ylabel('t')
axs[1].imshow(vz_obl.T, aspect='auto', vmin=-1, vmax=1,
               interpolation='nearest', cmap='gray',
               extent=(x.min(), x.max(), t.max(), t.min()))
axs[1].set_title(r'$v_z^{obl}$', fontsize=15)
axs[1].set_xlabel('x')
axs[1].set_ylabel('t')
axs[2].imshow(p_plus.T, aspect='auto', vmin=-1, vmax=1,
               interpolation='nearest', cmap='gray',
               extent=(x.min(), x.max(), t.max(), t.min()))
axs[2].set_title(r'$p^+$', fontsize=15)
axs[2].set_xlabel('x')
axs[2].set_ylabel('t')
axs[3].imshow(p_minus.T, aspect='auto',
               interpolation='nearest', cmap='gray',
               extent=(x.min(), x.max(), t.max(), t.min()),
               vmin=-1, vmax=1)
axs[3].set_title(r'$p^-$', fontsize=15)
axs[3].set_xlabel('x')
axs[3].set_ylabel('t')
plt.tight_layout()


```



Wavefield separation is first performed using the analytical expression for combining pressure and particle velocity data in the wavenumber-frequency domain

```
pup_sep, pdown_sep = \
    pylops.waveeqprocessing.WavefieldDecomposition(p, vz, par['nt'], par['nx'],
                                                    par['dt'], par['dx'],
                                                    rho_sep, vel_sep,
                                                    nffts=(nfft, nfft),
                                                    kind='analytical',
                                                    critical=critical*100,
                                                    ntaper=ntaper,
                                                    dtype='complex128')

fig = plt.figure(figsize=(12, 5))
axs0 = plt.subplot2grid((2, 5), (0, 0), rowspan=2)
axs1 = plt.subplot2grid((2, 5), (0, 1), rowspan=2)
axs2 = plt.subplot2grid((2, 5), (0, 2), colspan=3)
axs3 = plt.subplot2grid((2, 5), (1, 2), colspan=3)
axs0.imshow(pup_sep.T, cmap='gray', vmin=-1, vmax=1,
            extent=(x.min(), x.max(), t.max(), t.min()))
axs0.set_title(r'$p^-$ analytical')
axs0.axis('tight')
axs1.imshow(pdown_sep.T, cmap='gray', vmin=-1, vmax=1,
            extent=(x.min(), x.max(), t.max(), t.min()))
axs1.set_title(r'$p^+$ analytical')
axs1.axis('tight')
axs2.plot(t, p[par['nx']//2], 'r', lw=2, label=r'$p$')
axs2.plot(t, vz_obl[par['nx']//2], '--b', lw=2, label=r'$v_z^{obl}$')
axs2.set_ylim(-1, 1)
axs2.set_title('Data at x=%.2f' % x[par['nx']//2])
axs2.set_xlabel('t [s]')
axs2.legend()
axs3.plot(t, pup_sep[par['nx']//2], 'r', lw=2, label=r'$p^-$ ana')
axs3.plot(t, pdown_sep[par['nx']//2], '--b', lw=2, label=r'$p^+$ ana')
axs3.set_title('Separated wavefields at x=%.2f' % x[par['nx']//2])
axs3.set_xlabel('t [s]')
axs3.set_ylim(-1, 1)
axs3.legend()
plt.tight_layout()
```



We repeat the same exercise but this time we invert the composition operator `pylops.waveeqprocessing`.


UpDownComposition2D

```

pup_inv, pdown_inv = \
    pylops.waveeqprocessing.WavefieldDecomposition(p, vz, par['nt'], par['nx'],
                                                    par['dt'], par['dx'],
                                                    rho_sep, vel_sep,
                                                    nffts=(nfft, nfft),
                                                    kind='inverse',
                                                    critical=critical*100,
                                                    ntaper=ntaper,
                                                    dtype='complex128',
                                                    **dict(damp=1e-10,
                                                            iter_lim=20))

fig = plt.figure(figsize=(12, 5))
axs0 = plt.subplot2grid((2, 5), (0, 0), rowspan=2)
axs1 = plt.subplot2grid((2, 5), (0, 1), rowspan=2)
axs2 = plt.subplot2grid((2, 5), (0, 2), colspan=3)
axs3 = plt.subplot2grid((2, 5), (1, 2), colspan=3)
axs0.imshow(pup_inv.T, cmap='gray', vmin=-1, vmax=1,
             extent=(x.min(), x.max(), t.max(), t.min()))
axs0.set_title(r'$p^{-}$ inverse')
axs0.axis('tight')
axs1.imshow(pdown_inv.T, cmap='gray', vmin=-1, vmax=1,
             extent=(x.min(), x.max(), t.max(), t.min()))
axs1.set_title(r'$p^{+}$ inverse')
axs1.axis('tight')
axs2.plot(t, p[par['nx']//2], 'r', lw=2, label=r'$p$')
axs2.plot(t, vz_obl[par['nx']//2], '--b', lw=2, label=r'$v_z^{obl}$')
axs2.set_ylim(-1, 1)
axs2.set_title('Data at x=%.2f' % x[par['nx']//2])
axs2.set_xlabel('t [s]')
axs2.legend()
axs3.plot(t, pup_inv[par['nx']//2], 'r', lw=2, label=r'$p^{-}$ inv')
axs3.plot(t, pdown_inv[par['nx']//2], '--b', lw=2, label=r'$p^{+}$ inv')
axs3.set_title('Separated wavefields at x=%.2f' % x[par['nx']//2])
axs3.set_xlabel('t [s]')
axs3.set_ylim(-1, 1)
axs3.legend()
plt.tight_layout()

```




The up- and down-going constituents have been successfully separated in both cases. Finally, we use the `pylops.waveeqprocessing.UpDownComposition2D` operator to reconstruct the particle velocity wavefield from its up- and down-going pressure constituents

```
PtoVop = \
    pylops.waveeqprocessing.PressureToVelocity(par['nt'], par['nx'],
                                                par['dt'], par['dx'],
                                                rho_sep, vel_sep,
                                                nffts=(nfft, nfft),
                                                critical=critical * 100.,
                                                ntaper=ntaper,
                                                topressure=False)

vdown_rec = (PtoVop * pdown_inv.ravel()).reshape(par['nx'], par['nt'])
vup_rec = (PtoVop * pup_inv.ravel()).reshape(par['nx'], par['nt'])
vz_rec = np.real(vdown_rec - vup_rec)

fig, axs = plt.subplots(1, 3, figsize=(13, 6))
axs[0].imshow(vz.T, cmap='gray', vmin=-1e-6, vmax=1e-6,
               extent=(x.min(), x.max(), t.max(), t.min()))
axs[0].set_title(r'$vz$')
axs[0].axis('tight')
axs[1].imshow(vz_rec.T, cmap='gray', vmin=-1e-6, vmax=1e-6,
               extent=(x.min(), x.max(), t[-1], t[0]))
axs[1].set_title(r'$vz$ rec$')
axs[1].axis('tight')
axs[2].imshow(vz.T - vz_rec.T, cmap='gray', vmin=-1e-6, vmax=1e-6,
               extent=(x.min(), x.max(), t[-1], t[0]))
axs[2].set_title(r'$error$')
axs[2].axis('tight')
```



Out:

```
(-220.0, 220.0, 0.796, 0.0)
```

To see more examples, including applying wavefield separation and regularization simultaneously, as well as 3D examples, head over to the following notebooks: [notebook1](#) and [notebook2](#)

Total running time of the script: (0 minutes 7.642 seconds)

3.5.15 15. Least-squares migration

Seismic migration is the process by which seismic data are manipulated to create an image of the subsurface reflectivity.

While traditionally solved as the adjoint of the demigration operator, it is becoming more and more common to solve the underlying inverse problem in the quest for more accurate and detailed subsurface images.

Independently of the choice of the modelling operator (i.e., ray-based or full wavefield-based), the demigration/migration process can be expressed as a linear operator of such a kind:

$$d(\mathbf{x}_r, \mathbf{x}_s, t) = w(t) * \int_V G(\mathbf{x}, \mathbf{x}_s, t) G(\mathbf{x}_r, \mathbf{x}, t) m(\mathbf{x}) d\mathbf{x}$$

where $m(\mathbf{x})$ is the reflectivity at every location in the subsurface, $G(\mathbf{x}, \mathbf{x}_s, t)$ and $G(\mathbf{x}_r, \mathbf{x}, t)$ are the Green's functions from source-to-subsurface-to-receiver and finally $w(t)$ is the wavelet. Ultimately, while the Green's functions can be computed in many different ways, solving this system of equations for the reflectivity model is what we generally refer to as Least-squares migration (LSM).

In this tutorial we will consider the most simple scenario where we use an eikonal solver to compute the Green's functions and show how we can use the `pylops.waveeqprocessing.LSM` operator to perform LSM.

```
import numpy as np
import matplotlib.pyplot as plt
from scipy.sparse.linalg import lsqr

import pylops

plt.close('all')
np.random.seed(0)
```

To start we create a simple model with 2 interfaces

```
# Velocity Model
nx, nz = 81, 60
dx, dz = 4, 4
x, z = np.arange(nx)*dx, np.arange(nz)*dz
v0 = 1000 # initial velocity
kv = 0. # gradient
vel = np.outer(np.ones(nx), v0 + kv*z)

# Reflectivity Model
refl = np.zeros((nx, nz))
refl[:, 30] = -1
refl[:, 50] = 0.5

# Receivers
nr = 11
rx = np.linspace(10*dx, (nx-10)*dx, nr)
rz = 20*np.ones(nr)
recs = np.vstack((rx, rz))
dr = recs[0,1]-recs[0,0]

# Sources
ns = 10
sx = np.linspace(dx*10, (nx-10)*dx, ns)
sz = 10*np.ones(ns)
sources = np.vstack((sx, sz))
ds = sources[0,1]-sources[0,0]
```

(continues on next page)


(continued from previous page)


```

plt.figure(figsize=(10, 5))
im = plt.imshow(vel.T, cmap='gray', extent = (x[0], x[-1], z[-1], z[0]))
plt.scatter(recs[0], recs[1], marker='v', s=150, c='b', edgecolors='k')
plt.scatter(sources[0], sources[1], marker='*', s=150, c='r', edgecolors='k')
plt.colorbar(im)
plt.axis('tight')
plt.xlabel('x [m]'), plt.ylabel('y [m]')
plt.title('Velocity')
plt.xlim(x[0], x[-1])

plt.figure(figsize=(10, 5))
im = plt.imshow(refl.T, cmap='gray', extent = (x[0], x[-1], z[-1], z[0]))
plt.scatter(recs[0], recs[1], marker='v', s=150, c='b', edgecolors='k')
plt.scatter(sources[0], sources[1], marker='*', s=150, c='r', edgecolors='k')
plt.colorbar(im)
plt.axis('tight')
plt.xlabel('x [m]'), plt.ylabel('y [m]')
plt.title('Reflectivity')
plt.xlim(x[0], x[-1])

```





Out:

```
(0.0, 320.0)
```

We can now create our LSM object and invert for the reflectivity using two different solvers: `scipy.sparse.linalg.lsqr` (LS solution) and `pylops.optimization.sparsity.FISTA` (LS solution with sparse model).

```
nt = 651
dt = 0.004
t = np.arange(nt)*dt
wav, wavt, wavc = pylops.utils.wavelets.ricker(t[:41], f0=20)

lsm = pylops.waveeqprocessing.LSM(z, x, t, sources, recs, v0, wav, wavc,
                                  mode='analytic')

d = lsm.Demop * refl.ravel()
d = d.reshape(ns, nr, nt)

madj = lsm.Demop.H * d.ravel()
madj = madj.reshape(nx, nz)

minv = lsm.solve(d.ravel(), solver=lsqr, **dict(iter_lim=100))
minv = minv.reshape(nx, nz)

minv_sparse = lsm.solve(d.ravel(),
                        solver=pylops.optimization.sparsity.FISTA,
                        **dict(eps=1e2, niter=100))
minv_sparse = minv_sparse.reshape(nx, nz)

# demigration
dadj = lsm.Demop * madj.ravel()
dadj = dadj.reshape(ns, nr, nt)

dinv = lsm.Demop * minv.ravel()
dinv = dinv.reshape(ns, nr, nt)
```

(continues on next page)

```


dinv_sparse = lsm.Demop * minv_sparse.ravel()
dinv_sparse = dinv_sparse.reshape(ns, nr, nt)

# sphinx_gallery_thumbnail_number = 2
fig, axs = plt.subplots(2, 2, figsize=(10, 8))
axs[0][0].imshow(refl.T, cmap='gray', vmin=-1, vmax=1)
axs[0][0].axis('tight')
axs[0][0].set_title(r'$m$')
axs[0][1].imshow(madj.T, cmap='gray', vmin=-madj.max(), vmax=madj.max())
axs[0][1].set_title(r'$m_{adj}$')
axs[0][1].axis('tight')
axs[1][0].imshow(minv.T, cmap='gray', vmin=-1, vmax=1)
axs[1][0].axis('tight')
axs[1][0].set_title(r'$m_{inv}$')
axs[1][1].imshow(minv_sparse.T, cmap='gray', vmin=-1, vmax=1)
axs[1][1].axis('tight')
axs[1][1].set_title(r'$m_{FISTA}$')


fig, axs = plt.subplots(1, 4, figsize=(10, 4))
axs[0].imshow(d[0, :, :300].T, cmap='gray',
              vmin=-d.max(), vmax=d.max())
axs[0].set_title(r'$d$')
axs[0].axis('tight')
axs[1].imshow(dadj[0, :, :300].T, cmap='gray',
              vmin=-dadj.max(), vmax=dadj.max())
axs[1].set_title(r'$d_{adj}$')
axs[1].axis('tight')
axs[2].imshow(dinv[0, :, :300].T, cmap='gray',
              vmin=-d.max(), vmax=d.max())
axs[2].set_title(r'$d_{inv}$')
axs[2].axis('tight')
axs[3].imshow(dinv_sparse[0, :, :300].T, cmap='gray',
              vmin=-d.max(), vmax=d.max())
axs[3].set_title(r'$d_{fista}$')
axs[3].axis('tight')

fig, axs = plt.subplots(1, 4, figsize=(10, 4))
axs[0].imshow(d[ns//2, :, :300].T, cmap='gray',
              vmin=-d.max(), vmax=d.max())
axs[0].set_title(r'$d$')
axs[0].axis('tight')
axs[1].imshow(dadj[ns//2, :, :300].T, cmap='gray',
              vmin=-dadj.max(), vmax=dadj.max())
axs[1].set_title(r'$d_{adj}$')
axs[1].axis('tight')
axs[2].imshow(dinv[ns//2, :, :300].T, cmap='gray',
              vmin=-d.max(), vmax=d.max())
axs[2].set_title(r'$d_{inv}$')
axs[2].axis('tight')
axs[3].imshow(dinv_sparse[ns//2, :, :300].T, cmap='gray',
              vmin=-d.max(), vmax=d.max())
axs[3].set_title(r'$d_{fista}$')
axs[3].axis('tight')


```

•



•



Out:

```
(-0.5, 10.5, 299.5, -0.5)
```

This was just a short teaser, for a more advanced set of examples of 2D and 3D traveltime-based LSM head over to [this notebook](#).

Total running time of the script: (0 minutes 4.581 seconds)

3.5.16 16. CT Scan Imaging

This tutorial considers a very well-known inverse problem from the field of medical imaging.

We will be using the `pylops.signalprocessing.Radon2D` operator to model a *sinogram*, which is a graphic representation of the raw data obtained from a CT scan. The sinogram is further inverted using both a L2 solver and a TV-regularized solver like Split-Bregman.

```
# sphinx_gallery_thumbnail_number = 2
import numpy as np
import matplotlib.pyplot as plt
import pylops

from numba import jit

plt.close('all')
np.random.seed(10)
```

Let's start by loading the Shepp-Logan phantom model. We can then construct the sinogram by providing a custom-made function to the `pylops.signalprocessing.Radon2D` that samples parametric curves of such a type:

$$t(r, \theta; x) = \tan(90 - \theta) * x + r / \sin(\theta)$$

where θ is the angle between the x-axis (x) and the perpendicular to the summation line and r is the distance from the origin of the summation line.

```
@jit(nopython=True)
def radoncurve(x, r, theta):
    return (r - ny//2) / (np.sin(np.deg2rad(theta)) + 1e-15) + np.tan(np.deg2rad(90 -
    ↪ theta)) * x + ny//2
```

(continues on next page)

(continued from previous page)

```

x = np.load('../testdata/optimization/shepp_logan_phantom.npy')
x = x / x.max()
ny, nx = x.shape

ntheta = 150
theta = np.linspace(0., 180., ntheta, endpoint=False)

Rlop = \
    pylops.signalprocessing.Radon2D(np.arange(ny), np.arange(nx),
                                     theta, kind=radoncurve,
                                     centeredh=True, interp=False,
                                     engine='numba', dtype='float64')

y = Rlop.H * x.T.ravel()
y = y.reshape(ntheta, ny).T

```

We can now first perform the adjoint, which in the medical imaging literature is also referred to as back-projection.


This is the first step of a common reconstruction technique, named filtered back-projection, which simply applies a correction filter in the frequency domain to the adjoint model.

```

xrec = Rlop*y.T.ravel()
xrec = xrec.reshape(nx, ny).T

fig, axs = plt.subplots(1, 3, figsize=(10, 4))
axs[0].imshow(x, vmin=0, vmax=1, cmap='gray')
axs[0].set_title('Model')
axs[0].axis('tight')
axs[1].imshow(y, cmap='gray')
axs[1].set_title('Data')
axs[1].axis('tight')
axs[2].imshow(xrec, cmap='gray')
axs[2].set_title('Adjoint model')
axs[2].axis('tight')
fig.tight_layout()

```



Finally we take advantage of our different solvers and try to invert the modelling operator both in a least-squares sense and using TV-reg.

```

Dop = [
    pylops.FirstDerivative(ny * nx, dims=(nx, ny), dir=0, edge=True,
                           kind='backward', dtype=np.float),
    pylops.FirstDerivative(ny * nx, dims=(nx, ny), dir=1, edge=True,
                           kind='backward', dtype=np.float)]
D2op = pylops.Laplacian(dims=(nx, ny), edge=True, dtype=np.float)

# L2
xinv_sm = \
    pylops.optimization.leastsquares.RegularizedInversion(RLop.H,
                                                         [D2op],
                                                         y.T.flatten(),
                                                         epsRs=[1e1],
                                                         **dict(iter_lim=20))

xinv_sm = np.real(xinv_sm.reshape(nx, ny)).T


# TV
mu = 1.5
lamda = [1., 1.]
niter = 3
niterinner = 4

xinv, niter = pylops.optimization.sparsity.SplitBregman(RLop.H, Dop, y.T.flatten(),
                                                         niter, niterinner,
                                                         mu=mu, epsRLls=lamda, tol=1e-4, tau=1., show=False,
                                                         **dict(iter_lim=20, damp=1e-2))

xinv = np.real(xinv.reshape(nx, ny)).T

fig, axs = plt.subplots(1, 3, figsize=(10, 4))
axs[0].imshow(x, vmin=0, vmax=1, cmap='gray')
axs[0].set_title('Model')
axs[0].axis('tight')
axs[1].imshow(xinv_sm, vmin=0, vmax=1, cmap='gray')
axs[1].set_title('L2 Inversion')
axs[1].axis('tight')
axs[2].imshow(xinv, vmin=0, vmax=1, cmap='gray')
axs[2].set_title('TV-Reg Inversion')
axs[2].axis('tight')
fig.tight_layout()

```



Total running time of the script: (0 minutes 12.674 seconds)

3.5.17 17. Real/Complex Inversion

In this tutorial we will discuss two equivalent approaches to the solution of inverse problems with real-valued model vector and complex-valued data vector. In other words, we consider a modelling operator $\mathbf{A} : \mathbb{F}^m \rightarrow \mathbb{C}^n$ (which could be the case for example for the real FFT).

Mathematically speaking, this problem can be solved equivalently by inverting the complex-valued problem:

$$\mathbf{y} = \mathbf{A}\mathbf{x}$$

or the real-valued augmented system

$$\begin{bmatrix} \text{Re}(\mathbf{y}) \\ \text{Im}(\mathbf{y}) \end{bmatrix} = \begin{bmatrix} \text{Re}(\mathbf{A}) \\ \text{Im}(\mathbf{A}) \end{bmatrix} \mathbf{x}$$

Whilst we already know how to solve the first problem, let's see how we can solve the second one by taking advantage of the `real` method of the `pylops.LinearOperator` object. We will also wrap our linear operator into a `pylops.MemoizeOperator` which remembers the last N model and data vectors and by-passes the computation of the forward and/or adjoint pass whenever the same pair reappears. This is very useful in our case when we want to compute the real and the imag components of

```
import numpy as np
import matplotlib.pyplot as plt
import pylops

plt.close('all')
np.random.seed(0)
```

To start we create the forward problem

```
n = 5
x = np.arange(n) + 1.

# make A
Ar = np.random.normal(0, 1, (n, n))
Ai = np.random.normal(0, 1, (n, n))
A = Ar + 1j * Ai
Aop = pylops.MatrixMult(A, dtype=np.complex)
y = Aop @ x
```

Let's check we can solve this problem using the first formulation

```
Alop = Aop.toreal(forw=False, adj=True)
xinv = Alop.div(y)

print('xinv=%s\n' % xinv)
```

Out:

```
xinv=[1. 2. 3. 4. 5.]
```

Let's now see how we formulate the second problem

```
Amop = pylops.MemoizeOperator(Aop, max_neval=10)
Arop = Amop.toreal()
Aiop = Amop.toimag()

Alop = pylops.VStack([Arop, Aiop])
y1 = np.concatenate([np.real(y), np.imag(y)])
xinv1 = np.real(Alop.div(y1))

print('xinv1=%s\n' % xinv1)
```

Out:

```
xinv1=[1. 2. 3. 4. 5.]
```

Total running time of the script: (0 minutes 0.010 seconds)

3.6 Frequently Asked Questions

1. Can I visualize my operator?

Yes, you can. Every operator has a method called `todense` that will return the dense matrix equivalent of the operator. Note, however, that in order to do so we need to allocate a numpy array of the size of your operator and apply the operator N times, where N is the number of columns of the operator. The allocation can be very heavy on your memory and the computation may take long time, so use it with care only for small toy examples to understand what your operator looks like. This method should however not be abused, as the reason of working with linear operators is indeed that you don't really need to access the explicit matrix representation of an operator.

2. Can I have an older version of cupy installed in my system (*****“cupy-cudaXX<8.1.0“?***** Yes. Nevertheless you need to tell PyLops that you don't want to use its `cupy` backend by setting the environment variable `CUPY_PYLOPS=0`. Failing to do so will lead to an error when you import `pylops` because some of the `cupyx` routines that we use are not available in earlier version of cupy.

3.7 PyLops API

The Application Programming Interface (API) of PyLops can be loosely seen as composed of a stack of three main layers:

- *Linear operators*: building blocks for the setting up of inverse problems
- *Solvers*: interfaces to a variety of solvers, providing an easy way to augment an inverse problem with additional regularization and/or preconditioning term
- *Applications*: high-level interfaces allowing users to easily setup and solve specific problems (while hiding the non-needed details - i.e., creation and setup of linear operators and solvers).

3.7.1 Linear operators

Templates

<code>LinearOperator</code> ([Op, explicit, clinear])	Common interface for performing matrix-vector products.
<code>FunctionOperator</code> (f, *args, **kwargs)	Function Operator.
<code>MemoizeOperator</code> (Op[, max_neval])	Memoize Operator.

pylops.LinearOperator

class `pylops.LinearOperator` (Op=None, explicit=False, clinear=None)

Common interface for performing matrix-vector products.

This class is an overload of the `scipy.sparse.linalg.LinearOperator` class. It adds functionalities by overloading standard operators such as `__truediv__` as well as creating convenience methods such as `eigs`, `cond`, and `conj`.

Note: End users of PyLops should not use this class directly but simply use operators that are already implemented. This class is meant for developers and it has to be used as the parent class of any new operator developed within PyLops. Find more details regarding implementation of new operators at [Implementing new operators](#).

Parameters

Op [`scipy.sparse.linalg.LinearOperator` or `scipy.sparse.linalg._ProductLinearOperator` or `scipy.sparse.linalg._SumLinearOperator`] Operator

explicit [`bool`] Operator contains a matrix that can be solved explicitly (True) or not (False)

Methods

<code>__init__</code> ([Op, explicit, clinear])	Initialize this LinearOperator.
<code>adjoint</code> ()	Hermitian adjoint.
<code>apply_columns</code> (cols)	Apply subset of columns of operator
<code>cond</code> ([uslobpcg])	Condition number of linear operator.
<code>conj</code> ()	Complex conjugate operator
<code>div</code> (y[, niter])	Solve the linear problem $y = Ax$.
<code>dot</code> (x)	Matrix-matrix or matrix-vector multiplication.
<code>eigs</code> ([neigs, symmetric, niter, uslobpcg])	Most significant eigenvalues of linear operator.
<code>matmat</code> (X)	Matrix-matrix multiplication.
<code>matvec</code> (x)	Matrix-vector multiplication.
<code>rmatmat</code> (X)	Matrix-matrix multiplication.
<code>rmatvec</code> (x)	Adjoint matrix-vector multiplication.
<code>todense</code> ([backend])	Return dense matrix.
<code>toimag</code> ([forw, adj])	Imag operator
<code>toreal</code> ([forw, adj])	Real operator
<code>tosparse</code> ()	Return sparse matrix.
<code>trace</code> ([neval, method, backend])	Trace of linear operator.
<code>transpose</code> ()	Transpose this linear operator.

matvec (x)

Matrix-vector multiplication.

Modified version of scipy matvec which does not consider the case where the input vector is `np.matrix` (the use `np.matrix` is now discouraged in numpy's documentation).

Parameters

x [`numpy.ndarray`] Input array of shape (N,) or (N,1)

Returns

y [`numpy.ndarray`] Output array of shape (M,) or (M,1)

rmatvec (*x*)

Adjoint matrix-vector multiplication.

Modified version of scipy rmatvec which does not consider the case where the input vector is `np.matrix` (the use `np.matrix` is now discouraged in numpy's documentation).

Parameters

y [`numpy.ndarray`] Input array of shape (M,) or (M,1)

Returns

x [`numpy.ndarray`] Output array of shape (N,) or (N,1)

matmat (*X*)

Matrix-matrix multiplication.

Modified version of scipy matmat which does not consider the case where the input vector is `np.matrix` (the use `np.matrix` is now discouraged in numpy's documentation).

Parameters

x [`numpy.ndarray`] Input array of shape (N,K)

Returns

y [`numpy.ndarray`] Output array of shape (M,K)

rmatmat (*X*)

Matrix-matrix multiplication.

Modified version of scipy rmatmat which does not consider the case where the input vector is `np.matrix` (the use `np.matrix` is now discouraged in numpy's documentation).

Parameters

x [`numpy.ndarray`] Input array of shape (M,K)

Returns

y [`numpy.ndarray`] Output array of shape (N,K)

dot (*x*)

Matrix-matrix or matrix-vector multiplication.

Parameters

x [`np.ndarray`] Input array (or matrix)

Returns

y [`np.ndarray`] Output array (or matrix) that represents the result of applying the linear operator on *x*.

div (*y*, *niter*=100)

Solve the linear problem $y = Ax$.

Overloading of operator `/` to improve expressivity of *Pylops* when solving inverse problems.

Parameters

y [`np.ndarray`] Data

niter [`int`, optional] Number of iterations (to be used only when `explicit=False`)

Returns

xest [`np.ndarray`] Estimated model

todense (*backend='numpy'*)

Return dense matrix.

The operator is converted into its dense matrix equivalent. In order to do so, square or tall operators are applied to an identity matrix whose number of rows and columns is equivalent to the number of columns of the operator. Conversely, for skinny operators, the transpose operator is applied to an identity matrix whose number of rows and columns is equivalent to the number of rows of the operator and the resulting matrix is transposed (and complex conjugated).

Note that this operation may be costly for operators with large number of rows and columns and it should be used mostly as a way to inspect the structure of the matricial equivalent of the operator.

Parameters

backend [`str`, optional] Backend used to densify matrix (`numpy` or `cupy`). Note that this must be consistent with how the operator has been created.

Returns

matrix [`numpy.ndarray` or `cupy.ndarray`] Dense matrix.

tosparse ()

Return sparse matrix.

The operator is converted into its sparse (CSR) matrix equivalent. In order to do so, the operator is applied to series of unit vectors with length equal to the number of columns in the original operator.

Returns

matrix [`scipy.sparse.csr_matrix`] Sparse matrix.

eigs (*neigs=None, symmetric=False, niter=None, uselobpcg=False, **kwargs_eig*)

Most significant eigenvalues of linear operator.

Return an estimate of the most significant eigenvalues of the linear operator. If the operator has rectangular shape (`shape[0] != shape[1]`), eigenvalues are first computed for the square operator $\mathbf{A}^H \mathbf{A}$ and the square-root values are returned.

Parameters

neigs [`int`] Number of eigenvalues to compute (if `None`, return all). Note that for `explicit=False`, only $N - 1$ eigenvalues can be computed where N is the size of the operator in the model space

symmetric [`bool`, optional] Operator is symmetric (`True`) or not (`False`). User should set this parameter to `True` only when it is guaranteed that the operator is real-symmetric or complex-hermitian matrices

niter [`int`, optional] Number of iterations for eigenvalue estimation

uselobpcg [`bool`, optional] Use `scipy.sparse.linalg.lobpcg`

****kwargs_eig** Arbitrary keyword arguments for `scipy.sparse.linalg.eigs`, `scipy.sparse.linalg.eigsh`, or `scipy.sparse.linalg.lobpcg`

Returns

eigenvalues [`numpy.ndarray`] Operator eigenvalues.

Raises

ValueError If `uselobpcg=True` for a non-symmetric square matrix with complex type

Notes

Depending on the size of the operator, whether it is explicit or not and the number of eigenvalues requested, different algorithms are used by this routine.

More precisely, when only a limited number of eigenvalues is requested the `scipy.sparse.linalg.eigsh` method is used in case of `symmetric=True` and the `scipy.sparse.linalg.eigs` method is used `symmetric=False`. However, when the matrix is represented explicitly within the linear operator (`explicit=True`) and all the eigenvalues are requested the `scipy.linalg.eigvals` is used instead.

Finally, when only a limited number of eigenvalues is required, it is also possible to explicitly choose to use the `scipy.sparse.linalg.lobpcg` method via the `uselobpcg` input parameter flag.

Most of these algorithms are a port of ARPACK [1], a Fortran package which provides routines for quickly finding eigenvalues/eigenvectors of a matrix. As ARPACK requires only left-multiplication by the matrix in question, eigenvalues/eigenvectors can also be estimated for linear operators when the dense matrix is not available.

cond (`uselobpcg=False`, ****kwargs_eig**)

Condition number of linear operator.

Return an estimate of the condition number of the linear operator as the ratio of the largest and lowest estimated eigenvalues.

Parameters

uselobpcg [`bool`, optional] Use `scipy.sparse.linalg.lobpcg` to compute eigenvalues

****kwargs_eig** Arbitrary keyword arguments for `scipy.sparse.linalg.eigs`, `scipy.sparse.linalg.eigsh`, or `scipy.sparse.linalg.lobpcg`

Returns

eigenvalues [`numpy.ndarray`] Operator eigenvalues.

Notes

The condition number of a matrix (or linear operator) can be estimated as the ratio of the largest and lowest estimated eigenvalues:

$$k = \frac{\lambda_{max}}{\lambda_{min}}$$

The condition number provides an indication of the rate at which the solution of the inversion of the linear operator A will change with respect to a change in the data y .

Thus, if the condition number is large, even a small error in y may cause a large error in x . On the other hand, if the condition number is small then the error in x is not much bigger than the error in y . A problem with a low condition number is said to be *well-conditioned*, while a problem with a high condition number is said to be *ill-conditioned*.

conj()

Complex conjugate operator

Returns

conjop [*pylops.LinearOperator*] Complex conjugate operator

apply_columns(cols)

Apply subset of columns of operator

This method can be used to wrap a *LinearOperator* and mimic the action of a subset of columns of the operator on a reduced model in forward mode, and retrieve only the result of a subset of rows in adjoint mode.

Note that unless the operator has `explicit=True`, this is not optimal as the entire forward and adjoint passes of the original operator will have to be performed. It can however be useful for the implementation of solvers such as Orthogonal Matching Pursuit (OMP) that iteratively build a solution by evaluate only a subset of the columns of the operator.

Parameters

cols [*list*] Columns to be selected

Returns

colop [*pylops.LinearOperator*] Apply column operator

toreal(forw=True, adj=True)

Real operator

Parameters

forw [*bool*, optional] Apply real to output of forward pass

adj [*bool*, optional] Apply real to output of adjoint pass

Returns

realop [*pylops.LinearOperator*] Real operator

toimag(forw=True, adj=True)

Imag operator

Parameters

forw [*bool*, optional] Apply imag to output of forward pass

adj [*bool*, optional] Apply imag to output of adjoint pass

Returns

imagop [*pylops.LinearOperator*] Imag operator

trace(neval=None, method=None, backend='numpy', **kwargs_trace)

Trace of linear operator.

Returns the trace (or its estimate) of the linear operator.

Parameters

neval [*int*, optional] Maximum number of matrix-vector products compute. Default depends `method`.

method [*str*, optional] Should be one of the following:

- **explicit**: If the operator is not explicit, will convert to dense first.
- **hutchinson**: see *pylops.utils.trace_hutchinson*

- **hutch++**: see `pylops.utils.trace_hutchpp`
- **na-hutch++**: see `pylops.utils.trace_nahutchpp`

Defaults to 'explicit' for explicit operators, and 'Hutch++' for the rest.

backend [`str`, optional] Backend used to densify matrix (`numpy` or `cupy`). Note that this must be consistent with how the operator has been created.

****kwargs_trace** Arbitrary keyword arguments passed to `pylops.utils.trace_hutchinson`, `pylops.utils.trace_hutchpp`, or `pylops.utils.trace_nahutchpp`

Returns

trace [`self.dtype`] Operator trace.

Raises

ValueError If the operator has rectangular shape (`shape[0] != shape[1]`)

NotImplementedError If the method is not one of the available methods.

Examples using `pylops.LinearOperator`

- `sphx_glr_gallery_plot_sliding.py`
- `sphx_glr_gallery_plot_patching.py`
- `sphx_glr_gallery_plot_avo.py`
- `sphx_glr_gallery_plot_bilinear.py`
- `sphx_glr_gallery_plot_cgls.py`
- `sphx_glr_gallery_plot_causalintegration.py`
- `sphx_glr_gallery_plot_chirpradon.py`
- `sphx_glr_gallery_plot_conj.py`
- `sphx_glr_gallery_plot_convolve.py`
- `sphx_glr_gallery_plot_derivative.py`
- `sphx_glr_gallery_plot_diagonal.py`
- `sphx_glr_gallery_plot_flip.py`
- `sphx_glr_gallery_plot_fft.py`
- `sphx_glr_gallery_plot_identity.py`
- `sphx_glr_gallery_plot_imag.py`
- `sphx_glr_gallery_plot_linearregr.py`
- `sphx_glr_gallery_plot_ista.py`
- `sphx_glr_gallery_plot_matrixmult.py`
- `sphx_glr_gallery_plot_mdc.py`
- `sphx_glr_gallery_plot_stacking.py`
- `sphx_glr_gallery_plot_multiproc.py`
- `sphx_glr_gallery_plot_pad.py`

- sphx_glr_gallery_plot_phaseshift.py
- sphx_glr_gallery_plot_regr.py
- sphx_glr_gallery_plot_prestack.py
- sphx_glr_gallery_plot_real.py
- sphx_glr_gallery_plot_restriction.py
- sphx_glr_gallery_plot_roll.py
- sphx_glr_gallery_plot_seislet.py
- sphx_glr_gallery_plot_shift.py
- sphx_glr_gallery_plot_sum.py
- sphx_glr_gallery_plot_symmetrize.py
- sphx_glr_gallery_plot_tvreg.py
- sphx_glr_gallery_plot_transpose.py
- sphx_glr_gallery_plot_wavest.py
- sphx_glr_gallery_plot_wavelet.py
- sphx_glr_gallery_plot_zero.py
- *01. The LinearOperator*
- *02. The Dot-Test*
- *03. Solvers*
- *04. Bayesian Inversion*
- *05. Image deblurring*
- *06. 2D Interpolation*
- *07. Post-stack inversion*
- *08. Pre-stack (AVO) inversion*
- *09. Multi-Dimensional Deconvolution*
- *12. Seismic regularization*
- *14. Seismic wavefield decomposition*
- *15. Least-squares migration*
- *16. CT Scan Imaging*
- *17. Real/Complex Inversion*

pylops.FunctionOperator

class pylops.**FunctionOperator** (*f*, **args*, ***kwargs*)

Function Operator.

Simple wrapper to functions for forward *f* and adjoint *fc* multiplication.

Functions *f* and *fc* are such that $f : \mathbb{F}^m \rightarrow \mathbb{F}^n$ and $fc : \mathbb{F}^n \rightarrow \mathbb{F}^m$ where \mathbb{F} is the appropriate underlying type (e.g., \mathbb{R} for real or \mathbb{C} for complex)

FunctionOperator can be called in the following ways: `FunctionOperator(f, n)`, `FunctionOperator(f, n, m)`, `FunctionOperator(f, fc, n)`, and `FunctionOperator(f, fc, n, m)`.

The first two methods can only be used for forward modelling and will return *NotImplementedError* if the adjoint is called. The first and third method assume the matrix (or matrices) to be square. All methods can be called with the *dtype* keyword argument.

Parameters

- f** [callable] Function for forward multiplication.
- fc** [callable, optional] Function for adjoint multiplication.
- n** [int, optional] Number of rows (length of data vector).
- m** [int, optional] Number of columns (length of model vector).
- dtype** [str, optional] Type of elements in input array.

Examples

```
>>> from pylops.basicoperators import FunctionOperator
>>> def forward(v):
...     return np.array([2*v[0], 3*v[1]])
...
>>> A = FunctionOperator(forward, 2)
>>> A
<2x2 FunctionOperator with dtype=float64>
>>> A.matvec(np.ones(2))
array([2., 3.])
>>> A @ np.ones(2)
array([2., 3.])
```

Attributes

- shape** [tuple] Operator shape [$n \times m$]
- explicit** [bool] Operator contains a matrix that can be solved explicitly (True) or not (False)

Methods

<code>__init__(f, *args, **kwargs)</code>	Initialize this LinearOperator.
<code>adjoint()</code>	Hermitian adjoint.
<code>apply_columns(cols)</code>	Apply subset of columns of operator
<code>cond([uselobpcg])</code>	Condition number of linear operator.
<code>conj()</code>	Complex conjugate operator
<code>div(y[, niter])</code>	Solve the linear problem $y = Ax$.
<code>dot(x)</code>	Matrix-matrix or matrix-vector multiplication.
<code>eigs([neigs, symmetric, niter, uselobpcg])</code>	Most significant eigenvalues of linear operator.
<code>matmat(X)</code>	Matrix-matrix multiplication.
<code>matvec(x)</code>	Matrix-vector multiplication.
<code>rmatmat(X)</code>	Matrix-matrix multiplication.
<code>rmatvec(x)</code>	Adjoint matrix-vector multiplication.
<code>todense([backend])</code>	Return dense matrix.

Continued on next page

Table 3 – continued from previous page

<code>toimag([forw, adj])</code>	Imag operator
<code>toreal([forw, adj])</code>	Real operator
<code>tosparse()</code>	Return sparse matrix.
<code>trace([neval, method, backend])</code>	Trace of linear operator.
<code>transpose()</code>	Transpose this linear operator.

pylops.MemoizeOperator

class `pylops.MemoizeOperator` (*Op*, *max_neval*=10)

Memoize Operator.

This operator can be used to wrap any PyLops operator and add a memoize functionality and stores the last `max_neval` model/data vector pairs

Parameters

Op [`pylops.LinearOperator`] PyLops linear operator

max_neval [`int`, optional] Maximum number of previous evaluations stored, use `np.inf` for infinite memory

Attributes

shape [`tuple`] Operator shape [$n \times m$]

explicit [`bool`] Operator contains a matrix that can be solved explicitly (`True`) or not (`False`)

Methods

<code>__init__(Op[, max_neval])</code>	Initialize this LinearOperator.
<code>adjoint()</code>	Hermitian adjoint.
<code>apply_columns(cols)</code>	Apply subset of columns of operator
<code>cond([uselobpcg])</code>	Condition number of linear operator.
<code>conj()</code>	Complex conjugate operator
<code>div(y[, niter])</code>	Solve the linear problem $\mathbf{y} = \mathbf{A}\mathbf{x}$.
<code>dot(x)</code>	Matrix-matrix or matrix-vector multiplication.
<code>eigs([neigs, symmetric, niter, uselobpcg])</code>	Most significant eigenvalues of linear operator.
<code>matmat(X)</code>	Matrix-matrix multiplication.
<code>matvec(x)</code>	Matrix-vector multiplication.
<code>rmatmat(X)</code>	Matrix-matrix multiplication.
<code>rmatvec(x)</code>	Adjoint matrix-vector multiplication.
<code>todense([backend])</code>	Return dense matrix.
<code>toimag([forw, adj])</code>	Imag operator
<code>toreal([forw, adj])</code>	Real operator
<code>tosparse()</code>	Return sparse matrix.
<code>trace([neval, method, backend])</code>	Trace of linear operator.
<code>transpose()</code>	Transpose this linear operator.

Examples using `pylops.MemoizeOperator`

- 17. Real/Complex Inversion

Basic operators

<i>MatrixMult</i> (A[, dims, dtype])	Matrix multiplication.
<i>Identity</i> (N[, M, dtype, inplace])	Identity operator.
<i>Zero</i> (N[, M, dtype])	Zero operator.
<i>Diagonal</i> (diag[, dims, dir, dtype])	Diagonal operator.
<i>Transpose</i> (dims, axes[, dtype])	Transpose operator.
<i>Flip</i> (N[, dims, dir, dtype])	Flip along an axis.
<i>Roll</i> (N[, dims, dir, shift, dtype])	Roll along an axis.
<i>Pad</i> (dims, pad[, dtype])	Pad operator.
<i>Sum</i> (dims, dir[, dtype])	Sum operator.
<i>Symmetrize</i> (N[, dims, dir, dtype])	Symmetrize along an axis.
<i>Restriction</i> (M, iava[, dims, dir, dtype, inplace])	Restriction (or sampling) operator.
<i>Regression</i> (taxis, order[, dtype])	Polynomial regression.
<i>LinearRegression</i> (taxis[, dtype])	Linear regression.
<i>CausalIntegration</i> (N[, dims, dir, sampling, ...])	Causal integration.
<i>Spread</i> (dims, dimsd[, table, dtable, fh, ...])	Spread operator.
<i>VStack</i> (ops[, nproc, dtype])	Vertical stacking.
<i>HStack</i> (ops[, nproc, dtype])	Horizontal stacking.
<i>Block</i> (ops[, nproc, dtype])	Block operator.
<i>BlockDiag</i> (ops[, nproc, dtype])	Block-diagonal operator.
<i>Kronecker</i> (Op1, Op2[, dtype])	Kronecker operator.
<i>Real</i> (dims[, dtype])	Real operator.
<i>Imag</i> (dims[, dtype])	Imag operator.
<i>Conj</i> (dims[, dtype])	Complex conjugate operator.

pylops.MatrixMult

class `pylops.MatrixMult` (*A*, *dims=None*, *dtype='float64'*)

Matrix multiplication.

Simple wrapper to `numpy.dot` and `numpy.vdot` for an input matrix *A*.

Parameters

A [`numpy.ndarray` or `scipy.sparse` matrix] Matrix.

dims [`tuple`, optional] Number of samples for each other dimension of model (model/data will be reshaped and A applied multiple times to each column of the model/data).

dtype [`str`, optional] Type of elements in input array.

Attributes

shape [`tuple`] Operator shape

explicit [`bool`] Operator contains a matrix that can be solved explicitly (True) or not (False)

complex [`bool`] Matrix has complex numbers (True) or not (False)

Methods

<code>__init__</code> (A[, dims, dtype])	Initialize this LinearOperator.
<code>adjoint</code> ()	Hermitian adjoint.

Continued on next page

Table 6 – continued from previous page

<code>apply_columns(cols)</code>	Apply subset of columns of operator
<code>cond([uselobpcg])</code>	Condition number of linear operator.
<code>conj()</code>	Complex conjugate operator
<code>div(y[, niter])</code>	Solve the linear problem $\mathbf{y} = \mathbf{Ax}$.
<code>dot(x)</code>	Matrix-matrix or matrix-vector multiplication.
<code>eigs([neigs, symmetric, niter, uselobpcg])</code>	Most significant eigenvalues of linear operator.
<code>inv()</code>	Return the inverse of \mathbf{A} .
<code>matmat(X)</code>	Matrix-matrix multiplication.
<code>matvec(x)</code>	Matrix-vector multiplication.
<code>rmatmat(X)</code>	Matrix-matrix multiplication.
<code>rmatvec(x)</code>	Adjoint matrix-vector multiplication.
<code>todense([backend])</code>	Return dense matrix.
<code>toimag([forw, adj])</code>	Imag operator
<code>toreal([forw, adj])</code>	Real operator
<code>tosparse()</code>	Return sparse matrix.
<code>trace([neval, method, backend])</code>	Trace of linear operator.
<code>transpose()</code>	Transpose this linear operator.

inv()

Return the inverse of \mathbf{A} .

Returns

Ainv [numpy.ndarray] Inverse matrix.

Examples using `pylops.MatrixMult`

- `sphx_glr_gallery_plot_cgls.py`
- `sphx_glr_gallery_plot_ista.py`
- `sphx_glr_gallery_plot_matrixmult.py`
- `sphx_glr_gallery_plot_stacking.py`
- `sphx_glr_gallery_plot_multiproc.py`
- *02. The Dot-Test*
- *03. Solvers*
- *07. Post-stack inversion*
- *08. Pre-stack (AVO) inversion*
- *17. Real/Complex Inversion*

`pylops.Identity`

class `pylops.Identity` ($N, M=None, dtype='float64', inplace=True$)

Identity operator.

Simply move model to data in forward model and viceversa in adjoint mode if $M = N$. If $M > N$ removes last $M - N$ elements from model in forward and pads with 0 in adjoint. If $N > M$ removes last $N - M$ elements from data in adjoint and pads with 0 in forward.

Parameters

N [`int`] Number of samples in data (and model, if **M** is not provided).

M [`int`, optional] Number of samples in model.

dtype [`str`, optional] Type of elements in input array.

inplace [`bool`, optional] Work inplace (`True`) or make a new copy (`False`). By default, data is a reference to the model (in forward) and model is a reference to the data (in adjoint).

Notes

For $M = N$, an *Identity* operator simply moves the model \mathbf{x} to the data \mathbf{y} in forward mode and viceversa in adjoint mode:

$$y_i = x_i \quad \forall i = 1, 2, \dots, N$$

or in matrix form:

$$\mathbf{y} = \mathbf{I}\mathbf{x} = \mathbf{x}$$

and

$$\mathbf{x} = \mathbf{I}\mathbf{y} = \mathbf{y}$$

For $M > N$, the *Identity* operator takes the first M elements of the model \mathbf{x} into the data \mathbf{y} in forward mode

$$y_i = x_i \quad \forall i = 1, 2, \dots, N$$

and all the elements of the data \mathbf{y} into the first M elements of model in adjoint mode (other elements are 0):

$$\begin{aligned} x_i &= y_i \quad \forall i = 1, 2, \dots, M \\ x_i &= 0 \quad \forall i = M + 1, \dots, N \end{aligned}$$

Attributes

shape [`tuple`] Operator shape

explicit [`bool`] Operator contains a matrix that can be solved explicitly (`True`) or not (`False`)

Methods

<code>__init__(N[, M, dtype, inplace])</code>	Initialize this LinearOperator.
<code>adjoint()</code>	Hermitian adjoint.
<code>apply_columns(cols)</code>	Apply subset of columns of operator
<code>cond([uslobpcg])</code>	Condition number of linear operator.
<code>conj()</code>	Complex conjugate operator
<code>div(y[, niter])</code>	Solve the linear problem $\mathbf{y} = \mathbf{A}\mathbf{x}$.
<code>dot(x)</code>	Matrix-matrix or matrix-vector multiplication.
<code>eigs([neigs, symmetric, niter, uslobpcg])</code>	Most significant eigenvalues of linear operator.
<code>matmat(X)</code>	Matrix-matrix multiplication.
<code>matvec(x)</code>	Matrix-vector multiplication.
<code>rmatmat(X)</code>	Matrix-matrix multiplication.
<code>rmatvec(x)</code>	Adjoint matrix-vector multiplication.
<code>todense([backend])</code>	Return dense matrix.

Continued on next page

Table 7 – continued from previous page

<code>toimag([forw, adj])</code>	Imag operator
<code>toreal([forw, adj])</code>	Real operator
<code>tosparse()</code>	Return sparse matrix.
<code>trace([neval, method, backend])</code>	Trace of linear operator.
<code>transpose()</code>	Transpose this linear operator.

Examples using `pylops.Identity`

- `sphx_glr_gallery_plot_identity.py`
- `sphx_glr_gallery_plot_stacking.py`
- `sphx_glr_gallery_plot_tvreg.py`
- *04. Bayesian Inversion*

`pylops.Zero`

class `pylops.Zero` (N , $M=None$, $dtype='float64'$)

Zero operator.

Transform model into array of zeros of size N in forward and transform data into array of zeros of size N in adjoint.

Parameters

N [`int`] Number of samples in data (and model in M is not provided).

M [`int`, optional] Number of samples in model.

dtype [`str`, optional] Type of elements in input array.

Notes

An *Zero* operator simply creates a null data vector \mathbf{y} in forward mode:

$$\mathbf{0x} = \mathbf{0}_N$$

and a null model vector \mathbf{x} in forward mode:

$$\mathbf{0y} = \mathbf{0}_M$$

Attributes

shape [`tuple`] Operator shape

explicit [`bool`] Operator contains a matrix that can be solved explicitly (`True`) or not (`False`)

Methods

<code>__init__(N[, M, dtype])</code>	Initialize this LinearOperator.
<code>adjoint()</code>	Hermitian adjoint.
<code>apply_columns(cols)</code>	Apply subset of columns of operator

Continued on next page

Table 8 – continued from previous page

<code>cond([uselobpcg])</code>	Condition number of linear operator.
<code>conj()</code>	Complex conjugate operator
<code>div(y[, niter])</code>	Solve the linear problem $\mathbf{y} = \mathbf{Ax}$.
<code>dot(x)</code>	Matrix-matrix or matrix-vector multiplication.
<code>eigs([neigs, symmetric, niter, uselobpcg])</code>	Most significant eigenvalues of linear operator.
<code>matmat(X)</code>	Matrix-matrix multiplication.
<code>matvec(x)</code>	Matrix-vector multiplication.
<code>rmatmat(X)</code>	Matrix-matrix multiplication.
<code>rmatvec(x)</code>	Adjoint matrix-vector multiplication.
<code>todense([backend])</code>	Return dense matrix.
<code>toimag([forw, adj])</code>	Imag operator
<code>toreal([forw, adj])</code>	Real operator
<code>tosparse()</code>	Return sparse matrix.
<code>trace([neval, method, backend])</code>	Trace of linear operator.
<code>transpose()</code>	Transpose this linear operator.

Examples using `pylops.Zero`

- `sphx_glr_gallery_plot_zero.py`

`pylops.Diagonal`

class `pylops.Diagonal` (*diag, dims=None, dir=0, dtype='float64'*)

Diagonal operator.

Applies element-wise multiplication of the input vector with the vector `diag` in forward and with its complex conjugate in adjoint mode.

This operator can also broadcast; in this case the input vector is reshaped into its dimensions `dims` and the element-wise multiplication with `diag` is performed on the direction `dir`. Note that the vector `diag` will need to have size equal to `dims[dir]`.

Parameters

diag [`numpy.ndarray`] Vector to be used for element-wise multiplication.

dims [`list`, optional] Number of samples for each dimension (`None` if only one dimension is available)

dir [`int`, optional] Direction along which multiplication is applied.

dtype [`str`, optional] Type of elements in input array.

Notes

Element-wise multiplication between the model \mathbf{x} and/or data \mathbf{y} vectors and the array \mathbf{d} can be expressed as

$$y_i = d_i x_i \quad \forall i = 1, 2, \dots, N$$

This is equivalent to a matrix-vector multiplication with a matrix containing the vector \mathbf{d} along its main diagonal.

For real-valued `diag`, the `Diagonal` operator is self-adjoint as the adjoint of a diagonal matrix is the diagonal matrix itself. For complex-valued `diag`, the adjoint is equivalent to the element-wise multiplication with the complex conjugate elements of `diag`.

Attributes

shape [tuple] Operator shape

explicit [bool] Operator contains a matrix that can be solved explicitly (True) or not (False)

Methods

<code>__init__(diag[, dims, dir, dtype])</code>	Initialize this LinearOperator.
<code>adjoint()</code>	Hermitian adjoint.
<code>apply_columns(cols)</code>	Apply subset of columns of operator
<code>cond([uselobpcg])</code>	Condition number of linear operator.
<code>conj()</code>	Complex conjugate operator
<code>div(y[, niter])</code>	Solve the linear problem $y = Ax$.
<code>dot(x)</code>	Matrix-matrix or matrix-vector multiplication.
<code>eigs([neigs, symmetric, niter, uselobpcg])</code>	Most significant eigenvalues of linear operator.
<code>matmat(X)</code>	Matrix-matrix multiplication.
<code>matrix()</code>	Return diagonal matrix as dense <code>numpy.ndarray</code>
<code>matvec(x)</code>	Matrix-vector multiplication.
<code>rmatmat(X)</code>	Matrix-matrix multiplication.
<code>rmatvec(x)</code>	Adjoint matrix-vector multiplication.
<code>todense()</code>	Fast implementation of todense based on known structure of the operator
<code>toimag([forw, adj])</code>	Imag operator
<code>toreal([forw, adj])</code>	Real operator
<code>tosparse()</code>	Return sparse matrix.
<code>trace([neval, method, backend])</code>	Trace of linear operator.
<code>transpose()</code>	Transpose this linear operator.

matrix()

Return diagonal matrix as dense `numpy.ndarray`

Returns

densemat [numpy.ndarray] Dense matrix.

todense()

Fast implementation of todense based on known structure of the operator

Returns

densemat [numpy.ndarray] Dense matrix.

Examples using `pylops.Diagonal`

- `sphx_glr_gallery_plot_diagonal.py`
- *01. The LinearOperator*
- *02. The Dot-Test*

pylops.Transpose

class pylops.**Transpose** (*dims*, *axes*, *dtype*='float64')

Transpose operator.

Transpose axes of a multi-dimensional array. This operator works with flattened input model (or data), which are however multi-dimensional in nature and will be reshaped and treated as such in both forward and adjoint modes.

Parameters

dims [*tuple*, optional] Number of samples for each dimension

axes [*tuple*, optional] Direction along which transposition is applied

dtype [*str*, optional] Type of elements in input array

Raises

ValueError If *axes* contains repeated dimensions (or a dimension is missing)

Notes

The Transpose operator reshapes the input model into a multi-dimensional array of size *dims* and transposes (or swaps) its axes as defined in *axes*.

Similarly, in adjoint mode the data is reshaped into a multi-dimensional array whose size is a permuted version of *dims* defined by *axes*. The array is then rearranged into the original model dimensions *dims*.

Attributes

shape [*tuple*] Operator shape

explicit [*bool*] Operator contains a matrix that can be solved explicitly (*True*) or not (*False*)

Methods

<code>__init__(dims, axes[, dtype])</code>	Initialize this LinearOperator.
<code>adjoint()</code>	Hermitian adjoint.
<code>apply_columns(cols)</code>	Apply subset of columns of operator
<code>cond([uselobpcg])</code>	Condition number of linear operator.
<code>conj()</code>	Complex conjugate operator
<code>div(y[, niter])</code>	Solve the linear problem $\mathbf{y} = \mathbf{Ax}$.
<code>dot(x)</code>	Matrix-matrix or matrix-vector multiplication.
<code>eigs([neigs, symmetric, niter, uselobpcg])</code>	Most significant eigenvalues of linear operator.
<code>matmat(X)</code>	Matrix-matrix multiplication.
<code>matvec(x)</code>	Matrix-vector multiplication.
<code>rmatmat(X)</code>	Matrix-matrix multiplication.
<code>rmatvec(x)</code>	Adjoint matrix-vector multiplication.
<code>todense([backend])</code>	Return dense matrix.
<code>toimag([forw, adj])</code>	Imag operator
<code>toreal([forw, adj])</code>	Real operator
<code>tosparse()</code>	Return sparse matrix.
<code>trace([neval, method, backend])</code>	Trace of linear operator.
<code>transpose()</code>	Transpose this linear operator.

Examples using `pylops.Transpose`

- `sphx_glr_gallery_plot_transpose.py`

`pylops.Flip`

class `pylops.Flip` (*N*, *dims=None*, *dir=0*, *dtype='float64'*)

Flip along an axis.

Flip a multi-dimensional array along a specified direction *dir*.

Parameters

N [`int`] Number of samples in model.

dims [`list`, optional] Number of samples for each dimension (`None` if only one dimension is available)

dir [`int`, optional] Direction along which flipping is applied.

dtype [`str`, optional] Type of elements in input array.

Notes

The Flip operator flips the input model (and data) along any chosen direction. For simplicity, given a one dimensional array, in forward mode this is equivalent to:

$$y[i] = x[N - i] \quad \forall i = 0, 1, 2, \dots, N - 1$$

where N is the length of the input model. As this operator is self-adjoint, x and y in the equation above are simply swapped in adjoint mode.

Attributes

shape [`tuple`] Operator shape

explicit [`bool`] Operator contains a matrix that can be solved explicitly (`True`) or not (`False`)

Methods

<code>__init__(N[, dims, dir, dtype])</code>	Initialize this LinearOperator.
<code>adjoint()</code>	Hermitian adjoint.
<code>apply_columns(cols)</code>	Apply subset of columns of operator
<code>cond([uselobpcg])</code>	Condition number of linear operator.
<code>conj()</code>	Complex conjugate operator
<code>div(y[, niter])</code>	Solve the linear problem $\mathbf{y} = \mathbf{Ax}$.
<code>dot(x)</code>	Matrix-matrix or matrix-vector multiplication.
<code>eigs([neigs, symmetric, niter, uselobpcg])</code>	Most significant eigenvalues of linear operator.
<code>matmat(X)</code>	Matrix-matrix multiplication.
<code>matvec(x)</code>	Matrix-vector multiplication.
<code>rmatmat(X)</code>	Matrix-matrix multiplication.
<code>rmatvec(x)</code>	Adjoint matrix-vector multiplication.
<code>todense([backend])</code>	Return dense matrix.
<code>toimag([forw, adj])</code>	Imag operator

Continued on next page

Table 11 – continued from previous page

<code>toreal([forw, adj])</code>	Real operator
<code>tosparse()</code>	Return sparse matrix.
<code>trace([neval, method, backend])</code>	Trace of linear operator.
<code>transpose()</code>	Transpose this linear operator.

Examples using `pylops.Flip`

- `sphx_glr_gallery_plot_flip.py`

`pylops.Roll`

class `pylops.Roll` (*N*, *dims=None*, *dir=0*, *shift=1*, *dtype='float64'*)

Roll along an axis.

Roll a multi-dimensional array along a specified direction *dir* for a chosen number of samples (*shift*).

Parameters

N [*int*] Number of samples in model.

dims [*list*, optional] Number of samples for each dimension (*None* if only one dimension is available)

dir [*int*, optional] Direction along which rolling is applied.

shift [*int*, optional] Number of samples by which elements are shifted

dtype [*str*, optional] Type of elements in input array.

Notes

The Roll operator is a thin wrapper around `numpy.roll` and shifts elements in a multi-dimensional array along a specified direction for a chosen number of samples.

Attributes

shape [*tuple*] Operator shape

explicit [*bool*] Operator contains a matrix that can be solved explicitly (*True*) or not (*False*)

Methods

<code>__init__(N[, dims, dir, shift, dtype])</code>	Initialize this LinearOperator.
<code>adjoint()</code>	Hermitian adjoint.
<code>apply_columns(cols)</code>	Apply subset of columns of operator
<code>cond([uslobpcg])</code>	Condition number of linear operator.
<code>conj()</code>	Complex conjugate operator
<code>div(y[, niter])</code>	Solve the linear problem $y = Ax$.
<code>dot(x)</code>	Matrix-matrix or matrix-vector multiplication.
<code>eigs([neigs, symmetric, niter, uslobpcg])</code>	Most significant eigenvalues of linear operator.
<code>matmat(X)</code>	Matrix-matrix multiplication.
<code>matvec(x)</code>	Matrix-vector multiplication.
<code>rmatmat(X)</code>	Matrix-matrix multiplication.

Continued on next page

Table 12 – continued from previous page

<code>rmatvec(x)</code>	Adjoint matrix-vector multiplication.
<code>todense([backend])</code>	Return dense matrix.
<code>toimag([forw, adj])</code>	Imag operator
<code>toreal([forw, adj])</code>	Real operator
<code>tosparse()</code>	Return sparse matrix.
<code>trace([neval, method, backend])</code>	Trace of linear operator.
<code>transpose()</code>	Transpose this linear operator.

Examples using `pylops.Roll`

- `sphx_glr_gallery_plot_roll.py`

`pylops.Pad`

class `pylops.Pad` (*dims*, *pad*, *dtype*=`'float64'`)

Pad operator.

Zero-pad model in forward model and extract non-zero subsequence in adjoint. Padding can be performed in one or multiple directions to any multi-dimensional input arrays.

Parameters

dims [`int` or `tuple`] Number of samples for each dimension

pad [`tuple`] Number of samples to pad. If *dims* is a scalar, *pad* is a single tuple (`pad_in`, `pad_end`). If *dims* is a tuple, *pad* is a tuple of tuples where each inner tuple contains the number of samples to pad in each dimension

dtype [`str`, optional] Type of elements in input array.

Raises

ValueError If any element of *pad* is negative.

Notes

Given an array of size N , the *Pad* operator simply adds pad_{in} at the start and pad_{end} at the end in forward mode:

$$y_i = x_{i-pad_{in}} \quad \forall i = pad_{in}, pad_{in} + 1, \dots, pad_{in} + N - 1$$

and $y_i = 0 \quad \forall i = 0, \dots, pad_{in} - 1, pad_{in} + N - 1, \dots, N + pad_{in} + pad_{end}$

In adjoint mode, values from pad_{in} to $N - pad_{end}$ are extracted from the data:

$$x_i = y_{pad_{in}+i} \quad \forall i = 0, N - 1$$

Attributes

shape [`tuple`] Operator shape

explicit [`bool`] Operator contains a matrix that can be solved explicitly (`True`) or not (`False`)

Methods

<code>__init__(dims, pad[, dtype])</code>	Initialize this LinearOperator.
<code>adjoint()</code>	Hermitian adjoint.
<code>apply_columns(cols)</code>	Apply subset of columns of operator
<code>cond([uselobpcg])</code>	Condition number of linear operator.
<code>conj()</code>	Complex conjugate operator
<code>div(y[, niter])</code>	Solve the linear problem $\mathbf{y} = \mathbf{A}\mathbf{x}$.
<code>dot(x)</code>	Matrix-matrix or matrix-vector multiplication.
<code>eigs([neigs, symmetric, niter, uselobpcg])</code>	Most significant eigenvalues of linear operator.
<code>matmat(X)</code>	Matrix-matrix multiplication.
<code>matvec(x)</code>	Matrix-vector multiplication.
<code>rmatmat(X)</code>	Matrix-matrix multiplication.
<code>rmatvec(x)</code>	Adjoint matrix-vector multiplication.
<code>todense([backend])</code>	Return dense matrix.
<code>toimag([forw, adj])</code>	Imag operator
<code>toreal([forw, adj])</code>	Real operator
<code>tosparse()</code>	Return sparse matrix.
<code>trace([neval, method, backend])</code>	Trace of linear operator.
<code>transpose()</code>	Transpose this linear operator.

Examples using `pylops.Pad`

- `sphx_glr_gallery_plot_pad.py`

`pylops.Sum`

class `pylops.Sum` (*dims*, *dir*, *dtype*='float64')
Sum operator.

Sum along an axis of a multi-dimensional array (at least 2 dimensions are required) in forward model, and spread along the same axis in adjoint mode.

Parameters

- dims** [`tuple`] Number of samples for each dimension
- dir** [`int`] Direction along which summation is performed.
- dtype** [`str`, optional] Type of elements in input array.

Notes

Given a two dimensional array, the *Sum* operator re-arranges the input model into a multi-dimensional array of size *dims* and sums values along direction *dir*:

$$y_j = \sum_i x_{i,j}$$

In adjoint mode, the data is spread along the same direction:

$$x_{i,j} = y_j \quad \forall i = 0, N - 1$$

Attributes

- shape** [`tuple`] Operator shape
- explicit** [`bool`] Operator contains a matrix that can be solved explicitly (`True`) or not (`False`)

Methods

<code>__init__(dims, dir[, dtype])</code>	Initialize this LinearOperator.
<code>adjoint()</code>	Hermitian adjoint.
<code>apply_columns(cols)</code>	Apply subset of columns of operator
<code>cond([uselobpcg])</code>	Condition number of linear operator.
<code>conj()</code>	Complex conjugate operator
<code>div(y[, niter])</code>	Solve the linear problem $\mathbf{y} = \mathbf{A}\mathbf{x}$.
<code>dot(x)</code>	Matrix-matrix or matrix-vector multiplication.
<code>eigs([neigs, symmetric, niter, uselobpcg])</code>	Most significant eigenvalues of linear operator.
<code>matmat(X)</code>	Matrix-matrix multiplication.
<code>matvec(x)</code>	Matrix-vector multiplication.
<code>rmatmat(X)</code>	Matrix-matrix multiplication.
<code>rmatvec(x)</code>	Adjoint matrix-vector multiplication.
<code>todense([backend])</code>	Return dense matrix.
<code>toimag([forw, adj])</code>	Imag operator
<code>toreal([forw, adj])</code>	Real operator
<code>tosparse()</code>	Return sparse matrix.
<code>trace([neval, method, backend])</code>	Trace of linear operator.
<code>transpose()</code>	Transpose this linear operator.

Examples using `pylops.Sum`

- `sphx_glr_gallery_plot_sum.py`

`pylops.Symmetrize`

class `pylops.Symmetrize` (*N*, *dims=None*, *dir=0*, *dtype='float64'*)

Symmetrize along an axis.

Symmetrize a multi-dimensional array along a specified direction *dir*.

Parameters

N [`int`] Number of samples in model. Symmetric data has $2N - 1$ samples

dims [`list`, optional] Number of samples for each dimension (`None` if only one dimension is available)

dir [`int`, optional] Direction along which symmetrization is applied

dtype [`str`, optional] Type of elements in input array

Notes

The Symmetrize operator constructs a symmetric array given an input model in forward mode, by pre-pending the input model in reversed order.

For simplicity, given a one dimensional array, the forward operation can be expressed as:

$$y[i] = \begin{cases} x[i - N], & i \geq N \\ x[N - i], & \text{otherwise} \end{cases}$$

for $i = 0, 1, 2, \dots, 2N - 2$, where N is the lenght of the input model.

In adjoint mode, the Symmetrize operator assigns the sums of the elements in position $N - i$ and $N + i$ to position i as follows:

apart from the central sample where $x[0] = y[N]$.

Attributes

shape `[tuple]` Operator shape

explicit `[bool]` Operator contains a matrix that can be solved explicitly (`True`) or not (`False`)

Methods

<code>__init__(N[, dims, dir, dtype])</code>	Initialize this LinearOperator.
<code>adjoint()</code>	Hermitian adjoint.
<code>apply_columns(cols)</code>	Apply subset of columns of operator
<code>cond([uselobpcg])</code>	Condition number of linear operator.
<code>conj()</code>	Complex conjugate operator
<code>div(y[, niter])</code>	Solve the linear problem $\mathbf{y} = \mathbf{Ax}$.
<code>dot(x)</code>	Matrix-matrix or matrix-vector multiplication.
<code>eigs([neigs, symmetric, niter, uselobpcg])</code>	Most significant eigenvalues of linear operator.
<code>matmat(X)</code>	Matrix-matrix multiplication.
<code>matvec(x)</code>	Matrix-vector multiplication.
<code>rmatmat(X)</code>	Matrix-matrix multiplication.
<code>rmatvec(x)</code>	Adjoint matrix-vector multiplication.
<code>todense([backend])</code>	Return dense matrix.
<code>toimag([forw, adj])</code>	Imag operator
<code>toreal([forw, adj])</code>	Real operator
<code>tosparse()</code>	Return sparse matrix.
<code>trace([neval, method, backend])</code>	Trace of linear operator.
<code>transpose()</code>	Transpose this linear operator.

Examples using `pylops.Symmetrize`

- `sphx_glr_gallery_plot_symmetrize.py`
- `sphx_glr_gallery_plot_wavest.py`

`pylops.Restriction`

class `pylops.Restriction` (*M*, *iava*, *dims=None*, *dir=0*, *dtype='float64'*, *inplace=True*)

Restriction (or sampling) operator.

Extract subset of values from input vector at locations *iava* in forward mode and place those values at locations *iava* in an otherwise zero vector in adjoint mode.

Parameters

M `[int]` Number of samples in model.

iava `[list or numpy.ndarray]` Integer indices of available samples for data selection.

dims `[list]` Number of samples for each dimension (`None` if only one dimension is available)

dir [`int`, optional] Direction along which restriction is applied.

dtype [`str`, optional] Type of elements in input array.

inplace [`bool`, optional] Work inplace (`True`) or make a new copy (`False`). By default, data is a reference to the model (in forward) and model is a reference to the data (in adjoint).

See also:

`pylops.signalprocessing.Interp` Interpolation operator

Notes

Extraction (or *sampling*) of a subset of N values at locations `iava` from an input (or model) vector \mathbf{x} of size M can be expressed as:

$$y_i = x_{l_i} \quad \forall i = 1, 2, \dots, N$$

where $\mathbf{l} = [l_1, l_2, \dots, l_N]$ is a vector containing the indices of the original array at which samples are taken.

Conversely, in adjoint mode the available values in the data vector \mathbf{y} are placed at locations $\mathbf{l} = [l_1, l_2, \dots, l_M]$ in the model vector:

$$x_{l_i} = y_i \quad \forall i = 1, 2, \dots, N$$

and $x_j = 0 \quad j \neq l_i$ (i.e., at all other locations in input vector).

Attributes

shape [`tuple`] Operator shape

explicit [`bool`] Operator contains a matrix that can be solved explicitly (`True`) or not (`False`)

Methods

<code>__init__(M, iava[, dims, dir, dtype, inplace])</code>	Initialize this LinearOperator.
<code>adjoint()</code>	Hermitian adjoint.
<code>apply_columns(cols)</code>	Apply subset of columns of operator
<code>cond([uselobpcg])</code>	Condition number of linear operator.
<code>conj()</code>	Complex conjugate operator
<code>div(y[, niter])</code>	Solve the linear problem $\mathbf{y} = \mathbf{A}\mathbf{x}$.
<code>dot(x)</code>	Matrix-matrix or matrix-vector multiplication.
<code>eigs([neigs, symmetric, niter, uselobpcg])</code>	Most significant eigenvalues of linear operator.
<code>mask(x)</code>	Apply mask to input signal returning a signal of same size with values at <code>iava</code> locations and 0 at other locations
<code>matmat(X)</code>	Matrix-matrix multiplication.
<code>matvec(x)</code>	Matrix-vector multiplication.
<code>rmatmat(X)</code>	Matrix-matrix multiplication.
<code>rmatvec(x)</code>	Adjoint matrix-vector multiplication.
<code>todense([backend])</code>	Return dense matrix.
<code>toimag([forw, adj])</code>	Imag operator
<code>toreal([forw, adj])</code>	Real operator
<code>tosparse()</code>	Return sparse matrix.
<code>trace([neval, method, backend])</code>	Trace of linear operator.
<code>transpose()</code>	Transpose this linear operator.

mask (*x*)

Apply mask to input signal returning a signal of same size with values at `iava` locations and 0 at other locations

Parameters

x [`numpy.ndarray` or `cupy.ndarray`] Input array (can be either flattened or not)

Returns

y [`numpy.ma.core.MaskedArray`] Masked array.

Examples using `pylops.Restriction`

- `sphx_glr_gallery_plot_restriction.py`
- `sphx_glr_gallery_plot_tvreg.py`
- *03. Solvers*
- *04. Bayesian Inversion*
- *06. 2D Interpolation*
- *12. Seismic regularization*

`pylops.Regression`**class** `pylops.Regression` (*taxis*, *order*, *dtype*=`'float64'`)

Polynomial regression.

Creates an operator that applies polynomial regression to a set of points. Values along the `t`-axis must be provided while initializing the operator. The coefficients of the polynomial regression form the model vector to be provided in forward mode, while the values of the regression curve shall be provided in adjoint mode.

Parameters

taxis [`numpy.ndarray`] Elements along the `t`-axis.

order [`int`] Order of the regressed polynomial.

dtype [`str`, optional] Type of elements in input array.

Raises

TypeError If `t` is not `numpy.ndarray`.

See also:

[LinearRegression](#) Linear regression

Notes

The Regression operator solves the following problem:

$$y_i = \sum_{n=0}^{order} x_n t_i^n \quad \forall i = 1, 2, \dots, N$$

where N represents the order of the chosen polynomial. We can express this problem in a matrix form

$$\mathbf{y} = \mathbf{A}\mathbf{x}$$

where

$$\mathbf{y} = [y_1, y_2, \dots, y_N]^T, \quad \mathbf{x} = [x_0, x_1, \dots, x_{order}]^T$$

and

$$\mathbf{A} = \begin{bmatrix} 1 & t_1 & t_1^2 & \dots & t_1^{order} \\ 1 & t_2 & t_2^2 & \dots & t_2^{order} \\ \dots & \dots & \dots & \dots & \dots \\ 1 & t_N & t_N^2 & \dots & t_N^{order} \end{bmatrix}$$

Attributes

shape [tuple] Operator shape

explicit [bool] Operator contains a matrix that can be solved explicitly (True) or not (False)

Methods

<code>__init__(taxis, order[, dtype])</code>	Initialize this LinearOperator.
<code>adjoint()</code>	Hermitian adjoint.
<code>apply(t, x)</code>	Return values along y-axis given certain t location(s) along t-axis and regression coefficients x
<code>apply_columns(cols)</code>	Apply subset of columns of operator
<code>cond([uslobpcg])</code>	Condition number of linear operator.
<code>conj()</code>	Complex conjugate operator
<code>div(y[, niter])</code>	Solve the linear problem $\mathbf{y} = \mathbf{A}\mathbf{x}$.
<code>dot(x)</code>	Matrix-matrix or matrix-vector multiplication.
<code>eigs([neigs, symmetric, niter, uslobpcg])</code>	Most significant eigenvalues of linear operator.
<code>matmat(X)</code>	Matrix-matrix multiplication.
<code>matvec(x)</code>	Matrix-vector multiplication.
<code>rmatmat(X)</code>	Matrix-matrix multiplication.
<code>rmatvec(x)</code>	Adjoint matrix-vector multiplication.
<code>todense([backend])</code>	Return dense matrix.
<code>toimag([forw, adj])</code>	Imag operator
<code>toreal([forw, adj])</code>	Real operator
<code>tosparse()</code>	Return sparse matrix.
<code>trace([neval, method, backend])</code>	Trace of linear operator.
<code>transpose()</code>	Transpose this linear operator.

apply (t, x)

Return values along y-axis given certain t location(s) along t-axis and regression coefficients x

Parameters

taxis [numpy.ndarray] Elements along the t-axis.

x [numpy.ndarray] Regression coefficients

dtype [str, optional]

Returns

`y` [`numpy.ndarray`] Values along y-axis

Examples using `pylops.Regression`

- `sphx_glr_gallery_plot_linearregr.py`
- `sphx_glr_gallery_plot_regr.py`

`pylops.LinearRegression`

`pylops.LinearRegression` (*taxis*, *dtype*='float64')

Linear regression.

Creates an operator that applies linear regression to a set of points. Values along the t-axis must be provided while initializing the operator. Intercept and gradient form the model vector to be provided in forward mode, while the values of the regression line curve shall be provided in adjoint mode.

Parameters

taxis [`numpy.ndarray`] Elements along the t-axis.

dtype [`str`, optional] Type of elements in input array.

Raises

TypeError If `t` is not `numpy.ndarray`.

See also:

[*Regression*](#) Polynomial regression

Notes

The `LinearRegression` operator solves the following problem:

$$y_i = x_0 + x_1 t_i \quad \forall i = 1, 2, \dots, N$$

We can express this problem in a matrix form

$$\mathbf{y} = \mathbf{A}\mathbf{x}$$

where

$$\mathbf{y} = [y_1, y_2, \dots, y_N]^T, \quad \mathbf{x} = [x_0, x_1]^T$$

and

$$\mathbf{A} = \begin{bmatrix} 1 & t_1 \\ 1 & t_2 \\ \dots & \dots \\ 1 & t_N \end{bmatrix}$$

Note that this is a particular case of the `pylops.Regression` operator and it is in fact just a lazy call of that operator with `order=1`.

Attributes

shape [tuple] Operator shape

explicit [bool] Operator contains a matrix that can be solved explicitly (True) or not (False)

Examples using `pylops.LinearRegression`

- sphx_glr_gallery_plot_linearregr.py

`pylops.CausalIntegration`

class `pylops.CausalIntegration` (*N*, *dims=None*, *dir=-1*, *sampling=1*, *halfcurrent=True*, *dtype='float64'*, *kind='full'*, *removefirst=False*)

Causal integration.

Apply causal integration to a multi-dimensional array along `dir` axis.

Parameters

N [int] Number of samples in model.

dims [list, optional] Number of samples for each dimension (None if only one dimension is available)

dir [int, optional] Direction along which smoothing is applied.

sampling [float, optional] Sampling step dx .

halfcurrent [bool, optional] Add half of current value (True) or the entire value (False). This will be *deprecated* in v2.0.0, use instead *kind=half* to obtain the same behaviour.

dtype [str, optional] Type of elements in input array.

kind [str, optional] Integration kind (full, half, or trapezoidal).

removefirst [bool, optional] Remove first sample (True) or not (False).

Notes

The `CausalIntegration` operator applies a causal integration to any chosen direction of a multi-dimensional array.

For simplicity, given a one dimensional array, the causal integration is:

$$y(t) = \int x(t) dt$$

which can be discretised as :

$$y[i] = \sum_{j=0}^i x[j] dt$$

or

$$y[i] = \left(\sum_{j=0}^{i-1} x[j] + 0.5x[i] \right) dt$$

or

$$y[i] = \left(\sum_{j=1}^{i-1} x[j] + 0.5x[0] + 0.5x[i] \right) dt$$

where dt is the sampling interval. In our implementation, the choice to add $x[i]$ or $0.5x[i]$ is made by selecting `kind=full` or `kind=half`, respectively. The choice to add $0.5x[i]$ and $0.5x[0]$ instead of made by selecting the `kind=trapezoidal`.

Note that the integral of a signal has no unique solution, as any constant c can be added to y , for example if $x(t) = t^2$ the resulting integration is:

$$y(t) = \int t^2 dt = \frac{t^3}{3} + c$$

If we apply a first derivative to y we in fact obtain:

$$x(t) = \frac{dy}{dt} = t^2$$

no matter the choice of c .

Attributes

shape [tuple] Operator shape

explicit [bool] Operator contains a matrix that can be solved explicitly (True) or not (False)

Methods

<code>__init__(N[, dims, dir, sampling, ...])</code>	Initialize this LinearOperator.
<code>adjoint()</code>	Hermitian adjoint.
<code>apply_columns(cols)</code>	Apply subset of columns of operator
<code>cond([uselobpcg])</code>	Condition number of linear operator.
<code>conj()</code>	Complex conjugate operator
<code>div(y[, niter])</code>	Solve the linear problem $y = Ax$.
<code>dot(x)</code>	Matrix-matrix or matrix-vector multiplication.
<code>eigs([neigs, symmetric, niter, uselobpcg])</code>	Most significant eigenvalues of linear operator.
<code>matmat(X)</code>	Matrix-matrix multiplication.
<code>matvec(x)</code>	Matrix-vector multiplication.
<code>rmatmat(X)</code>	Matrix-matrix multiplication.
<code>rmatvec(x)</code>	Adjoint matrix-vector multiplication.
<code>todense([backend])</code>	Return dense matrix.
<code>toimag([forw, adj])</code>	Imag operator
<code>toreal([forw, adj])</code>	Real operator
<code>tosparse()</code>	Return sparse matrix.
<code>trace([neval, method, backend])</code>	Trace of linear operator.
<code>transpose()</code>	Transpose this linear operator.

Examples using `pylops.CausalIntegration`

- `sphx_glr_gallery_plot_causalintegration.py`

`pylops.Spread`

```
class pylops.Spread(dims, dimsd, table=None, dtable=None, fh=None, interp=False, engine='numpy', dtype='float64')
    Spread operator.
```

Spread values from the input model vector arranged as a 2-dimensional array of size $[n_{x0} \times n_{t0}]$ into the data vector of size $[n_x \times n_t]$. Spreading is performed along parametric curves provided as look-up table of pre-computed indices (`table`) or computed on-the-fly using a function handle (`fh`).

In adjoint mode, values from the data vector are instead stacked along the same parametric curves.

Parameters

- dims** [`tuple`] Dimensions of model vector (vector will be reshaped internally into a two-dimensional array of size $[n_{x0} \times n_{t0}]$, where the first dimension is the spreading/stacking direction)
- dimsd** [`tuple`] Dimensions of model vector (vector will be reshaped internal into a two-dimensional array of size $[n_x \times n_t]$)
- table** [`np.ndarray`, optional] Look-up table of indeces of size $[n_{x0} \times n_{t0} \times n_x]$ (if `None` use function handle `fh`)
- dtable** [`np.ndarray`, optional] Look-up table of decimals remainders for linear interpolation of size $[n_{x0} \times n_{t0} \times n_x]$ (if `None` use function handle `fh`)
- fh** [`np.ndarray`, optional] Function handle that returns an index (and a fractional value in case of `interp=True`) to be used for spreading/stacking given indices in $x0$ and t axes (if `None` use look-up table `table`)
- interp** [`bool`, optional] Apply linear interpolation (`True`) or nearest interpolation (`False`) during stacking/spreading along parametric curve. To be used only if `engine='numba'`, inferred directly from the number of outputs of `fh` for `engine='numpy'`
- engine** [`str`, optional] Engine used for fft computation (`numpy` or `numba`). Note that `numba` can only be used when providing a look-up table
- dtype** [`str`, optional] Type of elements in input array.

Raises

- KeyError** If `engine` is neither `numpy` nor `numba`
- NotImplementedError** If both `table` and `fh` are not provided
- ValueError** If `table` has shape different from $[n_{x0} \times n_{t0} \times n_x]$

Notes

The Spread operator applies the following linear transform in forward mode to the model vector after reshaping it into a 2-dimensional array of size $[n_x \times n_t]$:

$$m(x0, t0) \rightarrow d(x, t = f(x0, x, t0))$$

where $f(x0, x, t)$ is a mapping function that returns a value t given values $x0$, x , and $t0$.

In adjoint mode, the model is reconstructed by means of the following stacking operation:

$$m(x0, t0) = \int d(x, t = f(x0, x, t0)) dx$$

Note that `table` (or `fh`) must return integer numbers representing indices in the axis t . However it also possible to perform linear interpolation as part of the spreading/stacking process by providing the decimal part of the mapping function ($t - [t]$) either in `dtable` input parameter or as second value in the return of `fh` function.

Attributes

shape [tuple] Operator shape

explicit [bool] Operator contains a matrix that can be solved explicitly (True) or not (False)

Methods

<code>__init__(dims, dimsd[, table, dtable, fh, ...])</code>	Initialize this LinearOperator.
<code>adjoint()</code>	Hermitian adjoint.
<code>apply_columns(cols)</code>	Apply subset of columns of operator
<code>cond([uselobpcg])</code>	Condition number of linear operator.
<code>conj()</code>	Complex conjugate operator
<code>div(y[, niter])</code>	Solve the linear problem $y = Ax$.
<code>dot(x)</code>	Matrix-matrix or matrix-vector multiplication.
<code>eigs([neigs, symmetric, niter, uselobpcg])</code>	Most significant eigenvalues of linear operator.
<code>matmat(X)</code>	Matrix-matrix multiplication.
<code>matvec(x)</code>	Matrix-vector multiplication.
<code>rmatmat(X)</code>	Matrix-matrix multiplication.
<code>rmatvec(x)</code>	Adjoint matrix-vector multiplication.
<code>todense([backend])</code>	Return dense matrix.
<code>toimag([forw, adj])</code>	Imag operator
<code>toreal([forw, adj])</code>	Real operator
<code>tosparse()</code>	Return sparse matrix.
<code>trace([neval, method, backend])</code>	Trace of linear operator.
<code>transpose()</code>	Transpose this linear operator.

Examples using `pylops.Spread`

- `sphx_glr_gallery_plot_sliding.py`
- `sphx_glr_gallery_plot_radon.py`
- *11. Radon filtering*
- *12. Seismic regularization*
- *16. CT Scan Imaging*

`pylops.VStack`

class `pylops.VStack` (*ops, nproc=1, dtype=None*)

Vertical stacking.

Stack a set of N linear operators vertically.

Parameters

ops [list] Linear operators to be stacked. Alternatively, `numpy.ndarray` or `scipy.sparse` matrices can be passed in place of one or more operators.

nproc [int, optional] Number of processes used to evaluate the N operators in parallel using multiprocessing. If `nproc=1`, work in serial mode.

dtype [str, optional] Type of elements in input array.

Raises

ValueError If ops have different number of rows

Notes

A vertical stack of N linear operators is created such as its application in forward mode leads to

$$\begin{bmatrix} \mathbf{L}_1 \\ \mathbf{L}_2 \\ \dots \\ \mathbf{L}_N \end{bmatrix} \mathbf{x} = \begin{bmatrix} \mathbf{L}_1 \mathbf{x} \\ \mathbf{L}_2 \mathbf{x} \\ \dots \\ \mathbf{L}_N \mathbf{x} \end{bmatrix} = \begin{bmatrix} \mathbf{y}_1 \\ \mathbf{y}_2 \\ \dots \\ \mathbf{y}_N \end{bmatrix}$$

while its application in adjoint mode leads to

$$\begin{bmatrix} \mathbf{L}_1^H & \mathbf{L}_2^H & \dots & \mathbf{L}_N^H \end{bmatrix} \begin{bmatrix} \mathbf{y}_1 \\ \mathbf{y}_2 \\ \dots \\ \mathbf{y}_N \end{bmatrix} = \mathbf{L}_1^H \mathbf{y}_1 + \mathbf{L}_2^H \mathbf{y}_2 + \dots + \mathbf{L}_N^H \mathbf{y}_N$$

Attributes

shape [tuple] Operator shape

explicit [bool] Operator contains a matrix that can be solved explicitly (True) or not (False)

Methods

<code>__init__(ops[, nproc, dtype])</code>	Initialize this LinearOperator.
<code>adjoint()</code>	Hermitian adjoint.
<code>apply_columns(cols)</code>	Apply subset of columns of operator
<code>cond([uselobpcg])</code>	Condition number of linear operator.
<code>conj()</code>	Complex conjugate operator
<code>div(y[, niter])</code>	Solve the linear problem $\mathbf{y} = \mathbf{A}\mathbf{x}$.
<code>dot(x)</code>	Matrix-matrix or matrix-vector multiplication.
<code>eigs([neigs, symmetric, niter, uselobpcg])</code>	Most significant eigenvalues of linear operator.
<code>matmat(X)</code>	Matrix-matrix multiplication.
<code>matvec(x)</code>	Matrix-vector multiplication.
<code>rmatmat(X)</code>	Matrix-matrix multiplication.
<code>rmatvec(x)</code>	Adjoint matrix-vector multiplication.
<code>todense([backend])</code>	Return dense matrix.
<code>toimag([forw, adj])</code>	Imag operator
<code>toreal([forw, adj])</code>	Real operator
<code>tosparse()</code>	Return sparse matrix.
<code>trace([neval, method, backend])</code>	Trace of linear operator.
<code>transpose()</code>	Transpose this linear operator.

Examples using `pylops.VStack`

- `sphinx_glr_gallery_plot_derivative.py`
- `sphinx_glr_gallery_plot_stacking.py`
- `sphinx_glr_gallery_plot_multiproc.py`
- `sphinx_glr_gallery_plot_wavest.py`

- 08. Pre-stack (AVO) inversion
- 17. Real/Complex Inversion

pylops.HStack

class `pylops.HStack` (*ops*, *nproc*=1, *dtype*=None)

Horizontal stacking.

Stack a set of N linear operators horizontally.

Parameters

ops [`list`] Linear operators to be stacked. Alternatively, `numpy.ndarray` or `scipy.sparse` matrices can be passed in place of one or more operators.

nproc [`int`, optional] Number of processes used to evaluate the N operators in parallel using multiprocessing. If `nproc`=1, work in serial mode.

dtype [`str`, optional] Type of elements in input array.

Raises

ValueError If `ops` have different number of columns

Notes

An horizontal stack of N linear operators is created such as its application in forward mode leads to

$$\begin{bmatrix} \mathbf{L}_1 & \mathbf{L}_2 & \dots & \mathbf{L}_N \end{bmatrix} \begin{bmatrix} \mathbf{x}_1 \\ \mathbf{x}_2 \\ \dots \\ \mathbf{x}_N \end{bmatrix} = \mathbf{L}_1 \mathbf{x}_1 + \mathbf{L}_2 \mathbf{x}_2 + \dots + \mathbf{L}_N \mathbf{x}_N$$

while its application in adjoint mode leads to

$$\begin{bmatrix} \mathbf{L}_1^H \\ \mathbf{L}_2^H \\ \dots \\ \mathbf{L}_N^H \end{bmatrix} \mathbf{y} = \begin{bmatrix} \mathbf{L}_1^H \mathbf{y} \\ \mathbf{L}_2^H \mathbf{y} \\ \dots \\ \mathbf{L}_N^H \mathbf{y} \end{bmatrix} = \begin{bmatrix} \mathbf{x}_1 \\ \mathbf{x}_2 \\ \dots \\ \mathbf{x}_N \end{bmatrix}$$

Attributes

shape [`tuple`] Operator shape

explicit [`bool`] Operator contains a matrix that can be solved explicitly (`True`) or not (`False`)

Methods

<code>__init__(ops[, nproc, dtype])</code>	Initialize this LinearOperator.
<code>adjoint()</code>	Hermitian adjoint.
<code>apply_columns(cols)</code>	Apply subset of columns of operator
<code>cond([uselobpcg])</code>	Condition number of linear operator.
<code>conj()</code>	Complex conjugate operator
<code>div(y[, niter])</code>	Solve the linear problem $\mathbf{y} = \mathbf{A}\mathbf{x}$.
<code>dot(x)</code>	Matrix-matrix or matrix-vector multiplication.

Continued on next page

Table 21 – continued from previous page

<code>eigs([neigs, symmetric, niter, uselobpcg])</code>	Most significant eigenvalues of linear operator.
<code>matmat(X)</code>	Matrix-matrix multiplication.
<code>matvec(x)</code>	Matrix-vector multiplication.
<code>rmatmat(X)</code>	Matrix-matrix multiplication.
<code>rmatvec(x)</code>	Adjoint matrix-vector multiplication.
<code>todense([backend])</code>	Return dense matrix.
<code>toimag([forw, adj])</code>	Imag operator
<code>toreal([forw, adj])</code>	Real operator
<code>tosparse()</code>	Return sparse matrix.
<code>trace([neval, method, backend])</code>	Trace of linear operator.
<code>transpose()</code>	Transpose this linear operator.

Examples using `pylops.HStack`

- `sphx_glr_gallery_plot_stacking.py`
- `sphx_glr_gallery_plot_multiproc.py`

`pylops.Block`

`pylops.Block` (*ops*, *nproc*=1, *dtype*=None)

Block operator.

Create a block operator from N lists of M linear operators each.

Parameters

ops [*list*] List of lists of operators to be combined in block fashion. Alternatively, `numpy.ndarray` or `scipy.sparse` matrices can be passed in place of one or more operators.

nproc [*int*, optional] Number of processes used to evaluate the N operators in parallel using multiprocessing. If `nproc`=1, work in serial mode.

dtype [*str*, optional] Type of elements in input array.

Notes

In mathematics, a block or a partitioned matrix is a matrix that is interpreted as being broken into sections called blocks or submatrices. Similarly a block operator is composed of N sets of M linear operators each such that its application in forward mode leads to

$$\begin{bmatrix} \mathbf{L}_{1,1} & \mathbf{L}_{1,2} & \dots & \mathbf{L}_{1,M} \\ \mathbf{L}_{2,1} & \mathbf{L}_{2,2} & \dots & \mathbf{L}_{2,M} \\ \dots & \dots & \dots & \dots \\ \mathbf{L}_{N,1} & \mathbf{L}_{N,2} & \dots & \mathbf{L}_{N,M} \end{bmatrix} \begin{bmatrix} \mathbf{x}_1 \\ \mathbf{x}_2 \\ \dots \\ \mathbf{x}_M \end{bmatrix} = \begin{bmatrix} \mathbf{L}_{1,1}\mathbf{x}_1 + \mathbf{L}_{1,2}\mathbf{x}_2 + \mathbf{L}_{1,M}\mathbf{x}_M \\ \mathbf{L}_{2,1}\mathbf{x}_1 + \mathbf{L}_{2,2}\mathbf{x}_2 + \mathbf{L}_{2,M}\mathbf{x}_M \\ \dots \\ \mathbf{L}_{N,1}\mathbf{x}_1 + \mathbf{L}_{N,2}\mathbf{x}_2 + \mathbf{L}_{N,M}\mathbf{x}_M \end{bmatrix}$$

while its application in adjoint mode leads to

$$\begin{bmatrix} \mathbf{L}_{1,1}^H & \mathbf{L}_{2,1}^H & \dots & \mathbf{L}_{N,1}^H \\ \mathbf{L}_{1,2}^H & \mathbf{L}_{2,2}^H & \dots & \mathbf{L}_{N,2}^H \\ \dots & \dots & \dots & \dots \\ \mathbf{L}_{1,M}^H & \mathbf{L}_{2,M}^H & \dots & \mathbf{L}_{N,M}^H \end{bmatrix} \begin{bmatrix} \mathbf{y}_1 \\ \mathbf{y}_2 \\ \dots \\ \mathbf{y}_N \end{bmatrix} = \begin{bmatrix} \mathbf{L}_{1,1}^H\mathbf{y}_1 + \mathbf{L}_{2,1}^H\mathbf{y}_2 + \mathbf{L}_{N,1}^H\mathbf{y}_N \\ \mathbf{L}_{1,2}^H\mathbf{y}_1 + \mathbf{L}_{2,2}^H\mathbf{y}_2 + \mathbf{L}_{N,2}^H\mathbf{y}_N \\ \dots \\ \mathbf{L}_{1,M}^H\mathbf{y}_1 + \mathbf{L}_{2,M}^H\mathbf{y}_2 + \mathbf{L}_{N,M}^H\mathbf{y}_N \end{bmatrix}$$

Attributes

shape [tuple] Operator shape

explicit [bool] Operator contains a matrix that can be solved explicitly (True) or not (False)

Examples using `pylops.Block`

- sphx_glr_gallery_plot_stacking.py
- sphx_glr_gallery_plot_multiproc.py

`pylops.BlockDiag`

class `pylops.BlockDiag` (*ops*, *nproc*=1, *dtype*=None)

Block-diagonal operator.

Create a block-diagonal operator from N linear operators.

Parameters

ops [list] Linear operators to be stacked. Alternatively, `numpy.ndarray` or `scipy.sparse` matrices can be passed in place of one or more operators.

nproc [int, optional] Number of processes used to evaluate the N operators in parallel using multiprocessing. If `nproc`=1, work in serial mode.

dtype [str, optional] Type of elements in input array.

Notes

A block-diagonal operator composed of N linear operators is created such as its application in forward mode leads to

$$\begin{bmatrix} \mathbf{L}_1 & 0 & \dots & 0 \\ 0 & \mathbf{L}_2 & \dots & 0 \\ \dots & \dots & \dots & \dots \\ 0 & 0 & \dots & \mathbf{L}_N \end{bmatrix} \begin{bmatrix} \mathbf{x}_1 \\ \mathbf{x}_2 \\ \dots \\ \mathbf{x}_N \end{bmatrix} = \begin{bmatrix} \mathbf{L}_1 \mathbf{x}_1 \\ \mathbf{L}_2 \mathbf{x}_2 \\ \dots \\ \mathbf{L}_N \mathbf{x}_N \end{bmatrix}$$

while its application in adjoint mode leads to

$$\begin{bmatrix} \mathbf{L}_1^H & 0 & \dots & 0 \\ 0 & \mathbf{L}_2^H & \dots & 0 \\ \dots & \dots & \dots & \dots \\ 0 & 0 & \dots & \mathbf{L}_N^H \end{bmatrix} \begin{bmatrix} \mathbf{y}_1 \\ \mathbf{y}_2 \\ \dots \\ \mathbf{y}_N \end{bmatrix} = \begin{bmatrix} \mathbf{L}_1^H \mathbf{y}_1 \\ \mathbf{L}_2^H \mathbf{y}_2 \\ \dots \\ \mathbf{L}_N^H \mathbf{y}_N \end{bmatrix}$$

Attributes

shape [tuple] Operator shape

explicit [bool] Operator contains a matrix that can be solved explicitly (True) or not (False)

Methods

<code>__init__(ops[, nproc, dtype])</code>	Initialize this LinearOperator.
<code>adjoint()</code>	Hermitian adjoint.

Continued on next page

Table 22 – continued from previous page

<code>apply_columns(cols)</code>	Apply subset of columns of operator
<code>cond([uselobpcg])</code>	Condition number of linear operator.
<code>conj()</code>	Complex conjugate operator
<code>div(y[, niter])</code>	Solve the linear problem $\mathbf{y} = \mathbf{Ax}$.
<code>dot(x)</code>	Matrix-matrix or matrix-vector multiplication.
<code>eigs([neigs, symmetric, niter, uselobpcg])</code>	Most significant eigenvalues of linear operator.
<code>matmat(X)</code>	Matrix-matrix multiplication.
<code>matvec(x)</code>	Matrix-vector multiplication.
<code>rmatmat(X)</code>	Matrix-matrix multiplication.
<code>rmatvec(x)</code>	Adjoint matrix-vector multiplication.
<code>todense([backend])</code>	Return dense matrix.
<code>toimag([forw, adj])</code>	Imag operator
<code>toreal([forw, adj])</code>	Real operator
<code>tosparse()</code>	Return sparse matrix.
<code>trace([neval, method, backend])</code>	Trace of linear operator.
<code>transpose()</code>	Transpose this linear operator.

Examples using `pylops.BlockDiag`

- `sphx_glr_gallery_plot_stacking.py`
- `sphx_glr_gallery_plot_multiproc.py`

`pylops.Kronecker`

class `pylops.Kronecker` (*Op1*, *Op2*, *dtype*='float64')

Kronecker operator.

Perform Kronecker product of two operators. Note that the combined operator is never created explicitly, rather the product of this operator with the model vector is performed in forward mode, or the product of the adjoint of this operator and the data vector in adjoint mode.

Parameters

Op1 [`pylops.LinearOperator`] First operator

Op2 [`pylops.LinearOperator`] Second operator

dtype [`str`, optional] Type of elements in input array.

Notes

The Kronecker product (denoted with \otimes) is an operation on two operators \mathbf{Op}_1 and \mathbf{Op}_2 of sizes $[n_1 \times m_1]$ and $[n_2 \times m_2]$ respectively, resulting in a block matrix of size $[n_1 n_2 \times m_1 m_2]$.

$$\mathbf{Op}_1 \otimes \mathbf{Op}_2 = \begin{bmatrix} Op_1^{1,1} \mathbf{Op}_2 & \dots & Op_1^{1,m_1} \mathbf{Op}_2 \\ \dots & \dots & \dots \\ Op_1^{n_1,1} \mathbf{Op}_2 & \dots & Op_1^{n_1,m_1} \mathbf{Op}_2 \end{bmatrix}$$

The application of the resulting matrix to a vector \mathbf{x} of size $[m_1 m_2 \times 1]$ is equivalent to the application of the second operator \mathbf{Op}_2 to the rows of a matrix of size $[m_2 \times m_1]$ obtained by reshaping the input vector \mathbf{x} , followed by the application of the first operator to the transposed matrix produced by the first operator. In adjoint mode the same procedure is followed but the adjoint of each operator is used.

Attributes

shape [tuple] Operator shape

explicit [bool] Operator contains a matrix that can be solved explicitly (True) or not (False)

Methods

<code>__init__(Op1, Op2[, dtype])</code>	Initialize this LinearOperator.
<code>adjoint()</code>	Hermitian adjoint.
<code>apply_columns(cols)</code>	Apply subset of columns of operator
<code>cond([uselobpcg])</code>	Condition number of linear operator.
<code>conj()</code>	Complex conjugate operator
<code>div(y[, niter])</code>	Solve the linear problem $\mathbf{y} = \mathbf{A}\mathbf{x}$.
<code>dot(x)</code>	Matrix-matrix or matrix-vector multiplication.
<code>eigs([neigs, symmetric, niter, uselobpcg])</code>	Most significant eigenvalues of linear operator.
<code>matmat(X)</code>	Matrix-matrix multiplication.
<code>matvec(x)</code>	Matrix-vector multiplication.
<code>rmatmat(X)</code>	Matrix-matrix multiplication.
<code>rmatvec(x)</code>	Adjoint matrix-vector multiplication.
<code>todense([backend])</code>	Return dense matrix.
<code>toimag([forw, adj])</code>	Imag operator
<code>toreal([forw, adj])</code>	Real operator
<code>tosparse()</code>	Return sparse matrix.
<code>trace([neval, method, backend])</code>	Trace of linear operator.
<code>transpose()</code>	Transpose this linear operator.

Examples using `pylops.Kronecker`

- `sphx_glr_gallery_plot_stacking.py`

`pylops.Real`

class `pylops.Real` (*dims*, *dtype*=`'complex128'`)

Real operator.

Return the real component of the input. The adjoint returns a complex number with the same real component as the input and zero imaginary component.

Parameters

dims [int or tuple] Number of samples for each dimension

dtype [str, optional] Type of elements in input array.

Notes

In forward mode:

$$y_i = \Re\{x_i\} \quad \forall i = 0, \dots, N$$

In adjoint mode:

$$x_i = \Re\{y_i\} + 0i \quad \forall i = 0, \dots, N$$

Attributes

shape [tuple] Operator shape

explicit [bool] Operator contains a matrix that can be solved explicitly (True) or not (False)

Methods

<code>__init__(dims[, dtype])</code>	Initialize this LinearOperator.
<code>adjoint()</code>	Hermitian adjoint.
<code>apply_columns(cols)</code>	Apply subset of columns of operator
<code>cond([uselobpcg])</code>	Condition number of linear operator.
<code>conj()</code>	Complex conjugate operator
<code>div(y[, niter])</code>	Solve the linear problem $\mathbf{y} = \mathbf{A}\mathbf{x}$.
<code>dot(x)</code>	Matrix-matrix or matrix-vector multiplication.
<code>eigs([neigs, symmetric, niter, uselobpcg])</code>	Most significant eigenvalues of linear operator.
<code>matmat(X)</code>	Matrix-matrix multiplication.
<code>matvec(x)</code>	Matrix-vector multiplication.
<code>rmatmat(X)</code>	Matrix-matrix multiplication.
<code>rmatvec(x)</code>	Adjoint matrix-vector multiplication.
<code>todense([backend])</code>	Return dense matrix.
<code>toimag([forw, adj])</code>	Imag operator
<code>toreal([forw, adj])</code>	Real operator
<code>tosparse()</code>	Return sparse matrix.
<code>trace([neval, method, backend])</code>	Trace of linear operator.
<code>transpose()</code>	Transpose this linear operator.

Examples using `pylops.Real`

- `sphx_glr_gallery_plot_real.py`

`pylops.Imag`

class `pylops.Imag` (*dims*, *dtype*=`'complex128'`)

Imag operator.

Return the imaginary component of the input as a real value. The adjoint returns a complex number with zero real component and the imaginary component set to the real component of the input.

Parameters

dims [int or tuple] Number of samples for each dimension

dtype [str, optional] Type of elements in input array.

Notes

In forward mode:

$$y_i = \{x_i\} \quad \forall i = 0, \dots, N$$

In adjoint mode:

$$x_i = 0 + i\Re\{y_i\} \quad \forall i = 0, \dots, N$$

Attributes

shape [tuple] Operator shape

explicit [bool] Operator contains a matrix that can be solved explicitly (True) or not (False)

Methods

<code>__init__(dims[, dtype])</code>	Initialize this LinearOperator.
<code>adjoint()</code>	Hermitian adjoint.
<code>apply_columns(cols)</code>	Apply subset of columns of operator
<code>cond([uslobpcg])</code>	Condition number of linear operator.
<code>conj()</code>	Complex conjugate operator
<code>div(y[, niter])</code>	Solve the linear problem $\mathbf{y} = \mathbf{A}\mathbf{x}$.
<code>dot(x)</code>	Matrix-matrix or matrix-vector multiplication.
<code>eigs([neigs, symmetric, niter, uslobpcg])</code>	Most significant eigenvalues of linear operator.
<code>matmat(X)</code>	Matrix-matrix multiplication.
<code>matvec(x)</code>	Matrix-vector multiplication.
<code>rmatmat(X)</code>	Matrix-matrix multiplication.
<code>rmatvec(x)</code>	Adjoint matrix-vector multiplication.
<code>todense([backend])</code>	Return dense matrix.
<code>toimag([forw, adj])</code>	Imag operator
<code>toreal([forw, adj])</code>	Real operator
<code>tosparse()</code>	Return sparse matrix.
<code>trace([neval, method, backend])</code>	Trace of linear operator.
<code>transpose()</code>	Transpose this linear operator.

Examples using `pylops.Imag`

- `sphx_glr_gallery_plot_imag.py`

`pylops.Conj`

class `pylops.Conj` (*dims*, *dtype*=`'complex128'`)

Complex conjugate operator.

Return the complex conjugate of the input. It is self-adjoint.

Parameters

dims [int or tuple] Number of samples for each dimension

dtype [str, optional] Type of elements in input array.

Notes

In forward mode:

$$y_i = \Re\{x_i\} - i\Im\{x_i\} \quad \forall i = 0, \dots, N$$

In adjoint mode:

$$x_i = \Re\{y_i\} - i\Im\{y_i\} \quad \forall i = 0, \dots, N$$

Attributes

shape [tuple] Operator shape

explicit [bool] Operator contains a matrix that can be solved explicitly (True) or not (False)

Methods

<code>__init__(dims[, dtype])</code>	Initialize this LinearOperator.
<code>adjoint()</code>	Hermitian adjoint.
<code>apply_columns(cols)</code>	Apply subset of columns of operator
<code>cond([uselobpcg])</code>	Condition number of linear operator.
<code>conj()</code>	Complex conjugate operator
<code>div(y[, niter])</code>	Solve the linear problem $y = Ax$.
<code>dot(x)</code>	Matrix-matrix or matrix-vector multiplication.
<code>eigs([neigs, symmetric, niter, uselobpcg])</code>	Most significant eigenvalues of linear operator.
<code>matmat(X)</code>	Matrix-matrix multiplication.
<code>matvec(x)</code>	Matrix-vector multiplication.
<code>rmatmat(X)</code>	Matrix-matrix multiplication.
<code>rmatvec(x)</code>	Adjoint matrix-vector multiplication.
<code>todense([backend])</code>	Return dense matrix.
<code>toimag([forw, adj])</code>	Imag operator
<code>toreal([forw, adj])</code>	Real operator
<code>tosparse()</code>	Return sparse matrix.
<code>trace([neval, method, backend])</code>	Trace of linear operator.
<code>transpose()</code>	Transpose this linear operator.

Examples using `pylops.Conj`

- `sphx_glr_gallery_plot_conj.py`

Smoothing and derivatives

<code>Smoothing1D(nsmooth, dims[, dir, dtype])</code>	1D Smoothing.
<code>Smoothing2D(nsmooth, dims[, nodir, dtype])</code>	2D Smoothing.
<code>FirstDerivative(N[, dims, dir, sampling, ...])</code>	First derivative.
<code>SecondDerivative(N[, dims, dir, sampling, ...])</code>	Second derivative.
<code>Laplacian(dims[, dirs, weights, sampling, ...])</code>	Laplacian.
<code>Gradient(dims[, sampling, edge, dtype, kind])</code>	Gradient.
<code>FirstDirectionalDerivative(dims, v[, ...])</code>	First Directional derivative.
<code>SecondDirectionalDerivative(dims, v[, ...])</code>	Second Directional derivative.

`pylops.Smoothing1D`

`pylops.Smoothing1D(nsmooth, dims, dir=0, dtype='float64')`
1D Smoothing.

Apply smoothing to model (and data) along a specific direction of a multi-dimensional array depending on the choice of `dir`.

Parameters

nsmooth [`int`] Length of smoothing operator (must be odd)
dims [`tuple` or `int`] Number of samples for each dimension
dir [`int`, optional] Direction along which smoothing is applied
dtype [`str`, optional] Type of elements in input array.

Notes

The Smoothing1D operator is a special type of convolutional operator that convolves the input model (or data) with a constant filter of size n_{smooth} :

$$\mathbf{f} = [1/n_{smooth}, 1/n_{smooth}, \dots, 1/n_{smooth}]$$

When applied to the first direction:

$$y[i, j, k] = 1/n_{smooth} \sum_{l=-(n_{smooth}-1)/2}^{(n_{smooth}-1)/2} x[l, j, k]$$

Similarly when applied to the second direction:

$$y[i, j, k] = 1/n_{smooth} \sum_{l=-(n_{smooth}-1)/2}^{(n_{smooth}-1)/2} x[i, l, k]$$

and the third direction:

$$y[i, j, k] = 1/n_{smooth} \sum_{l=-(n_{smooth}-1)/2}^{(n_{smooth}-1)/2} x[i, j, l]$$

Note that since the filter is symmetrical, the *Smoothing1D* operator is self-adjoint.

Attributes

shape [`tuple`] Operator shape
explicit [`bool`] Operator contains a matrix that can be solved explicitly (`True`) or not (`False`)

Examples using `pylops.Smoothing1D`

- `sphx_glr_gallery_plot_smoothing1d.py`
- `sphx_glr_gallery_plot_causalintegration.py`
- `sphx_glr_gallery_plot_wavest.py`
- *03. Solvers*

`pylops.Smoothing2D`

`pylops.Smoothing2D` (*nsmooth*, *dims*, *nodir=None*, *dtype='float64'*)
2D Smoothing.

Apply smoothing to model (and data) along two directions of a multi-dimensional array depending on the choice of *nodir*.

Parameters

- nsmooth** [tuple or list] Length of smoothing operator in 1st and 2nd dimensions (must be odd)
- dims** [tuple] Number of samples for each dimension
- nodir** [int, optional] Direction along which smoothing is NOT applied (set to None for 2d arrays)
- dtype** [str, optional] Type of elements in input array.

See also:

[`pylops.signalprocessing.Convolve2D`](#) 2D convolution

Notes

The 2D Smoothing operator is a special type of convolutional operator that convolves the input model (or data) with a constant 2d filter of size $n_{smooth,1} \times n_{smooth,2}$:

Its application to a two dimensional input signal is:

$$y[i, j] = 1/(n_{smooth,1} * n_{smooth,2}) \sum_{l=-(n_{smooth,1}-1)/2}^{(n_{smooth,1}-1)/2} \sum_{m=-(n_{smooth,2}-1)/2}^{(n_{smooth,2}-1)/2} x[l, m]$$

Note that since the filter is symmetrical, the *Smoothing2D* operator is self-adjoint.

Attributes

- shape** [tuple] Operator shape
- explicit** [bool] Operator contains a matrix that can be solved explicitly (True) or not (False)

Examples using `pylops.Smoothing2D`

- sphx_glr_gallery_plot_smoothing2d.py
- sphx_glr_gallery_plot_causalintegration.py

`pylops.FirstDerivative`

class `pylops.FirstDerivative` (*N, dims=None, dir=0, sampling=1.0, edge=False, dtype='float64', kind='centered'*)

First derivative.

Apply first derivative.

Parameters

- N** [int] Number of samples in model.
- dims** [tuple, optional] Number of samples for each dimension (None if only one dimension is available)
- dir** [int, optional] Direction along which the derivative is applied.
- sampling** [float, optional] Sampling step dx.
- edge** [bool, optional] Use reduced order derivative at edges (True) or ignore them (False)

dtype [`str`, optional] Type of elements in input array.

kind [`str`, optional] Derivative kind (forward, centered, or backward).

Notes

The FirstDerivative operator applies a first derivative to any chosen direction of a multi-dimensional array using either a second-order centered stencil or first-order forward/backward stencils.

For simplicity, given a one dimensional array, the second-order centered first derivative is:

$$y[i] = (0.5x[i + 1] - 0.5x[i - 1])/dx$$

while the first-order forward stencil is:

$$y[i] = (x[i + 1] - x[i])/dx$$

and the first-order backward stencil is:

$$y[i] = (x[i] - x[i - 1])/dx$$

Attributes

shape [`tuple`] Operator shape

explicit [`bool`] Operator contains a matrix that can be solved explicitly (`True`) or not (`False`)

Methods

<code>__init__(N[, dims, dir, sampling, edge, ...])</code>	Initialize this LinearOperator.
<code>adjoint()</code>	Hermitian adjoint.
<code>apply_columns(cols)</code>	Apply subset of columns of operator
<code>cond([uselobpcg])</code>	Condition number of linear operator.
<code>conj()</code>	Complex conjugate operator
<code>div(y[, niter])</code>	Solve the linear problem $\mathbf{y} = \mathbf{A}\mathbf{x}$.
<code>dot(x)</code>	Matrix-matrix or matrix-vector multiplication.
<code>eigs([neigs, symmetric, niter, uselobpcg])</code>	Most significant eigenvalues of linear operator.
<code>matmat(X)</code>	Matrix-matrix multiplication.
<code>matvec(x)</code>	Matrix-vector multiplication.
<code>rmatmat(X)</code>	Matrix-matrix multiplication.
<code>rmatvec(x)</code>	Adjoint matrix-vector multiplication.
<code>todense([backend])</code>	Return dense matrix.
<code>toimag([forw, adj])</code>	Imag operator
<code>toreal([forw, adj])</code>	Real operator
<code>tosparse()</code>	Return sparse matrix.
<code>trace([neval, method, backend])</code>	Trace of linear operator.
<code>transpose()</code>	Transpose this linear operator.

Examples using `pylops.FirstDerivative`

- `sphx_glr_gallery_plot_causalintegration.py`
- `sphx_glr_gallery_plot_derivative.py`

- sphx_glr_gallery_plot_stacking.py
- sphx_glr_gallery_plot_tvreg.py
- 05. Image deblurring
- 16. CT Scan Imaging

pylops.SecondDerivative

class pylops.SecondDerivative (*N, dims=None, dir=0, sampling=1, edge=False, dtype='float64'*)
Second derivative.

Apply second-order second derivative.

Parameters

- N** [*int*] Number of samples in model.
- dims** [*tuple*, optional] Number of samples for each dimension (*None* if only one dimension is available)
- dir** [*int*, optional] Direction along which the derivative is applied.
- sampling** [*float*, optional] Sampling step dx .
- edge** [*bool*, optional] Use reduced order derivative at edges (*True*) or ignore them (*False*)
- dtype** [*str*, optional] Type of elements in input array.

Notes

The SecondDerivative operator applies a second derivative to any chosen direction of a multi-dimensional array.

For simplicity, given a one dimensional array, the second-order centered first derivative is:

$$y[i] = (x[i + 1] - 2x[i] + x[i - 1])/dx^2$$

Attributes

- shape** [*tuple*] Operator shape
- explicit** [*bool*] Operator contains a matrix that can be solved explicitly (*True*) or not (*False*)

Methods

<code>__init__(N[, dims, dir, sampling, edge, dtype])</code>	Initialize this LinearOperator.
<code>adjoint()</code>	Hermitian adjoint.
<code>apply_columns(cols)</code>	Apply subset of columns of operator
<code>cond([uselobpcg])</code>	Condition number of linear operator.
<code>conj()</code>	Complex conjugate operator
<code>div(y[, niter])</code>	Solve the linear problem $y = Ax$.
<code>dot(x)</code>	Matrix-matrix or matrix-vector multiplication.
<code>eigs([neigs, symmetric, niter, uselobpcg])</code>	Most significant eigenvalues of linear operator.
<code>matmat(X)</code>	Matrix-matrix multiplication.
<code>matvec(x)</code>	Matrix-vector multiplication.
<code>rmatmat(X)</code>	Matrix-matrix multiplication.

Continued on next page

Table 29 – continued from previous page

<code>rmatvec(x)</code>	Adjoint matrix-vector multiplication.
<code>todense([backend])</code>	Return dense matrix.
<code>toimag([forw, adj])</code>	Imag operator
<code>toreal([forw, adj])</code>	Real operator
<code>tosparse()</code>	Return sparse matrix.
<code>trace([neval, method, backend])</code>	Trace of linear operator.
<code>transpose()</code>	Transpose this linear operator.

Examples using `pylops.SecondDerivative`

- `sphx_glr_gallery_plot_causalintegration.py`
- `sphx_glr_gallery_plot_derivative.py`
- `sphx_glr_gallery_plot_stacking.py`
- `sphx_glr_gallery_plot_tvreg.py`
- `sphx_glr_gallery_plot_wavest.py`
- *03. Solvers*
- *12. Seismic regularization*

`pylops.Laplacian`

`pylops.Laplacian` (*dims*, *dirs*=(0, 1), *weights*=(1, 1), *sampling*=(1, 1), *edge*=False, *dtype*='float64')
Laplacian.

Apply second-order centered Laplacian operator to a multi-dimensional array (at least 2 dimensions are required)

Parameters

- dims** [`tuple`] Number of samples for each dimension.
- dirs** [`tuple`, optional] Directions along which laplacian is applied.
- weights** [`tuple`, optional] Weight to apply to each direction (real laplacian operator if `weights`=[1, 1])
- sampling** [`tuple`, optional] Sampling steps for each direction
- edge** [`bool`, optional] Use reduced order derivative at edges (True) or ignore them (False)
- dtype** [`str`, optional] Type of elements in input array.

Returns

- l2op** [`pylops.LinearOperator`] Laplacian linear operator

Notes

The Laplacian operator applies a second derivative along two directions of a multi-dimensional array.

For simplicity, given a two dimensional array, the Laplacian is:

$$y[i, j] = (x[i + 1, j] + x[i - 1, j] + x[i, j - 1] + x[i, j + 1] - 4x[i, j]) / (dx * dy)$$

Examples using `pylops.Laplacian`

- `sphx_glr_gallery_plot_bilinear.py`
- `sphx_glr_gallery_plot_causalintegration.py`
- `sphx_glr_gallery_plot_derivative.py`
- [06. 2D Interpolation](#)
- [16. CT Scan Imaging](#)

`pylops.Gradient`

`pylops.Gradient` (*dims*, *sampling=1*, *edge=False*, *dtype='float64'*, *kind='centered'*)
Gradient.

Apply gradient operator to a multi-dimensional array (at least 2 dimensions are required).

Parameters

- dims** [`tuple`] Number of samples for each dimension.
- sampling** [`tuple`, optional] Sampling steps for each direction.
- edge** [`bool`, optional] Use reduced order derivative at edges (`True`) or ignore them (`False`).
- dtype** [`str`, optional] Type of elements in input array.
- kind** [`str`, optional] Derivative kind (`forward`, `centered`, or `backward`).

Returns

l2op [`pylops.LinearOperator`] Gradient linear operator

Notes

The Gradient operator applies a first-order derivative to each dimension of a multi-dimensional array in forward mode.

For simplicity, given a three dimensional array, the Gradient in forward mode using a centered stencil can be expressed as:

$$\mathbf{g}_{i,j,k} = (f_{i+1,j,k} - f_{i-1,j,k})/d_1 \mathbf{i}_1 + (f_{i,j+1,k} - f_{i,j-1,k})/d_2 \mathbf{i}_2 + (f_{i,j,k+1} - f_{i,j,k-1})/d_3 \mathbf{i}_3$$

which is discretized as follows:

$$\mathbf{g} = \begin{bmatrix} \mathbf{df}_1 \\ \mathbf{df}_2 \\ \mathbf{df}_3 \end{bmatrix}$$

In adjoint mode, the adjoints of the first derivatives along different axes are instead summed together.

Examples using `pylops.Gradient`

- `sphx_glr_gallery_plot_derivative.py`

pylops.FirstDirectionalDerivative

`pylops.FirstDirectionalDerivative` (*dims*, *v*, *sampling=1*, *edge=False*, *dtype='float64'*,
kind='centered')

First Directional derivative.

Apply directional derivative operator to a multi-dimensional array (at least 2 dimensions are required) along either a single common direction or different directions for each point of the array.

Parameters

- dims** [tuple] Number of samples for each dimension.
- v** [np.ndarray, optional] Single direction (array of size n_{dims}) or group of directions (array of size $[n_{dims} \times n_{d0} \times \dots \times n_{d_{n_{dims}}}]$)
- sampling** [tuple, optional] Sampling steps for each direction.
- edge** [bool, optional] Use reduced order derivative at edges (True) or ignore them (False).
- dtype** [str, optional] Type of elements in input array.
- kind** [str, optional] Derivative kind (forward, centered, or backward).

Returns

- ddop** [`pylops.LinearOperator`] First directional derivative linear operator

Notes

The FirstDirectionalDerivative applies a first-order derivative to a multi-dimensional array along the direction defined by the unitary vector \mathbf{v} :

$$df_{\mathbf{v}} = \nabla f \mathbf{v}$$

or along the directions defined by the unitary vectors $\mathbf{v}(x, y)$:

$$df_{\mathbf{v}}(x, y) = \nabla f(x, y) \mathbf{v}(x, y)$$

where we have here considered the 2-dimensional case.

This operator can be easily implemented as the concatenation of the `pylops.Gradient` operator and the `pylops.Diagonal` operator with \mathbf{v} along the main diagonal.

Examples using `pylops.FirstDirectionalDerivative`

- sphx_glr_gallery_plot_derivative.py

pylops.SecondDirectionalDerivative

`pylops.SecondDirectionalDerivative` (*dims*, *v*, *sampling=1*, *edge=False*, *dtype='float64'*)

Second Directional derivative.

Apply second directional derivative operator to a multi-dimensional array (at least 2 dimensions are required) along either a single common direction or different directions for each point of the array.

Parameters

- dims** [tuple] Number of samples for each dimension.

v [`np.ndarray`, optional] Single direction (array of size n_{dims}) or group of directions (array of size $[n_{dims} \times n_{d0} \times \dots \times n_{d_{n_{dims}}}]$)

sampling [`tuple`, optional] Sampling steps for each direction.

edge [`bool`, optional] Use reduced order derivative at edges (`True`) or ignore them (`False`).

dtype [`str`, optional] Type of elements in input array.

Returns

ddop [`pylops.LinearOperator`] Second directional derivative linear operator

Notes

The `SecondDirectionalDerivative` applies a second-order derivative to a multi-dimensional array along the direction defined by the unitary vector \mathbf{v} :

$$d^2 f_{\mathbf{v}} = -D_{\mathbf{v}}^T [D_{\mathbf{v}} f]$$

where $D_{\mathbf{v}}$ is the first-order directional derivative implemented by `pylops.SecondDirectionalDerivative`.

This operator is sometimes also referred to as directional Laplacian in the literature.

Examples using `pylops.SecondDirectionalDerivative`

- `sphx_glr_gallery_plot_derivative.py`

Signal processing

<code>Convolve1D(N, h[, offset, dims, dir, dtype, ...])</code>	1D convolution operator.
<code>Convolve2D(N, h, dims[, offset, nodir, ...])</code>	2D convolution operator.
<code>ConvolveND(N, h, dims[, offset, dirs, ...])</code>	ND convolution operator.
<code>Interp(M, iava[, dims, dir, kind, dtype])</code>	Interpolation operator.
<code>Bilinear(iava, dims[, dtype])</code>	Bilinear interpolation operator.
<code>FFT(dims[, dir, nfft, sampling, real, ...])</code>	One dimensional Fast-Fourier Transform.
<code>FFT2D(dims[, dirs, nffts, sampling, dtype])</code>	Two dimensional Fast-Fourier Transform.
<code>FFTND(dims[, dirs, nffts, sampling, dtype])</code>	N-dimensional Fast-Fourier Transform.
<code>Shift(dims, shift[, dir, nfft, sampling, ...])</code>	Shift operator
<code>DWT(dims[, dir, wavelet, level, dtype])</code>	One dimensional Wavelet operator.
<code>DWT2D(dims[, dirs, wavelet, level, dtype])</code>	Two dimensional Wavelet operator.
<code>Seislet(slopes[, sampling, level, kind, ...])</code>	Two dimensional Seislet operator.
<code>Radon2D(taxis, haxis, paxis[, kind, ...])</code>	Two dimensional Radon transform.
<code>Radon3D(taxis, hyaxis, hxaxis, pyaxis, paxis)</code>	Three dimensional Radon transform.
<code>ChirpRadon2D(taxis, haxis, pmax[, dtype])</code>	2D Chirp Radon transform
<code>ChirpRadon3D(taxis, hyaxis, hxaxis, pmax[, ...])</code>	3D Chirp Radon transform
<code>Sliding1D(Op, dim, dimd, nwin, nover[, ...])</code>	1D Sliding transform operator.
<code>Sliding2D(Op, dims, dimsd, nwin, nover[, ...])</code>	2D Sliding transform operator.
<code>Sliding3D(Op, dims, dimsd, nwin, nover, nop)</code>	3D Sliding transform operator.
<code>Patch2D(Op, dims, dimsd, nwin, nover, nop[, ...])</code>	2D Patch transform operator.
<code>Fredholm1(G[, nz, saveGt, usematmul, dtype])</code>	Fredholm integral of first kind.

pylops.signalprocessing.Convolve1D

```
class pylops.signalprocessing.Convolve1D(N, h, offset=0, dims=None, dir=0,
                                         dtype='float64', method=None)
```

1D convolution operator.

Apply one-dimensional convolution with a compact filter to model (and data) along a specific direction of a multi-dimensional array depending on the choice of `dir`.

Parameters

N [`int`] Number of samples in model.

h [`numpy.ndarray`] 1d compact filter to be convolved to input signal

offset [`int`] Index of the center of the compact filter

dims [`tuple`] Number of samples for each dimension (None if only one dimension is available)

dir [`int`, optional] Direction along which convolution is applied

method [`str`, optional] Method used to calculate the convolution (`direct`, `fft`, or `overlapadd`). Note that only `direct` and `fft` are allowed when `dims=None`, whilst `fft` and `overlapadd` are allowed when `dims` is provided.

dtype [`str`, optional] Type of elements in input array.

Raises

ValueError If `offset` is bigger than `len(h) - 1`

NotImplementedError If `method` provided is not allowed

Notes

The `Convolve1D` operator applies convolution between the input signal $x(t)$ and a compact filter kernel $h(t)$ in forward model:

$$y(t) = \int_{-\infty}^{\infty} h(t - \tau)x(\tau)d\tau$$

This operation can be discretized as follows

$$y[n] = \sum_{m=-\infty}^{\infty} h[n - m]x[m]$$

as well as performed in the frequency domain.

$$Y(f) = F(h(t)) * F(x(t))$$

`Convolve1D` operator uses `scipy.signal.convolve` that automatically chooses the best domain for the operation to be carried out for one dimensional inputs. The `fft` implementation `scipy.signal.fftconvolve` is however enforced for signals in 2 or more dimensions as this routine efficiently operates on multi-dimensional arrays.

As the adjoint of convolution is correlation, `Convolve1D` operator applies correlation in the adjoint mode.

In time domain:

$$x(t) = \int_{-\infty}^{\infty} h(t + \tau)x(\tau)d\tau$$

or in frequency domain:

$$y(t) = F^{-1}(H(f)^* * X(f))$$

Attributes

shape [tuple] Operator shape

explicit [bool] Operator contains a matrix that can be solved explicitly (True) or not (False)

Methods

<code>__init__(N, h[, offset, dims, dir, dtype, ...])</code>	Initialize this LinearOperator.
<code>adjoint()</code>	Hermitian adjoint.
<code>apply_columns(cols)</code>	Apply subset of columns of operator
<code>cond([uselobpcg])</code>	Condition number of linear operator.
<code>conj()</code>	Complex conjugate operator
<code>div(y[, niter])</code>	Solve the linear problem $\mathbf{y} = \mathbf{A}\mathbf{x}$.
<code>dot(x)</code>	Matrix-matrix or matrix-vector multiplication.
<code>eigs([neigs, symmetric, niter, uselobpcg])</code>	Most significant eigenvalues of linear operator.
<code>matmat(X)</code>	Matrix-matrix multiplication.
<code>matvec(x)</code>	Matrix-vector multiplication.
<code>rmatmat(X)</code>	Matrix-matrix multiplication.
<code>rmatvec(x)</code>	Adjoint matrix-vector multiplication.
<code>todense([backend])</code>	Return dense matrix.
<code>toimag([forw, adj])</code>	Imag operator
<code>toreal([forw, adj])</code>	Real operator
<code>tosparse()</code>	Return sparse matrix.
<code>trace([neval, method, backend])</code>	Trace of linear operator.
<code>transpose()</code>	Transpose this linear operator.

Examples using `pylops.signalprocessing.Convolve1D`

- `sphx_glr_gallery_plot_smoothing1d.py`
- `sphx_glr_gallery_plot_convolve.py`
- `sphx_glr_gallery_plot_ista.py`
- `sphx_glr_gallery_plot_wavest.py`
- [03. Solvers](#)
- [04. Bayesian Inversion](#)

`pylops.signalprocessing.Convolve2D`

`pylops.signalprocessing.Convolve2D(N, h, dims, offset=(0, 0), nodir=None, dtype='float64', method='fft')`

2D convolution operator.

Apply two-dimensional convolution with a compact filter to model (and data) along a pair of specific directions of a two or three-dimensional array depending on the choice of `nodir`.

Parameters

N [`int`] Number of samples in model

h [`numpy.ndarray`] 2d compact filter to be convolved to input signal

dims [`list`] Number of samples for each dimension

offset [`tuple`, optional] Indices of the center of the compact filter

nodir [`int`, optional] Direction along which convolution is NOT applied (set to None for 2d arrays)

dtype [`str`, optional] Type of elements in input array.

method [`str`, optional] Method used to calculate the convolution (`direct` or `fft`).

Returns

cop [`pylops.LinearOperator`] Convolve2D linear operator

Notes

The Convolve2D operator applies two-dimensional convolution between the input signal $d(t, x)$ and a compact filter kernel $h(t, x)$ in forward model:

$$y(t, x) = \int_{-\infty}^{\infty} \int_{-\infty}^{\infty} h(t - \tau, x - \chi) d(\tau, \chi) d\tau d\chi$$

This operation can be discretized as follows

$$y[i, n] = \sum_{j=-\infty}^{\infty} \sum_{m=-\infty}^{\infty} h[i - j, n - m] d[j, m]$$

as well as performed in the frequency domain.

$$Y(f, k_x) = F(h(t, x)) * F(d(t, x))$$

Convolve2D operator uses `scipy.signal.convolve2d` that automatically chooses the best domain for the operation to be carried out.

As the adjoint of convolution is correlation, Convolve2D operator applies correlation in the adjoint mode.

In time domain:

$$y(t, x) = \int_{-\infty}^{\infty} \int_{-\infty}^{\infty} h(t + \tau, x + \chi) d(\tau, \chi) d\tau d\chi$$

or in frequency domain:

$$y(t, x) = F^{-1}(H(f, k_x)^* * X(f, k_x))$$

Examples using `pylops.signalprocessing.Convolve2D`

- `sphx_glr_gallery_plot_convolve.py`
- [05. Image deblurring](#)

pylops.signalprocessing.ConvolveND

class pylops.signalprocessing.**ConvolveND** (*N*, *h*, *dims*, *offset=None*, *dirs=None*,
method='fft', *dtype='float64'*)

ND convolution operator.

Apply n-dimensional convolution with a compact filter to model (and data) along a set of directions *dirs* of a n-dimensional array.

Parameters

N [*int*] Number of samples in model

h [*numpy.ndarray*] nd compact filter to be convolved to input signal

dims [*list*] Number of samples for each dimension

offset [*tuple*, optional] Indices of the center of the compact filter

dirs [*tuple*, optional] Directions along which convolution is applied (set to *None* for filter of same dimension as input vector)

method [*str*, optional] Method used to calculate the convolution (*direct* or *fft*).

dtype [*str*, optional] Type of elements in input array.

Notes

The ConvolveND operator applies n-dimensional convolution between the input signal $d(x_1, x_2, \dots, x_N)$ and a compact filter kernel $h(x_1, x_2, \dots, x_N)$ in forward model. This is a straightforward extension to multiple dimensions of [pylops.signalprocessing.Convolve2D](#) operator.

Attributes

shape [*tuple*] Operator shape

explicit [*bool*] Operator contains a matrix that can be solved explicitly (*True*) or not (*False*)

Methods

<code>__init__(N, h, dims[, offset, dirs, method, ...])</code>	Initialize this LinearOperator.
<code>adjoint()</code>	Hermitian adjoint.
<code>apply_columns(cols)</code>	Apply subset of columns of operator
<code>cond([uslobpcg])</code>	Condition number of linear operator.
<code>conj()</code>	Complex conjugate operator
<code>div(y[, niter])</code>	Solve the linear problem $\mathbf{y} = \mathbf{A}\mathbf{x}$.
<code>dot(x)</code>	Matrix-matrix or matrix-vector multiplication.
<code>eigs([neigs, symmetric, niter, uslobpcg])</code>	Most significant eigenvalues of linear operator.
<code>matmat(X)</code>	Matrix-matrix multiplication.
<code>matvec(x)</code>	Matrix-vector multiplication.
<code>rmatmat(X)</code>	Matrix-matrix multiplication.
<code>rmatvec(x)</code>	Adjoint matrix-vector multiplication.
<code>todense([backend])</code>	Return dense matrix.
<code>toimag([forw, adj])</code>	Imag operator
<code>toreal([forw, adj])</code>	Real operator
<code>tosparse()</code>	Return sparse matrix.

Continued on next page

Table 32 – continued from previous page

<code>trace([neval, method, backend])</code>	Trace of linear operator.
<code>transpose()</code>	Transpose this linear operator.

Examples using `pylops.signalprocessing.ConvolveND`

- `sphx_glr_gallery_plot_smoothing2d.py`
- `sphx_glr_gallery_plot_causalintegration.py`
- `sphx_glr_gallery_plot_convolve.py`
- *05. Image deblurring*

`pylops.signalprocessing.Interp`

`pylops.signalprocessing.Interp` (*M*, *iava*, *dims=None*, *dir=0*, *kind='linear'*, *dtype='float64'*)
Interpolation operator.

Apply interpolation along direction *dir* from regularly sampled input vector into fractionary positions *iava* using one of the following algorithms:

- *Nearest neighbour* interpolation is a thin wrapper around `pylops.Restriction` at `np.round(iava)` locations.
- *Linear interpolation* extracts values from input vector at locations `np.floor(iava)` and `np.floor(iava)+1` and linearly combines them in forward mode, places weighted versions of the interpolated values at locations `np.floor(iava)` and `np.floor(iava)+1` in an otherwise zero vector in adjoint mode.
- *Sinc interpolation* performs sinc interpolation at locations *iava*. Note that this is the most accurate method but it has higher computational cost as it involves multiplying the input data by a matrix of size $N \times M$.

Note: The vector *iava* should contain unique values. If the same index is repeated twice an error will be raised. This also applies when values beyond the last element of the input array for *linear interpolation* as those values are forced to be just before this element.

Parameters

M [*int*] Number of samples in model.

iava [*list* or `numpy.ndarray`] Floating indices of locations of available samples for interpolation.

dims [*list*, optional] Number of samples for each dimension (*None* if only one dimension is available)

dir [*int*, optional] Direction along which restriction is applied.

kind [*str*, optional] Kind of interpolation (*nearest*, *linear*, and *sinc* are currently supported)

dtype [*str*, optional] Type of elements in input array.

Returns

op [`pylops.LinearOperator`] Linear interpolation operator

iava [list or numpy.ndarray] Corrected indices of locations of available samples (samples at $M-1$ or beyond are forced to be at $M-1-\text{eps}$)

Raises

ValueError If the vector `iava` contains repeated values.

NotImplementedError If `kind` is not `nearest`, `linear` or `sinc`

See also:

`pylops.Restriction` Restriction operator

Notes

Linear interpolation of a subset of N values at locations `iava` from an input (or model) vector \mathbf{x} of size M can be expressed as:

$$y_i = (1 - w_i)x_{l_i^l} + w_i x_{l_i^r} \quad \forall i = 1, 2, \dots, N$$

where $\mathbf{l}^l = [\lfloor l_1 \rfloor, \lfloor l_2 \rfloor, \dots, \lfloor l_N \rfloor]$ and $\mathbf{l}^r = [\lfloor l_1 \rfloor + 1, \lfloor l_2 \rfloor + 1, \dots, \lfloor l_N \rfloor + 1]$ are vectors containing the indices of the original array at which samples are taken, and $\mathbf{w} = [l_1 - \lfloor l_1 \rfloor, l_2 - \lfloor l_2 \rfloor, \dots, l_N - \lfloor l_N \rfloor]$ are the linear interpolation weights. This operator can be implemented by simply summing two `pylops.Restriction` operators which are weighted using `pylops.basicoperators.Diagonal` operators.

Sinc interpolation of a subset of N values at locations `iava` from an input (or model) vector \mathbf{x} of size M can be expressed as:

$$y_i = \sum_{j=0}^M x_j \text{sinc}(i - j) \quad \forall i = 1, 2, \dots, N$$

This operator can be implemented using the `pylops.MatrixMult` operator with a matrix containing the values of the sinc function at all i, j possible combinations.

Examples using `pylops.signalprocessing.Interp`

- `sphx_glr_gallery_plot_restriction.py`

`pylops.signalprocessing.Bilinear`

class `pylops.signalprocessing.Bilinear` (*iava*, *dims*, *dtype*='float64')

Bilinear interpolation operator.

Apply bilinear interpolation onto fractionary positions `iava` along the first two axes of a n-dimensional array.

Note: The vector `iava` should contain unique pairs. If the same pair is repeated twice an error will be raised.

Parameters

iava [list or numpy.ndarray] Array of size $[2 \times n_{ava}]$ containing pairs of floating indices of locations of available samples for interpolation.

dims [list] Number of samples for each dimension

dtype [`str`, optional] Type of elements in input array.

Raises

ValueError If the vector `iava` contains repeated values.

Notes

Bilinear interpolation of a subset of N values at locations `iava` from an input n -dimensional vector \mathbf{x} of size $[m_1 \times m_2 \times \dots \times m_{ndim}]$ can be expressed as:

$$y_i = (1 - w_i^0)(1 - w_i^1)x_{l_i^{l,0}, l_i^{l,1}} + w_i^0(1 - w_i^1)x_{l_i^{r,0}, l_i^{l,1}} + (1 - w_i^0)w_i^1x_{l_i^{l,0}, l_i^{r,1}} + w_i^0w_i^1x_{l_i^{r,0}, l_i^{r,1}} \quad \forall i = 1, 2, \dots, M$$

where $\mathbf{l}^{l,0} = [\lfloor l_1^0 \rfloor, \lfloor l_2^0 \rfloor, \dots, \lfloor l_N^0 \rfloor]$, $\mathbf{l}^{l,1} = [\lfloor l_1^1 \rfloor, \lfloor l_2^1 \rfloor, \dots, \lfloor l_N^1 \rfloor]$, $\mathbf{l}^{r,0} = [\lfloor l_1^0 \rfloor + 1, \lfloor l_2^0 \rfloor + 1, \dots, \lfloor l_N^0 \rfloor + 1]$, $\mathbf{l}^{r,1} = [\lfloor l_1^1 \rfloor + 1, \lfloor l_2^1 \rfloor + 1, \dots, \lfloor l_N^1 \rfloor + 1]$, are vectors containing the indices of the original array at which samples are taken, and $\mathbf{w}^j = [l_1^i - \lfloor l_1^i \rfloor, l_2^i - \lfloor l_2^i \rfloor, \dots, l_N^i - \lfloor l_N^i \rfloor] (\forall j = 0, 1)$ are the bilinear interpolation weights.

Attributes

shape [`tuple`] Operator shape

explicit [`bool`] Operator contains a matrix that can be solved explicitly (`True`) or not (`False`)

Methods

<code>__init__(iava, dims[, dtype])</code>	Initialize this LinearOperator.
<code>adjoint()</code>	Hermitian adjoint.
<code>apply_columns(cols)</code>	Apply subset of columns of operator
<code>cond([uslobpcg])</code>	Condition number of linear operator.
<code>conj()</code>	Complex conjugate operator
<code>div(y[, niter])</code>	Solve the linear problem $\mathbf{y} = \mathbf{A}\mathbf{x}$.
<code>dot(x)</code>	Matrix-matrix or matrix-vector multiplication.
<code>eigs([neigs, symmetric, niter, uslobpcg])</code>	Most significant eigenvalues of linear operator.
<code>matmat(X)</code>	Matrix-matrix multiplication.
<code>matvec(x)</code>	Matrix-vector multiplication.
<code>rmatmat(X)</code>	Matrix-matrix multiplication.
<code>rmatvec(x)</code>	Adjoint matrix-vector multiplication.
<code>todense([backend])</code>	Return dense matrix.
<code>toimag([forw, adj])</code>	Imag operator
<code>toreal([forw, adj])</code>	Real operator
<code>tosparse()</code>	Return sparse matrix.
<code>trace([neval, method, backend])</code>	Trace of linear operator.
<code>transpose()</code>	Transpose this linear operator.

Examples using `pylops.signalprocessing.Bilinear`

- `sphx_glr_gallery_plot_bilinear.py`

pylops.signalprocessing.FFT

`pylops.signalprocessing.FFT` (*dims*, *dir*=0, *nfft*=None, *sampling*=1.0, *real*=False, *fftshift*=False, *engine*='numpy', *dtype*='complex128', ***kwargs_fft*)

One dimensional Fast-Fourier Transform.

Apply Fast-Fourier Transform (FFT) along a specific direction *dir* of a multi-dimensional array of size *dim*.

Note that the FFT operator is an overload to either the numpy `numpy.fft.fft` (or `numpy.fft.rfft` for real models) in forward mode and to the numpy `numpy.fft.ifft` (or `numpy.fft.irfft` for real models) in adjoint mode, or their cupy equivalents. Alternatively, the `pyfftw.FFTW` class is used when `engine='fftw'` is chosen.

In both cases, scaling is properly taken into account to guarantee that the operator is passing the dot-test.

Note: For a real valued input signal, it is possible to store the values of the Fourier transform at positive frequencies only as values at negative frequencies are simply their complex conjugates. However as the operation of removing the negative part of the frequency axis in forward mode and adding the complex conjugates in adjoint mode is nonlinear, the Linear Operator FTT with `real=True` is not expected to pass the dot-test. It is thus *only* advised to use this flag when a forward and adjoint FFT is used in the same chained operator (e.g., `FFT.H*Op*FFT`) such as in `pylops.waveeqprocessing.mdd.MDC`.

Parameters

- dims** [`tuple`] Number of samples for each dimension
- dir** [`int`, optional] Direction along which FFT is applied.
- nfft** [`int`, optional] Number of samples in Fourier Transform (same as input if `nfft=None`)
- sampling** [`float`, optional] Sampling step *dt*.
- real** [`bool`, optional] Model to which fft is applied has real numbers (`True`) or not (`False`).
Used to enforce that the output of adjoint of a real model is real.
- fftshift** [`bool`, optional] Apply `fftshift/ifftshift` (`True`) or not (`False`)
- engine** [`str`, optional] Engine used for fft computation (numpy or `fftw`). Choose `numpy` when working with cupy arrays.
- dtype** [`str`, optional] Type of elements in input array. Note that the *dtype* of the operator is the corresponding complex type even when a real type is provided. Nevertheless, the provided *dtype* will be enforced on the vector returned by the *rmatvec* method.
- **kwargs_fft** Arbitrary keyword arguments for `pyfftw.FFTW`

Raises

- ValueError** If *dims* is provided and *dir* is bigger than `len(dims)`
- NotImplementedError** If *engine* is neither `numpy` nor `fftw`

Notes

The FFT operator applies the forward Fourier transform to a signal $d(t)$ in forward mode:

$$D(f) = F(d) = \int d(t)e^{-j2\pi ft}dt$$

Similarly, the inverse Fourier transform is applied to the Fourier spectrum $D(f)$ in adjoint mode:

$$d(t) = F^{-1}(D) = \int D(f) e^{j2\pi ft} df$$

Both operators are effectively discretized and solved by a fast iterative algorithm known as Fast Fourier Transform.

Note that the FFT operator is a special operator in that the adjoint is also the inverse of the forward mode. Moreover, in case of real signal in time domain, the Fourier transform is Hermitian.

Attributes

shape [`tuple`] Operator shape

explicit [`bool`] Operator contains a matrix that can be solved explicitly (True) or not (False)

Examples using `pylops.signalprocessing.FFT`

- `sphx_glr_gallery_plot_sliding.py`
- `sphx_glr_gallery_plot_fft.py`
- *02. The Dot-Test*
- *03. Solvers*
- *04. Bayesian Inversion*

`pylops.signalprocessing.FFT2D`

```
class pylops.signalprocessing.FFT2D (dims, dirs=(0, 1), nffts=(None, None), sampling=(1.0,  
1.0), dtype='complex128')
```

Two dimensional Fast-Fourier Transform.

Apply two dimensional Fast-Fourier Transform (FFT) to any pair of axes of a multi-dimensional array depending on the choice of `dirs`. Note that the FFT2D operator is a simple overload to the numpy `numpy.fft.fft2` in forward mode and to the numpy `numpy.fft.ifft2` in adjoint mode (or their cupy equivalents), however scaling is taken into account differently to guarantee that the operator is passing the dot-test.

Parameters

dims [`tuple`] Number of samples for each dimension

dirs [`tuple`, optional] Pair of directions along which FFT2D is applied

nffts [`tuple`, optional] Number of samples in Fourier Transform for each direction (same as input if `nffts=(None, None)`)

sampling [`tuple`, optional] Sampling steps `dy` and `dx`

dtype [`str`, optional] Type of elements in input array. Note that the `dtype` of the operator is the corresponding complex type even when a real type is provided. Nevertheless, the provided `dtype` will be enforced on the vector returned by the `rmatvec` method.

Raises

ValueError If `dims` has less than two elements, and if `dirs`, `nffts`, or `sampling` has more or less than two elements.

Notes

The FFT2D operator applies the two-dimensional forward Fourier transform to a signal $d(y, x)$ in forward mode:

$$D(k_y, k_x) = F(d) = \int \int d(y, x) e^{-j2\pi k_y y} e^{-j2\pi k_x x} dy dx$$

Similarly, the two-dimensional inverse Fourier transform is applied to the Fourier spectrum $D(k_y, k_x)$ in adjoint mode:

$$d(y, x) = F^{-1}(D) = \int \int D(k_y, k_x) e^{j2\pi k_y y} e^{j2\pi k_x x} dk_y dk_x$$

Both operators are effectively discretized and solved by a fast iterative algorithm known as Fast Fourier Transform.

Attributes

shape [tuple] Operator shape

explicit [bool] Operator contains a matrix that can be solved explicitly (True) or not (False)

Methods

<code>__init__(dims[, dirs, nffts, sampling, dtype])</code>	Initialize this LinearOperator.
<code>adjoint()</code>	Hermitian adjoint.
<code>apply_columns(cols)</code>	Apply subset of columns of operator
<code>cond([uslobpcg])</code>	Condition number of linear operator.
<code>conj()</code>	Complex conjugate operator
<code>div(y[, niter])</code>	Solve the linear problem $y = Ax$.
<code>dot(x)</code>	Matrix-matrix or matrix-vector multiplication.
<code>eigs([neigs, symmetric, niter, uslobpcg])</code>	Most significant eigenvalues of linear operator.
<code>matmat(X)</code>	Matrix-matrix multiplication.
<code>matvec(x)</code>	Matrix-vector multiplication.
<code>rmatmat(X)</code>	Matrix-matrix multiplication.
<code>rmatvec(x)</code>	Adjoint matrix-vector multiplication.
<code>todense([backend])</code>	Return dense matrix.
<code>toimag([forw, adj])</code>	Imag operator
<code>toreal([forw, adj])</code>	Real operator
<code>tosparse()</code>	Return sparse matrix.
<code>trace([neval, method, backend])</code>	Trace of linear operator.
<code>transpose()</code>	Transpose this linear operator.

Examples using `pylops.signalprocessing.FFT2D`

- `sphx_glr_gallery_plot_patching.py`
- `sphx_glr_gallery_plot_fft.py`
- `sphx_glr_gallery_plot_tvreg.py`
- *12. Seismic regularization*
- *14. Seismic wavefield decomposition*

pylops.signalprocessing.FFTND

class pylops.signalprocessing.**FFTND** (*dims*, *dirs*=(0, 1, 2), *nffts*=(None, None, None), *sampling*=(1.0, 1.0, 1.0), *dtype*='complex128')

N-dimensional Fast-Fourier Transform.

Apply n-dimensional Fast-Fourier Transform (FFT) to any n axes of a multi-dimensional array depending on the choice of *dirs*. Note that the FFTND operator is a simple overload to the numpy `numpy.fft.fftn` in forward mode and to the numpy `numpy.fft.ifftn` in adjoint mode, however scaling is taken into account differently to guarantee that the operator is passing the dot-test.

Parameters

- dims** [tuple] Number of samples for each dimension
- dirs** [tuple, optional] Directions along which FFTND is applied
- nffts** [tuple, optional] Number of samples in Fourier Transform for each direction (same as input if *nffts*=(None, None, None, ..., None))
- sampling** [tuple, optional] Sampling steps in each direction
- dtype** [str, optional] Type of elements in input array

Raises

- ValueError** If *dims*, *dirs*, *nffts*, or *sampling* have less than three elements and if the dimension of *dirs*, *nffts*, and *sampling* is not the same

Notes

The FFTND operator applies the n-dimensional forward Fourier transform to a multi-dimensional array. Without loss of generality we consider here a three-dimensional signal $d(z, y, x)$. The FFTND in forward mode is:

$$D(k_z, k_y, k_x) = F(d) = \int \int d(z, y, x) e^{-j2\pi k_z z} e^{-j2\pi k_y y} e^{-j2\pi k_x x} dz dy dx$$

Similarly, the three-dimensional inverse Fourier transform is applied to the Fourier spectrum $D(k_z, k_y, k_x)$ in adjoint mode:

$$d(z, y, x) = F^{-1}(D) = \int \int D(k_z, k_y, k_x) e^{j2\pi k_z z} e^{j2\pi k_y y} e^{j2\pi k_x x} dk_z dk_y dk_x$$

Both operators are effectively discretized and solved by a fast iterative algorithm known as Fast Fourier Transform.

Attributes

- shape** [tuple] Operator shape
- explicit** [bool] Operator contains a matrix that can be solved explicitly (True) or not (False)

Methods

<code>__init__(dims[, dirs, nffts, sampling, dtype])</code>	Initialize this LinearOperator.
<code>adjoint()</code>	Hermitian adjoint.
<code>apply_columns(cols)</code>	Apply subset of columns of operator
<code>cond([uslobpcg])</code>	Condition number of linear operator.

Continued on next page

Table 35 – continued from previous page

<code>conj()</code>	Complex conjugate operator
<code>div(y[, niter])</code>	Solve the linear problem $y = Ax$.
<code>dot(x)</code>	Matrix-matrix or matrix-vector multiplication.
<code>eigs([neigs, symmetric, niter, uselobpcg])</code>	Most significant eigenvalues of linear operator.
<code>matmat(X)</code>	Matrix-matrix multiplication.
<code>matvec(x)</code>	Matrix-vector multiplication.
<code>rmatmat(X)</code>	Matrix-matrix multiplication.
<code>rmatvec(x)</code>	Adjoint matrix-vector multiplication.
<code>todense([backend])</code>	Return dense matrix.
<code>toimag([forw, adj])</code>	Imag operator
<code>toreal([forw, adj])</code>	Real operator
<code>tosparse()</code>	Return sparse matrix.
<code>trace([neval, method, backend])</code>	Trace of linear operator.
<code>transpose()</code>	Transpose this linear operator.

Examples using `pylops.signalprocessing.FFTND`

- `sphx_glr_gallery_plot_fft.py`

`pylops.signalprocessing.Shift`

`pylops.signalprocessing.Shift` (*dims*, *shift*, *dir*=0, *nfft*=None, *sampling*=1.0, *real*=False, *engine*='numpy', *dtype*='complex128', ***kwargs_fft*)

Shift operator

Apply fractional shift in the frequency domain along a specific direction] *dir* of a multi-dimensional array of size *dim*.

Parameters

- dims** [*tuple*] Number of samples for each dimension
- shift** [*float*] Fractional shift to apply
- dir** [*int*, optional] Direction along which FFT is applied.
- nfft** [*int*, optional] Number of samples in Fourier Transform (same as input if *nfft*=None)
- sampling** [*float*, optional] Sampling step *dt*.
- real** [*bool*, optional] Model to which fft is applied has real numbers (True) or not (False).
Used to enforce that the output of adjoint of a real model is real.
- engine** [*str*, optional] Engine used for fft computation (numpy or fftw). Choose numpy when working with cupy arrays.
- dtype** [*str*, optional] Type of elements in input array.
- **kwargs_fftw** Arbitrary keyword arguments for `pyfftw.FFTW`

Raises

- ValueError** If *dims* is provided and *dir* is bigger than `len(dims)`
- NotImplementedError** If *engine* is neither numpy nor fftw

Notes

The Shift operator applies the forward Fourier transform, an element-wise scaling, and inverse fourier transform

$$\mathbf{y} = \mathbf{F}^{-1} \mathbf{S} \mathbf{F} \mathbf{x}$$

Here \mathbf{S} is a diagonal operator that scales the Fourier transformed input by $e^{-j2\pi f t_S}$, whee t_S is the chosen shift.

Attributes

shape [tuple] Operator shape

explicit [bool] Operator contains a matrix that can be solved explicitly (True) or not (False)

Examples using `pylops.signalprocessing.Shift`

- sphx_glr_gallery_plot_shift.py

`pylops.signalprocessing.DWT`

class `pylops.signalprocessing.DWT` (*dims*, *dir*=0, *wavelet*='haar', *level*=1, *dtype*='float64')
One dimensional Wavelet operator.

Apply 1D-Wavelet Transform along a specific direction `dir` of a multi-dimensional array of size `dims`.

Note that the Wavelet operator is an overload of the `pywt` implementation of the wavelet transform. Refer to <https://pywavelets.readthedocs.io> for a detailed description of the input parameters.

Parameters

dims [int or tuple] Number of samples for each dimension

dir [int, optional] Direction along which DWT is applied.

wavelet [str, optional] Name of wavelet type. Use `pywt.wavelist(kind='discrete')` for a list of available wavelets.

level [int, optional] Number of scaling levels (must be ≥ 0).

dtype [str, optional] Type of elements in input array.

Raises

ModuleNotFoundError If `pywt` is not installed

ValueError If `wavelet` does not belong to `pywt.families`

Notes

The Wavelet operator applies the multilevel Discrete Wavelet Transform (DWT) in forward mode and the multilevel Inverse Discrete Wavelet Transform (IDWT) in adjoint mode.

Wavelet transforms can be used to compress signals and present a key advantage over Fourier transforms in that they captures both frequency and location information in time. Consider using this operator as sparsifying transform when using L1 solvers.

Attributes

shape [tuple] Operator shape

explicit [`bool`] Operator contains a matrix that can be solved explicitly (True) or not (False)

Methods

<code>__init__(dims[, dir, wavelet, level, dtype])</code>	Initialize this LinearOperator.
<code>adjoint()</code>	Hermitian adjoint.
<code>apply_columns(cols)</code>	Apply subset of columns of operator
<code>cond([uselobpcg])</code>	Condition number of linear operator.
<code>conj()</code>	Complex conjugate operator
<code>div(y[, niter])</code>	Solve the linear problem $y = Ax$.
<code>dot(x)</code>	Matrix-matrix or matrix-vector multiplication.
<code>eigs([neigs, symmetric, niter, uselobpcg])</code>	Most significant eigenvalues of linear operator.
<code>matmat(X)</code>	Matrix-matrix multiplication.
<code>matvec(x)</code>	Matrix-vector multiplication.
<code>rmatmat(X)</code>	Matrix-matrix multiplication.
<code>rmatvec(x)</code>	Adjoint matrix-vector multiplication.
<code>todense([backend])</code>	Return dense matrix.
<code>toimag([forw, adj])</code>	Imag operator
<code>toreal([forw, adj])</code>	Real operator
<code>tosparse()</code>	Return sparse matrix.
<code>trace([neval, method, backend])</code>	Trace of linear operator.
<code>transpose()</code>	Transpose this linear operator.

Examples using `pylops.signalprocessing.DWT`

- `sphx_glr_gallery_plot_wavelet.py`

`pylops.signalprocessing.DWT2D`

class `pylops.signalprocessing.DWT2D` (*dims*, *dirs*=(0, 1), *wavelet*='haar', *level*=1, *dtype*='float64')

Two dimensional Wavelet operator.

Apply 2D-Wavelet Transform along two directions *dirs* of a multi-dimensional array of size *dims*.

Note that the Wavelet operator is an overload of the `pywt` implementation of the wavelet transform. Refer to <https://pywavelets.readthedocs.io> for a detailed description of the input parameters.

Parameters

dims [`tuple`] Number of samples for each dimension

dirs [`tuple`, optional] Direction along which DWT2D is applied.

wavelet [`str`, optional] Name of wavelet type. Use `pywt.wavelist(kind='discrete')` for a list of available wavelets.

level [`int`, optional] Number of scaling levels (must be ≥ 0).

dtype [`str`, optional] Type of elements in input array.

Raises

ModuleNotFoundError If `pywt` is not installed

ValueError If `wavelet` does not belong to `pywt.families`

Notes

The Wavelet operator applies the 2-dimensional multilevel Discrete Wavelet Transform (DWT2) in forward mode and the 2-dimensional multilevel Inverse Discrete Wavelet Transform (IDWT2) in adjoint mode.

Attributes

shape [tuple] Operator shape

explicit [bool] Operator contains a matrix that can be solved explicitly (True) or not (False)

Methods

<code>__init__(dims[, dirs, wavelet, level, dtype])</code>	Initialize this LinearOperator.
<code>adjoint()</code>	Hermitian adjoint.
<code>apply_columns(cols)</code>	Apply subset of columns of operator
<code>cond([uslobpcg])</code>	Condition number of linear operator.
<code>conj()</code>	Complex conjugate operator
<code>div(y[, niter])</code>	Solve the linear problem $\mathbf{y} = \mathbf{Ax}$.
<code>dot(x)</code>	Matrix-matrix or matrix-vector multiplication.
<code>eigs([neigs, symmetric, niter, uslobpcg])</code>	Most significant eigenvalues of linear operator.
<code>matmat(X)</code>	Matrix-matrix multiplication.
<code>matvec(x)</code>	Matrix-vector multiplication.
<code>rmatmat(X)</code>	Matrix-matrix multiplication.
<code>rmatvec(x)</code>	Adjoint matrix-vector multiplication.
<code>todense([backend])</code>	Return dense matrix.
<code>toimag([forw, adj])</code>	Imag operator
<code>toreal([forw, adj])</code>	Real operator
<code>tosparse()</code>	Return sparse matrix.
<code>trace([neval, method, backend])</code>	Trace of linear operator.
<code>transpose()</code>	Transpose this linear operator.

Examples using `pylops.signalprocessing.DWT2D`

- `sphx_glr_gallery_plot_wavelet.py`
- *05. Image deblurring*

`pylops.signalprocessing.Seislet`

```
class pylops.signalprocessing.Seislet (slopes,      sampling=(1.0,    1.0),    level=None,
                                       kind='haar', inv=False, dtype='float64')
```

Two dimensional Seislet operator.

Apply 2D-Seislet Transform to an input array given an estimate of its local `slopes`. In forward mode, the input array is reshaped into a two-dimensional array of size $n_x \times n_t$ and the transform is performed along the first (spatial) axis (see Notes for more details).

Parameters

slopes [numpy.ndarray] Slope field of size $n_x \times n_t$

sampling [tuple, optional] Sampling steps in x- and t-axis.

level [int, optional] Number of scaling levels (must be ≥ 0).

kind [str, optional] Basis function used for predict and update steps: haar or linear.

inv [int, optional] Apply inverse transform when invoking the adjoint (True) or not (False). Note that in some scenario it may be more appropriate to use the exact inverse as adjoint of the Seislet operator even if this is not an orthogonal operator and the dot-test would not be satisfied (see Notes for details). Otherwise, the user can access the inverse directly as method of this class.

dtype [str, optional] Type of elements in input array.

Raises

NotImplementedError If `kind` is different from haar or linear

ValueError If `sampling` has more or less than two elements.

Notes

The Seislet transform [1] is implemented using the lifting scheme.

In its simplest form (i.e., corresponding to the Haar basis function for the Wavelet transform) the input dataset is separated into even (**e**) and odd (**o**) traces. Even traces are used to forward predict the odd traces using local slopes and the new odd traces (also referred to as residual) is defined as:

$$\mathbf{o}^{i+1} = \mathbf{r}^i = \mathbf{o}^i - P(\mathbf{e}^i)$$

where $P = P^+$ is the slope-based forward prediction operator (which is here implemented as a sinc-based resampling). The residual is then updated and summed to the even traces to obtain the new even traces (also referred to as coarse representation):

$$\mathbf{e}^{i+1} = \mathbf{c}^i = \mathbf{e}^i + U(\mathbf{o}^{i+1})$$

where $U = P^-/2$ is the update operator which performs a slope-based backward prediction. At this point \mathbf{e}^{i+1} becomes the new data and the procedure is repeated *level* times (at maximum until \mathbf{e}^{i+1} is a single trace. The Seislet transform is effectively composed of all residuals and the coarsest data representation.

In the inverse transform the two operations are reverted. Starting from the coarsest scale data representation **c** and residual **r**, the even and odd parts of the previous scale are reconstructed as:

$$\mathbf{e}^i = \mathbf{c}^i - U(\mathbf{r}^i) = \mathbf{e}^{i+1} - U(\mathbf{o}^{i+1})$$

and:

$$\mathbf{o}^i = \mathbf{r}^i + P(\mathbf{e}^i) = \mathbf{o}^{i+1} + P(\mathbf{e}^i)$$

A new data is formed by interleaving \mathbf{e}^i and \mathbf{o}^i and the procedure repeated until the new data as the same number of traces as the original one.

Finally the adjoint operator can be easily derived by writing the lifting scheme in a matricial form:

$$\begin{bmatrix} \mathbf{r}_1 \\ \mathbf{r}_2 \\ \dots \\ \mathbf{r}_N \\ \mathbf{c}_1 \\ \mathbf{c}_2 \\ \dots \\ \mathbf{c}_N \end{bmatrix} = \begin{bmatrix} \mathbf{I} & \mathbf{0} & \dots & \mathbf{0} & -\mathbf{P} & \mathbf{0} & \dots & \mathbf{0} \\ \mathbf{0} & \mathbf{I} & \dots & \mathbf{0} & \mathbf{0} & -\mathbf{P} & \dots & \mathbf{0} \\ \dots & \dots & \dots & \dots & \dots & \dots & \dots & \dots \\ \mathbf{0} & \mathbf{0} & \dots & \mathbf{I} & \mathbf{0} & \mathbf{0} & \dots & -\mathbf{P} \\ \mathbf{U} & \mathbf{0} & \dots & \mathbf{0} & \mathbf{I} - \mathbf{UP} & \mathbf{0} & \dots & \mathbf{0} \\ \mathbf{0} & \mathbf{U} & \dots & \mathbf{0} & \mathbf{0} & \mathbf{I} - \mathbf{UP} & \dots & \mathbf{0} \\ \dots & \dots & \dots & \dots & \dots & \dots & \dots & \dots \\ \mathbf{0} & \mathbf{0} & \dots & \mathbf{U} & \mathbf{0} & \mathbf{0} & \dots & \mathbf{I} - \mathbf{UP} \end{bmatrix} \begin{bmatrix} \mathbf{o}_1 \\ \mathbf{o}_2 \\ \dots \\ \mathbf{o}_N \\ \mathbf{e}_1 \\ \mathbf{e}_2 \\ \dots \\ \mathbf{e}_N \end{bmatrix}$$

Transposing the operator leads to:

$$\begin{bmatrix} \mathbf{o}_1 \\ \mathbf{o}_2 \\ \dots \\ \mathbf{o}_N \\ \mathbf{e}_1 \\ \mathbf{e}_2 \\ \dots \\ \mathbf{e}_N \end{bmatrix} = \begin{bmatrix} \mathbf{I} & \mathbf{0} & \dots & \mathbf{0} & -\mathbf{U}^T & \mathbf{0} & \dots & \mathbf{0} \\ \mathbf{0} & \mathbf{I} & \dots & \mathbf{0} & \mathbf{0} & -\mathbf{U}^T & \dots & \mathbf{0} \\ \dots & \dots & \dots & \dots & \dots & \dots & \dots & \dots \\ \mathbf{0} & \mathbf{0} & \dots & \mathbf{I} & \mathbf{0} & \mathbf{0} & \dots & -\mathbf{U}^T \\ \mathbf{P}^T & \mathbf{0} & \dots & \mathbf{0} & \mathbf{I} - \mathbf{P}^T \mathbf{U}^T & \mathbf{0} & \dots & \mathbf{0} \\ \mathbf{0} & \mathbf{P}^T & \dots & \mathbf{0} & \mathbf{0} & \mathbf{I} - \mathbf{P}^T \mathbf{U}^T & \dots & \mathbf{0} \\ \dots & \dots & \dots & \dots & \dots & \dots & \dots & \dots \\ \mathbf{0} & \mathbf{0} & \dots & \mathbf{P}^T & \mathbf{0} & \mathbf{0} & \dots & \mathbf{I} - \mathbf{P}^T \mathbf{U}^T \end{bmatrix} \begin{bmatrix} \mathbf{r}_1 \\ \mathbf{r}_2 \\ \dots \\ \mathbf{r}_N \\ \mathbf{c}_1 \\ \mathbf{c}_2 \\ \dots \\ \mathbf{c}_N \end{bmatrix}$$

which can be written more easily in the following two steps:

$$\mathbf{o} = \mathbf{r} + \mathbf{U}^H \mathbf{c}$$

and:

$$\mathbf{e} = \mathbf{c} - \mathbf{P}^H (\mathbf{r} + \mathbf{U}^H (\mathbf{c})) = \mathbf{c} - \mathbf{P}^H \mathbf{o}$$

Similar derivations follow for more complex wavelet bases.

Attributes

shape [tuple] Operator shape

explicit [bool] Operator contains a matrix that can be solved explicitly (True) or not (False)

Methods

<code>__init__(slopes[, sampling, level, kind, ...])</code>	Initialize this LinearOperator.
<code>adjoint()</code>	Hermitian adjoint.
<code>apply_columns(cols)</code>	Apply subset of columns of operator
<code>cond([uselobpcg])</code>	Condition number of linear operator.
<code>conj()</code>	Complex conjugate operator
<code>div(y[, niter])</code>	Solve the linear problem $\mathbf{y} = \mathbf{A}\mathbf{x}$.
<code>dot(x)</code>	Matrix-matrix or matrix-vector multiplication.
<code>eigs([neigs, symmetric, niter, uselobpcg])</code>	Most significant eigenvalues of linear operator.
<code>inverse(x)</code>	
<code>matmat(X)</code>	Matrix-matrix multiplication.
<code>matvec(x)</code>	Matrix-vector multiplication.
<code>rmatmat(X)</code>	Matrix-matrix multiplication.
<code>rmatvec(x)</code>	Adjoint matrix-vector multiplication.
<code>todense([backend])</code>	Return dense matrix.
<code>toimag([forw, adj])</code>	Imag operator
<code>toreal([forw, adj])</code>	Real operator
<code>tosparse()</code>	Return sparse matrix.
<code>trace([neval, method, backend])</code>	Trace of linear operator.
<code>transpose()</code>	Transpose this linear operator.

Examples using `pylops.signalprocessing.Seislet`

- `sphx_glr_gallery_plot_seislet.py`
- `sphx_glr_gallery_plot_slopeest.py`

pylops.signalprocessing.Radon2D

`pylops.signalprocessing.Radon2D` (*axis*, *haxis*, *pxaxis*, *kind*='linear', *centeredh*=True, *interp*=True, *onthe-fly*=False, *engine*='numpy', *dtype*='float64')

Two dimensional Radon transform.

Apply two dimensional Radon forward (and adjoint) transform to a 2-dimensional array of size $[n_{px} \times n_t]$ (and $[n_x \times n_t]$).

In forward mode this entails to spreading the model vector along parametric curves (lines, parabolas, or hyperbolas depending on the choice of *kind*), while stacking values in the data vector along the same parametric curves is performed in adjoint mode.

Parameters

axis [np.ndarray] Time axis

haxis [np.ndarray] Spatial axis

pxaxis [np.ndarray] Axis of scanning variable p_x of parametric curve

kind [str, optional] Curve to be used for stacking/spreading (linear, parabolic, and hyperbolic are currently supported) or a function that takes (x, t0, px) as input and returns t as output

centeredh [bool, optional] Assume centered spatial axis (True) or not (False). If True the original haxis is ignored and a new axis is created.

interp [bool, optional] Apply linear interpolation (True) or nearest interpolation (False) during stacking/spreading along parametric curve

onthe-fly [bool, optional] Compute stacking parametric curves on-the-fly as part of forward and adjoint modelling (True) or at initialization and store them in look-up table (False). Using a look-up table is computationally more efficient but increases the memory burden

engine [str, optional] Engine used for computation (numpy or numba)

dtype [str, optional] Type of elements in input array.

Returns

r2op [pylops.LinearOperator] Radon operator

Raises

KeyError If *engine* is neither numpy nor numba

NotImplementedError If *kind* is not linear, parabolic, or hyperbolic

See also:

`pylops.signalprocessing.Radon3D` Three dimensional Radon transform

`pylops.Spread` Spread operator

Notes

The Radon2D operator applies the following linear transform in adjoint mode to the data after reshaping it into a 2-dimensional array of size $[n_x \times n_t]$ in adjoint mode:

$$m(p_x, t_0) = \int d(x, t = f(p_x, x, t)) dx$$

where $f(p_x, x, t) = t_0 + p_x * x$ where $p_x = \sin(\theta)/v$ in linear mode, $f(p_x, x, t) = t_0 + p_x * x^2$ in parabolic mode, and $f(p_x, x, t) = \sqrt{t_0^2 + x^2/p_x^2}$ in hyperbolic mode. Note that internally the p_x axis will be normalized by the ratio of the spatial and time axes and used alongside unitless axes. Whilst this makes the linear mode fully unitless, users are required to apply additional scalings to the p_x axis for other relationships:

- p_x should be pre-multiplied by d_x for the parabolic relationship;
- p_x should be pre-multiplied by $(d_t/d_x)^2$ for the hyperbolic relationship.

As the adjoint operator can be interpreted as a repeated summation of sets of elements of the model vector along chosen parametric curves, the forward is implemented as spreading of values in the data vector along the same parametric curves. This operator is actually a thin wrapper around the `pylops.Spread` operator.

Examples using `pylops.signalprocessing.Radon2D`

- `sphx_glr_gallery_plot_sliding.py`
- `sphx_glr_gallery_plot_chirpradon.py`
- `sphx_glr_gallery_plot_radon.py`
- [11. Radon filtering](#)
- [12. Seismic regularization](#)
- [16. CT Scan Imaging](#)

`pylops.signalprocessing.Radon3D`

`pylops.signalprocessing.Radon3D` (*taxis*, *hyaxis*, *hxaxis*, *pyaxis*, *pxaxis*, *kind*='linear', *centeredh*=True, *interp*=True, *ontheft*=False, *engine*='numpy', *dtype*='float64')

Three dimensional Radon transform.

Apply three dimensional Radon forward (and adjoint) transform to a 3-dimensional array of size $[n_{py} \times n_{px} \times n_t]$ (and $[n_y \times n_x \times n_t]$).

In forward mode this entails to spreading the model vector along parametric curves (lines, parabolas, or hyperbolas depending on the choice of *kind*), while stacking values in the data vector along the same parametric curves is performed in adjoint mode.

Parameters

taxis [np.ndarray] Time axis

hxaxis [np.ndarray] Fast patial axis

hyaxis [np.ndarray] Slow spatial axis

pyaxis [np.ndarray] Axis of scanning variable p_y of parametric curve

pxaxis [np.ndarray] Axis of scanning variable p_x of parametric curve

kind [str, optional] Curve to be used for stacking/spreading (linear, parabolic, and hyperbolic are currently supported)

centeredh [bool, optional] Assume centered spatial axis (True) or not (False). If True the original *hxaxis* is ignored and a new axis is created.

interp [bool, optional] Apply linear interpolation (True) or nearest interpolation (False) during stacking/spreading along parametric curve

onthe-fly [`bool`, optional] Compute stacking parametric curves on-the-fly as part of forward and adjoint modelling (`True`) or at initialization and store them in look-up table (`False`). Using a look-up table is computationally more efficient but increases the memory burden

engine [`str`, optional] Engine used for computation (`numpy` or `numba`)

dtype [`str`, optional] Type of elements in input array.

Returns

r3op [`pylops.LinearOperator`] Radon operator

Raises

KeyError If engine is neither `numpy` nor `numba`

NotImplementedError If kind is not `linear`, `parabolic`, or `hyperbolic`

See also:

`pylops.signalprocessing.Radon2D` Two dimensional Radon transform

`pylops.Spread` Spread operator

Notes

The Radon3D operator applies the following linear transform in adjoint mode to the data after reshaping it into a 3-dimensional array of size $[n_y \times n_x \times n_t]$ in adjoint mode:

$$m(p_y, p_x, t_0) = \int d(y, x, t = f(p_y, p_x, y, x, t)) dx dy$$

where $f(p_y, p_x, y, x, t) = t_0 + p_y * y + p_x * x$ in linear mode, $f(p_y, p_x, y, x, t) = t_0 + p_y * y^2 + p_x * x^2$ in parabolic mode, and $f(p_y, p_x, y, x, t) = \sqrt{t_0^2 + y^2/p_y^2 + x^2/p_x^2}$ in hyperbolic mode. Note that internally the p_x and p_y axes will be normalized by the ratio of the spatial and time axes and used alongside unitless axes. Whilst this makes the linear mode fully unitless, users are required to apply additional scalings to the p_x axis for other relationships

- p_x should be pre-multiplied by d_x/d_y for the parabolic relationship;
- p_x should be pre-multiplied by $(d_t/d_x)^2/(d_t/d_y)^2$ for the hyperbolic relationship.

As the adjoint operator can be interpreted as a repeated summation of sets of elements of the model vector along chosen parametric curves, the forward is implemented as spreading of values in the data vector along the same parametric curves. This operator is actually a thin wrapper around the `pylops.Spread` operator.

Examples using `pylops.signalprocessing.Radon3D`

- `sphx_glr_gallery_plot_sliding.py`
- `sphx_glr_gallery_plot_chirpradon.py`
- `sphx_glr_gallery_plot_radon.py`

pylops.signalprocessing.ChirpRadon2D

class pylops.signalprocessing.**ChirpRadon2D** (*taxis*, *haxis*, *pmax*, *dtype*='float64')

2D Chirp Radon transform

Apply Radon forward (and adjoint) transform using Fast Fourier Transform and Chirp functions to a 2-dimensional array of size $[n_x \times n_t]$ (both in forward and adjoint mode).

Note that forward and adjoint are swapped compared to the time-space implementation in [pylops.signalprocessing.Radon2D](#) and a direct *inverse* method is also available for this implementation.

Parameters

taxis [np.ndarray] Time axis

haxis [np.ndarray] Spatial axis

pmax [np.ndarray] Maximum slope defined as tan of maximum stacking angle in x direction $p_{max} = \tan(\alpha_{x,max})$. If one operates in terms of minimum velocity c_0 , set $p_{x,max} = c_0 dy/dt$.

dtype [str, optional] Type of elements in input array.

Notes

Refer to [1] for the theoretical and implementation details.

Attributes

shape [tuple] Operator shape

explicit [bool] Operator contains a matrix that can be solved explicitly (True) or not (False)

Methods

<code>__init__(taxis, haxis, pmax[, dtype])</code>	Initialize this LinearOperator.
<code>adjoint()</code>	Hermitian adjoint.
<code>apply_columns(cols)</code>	Apply subset of columns of operator
<code>cond([uslobpcg])</code>	Condition number of linear operator.
<code>conj()</code>	Complex conjugate operator
<code>div(y[, niter])</code>	Solve the linear problem $\mathbf{y} = \mathbf{Ax}$.
<code>dot(x)</code>	Matrix-matrix or matrix-vector multiplication.
<code>eigs([neigs, symmetric, niter, uslobpcg])</code>	Most significant eigenvalues of linear operator.
<code>inverse(x)</code>	
<code>matmat(X)</code>	Matrix-matrix multiplication.
<code>matvec(x)</code>	Matrix-vector multiplication.
<code>rmatmat(X)</code>	Matrix-matrix multiplication.
<code>rmatvec(x)</code>	Adjoint matrix-vector multiplication.
<code>todense([backend])</code>	Return dense matrix.
<code>toimag([forw, adj])</code>	Imag operator
<code>toreal([forw, adj])</code>	Real operator
<code>tosparse()</code>	Return sparse matrix.
<code>trace([neval, method, backend])</code>	Trace of linear operator.
<code>transpose()</code>	Transpose this linear operator.

Examples using `pylops.signalprocessing.ChirpRadon2D`

- `sphx_glr_gallery_plot_chirpradon.py`

`pylops.signalprocessing.ChirpRadon3D`

class `pylops.signalprocessing.ChirpRadon3D` (*taxis, hyaxis, hxaxis, pmax, engine='numpy', dtype='float64', **kwargs_fftw*)

3D Chirp Radon transform

Apply Radon forward (and adjoint) transform using Fast Fourier Transform and Chirp functions to a 3-dimensional array of size $[n_y \times n_x \times n_t]$ (both in forward and adjoint mode).

Note that forward and adjoint are swapped compared to the time-space implementation in `pylops.signalprocessing.Radon3D` and a direct *inverse* method is also available for this implementation.

Parameters

taxis [`np.ndarray`] Time axis

hxaxis [`np.ndarray`] Fast patial axis

hyaxis [`np.ndarray`] Slow spatial axis

pmax [`np.ndarray`] Two element array ($p_{y,max}, p_{x,max}$) of tan of maximum stacking angles in y and x directions ($\tan(\alpha_{y,max}), \tan(\alpha_{x,max})$). If one operates in terms of minimum velocity c_0 , then $p_{y,max} = c_0 dy/dt$ and $p_{x,max} = c_0 dx/dt$

engine [`str`, optional] Engine used for fft computation (numpy or fftw)

dtype [`str`, optional] Type of elements in input array.

****kwargs_fftw** Arbitrary keyword arguments for `pyfftw.FFTW` (reccomended: `flags=('FFTW_ESTIMATE',), threads=NTHREADS`)

Notes

Refer to [1] for the theoretical and implementation details.

Attributes

shape [`tuple`] Operator shape

explicit [`bool`] Operator contains a matrix that can be solved explicitly (True) or not (False)

Methods

<code>__init__(taxis, hyaxis, hxaxis, pmax[, ...])</code>	Initialize this LinearOperator.
<code>adjoint()</code>	Hermitian adjoint.
<code>apply_columns(cols)</code>	Apply subset of columns of operator
<code>cond([uslobpcg])</code>	Condition number of linear operator.
<code>conj()</code>	Complex conjugate operator
<code>div(y[, niter])</code>	Solve the linear problem $y = Ax$.
<code>dot(x)</code>	Matrix-matrix or matrix-vector multiplication.
<code>eigs([neigs, symmetric, niter, uslobpcg])</code>	Most significant eigenvalues of linear operator.
<code>inverse(x)</code>	

Continued on next page

Table 40 – continued from previous page

<code>matmat(X)</code>	Matrix-matrix multiplication.
<code>matvec(x)</code>	Matrix-vector multiplication.
<code>rmatmat(X)</code>	Matrix-matrix multiplication.
<code>rmatvec(x)</code>	Adjoint matrix-vector multiplication.
<code>todense([backend])</code>	Return dense matrix.
<code>toimag([forw, adj])</code>	Imag operator
<code>toreal([forw, adj])</code>	Real operator
<code>tosparse()</code>	Return sparse matrix.
<code>trace([neval, method, backend])</code>	Trace of linear operator.
<code>transpose()</code>	Transpose this linear operator.

Examples using `pylops.signalprocessing.ChirpRadon3D`

- `sphx_glr_gallery_plot_chirpradon.py`

`pylops.signalprocessing.Sliding1D`

`pylops.signalprocessing.Sliding1D` (*Op*, *dim*, *dimd*, *nwin*, *nover*, *tapertype*='hanning', *design*=*False*)

1D Sliding transform operator.

Apply a transform operator *Op* repeatedly to slices of the model vector in forward mode and slices of the data vector in adjoint mode. More specifically, in forward mode the model vector is divided into slices, each slice is transformed, and slices are then recombined in a sliding window fashion.

This operator can be used to perform local, overlapping transforms (e.g., `pylops.signalprocessing.FFT`) on 1-dimensional arrays.

Note: The shape of the model has to be consistent with the number of windows for this operator not to return an error. As the number of windows depends directly on the choice of *nwin* and *nover*, it is recommended to use *design*=True if unsure about the choice *dims* and use the number of windows printed on screen to define such input parameter.

Warning: Depending on the choice of *nwin* and *nover* as well as the size of the data, sliding windows may not cover the entire data. The start and end indices of each window can be displayed using *design*=True while defining the best sliding window approach.

Parameters

- Op** [`pylops.LinearOperator`] Transform operator
- dim** [`tuple`] Shape of 1-dimensional model.
- dimd** [`tuple`] Shape of 1-dimensional data
- nwin** [`int`] Number of samples of window
- nover** [`int`] Number of samples of overlapping part of window
- tapertype** [`str`, optional] Type of taper (hanning, cosine, cosinesquare or None)
- design** [`bool`, optional] Print number of sliding window (True) or not (False)

Returns

Sop [`pylops.LinearOperator`] Sliding operator

Raises

ValueError Identified number of windows is not consistent with provided model shape (`dims`).

Examples using `pylops.signalprocessing.Sliding1D`

- `sphx_glr_gallery_plot_sliding.py`

`pylops.signalprocessing.Sliding2D`

`pylops.signalprocessing.Sliding2D` (*Op*, *dims*, *dimsd*, *nwin*, *nover*, *tapertype*='hanning', *design*=False)

2D Sliding transform operator.

Apply a transform operator `Op` repeatedly to slices of the model vector in forward mode and slices of the data vector in adjoint mode. More specifically, in forward mode the model vector is divided into slices, each slice is transformed, and slices are then recombined in a sliding window fashion. Both model and data are internally reshaped and interpreted as 2-dimensional arrays: each slice contains a portion of the array in the first dimension (and the entire second dimension).

This operator can be used to perform local, overlapping transforms (e.g., `pylops.signalprocessing.FFT2D` or `pylops.signalprocessing.Radon2D`) on 2-dimensional arrays.

Note: The shape of the model has to be consistent with the number of windows for this operator not to return an error. As the number of windows depends directly on the choice of `nwin` and `nover`, it is recommended to use `design=True` if unsure about the choice `dims` and use the number of windows printed on screen to define such input parameter.

Warning: Depending on the choice of `nwin` and `nover` as well as the size of the data, sliding windows may not cover the entire first dimension. The start and end indices of each window can be displayed using `design=True` while defining the best sliding window approach.

Parameters

Op [`pylops.LinearOperator`] Transform operator

dims [`tuple`] Shape of 2-dimensional model. Note that `dims[0]` should be multiple of the model size of the transform in the first dimension

dimsd [`tuple`] Shape of 2-dimensional data

nwin [`int`] Number of samples of window

nover [`int`] Number of samples of overlapping part of window

tapertype [`str`, optional] Type of taper (hanning, cosine, cosinesquare or None)

design [`bool`, optional] Print number of sliding window (True) or not (False)

Returns

Sop [`pylops.LinearOperator`] Sliding operator

Raises

ValueError Identified number of windows is not consistent with provided model shape (`dims`).

Examples using `pylops.signalprocessing.Sliding2D`

- `sphx_glr_gallery_plot_sliding.py`
- `sphx_glr_gallery_plot_patching.py`
- *12. Seismic regularization*

`pylops.signalprocessing.Sliding3D`

`pylops.signalprocessing.Sliding3D` (*Op, dims, dimsd, nwin, nover, nop, tapertype='hanning', design=False, nproc=1*)

3D Sliding transform operator.

Apply a transform operator `Op` repeatedly to patches of the model vector in forward mode and patches of the data vector in adjoint mode. More specifically, in forward mode the model vector is divided into patches each patch is transformed, and patches are then recombined in a sliding window fashion. Both model and data should be 3-dimensional arrays in nature as they are internally reshaped and interpreted as 3-dimensional arrays. Each patch contains in fact a portion of the array in the first and second dimensions (and the entire third dimension).

This operator can be used to perform local, overlapping transforms (e.g., `pylops.signalprocessing.FFTND` or `pylops.signalprocessing.Radon3D`) of 3-dimensional arrays.

Note: The shape of the model has to be consistent with the number of windows for this operator not to return an error. As the number of windows depends directly on the choice of `nwin` and `nover`, it is recommended to use `design=True` if unsure about the choice `dims` and use the number of windows printed on screen to define such input parameter.

Warning: Depending on the choice of `nwin` and `nover` as well as the size of the data, sliding windows may not cover the entire first and/or second dimensions. The start and end indices of each window can be displayed using `design=True` while defining the best sliding window approach.

Parameters

- Op** [`pylops.LinearOperator`] Transform operator
- dims** [`tuple`] Shape of 3-dimensional model. Note that `dims[0]` and `dims[1]` should be multiple of the model sizes of the transform in the first and second dimensions
- dimsd** [`tuple`] Shape of 3-dimensional data
- nwin** [`tuple`] Number of samples of window
- nover** [`tuple`] Number of samples of overlapping part of window
- nop** [`tuple`] Number of samples in axes of transformed domain associated to spatial axes in the data
- tapertype** [`str`, optional] Type of taper (hanning, cosine, cosinesquare or None)
- design** [`bool`, optional] Print number sliding window (True) or not (False)

Returns

Sop [*pylops.LinearOperator*] Sliding operator

Raises

ValueError Identified number of windows is not consistent with provided model shape (*dims*).

Examples using `pylops.signalprocessing.Sliding3D`

- sphx_glr_gallery_plot_sliding.py

`pylops.signalprocessing.Patch2D`

`pylops.signalprocessing.Patch2D` (*Op, dims, dimsd, nwin, nover, nop, tapertype='hanning', design=False*)

2D Patch transform operator.

Apply a transform operator *Op* repeatedly to patches of the model vector in forward mode and patches of the data vector in adjoint mode. More specifically, in forward mode the model vector is divided into patches, each patch is transformed, and patches are then recombined together. Both model and data are internally reshaped and interpreted as 2-dimensional arrays: each patch contains a portion of the array in both the first and second dimension.

This operator can be used to perform local, overlapping transforms (e.g., *pylops.signalprocessing.FFT2D* or *pylops.signalprocessing.Radon2D*) on 2-dimensional arrays.

Note: The shape of the model has to be consistent with the number of windows for this operator not to return an error. As the number of windows depends directly on the choice of *nwin* and *nover*, it is recommended to use *design=True* if unsure about the choice *dims* and use the number of windows printed on screen to define such input parameter.

Warning: Depending on the choice of *nwin* and *nover* as well as the size of the data, patches may not cover the entire size of the data. The start and end indices of each window can be displayed using *design=True* while defining the best patching approach.

Parameters

Op [*pylops.LinearOperator*] Transform operator

dims [*tuple*] Shape of 2-dimensional model. Note that *dims[0]* and *dims[1]* should be multiple of the model size of the transform in their respective dimensions

dimsd [*tuple*] Shape of 2-dimensional data

nwin [*tuple*] Number of samples of window

nover [*tuple*] Number of samples of overlapping part of window

nop [*tuple*] Size of model in the transformed domain

tapertype [*str*, optional] Type of taper (hanning, cosine, cosinesquare or None)

design [*bool*, optional] Print number of sliding window (True) or not (False)

Returns

Sop [`pylops.LinearOperator`] Sliding operator

Raises

ValueError Identified number of windows is not consistent with provided model shape (dims).

See also:

Sliding2d 2D Sliding transform operator.

Examples using `pylops.signalprocessing.Patch2D`

- `sphx_glr_gallery_plot_patching.py`

`pylops.signalprocessing.Fredholm1`

```
class pylops.signalprocessing.Fredholm1(G,  nz=1,  saveGt=True,  usematmul=True,
                                         dtype='float64')
```

Fredholm integral of first kind.

Implement a multi-dimensional Fredholm integral of first kind. Note that if the integral is two dimensional, this can be directly implemented using `pylops.basicoperators.MatrixMult`. A multi-dimensional Fredholm integral can be performed as a `pylops.basicoperators.BlockDiag` operator of a series of `pylops.basicoperators.MatrixMult`. However, here we take advantage of the structure of the kernel and perform it in a more efficient manner.

Parameters

G [`numpy.ndarray`] Multi-dimensional convolution kernel of size $[n_{slice} \times n_x \times n_y]$

nz [`numpy.ndarray`, optional] Additional dimension of model

saveGt [`bool`, optional] Save G and G^H to speed up the computation of adjoint (`True`) or create G^H on-the-fly (`False`) Note that `saveGt=True` will double the amount of required memory

usematmul [`bool`, optional] Use `numpy.matmul` (`True`) or for-loop with `numpy.dot` (`False`). As it is not possible to define which approach is more performant (this is highly dependent on the size of G and input arrays as well as the hardware used in the computation), we advise users to time both methods for their specific problem prior to making a choice.

dtype [`str`, optional] Type of elements in input array.

Notes

A multi-dimensional Fredholm integral of first kind can be expressed as

$$d(sl, x, z) = \int G(sl, x, y) m(sl, y, z) dy \quad \forall sl = 1, n_{slice}$$

on the other hand its adjoin is expressed as

$$m(sl, y, z) = \int G^*(sl, y, x) d(sl, x, z) dx \quad \forall sl = 1, n_{slice}$$

In discrete form, this operator can be seen as a block-diagonal matrix multiplication:

$$\begin{bmatrix} \mathbf{G}_{sl1} & 0 & \dots & 0 \\ 0 & \mathbf{G}_{sl2} & \dots & 0 \\ \dots & \dots & \dots & \dots \\ 0 & 0 & \dots & \mathbf{G}_{slN} \end{bmatrix} \begin{bmatrix} \mathbf{m}_{sl1} \\ \mathbf{m}_{sl2} \\ \dots \\ \mathbf{m}_{slN} \end{bmatrix}$$

Attributes

shape [tuple] Operator shape

explicit [bool] Operator contains a matrix that can be solved explicitly (True) or not (False)

Methods

<code>__init__(G[, nz, saveGt, usematmul, dtype])</code>	Initialize this LinearOperator.
<code>adjoint()</code>	Hermitian adjoint.
<code>apply_columns(cols)</code>	Apply subset of columns of operator
<code>cond([uselobpcg])</code>	Condition number of linear operator.
<code>conj()</code>	Complex conjugate operator
<code>div(y[, niter])</code>	Solve the linear problem $\mathbf{y} = \mathbf{A}\mathbf{x}$.
<code>dot(x)</code>	Matrix-matrix or matrix-vector multiplication.
<code>eigs([neigs, symmetric, niter, uselobpcg])</code>	Most significant eigenvalues of linear operator.
<code>matmat(X)</code>	Matrix-matrix multiplication.
<code>matvec(x)</code>	Matrix-vector multiplication.
<code>rmatmat(X)</code>	Matrix-matrix multiplication.
<code>rmatvec(x)</code>	Adjoint matrix-vector multiplication.
<code>todense([backend])</code>	Return dense matrix.
<code>toimag([forw, adj])</code>	Imag operator
<code>toreal([forw, adj])</code>	Real operator
<code>tosparse()</code>	Return sparse matrix.
<code>trace([neval, method, backend])</code>	Trace of linear operator.
<code>transpose()</code>	Transpose this linear operator.

Wave-Equation processing

<code>PressureToVelocity(nt, nr, dt, dr, rho, vel)</code>	Pressure to Vertical velocity conversion.
<code>UpDownComposition2D(nt, nr, dt, dr, rho, vel)</code>	2D Up-down wavefield composition.
<code>UpDownComposition3D(nt, nr, dt, dr, rho, vel)</code>	3D Up-down wavefield composition.
<code>MDC(G, nt, nv[, dt, dr, twosided, fast, ...])</code>	Multi-dimensional convolution.
<code>PhaseShift(vel, dz, nt, freq, kx[, ky, dtype])</code>	Phase shift operator
<code>Demigration(z, x, t, srcs, recs, vel, wav, ...)</code>	Kirchoff Demigration operator.

pylops.waveeqprocessing.PressureToVelocity

`pylops.waveeqprocessing.PressureToVelocity`(*nt*, *nr*, *dt*, *dr*, *rho*, *vel*, *nffts*=(None, None, None), *critical*=100.0, *ntaper*=10, *topressure*=False, *backend*='numpy', *dtype*='complex128')

Pressure to Vertical velocity conversion.

Apply conversion from pressure to vertical velocity seismic wavefield (or vertical velocity to pressure). The

input model and data required by the operator should be created by flattening the a wavefield of size $([n_{r_y}] \times n_{r_x} \times n_t)$.

Parameters

- nt** [int] Number of samples along the time axis
- nr** [int or tuple] Number of samples along the receiver axis (or axes)
- dt** [float] Sampling along the time axis
- dr** [float or tuple] Sampling(s) along the receiver array
- rho** [float] Density along the receiver array (must be constant)
- vel** [float] Velocity along the receiver array (must be constant)
- nffts** [tuple, optional] Number of samples along the wavenumber and frequency axes
- critical** [float, optional] Percentage of angles to retain in obliquity factor. For example, if `critical=100` only angles below the critical angle $\sqrt{k_y^2 + k_x^2} < \frac{\omega}{vel}$ will be retained
- ntaper** [float, optional] Number of samples of taper applied to obliquity factor around critical angle
- topressure** [bool, optional] Perform conversion from particle velocity to pressure (True) or from pressure to particle velocity (False)
- backend** [str, optional] Backend used for creation of obliquity factor operator (numpy or cupy)
- dtype** [str, optional] Type of elements in input array.

Returns

- Cop** [`pylops.LinearOperator`] Pressure to particle velocity (or particle velocity to pressure) conversion operator

See also:

[*UpDownComposition2D*](#) 2D Wavefield composition

[*UpDownComposition3D*](#) 3D Wavefield composition

[*WavefieldDecomposition*](#) Wavefield decomposition

Notes

A pressure wavefield $(p(x, t))$ can be converted into an equivalent vertical particle velocity wavefield $(v_z(x, t))$ by applying the following frequency-wavenumber dependant scaling [1]:

$$v_z(k_x, \omega) = \frac{k_z}{\omega \rho} p(k_x, \omega)$$

where the vertical wavenumber k_z is defined as $k_z = \sqrt{\omega^2/c^2 - k_x^2}$.

Similarly a vertical particle velocity can be converted into an equivalent pressure wavefield by applying the following frequency-wavenumber dependant scaling [1]:

$$p(k_x, \omega) = \frac{\omega \rho}{k_z} v_z(k_x, \omega)$$

For 3-dimensional applications the only difference is represented by the vertical wavenumber k_z , which is defined as $k_z = \sqrt{\omega^2/c^2 - k_x^2 - k_y^2}$.

In both cases, this operator is implemented as a concatenation of a 2 or 3-dimensional forward FFT (`pylops.signalprocessing.FFT2` or `pylops.signalprocessing.FFTN`), a weighting matrix implemented via `pylops.basicprocessing.Diagonal`, and 2 or 3-dimensional inverse FFT.

Examples using `pylops.waveeqprocessing.PressureToVelocity`

- 14. *Seismic wavefield decomposition*

`pylops.waveeqprocessing.UpDownComposition2D`

```
pylops.waveeqprocessing.UpDownComposition2D(nt, nr, dt, dr, rho, vel, nffts=(None, None),
                                             critical=100.0, ntaper=10, scaling=1.0,
                                             backend='numpy', dtype='complex128')
```

2D Up-down wavefield composition.

Apply multi-component seismic wavefield composition from its up- and down-going constituents. The input model required by the operator should be created by flattening the separated wavefields of size $[n_r \times n_t]$ concatenated along the spatial axis.

Similarly, the data is also a flattened concatenation of pressure and vertical particle velocity wavefields.

Parameters

- nt** [int] Number of samples along the time axis
- nr** [int] Number of samples along the receiver axis
- dt** [float] Sampling along the time axis
- dr** [float] Sampling along the receiver array
- rho** [float] Density along the receiver array (must be constant)
- vel** [float] Velocity along the receiver array (must be constant)
- nffts** [tuple, optional] Number of samples along the wavenumber and frequency axes
- critical** [float, optional] Percentage of angles to retain in obliquity factor. For example, if `critical=100` only angles below the critical angle $|k_x| < \frac{f(k_x)}{vel}$ will be retained
- ntaper** [float, optional] Number of samples of taper applied to obliquity factor around critical angle
- scaling** [float, optional] Scaling to apply to the operator (see Notes for more details)
- backend** [str, optional] Backend used for creation of obliquity factor operator (numpy or cupy)
- dtype** [str, optional] Type of elements in input array.

Returns

UDop [`pylops.LinearOperator`] Up-down wavefield composition operator

See also:

[`UpDownComposition3D`](#) 3D Wavefield composition

[`WavefieldDecomposition`](#) Wavefield decomposition

Notes

Multi-component seismic data ($p(x, t)$ and $v_z(x, t)$) can be synthesized in the frequency-wavenumber domain as the superposition of the up- and downgoing constituents of the pressure wavefield ($p^-(x, t)$ and $p^+(x, t)$) as follows [1]:

$$\begin{bmatrix} \mathbf{p}(k_x, \omega) \\ \mathbf{v}_z(k_x, \omega) \end{bmatrix} = \begin{bmatrix} 1 & 1 \\ \frac{k_z}{\omega\rho} & -\frac{k_z}{\omega\rho} \end{bmatrix} \begin{bmatrix} \mathbf{p}^+(k_x, \omega) \\ \mathbf{p}^-(k_x, \omega) \end{bmatrix}$$

where the vertical wavenumber k_z is defined as $k_z = \sqrt{\omega^2/c^2 - k_x^2}$.

We can write the entire composition process in a compact matrix-vector notation as follows:

$$\begin{bmatrix} \mathbf{p} \\ s * \mathbf{v}_z \end{bmatrix} = \begin{bmatrix} \mathbf{F} & 0 \\ 0 & s * \mathbf{F} \end{bmatrix} \begin{bmatrix} \mathbf{I} & \mathbf{I} \\ \mathbf{W}^+ & \mathbf{W}^- \end{bmatrix} \begin{bmatrix} \mathbf{F}^H & 0 \\ 0 & \mathbf{F}^H \end{bmatrix} \mathbf{p}^\pm$$

where \mathbf{F} is the 2-dimensional FFT (`pylops.signalprocessing.FFT2`), \mathbf{W}^\pm are weighting matrices which contain the scalings $\pm \frac{k_z}{\omega\rho}$ implemented via `pylops.basicprocessing.Diagonal`, and s is a scaling factor that is applied to both the particle velocity data and to the operator has shown above. Such a scaling is required to balance out the different dynamic range of pressure and particle velocity when solving the wavefield separation problem as an inverse problem.

As the operator is effectively obtained by chaining basic PyLops operators the adjoint is automatically implemented for this operator.

Examples using `pylops.waveeqprocessing.UpDownComposition2D`

- 14. *Seismic wavefield decomposition*

`pylops.waveeqprocessing.UpDownComposition3D`

```
pylops.waveeqprocessing.UpDownComposition3D(nt, nr, dt, dr, rho, vel, nffts=(None,
None, None), critical=100.0, nta-
per=10, scaling=1.0, backend='numpy',
dtype='complex128')
```

3D Up-down wavefield composition.

Apply multi-component seismic wavefield composition from its up- and down-going constituents. The input model required by the operator should be created by flattening the separated wavefields of size $[n_{r_y} \times n_{r_x} \times n_t]$ concatenated along the first spatial axis.

Similarly, the data is also a flattened concatenation of pressure and vertical particle velocity wavefields.

Parameters

- nt** [`int`] Number of samples along the time axis
- nr** [`tuple`] Number of samples along the receiver axes
- dt** [`float`] Sampling along the time axis
- dr** [`tuple`] Samplings along the receiver array
- rho** [`float`] Density along the receiver array (must be constant)
- vel** [`float`] Velocity along the receiver array (must be constant)
- nffts** [`tuple`, optional] Number of samples along the wavenumbers and frequency axes (for the wavenumbers axes the same order as **nr** and **dr** must be followed)

critical [`float`, optional] Percentage of angles to retain in obliquity factor. For example, if `critical=100` only angles below the critical angle $\sqrt{k_y^2 + k_x^2} < \frac{\omega}{v_{el}}$ will be retained

ntaper [`float`, optional] Number of samples of taper applied to obliquity factor around critical angle

scaling [`float`, optional] Scaling to apply to the operator (see Notes for more details)

backend [`str`, optional] Backend used for creation of obliquity factor operator (numpy or cupy)

dtype [`str`, optional] Type of elements in input array.

Returns

UDop [`pylops.LinearOperator`] Up-down wavefield composition operator

See also:

[`UpDownComposition2D`](#) 2D Wavefield composition

[`WavefieldDecomposition`](#) Wavefield decomposition

Notes

Multi-component seismic data ($p(y, x, t)$ and $v_z(y, x, t)$) can be synthesized in the frequency-wavenumber domain as the superposition of the up- and downgoing constituents of the pressure wavefield ($p^-(y, x, t)$ and $p^+(y, x, t)$) as described [`pylops.waveeqprocessing.UpDownComposition2D`](#).

Here the vertical wavenumber k_z is defined as $k_z = \sqrt{\omega^2/c^2 - k_y^2 - k_x^2}$.

`pylops.waveeqprocessing.MDC`

`pylops.waveeqprocessing.MDC` (*G*, *nt*, *nv*, *dt=1.0*, *dr=1.0*, *twosided=True*, *fast=None*, *dtype=None*, *fftengine='numpy'*, *transpose=True*, *saveGt=True*, *conj=False*, *usematmul=False*, *prescaled=False*)

Multi-dimensional convolution.

Apply multi-dimensional convolution between two datasets. If `transpose=True`, model and data should be provided after flattening 2- or 3-dimensional arrays of size $[n_r(\times n_{vs}) \times n_t]$ and $[n_s(\times n_{vs}) \times n_t]$ (or $2 \times n_t - 1$ for `twosided=True`), respectively. If `transpose=False`, model and data should be provided after flattening 2- or 3-dimensional arrays of size $[n_t \times n_r(\times n_{vs})]$ and $[n_t \times n_s(\times n_{vs})]$ (or $2 \times n_t - 1$ for `twosided=True`), respectively.

Warning: A new implementation of MDC is provided in v1.5.0. This currently affects only the inner working of the operator and end-users can use the operator in the same way as they used to do with the previous one. Nevertheless, it is now recommended to use the operator with `transpose=False`, as this behaviour will become default in version v2.0.0 and the behaviour with `transpose=True` will be deprecated.

Parameters

G [`numpy.ndarray`] Multi-dimensional convolution kernel in frequency domain of size $[n_s \times n_r \times n_{fmax}]$ if `transpose=True` or size $[n_{fmax} \times n_s \times n_r]$ if `transpose=False`

nt [`int`] Number of samples along time axis for model and data (note that this must be equal to $2 \times n_t - 1$ when working with `twosided=True`).

nv [int] Number of samples along virtual source axis

dt [float, optional] Sampling of time integration axis

dr [float, optional] Sampling of receiver integration axis

twosided [bool, optional] MDC operator has both negative and positive time (True) or only positive (False)

fast [bool, optional] *Deprecated*, will be removed in v2.0.0

dtype [str, optional] *Deprecated*, will be removed in v2.0.0

fftengine [str, optional] Engine used for fft computation (numpy or fftw)

transpose [bool, optional] Transpose G and inputs such that time/frequency is placed in first dimension. This allows back-compatibility with v1.4.0 and older but will be removed in v2.0.0 where time/frequency axis will be required to be in first dimension for efficiency reasons.

saveGt [bool, optional] Save G and G^H to speed up the computation of adjoint of `pylops.signalprocessing.Fredholm1` (True) or create G^H on-the-fly (False) Note that saveGt=True will be faster but double the amount of required memory

conj [str, optional] Perform Fredholm integral computation with complex conjugate of G

usematmul [bool, optional] Use numpy.matmul (True) or for-loop with numpy.dot (False) in `pylops.signalprocessing.Fredholm1` operator. Refer to Fredholm1 documentation for details.

prescaled [bool, optional] Apply scaling to kernel (False) or not (False) when performing spatial and temporal summations. In case prescaled=True, the kernel is assumed to have been pre-scaled when passed to the MDC routine.

Raises

ValueError If nt is even and twosided=True

See also:

MDD Multi-dimensional deconvolution

Notes

The so-called multi-dimensional convolution (MDC) is a chained operator [1]. It is composed of a forward Fourier transform, a multi-dimensional integration, and an inverse Fourier transform:

$$y(t, s, v) = F^{-1} \left(\int_S G(f, s, r) F(x(t, r, v)) dr \right)$$

which is discretized as follows:

$$y(t, s, v) = F^{-1} \left(\sum_{i_r=0}^{n_r} (\sqrt{n_t} * d_t * d_r) G(f, s, i_r) F(x(t, i_r, v)) \right)$$

where $(\sqrt{n_t} * d_t * d_r)$ is not applied if prescaled=True.

This operation can be discretized and performed by means of a linear operator

$$\mathbf{D} = \mathbf{F}^H \mathbf{G} \mathbf{F}$$

where \mathbf{F} is the Fourier transform applied along the time axis and \mathbf{G} is the multi-dimensional convolution kernel.

Examples using `pylops.waveeqprocessing.MDC`

- `sphx_glr_gallery_plot_mdc.py`
- *09. Multi-Dimensional Deconvolution*

`pylops.waveeqprocessing.PhaseShift`

`pylops.waveeqprocessing.PhaseShift` (*vel, dz, nt, freq, kx, ky=None, dtype='float64'*)

Phase shift operator

Apply positive (forward) phase shift with constant velocity in forward mode, and negative (backward) phase shift with constant velocity in adjoint mode. Input model and data should be 2- or 3-dimensional arrays in time-space domain of size $[n_t \times n_x (\times n_y)]$.

Parameters

- vel** [`float`, optional] Constant propagation velocity
- dz** [`float`, optional] Depth step
- nt** [`int`, optional] Number of time samples of model and data
- freq** [`numpy.ndarray`] Positive frequency axis
- kx** [`int`, optional] Horizontal wavenumber axis (centered around 0) of size $[n_x \times 1]$.
- ky** [`int`, optional] Second horizontal wavenumber axis for 3d phase shift (centered around 0) of size $[n_y \times 1]$.
- dtype** [`str`, optional] Type of elements in input array

Returns

- Pop** [`pylops.LinearOperator`] Phase shift operator

Notes

The phase shift operator implements a one-way wave equation forward propagation in frequency-wavenumber domain by applying the following transformation to the input model:

$$d(f, k_x, k_y) = m(f, k_x, k_y) * e^{-j\sqrt{\omega^2/v^2 - k_x^2 - k_y^2}\Delta z}$$

where v is the constant propagation velocity and Δz is the propagation depth. In adjoint mode, the data is propagated backward using the following transformation:

$$m(f, k_x, k_y) = d(f, k_x, k_y) * e^{j\sqrt{\omega^2/v^2 - k_x^2 - k_y^2}\Delta z}$$

Effectively, the input model and data are assumed to be in time-space domain and forward Fourier transform is applied to both dimensions, leading to the following operator:

$$\mathbf{d} = \mathbf{F}_t^H \mathbf{F}_x^H \mathbf{P} \mathbf{F}_x \mathbf{F}_t \mathbf{m}$$

where \mathbf{P} performs the phase-shift as discussed above.

Examples using `pylops.waveeqprocessing.PhaseShift`

- `sphx_glr_gallery_plot_phaseshift.py`

pylops.waveeqprocessing.Demigration

`pylops.waveeqprocessing.Demigration`(*z, x, t, srcs, recs, vel, wav, wavcenter, y=None, trav=None, mode='eikonal'*)

Kirchoff Demigration operator.

Traveltime based seismic demigration/migration operator.

Parameters

- z** [`numpy.ndarray`] Depth axis
- x** [`numpy.ndarray`] Spatial axis
- t** [`numpy.ndarray`] Time axis for data
- srcs** [`numpy.ndarray`] Sources in array of size $[2/3 \times n_s]$ The first axis should be ordered as (y,) x, z.
- recs** [`numpy.ndarray`] Receivers in array of size $[2/3 \times n_r]$ The first axis should be ordered as (y,) x, z.
- vel** [`numpy.ndarray` or `float`] Velocity model of size $[(n_y \times) n_x \times n_z]$ (or constant)
- wav** [`numpy.ndarray`] Wavelet
- wavcenter** [`int`] Index of wavelet center
- y** [`numpy.ndarray`] Additional spatial axis (for 3-dimensional problems)
- mode** [`str`, optional] Computation mode (analytic, eikonal or byot, see Notes for more details)
- trav** [`numpy.ndarray`, optional] Traveltime table of size $[(n_y \times) n_x \times n_z \times n_t]$ (to be provided if mode='byot')

Returns

demop [`pylops.LinearOperator`] Demigration/Migration operator

Raises

NotImplementedError If mode is neither analytic, eikonal, or byot

Notes

The demigration operator synthesizes seismic data given from a propagation velocity model v and a reflectivity model m . In forward mode:

$$d(\mathbf{x}_r, \mathbf{x}_s, t) = w(t) * \int_V G(\mathbf{x}, \mathbf{x}_s, t) G(\mathbf{x}_r, \mathbf{x}, t) m(\mathbf{x}) d\mathbf{x}$$

where $m(\mathbf{x})$ is the model and it represents the reflectivity at every location in the subsurface, $G(\mathbf{x}, \mathbf{x}_s, t)$ and $G(\mathbf{x}_r, \mathbf{x}, t)$ are the Green's functions from source-to-subsurface-to-receiver and finally $w(t)$ is the wavelet. Depending on the choice of mode the Green's function will be computed and applied differently:

- `mode=analytic` or `mode=eikonal`: traveltimes curves between source to receiver pairs are computed for every subsurface point and Green's functions are implemented from traveltimes look-up tables, placing the reflectivity values at corresponding source-to-receiver time in the data.
- `byot`: bring your own table. Traveltime table provided directly by user using `trav` input parameter. Green's functions are then implemented in the same way as previous options.

The adjoint of the demigration operator is a *migration* operator which projects data in the model domain creating an image of the subsurface reflectivity.

Geophysical subsurface characterization

<code>avo.AVOLinearModelling(theta[, vsvp, nt0, ...])</code>	AVO Linearized modelling.
<code>poststack.PoststackLinearModelling(wav, nt0)</code>	Post-stack linearized seismic modelling operator.
<code>prestack.PrestackLinearModelling(wav, theta)</code>	Pre-stack linearized seismic modelling operator.
<code>prestack.PrestackWaveletModelling(m, theta, nwav)</code>	Pre-stack linearized seismic modelling operator for wavelet.

pylops.avo.avo.AVOLinearModelling

class `pylops.avo.avo.AVOLinearModelling` (*theta*, *vsvp*=0.5, *nt0*=1, *spatdims*=None, *linearization*='akirich', *dtype*='float64')

AVO Linearized modelling.

Create operator to be applied to a combination of elastic parameters for generation of seismic pre-stack reflectivity.

Parameters

theta [`np.ndarray`] Incident angles in degrees

vsvp [`np.ndarray` or `float`] VS/VP ratio

nt0 [`int`, optional] number of samples (if `vsvp` is a scalar)

spatdims [`int` or `tuple`, optional] Number of samples along spatial axis (or axes) (None if only one dimension is available)

linearization [`str`, optional] choice of linearization: `akirich`: PP Aki-Richards, `fatti`: PP Fatti, `ps`: PS reflection,

dtype [`str`, optional] Type of elements in input array.

Raises

NotImplementedError If `linearization` is not an implemented linearization

Notes

The AVO linearized operator performs a linear combination of three (or two) elastic parameters arranged in input vector \mathbf{m} of size $n_{t0} \times N$ to create the so-called seismic reflectivity:

$$r(t, \theta, x, y) = \sum_{i=1}^N G_i(t, \theta) m_i(t, x, y) \quad \forall \quad t, \theta$$

where $N = 2/3$. Note that the reflectivity can be in 1d, 2d or 3d and `spatdims` contains the dimensions of the spatial axis (or axes) x and y .

Attributes

shape [`tuple`] Operator shape

explicit [`bool`] Operator contains a matrix that can be solved explicitly (`True`) or not (`False`)

Methods

<code>__init__(theta[, vsvp, nt0, spatdims, ...])</code>	Initialize this LinearOperator.
<code>adjoint()</code>	Hermitian adjoint.
<code>apply_columns(cols)</code>	Apply subset of columns of operator
<code>cond([uselobpcg])</code>	Condition number of linear operator.
<code>conj()</code>	Complex conjugate operator
<code>div(y[, niter])</code>	Solve the linear problem $\mathbf{y} = \mathbf{A}\mathbf{x}$.
<code>dot(x)</code>	Matrix-matrix or matrix-vector multiplication.
<code>eigs([neigs, symmetric, niter, uselobpcg])</code>	Most significant eigenvalues of linear operator.
<code>matmat(X)</code>	Matrix-matrix multiplication.
<code>matvec(x)</code>	Matrix-vector multiplication.
<code>rmatmat(X)</code>	Matrix-matrix multiplication.
<code>rmatvec(x)</code>	Adjoint matrix-vector multiplication.
<code>todense([backend])</code>	Return dense matrix.
<code>toimag([forw, adj])</code>	Imag operator
<code>toreal([forw, adj])</code>	Real operator
<code>tosparse()</code>	Return sparse matrix.
<code>trace([neval, method, backend])</code>	Trace of linear operator.
<code>transpose()</code>	Transpose this linear operator.

Examples using `pylops.avo.avo.AVOLinearModelling`

- `sphx_glr_gallery_plot_avo.py`

`pylops.avo.poststack.PoststackLinearModelling`

`pylops.avo.poststack.PoststackLinearModelling` (*wav*, *nt0*, *spatdims=None*, *explicit=False*, *sparse=False*, *kind='centered'*)

Post-stack linearized seismic modelling operator.

Create operator to be applied to an elastic parameter trace (or stack of traces) for generation of band-limited seismic post-stack data. The input model and data have shape $[n_{t0}(\times n_x \times n_y)]$.

Parameters

wav [`np.ndarray`] Wavelet in time domain (must have odd number of elements and centered to zero). If 1d, assume stationary wavelet for the entire time axis. If 2d, use as non-stationary wavelet (user must provide one wavelet per time sample in an array of size $[n_{t0} \times n_{wav}]$ where n_{wav} is the length of each wavelet). Note that the `dtype` of this variable will define that of the operator

nt0 [`int`] Number of samples along time axis

spatdims [`int` or `tuple`, optional] Number of samples along spatial axis (or axes) (`None` if only one dimension is available)

explicit [`bool`, optional] Create a chained linear operator (`False`, preferred for large data) or a `MatrixMult` linear operator with dense matrix (`True`, preferred for small data)

sparse [`bool`, optional] Create a sparse matrix (`True`) or dense (`False`) when `explicit=True`

Returns

Pop [LinearOperator] post-stack modelling operator.

Raises

ValueError If `wav` is two dimensional but does not contain `nt0` wavelets

Notes

Post-stack seismic modelling is the process of constructing seismic post-stack data from a profile of an elastic parameter of choice in time (or depth) domain. This can be easily achieved using the following forward model:

$$d(t, \theta = 0) = w(t) * \frac{d \ln(m(t))}{dt}$$

where $m(t)$ is the elastic parameter profile and $w(t)$ is the time domain seismic wavelet. In compact form:

$$\mathbf{d} = \mathbf{W} \mathbf{D} \mathbf{m}$$

In the special case of acoustic impedance ($m(t) = AI(t)$), the modelling operator can be used to create zero-offset data:

$$d(t, \theta = 0) = \frac{1}{2} w(t) * \frac{d \ln(m(t))}{dt}$$

where the scaling factor $\frac{1}{2}$ can be easily included in the wavelet.

Examples using `pylops.avo.poststack.PoststackLinearModelling`

- *07. Post-stack inversion*

`pylops.avo.prestack.PrestackLinearModelling`

`pylops.avo.prestack.PrestackLinearModelling`(`wav`, `theta`, `vsvp=0.5`, `nt0=1`, `spatdims=None`, `linearization='akirich'`, `explicit=False`, `kind='centered'`)

Pre-stack linearized seismic modelling operator.

Create operator to be applied to elastic property profiles for generation of band-limited seismic angle gathers from a linearized version of the Zoeppritz equation. The input model must be arranged in a vector of size $n_m \times n_{t0} (\times n_x \times n_y)$ for `explicit=True` and $n_{t0} \times n_m (\times n_x \times n_y)$ for `explicit=False`. Similarly the output data is arranged in a vector of size $n_{theta} \times n_{t0} (\times n_x \times n_y)$ for `explicit=True` and $n_{t0} \times n_{theta} (\times n_x \times n_y)$ for `explicit=False`.

Parameters

- wav** [np.ndarray] Wavelet in time domain (must had odd number of elements and centered to zero). Note that the dtype of this variable will define that of the operator
- theta** [np.ndarray] Incident angles in degrees. Must have same dtype of `wav` (or it will be automatically casted to it)
- vsvp** [float or np.ndarray] VS/VP ratio (constant or time/depth variant)
- nt0** [int, optional] number of samples (if `vsvp` is a scalar)
- spatdims** [int or tuple, optional] Number of samples along spatial axis (or axes) (None if only one dimension is available)

linearization [`str` or `func`, optional] choice of linearization, `akirich`: Aki-Richards, `fatti`: Fatti, `ps`: PS or any function on the form of `pylops.avo.avo.akirichards`

explicit [`bool`, optional] Create a chained linear operator (`False`, preferred for large data) or a `MatrixMult` linear operator with dense matrix (`True`, preferred for small data)

kind [`str`, optional] Derivative kind (`forward` or `centered`).

Returns

Preop [`LinearOperator`] pre-stack modelling operator.

Raises

NotImplementedError If `linearization` is not an implemented linearization

NotImplementedError If `kind` is not `forward` nor `centered`

Notes

Pre-stack seismic modelling is the process of constructing seismic pre-stack data from three (or two) profiles of elastic parameters in time (or depth) domain. This can be easily achieved using the following forward model:

$$d(t, \theta) = w(t) * \sum_{i=1}^{n_m} G_i(t, \theta) m_i(t)$$

where $w(t)$ is the time domain seismic wavelet. In compact form:

$$\mathbf{d} = \mathbf{Gm}$$

On the other hand, pre-stack inversion aims at recovering the different profiles of elastic properties from the band-limited seismic pre-stack data.

Examples using `pylops.avo.prestack.PrestackLinearModelling`

- `sphx_glr_gallery_plot_prestack.py`
- *08. Pre-stack (AVO) inversion*

`pylops.avo.prestack.PrestackWaveletModelling`

`pylops.avo.prestack.PrestackWaveletModelling` (m , θ , n_{wav} , $wavc=None$, $vsvp=0.5$, $linearization='akirich'$)

Pre-stack linearized seismic modelling operator for wavelet.

Create operator to be applied to a wavelet for generation of band-limited seismic angle gathers using a linearized version of the Zoeppritz equation.

Parameters

m [`np.ndarray`] elastic parameter profiles of size $[n_{t0} \times N]$ where $N = 3/2$. Note that the `dtype` of this variable will define that of the operator

theta [`int`] Incident angles in degrees. Must have same `dtype` of `m` (or it will be automatically casted to it)

nwav [`np.ndarray`] Number of samples of wavelet to be applied/estimated

wavc [`int`, optional] Index of the center of the wavelet

vsvp [`np.ndarray` or `float`, optional] VS/VP ratio

linearization [`str`, optional] choice of linearization, `akirich`: Aki-Richards, `fatti`: Fatti, `ps`: PS, or any function on the form of `pylops.avo.avo.akirichards`

Returns

Mconv [`LinearOperator`] pre-stack modelling operator for wavelet estimation.

Raises

NotImplementedError If `linearization` is not an implemented linearization

Notes

Pre-stack seismic modelling for wavelet estimate is the process of constructing seismic reflectivities using three (or two) profiles of elastic parameters in time (or depth) domain arranged in an input vector \mathbf{m} of size $nt0 \times N$:

$$d(t, \theta) = \sum_{i=1}^N G_i(t, \theta) m_i(t) * w(t)$$

where $w(t)$ is the time domain seismic wavelet. In compact form:

$$\mathbf{d} = \mathbf{G}\mathbf{w}$$

On the other hand, pre-stack wavelet estimation aims at recovering the wavelet given knowledge of the band-limited seismic pre-stack data and the elastic parameter profiles.

Examples using `pylops.avo.prestack.PrestackWaveletModelling`

- `sphx_glr_gallery_plot_wavest.py`

3.7.2 Solvers

Basic

<code>solver.cg(Op, y, x0[, niter, damp, tol, ...])</code>	Conjugate gradient
<code>solver.cgls(Op, y, x0[, niter, damp, tol, ...])</code>	Conjugate gradient least squares
<code>solver.lsqr(Op, y, x0[, damp, atol, btol, ...])</code>	LSQR

`pylops.optimization.solver.cg`

`pylops.optimization.solver.cg` (*Op*, *y*, *x0*, *niter*=10, *damp*=0.0, *tol*=0.0001, *show*=False, *callback*=None)

Conjugate gradient

Solve a square system of equations given an operator *Op* and data *y* using conjugate gradient iterations.

Parameters

Op [`pylops.LinearOperator`] Operator to invert of size $[N \times N]$

y [`np.ndarray`] Data of size $[N \times 1]$

x0 [`np.ndarray`, optional] Initial guess

niter [`int`, optional] Number of iterations
damp [`float`, optional] *Deprecated*, will be removed in v2.0.0
tol [`float`, optional] Tolerance on residual norm
show [`bool`, optional] Display iterations log
callback [`callable`, optional] Function with signature (`callback(x)`) to call after each iteration where `x` is the current model vector

Returns

x [`np.ndarray`] Estimated model of size $[N \times 1]$
iit [`int`] Number of executed iterations
cost [`numpy.ndarray`, optional] History of the L2 norm of the residual

Notes

Solve the $y = \text{Op}x$ problem using conjugate gradient iterations.

`pylops.optimization.solver.cgls`

`pylops.optimization.solver.cgls` (`Op`, `y`, `x0`, `niter=10`, `damp=0.0`, `tol=0.0001`, `show=False`, `callback=None`)

Conjugate gradient least squares

Solve an overdetermined system of equations given an operator `Op` and data `y` using conjugate gradient iterations.

Parameters

Op [`pylops.LinearOperator`] Operator to invert of size $[N \times M]$
y [`np.ndarray`] Data of size $[N \times 1]$
x0 [`np.ndarray`, optional] Initial guess
niter [`int`, optional] Number of iterations
damp [`float`, optional] Damping coefficient
tol [`float`, optional] Tolerance on residual norm
show [`bool`, optional] Display iterations log
callback [`callable`, optional] Function with signature (`callback(x)`) to call after each iteration where `x` is the current model vector

Returns

x [`np.ndarray`] Estimated model of size $[M \times 1]$
istop [`int`] Gives the reason for termination
 1 means `x` is an approximate solution to $d = \text{Op}x$
 2 means `x` approximately solves the least-squares problem
iit [`int`] Iteration number upon termination
rlnorm [`float`] $\|r\|_2$, where $r = d - \text{Op}x$

r2norm [`float`] $\sqrt{\mathbf{r}^T \mathbf{r} + \epsilon^2 \mathbf{x}^T \mathbf{x}}$. Equal to `r1norm` if $\epsilon = 0$

cost [`numpy.ndarray`, optional] History of `r1norm` through iterations

Notes

Minimize the following functional using conjugate gradient iterations:

$$J = \|\mathbf{y} - \mathbf{Op}\mathbf{x}\|_2^2 + \epsilon^2 \|\mathbf{x}\|_2^2$$

where ϵ is the damping coefficient.

Examples using `pylops.optimization.solver.cgls`

- `sphx_glr_gallery_plot_cgls.py`

`pylops.optimization.solver.lsqr`

```
pylops.optimization.solver.lsqr(Op, y, x0, damp=0.0, atol=1e-08, btol=1e-08, con-
lim=100000000.0, niter=10, calc_var=True, show=False,
callback=None)
```

LSQR

Solve an overdetermined system of equations given an operator `Op` and data `y` using LSQR iterations.

Parameters

Op [`pylops.LinearOperator`] Operator to invert of size $[N \times M]$

y [`np.ndarray`] Data of size $[N \times 1]$

x0 [`np.ndarray`, optional] Initial guess

damp [`float`, optional] Damping coefficient

atol, btol [`float`, optional] Stopping tolerances. If both are $1.0\text{e-}9$, the final residual norm should be accurate to about 9 digits. (The final `x` will usually have fewer correct digits, depending on `cond(A)` and the size of `damp`.)

conlim [`float`, optional] Stopping tolerance on `cond(Op)` exceeds `conlim`. For square, `conlim` could be as large as $1.0\text{e+}12$. For least-squares problems, `conlim` should be less than $1.0\text{e+}8$. Maximum precision can be obtained by setting `atol = btol = conlim = 0`, but the number of iterations may then be excessive.

niter [`int`, optional] Number of iterations

calc_var [`bool`, optional] Estimate diagonals of $(\mathbf{Op}^H \mathbf{Op} + \epsilon^2 \mathbf{I})^{-1}$.

show [`bool`, optional] Display iterations log

callback [`callable`, optional] Function with signature `(callback(x))` to call after each iteration where `x` is the current model vector

Returns

x [`np.ndarray`] Estimated model of size $[M \times 1]$

istop [`int`] Gives the reason for termination

0 means the exact solution is $\mathbf{x} = 0$

1 means \mathbf{x} is an approximate solution to $\mathbf{y} = \mathbf{Op}\mathbf{x}$

2 means \mathbf{x} approximately solves the least-squares problem

3 means the estimate of $\text{cond}(\tilde{\mathbf{Op}})$ has exceeded `conlim`

4 means $\mathbf{y} - \mathbf{Op}\mathbf{x}$ is small enough for this machine

5 means the least-squares solution is good enough for this machine

6 means $\text{cond}(\tilde{\mathbf{Op}})$ seems to be too large for this machine

7 means the iteration limit has been reached

r1norm [`float`] $\|\mathbf{r}\|_2^2$, where $\mathbf{r} = \mathbf{y} - \mathbf{Op}\mathbf{x}$

r2norm [`float`] $\sqrt{\mathbf{r}^T \mathbf{r} + \epsilon^2 \mathbf{x}^T \mathbf{x}}$. Equal to `r1norm` if $\epsilon = 0$

anorm [`float`] Estimate of Frobenius norm of $\tilde{\mathbf{Op}} = [\mathbf{Op} \ \epsilon \mathbf{I}]$

acond [`float`] Estimate of $\text{cond}(\tilde{\mathbf{Op}})$

arnorm [`float`] Estimate of norm of $\text{cond}(\mathbf{Op}^H \mathbf{r} - \epsilon^2 \mathbf{x})$

var [`float`] Diagonals of $(\mathbf{Op}^H \mathbf{Op})^{-1}$ (if `damp=0`) or more generally $(\mathbf{Op}^H \mathbf{Op} + \epsilon^2 \mathbf{I})^{-1}$.

cost [`numpy.ndarray`, optional] History of `r1norm` through iterations

Notes

Minimize the following functional using LSQR iterations [1]:

$$J = \|\mathbf{y} - \mathbf{Op}\mathbf{x}\|_2^2 + \epsilon^2 \|\mathbf{x}\|_2^2$$

where ϵ is the damping coefficient.

Examples using `pylops.optimization.solver.lsqr`

- `sphx_glr_gallery_plot_cgls.py`

Least-squares

`leastsquares.NormalEquationsInversion`(`Op`, ...) Inversion of normal equations.

`leastsquares.RegularizedInversion`(`Op`, `Regs`, `data`) Regularized inversion.

`leastsquares.PreconditionedInversion`(`Op`, `P`, `data`) Preconditioned inversion.

pylops.optimization.leastsquares.NormalEquationsInversion

```
pylops.optimization.leastsquares.NormalEquationsInversion(Op,      Regs,      data,
                                                            Weight=None,
                                                            dataregs=None,
                                                            epsI=0,   epsRs=None,
                                                            x0=None,          re-
                                                            turninfo=False,
                                                            NRegs=None,
                                                            epsNRs=None,
                                                            **kwargs_solver)
```

Inversion of normal equations.

Solve the regularized normal equations for a system of equations given the operator `Op`, a data weighting operator `Weight` and optionally a list of regularization terms `Regs` and/or `NRegs`.

Parameters

- Op** [*pylops.LinearOperator*] Operator to invert
- Regs** [*list*] Regularization operators (`None` to avoid adding regularization)
- data** [*numpy.ndarray*] Data
- Weight** [*pylops.LinearOperator*, optional] Weight operator
- dataregs** [*list*, optional] Regularization data (must have the same number of elements as `Regs`)
- epsI** [*float*, optional] Tikhonov damping
- epsRs** [*list*, optional] Regularization dampings (must have the same number of elements as `Regs`)
- x0** [*numpy.ndarray*, optional] Initial guess
- returninfo** [*bool*, optional] Return info of CG solver
- NRegs** [*list*] Normal regularization operators (`None` to avoid adding regularization). Such operators must apply the chain of the forward and the adjoint in one go. This can be convenient in cases where a faster implementation is available compared to applying the forward followed by the adjoint.
- epsNRs** [*list*, optional] Regularization dampings for normal operators (must have the same number of elements as `NRegs`)
- **kwargs_solver** Arbitrary keyword arguments for chosen solver (*scipy.sparse.linalg.cg* and *pylops.optimization.solver.cg* are used as default for numpy and cupy *data*, respectively)

Returns

- xinv** [*numpy.ndarray*] Inverted model.
- istop** [*int*] Convergence information:
 - 0: successful exit
 - >0: convergence to tolerance not achieved, number of iterations
 - <0: illegal input or breakdown

See also:

RegularizedInversion Regularized inversion

PreconditionedInversion Preconditioned inversion

Notes

Solve the following normal equations for a system of regularized equations given the operator **Op**, a data weighting operator **W**, a list of regularization terms (**R_i** and/or **N_i**), the data **d** and regularization data **d_{R_i}**, and the damping factors ϵ_I , ϵ_{R_i} and ϵ_{N_i} :

$$(\mathbf{Op}^T \mathbf{W} \mathbf{Op} + \sum_i \epsilon_{R_i}^2 \mathbf{R}_i^T \mathbf{R}_i + \sum_i \epsilon_{N_i}^2 \mathbf{N}_i + \epsilon_I^2 \mathbf{I}) \mathbf{x} = \mathbf{Op}^T \mathbf{W} \mathbf{d} + \sum_i \epsilon_{R_i}^2 \mathbf{R}_i^T \mathbf{d}_{R_i}$$

Note that the data term of the regularizations **N_i** is implicitly assumed to be zero.

Examples using `pylops.optimization.leastsquares.NormalEquationsInversion`

- `sphx_glr_gallery_plot_bilinear.py`
- *03. Solvers*
- *05. Image deblurring*
- *06. 2D Interpolation*

`pylops.optimization.leastsquares.RegularizedInversion`

```
pylops.optimization.leastsquares.RegularizedInversion (Op, Regs, data, Weight=None,  
                                                         dataregs=None, epsRs=None,  
                                                         x0=None, returninfo=False,  
                                                         **kwargs_solver)
```

Regularized inversion.

Solve a system of regularized equations given the operator **Op**, a data weighting operator **Weight**, and a list of regularization terms **Regs**.

Parameters

Op [`pylops.LinearOperator`] Operator to invert

Regs [`list`] Regularization operators (None to avoid adding regularization)

data [`numpy.ndarray`] Data

Weight [`pylops.LinearOperator`, optional] Weight operator

dataregs [`list`, optional] Regularization data (if None a zero data will be used for every regularization operator in **Regs**)

epsRs [`list`, optional] Regularization dampings

x0 [`numpy.ndarray`, optional] Initial guess

returninfo [`bool`, optional] Return info of LSQR solver

****kwargs_solver** Arbitrary keyword arguments for chosen solver (`scipy.sparse.linalg.lsqr` and `pylops.optimization.solver.cgls` are used as default for numpy and cupy *data*, respectively)

Returns

xinv [`numpy.ndarray`] Inverted model.
istop [`int`] Gives the reason for termination
 1 means **x** is an approximate solution to **d** = **Op****x**
 2 means **x** approximately solves the least-squares problem
itn [`int`] Iteration number upon termination
r1norm [`float`] $\|\mathbf{r}\|_2^2$, where **r** = **d** - **Op****x**
r2norm [`float`] $\sqrt{\mathbf{r}^T \mathbf{r} + \epsilon^2 \mathbf{x}^T \mathbf{x}}$. Equal to **r1norm** if $\epsilon = 0$

See also:

RegularizedOperator Regularized operator
NormalEquationsInversion Normal equations inversion
PreconditionedInversion Preconditioned inversion

Notes

Solve the following system of regularized equations given the operator **Op**, a data weighting operator $\mathbf{W}^{1/2}$, a list of regularization terms **R_i**, the data **d** and regularization damping factors ϵ_I : and ϵ_{R_i} :

$$\begin{bmatrix} \mathbf{W}^{1/2} \mathbf{Op} \\ \epsilon_{R_1} \mathbf{R}_1 \\ \dots \\ \epsilon_{R_N} \mathbf{R}_N \end{bmatrix} \mathbf{x} = \begin{bmatrix} \mathbf{W}^{1/2} \mathbf{d} \\ \epsilon_{R_1} \mathbf{d}_{R_1} \\ \dots \\ \epsilon_{R_N} \mathbf{d}_{R_N} \end{bmatrix}$$

where the `Weight` provided here is equivalent to the square-root of the weight in `pylops.optimization.leastsquares.NormalEquationsInversion`. Note that this system is solved using the `scipy.sparse.linalg.lsqr` and an initial guess **x0** can be provided to this solver, despite the original solver does not allow so.

Examples using `pylops.optimization.leastsquares.RegularizedInversion`

- `sphx_glr_gallery_plot_ista.py`
- `sphx_glr_gallery_plot_tvreg.py`
- `sphx_glr_gallery_plot_wavest.py`
- [03. Solvers](#)
- [06. 2D Interpolation](#)
- [16. CT Scan Imaging](#)

`pylops.optimization.leastsquares.PreconditionedInversion`

`pylops.optimization.leastsquares.PreconditionedInversion`(*Op*, *P*, *data*, *x0=None*,
returninfo=False,
***kwargs_solver*)

Preconditioned inversion.

Solve a system of preconditioned equations given the operator **Op** and a preconditioner **P**.

Parameters

Op [*pylops.LinearOperator*] Operator to invert
P [*pylops.LinearOperator*] Preconditioner
data [*numpy.ndarray*] Data
x0 [*numpy.ndarray*] Initial guess
returninfo [*bool*] Return info of LSQR solver
****kwargs_solver** Arbitrary keyword arguments for chosen solver (*scipy.sparse.linalg.lsqr* and *pylops.optimization.solver.cgls* are used as default for *numpy* and *cupy data*, respectively)

Returns

———
xinv [*numpy.ndarray*] Inverted model.
istop [*int*] Gives the reason for termination
1 means **x** is an approximate solution to $\mathbf{d} = \mathbf{Op}\mathbf{x}$
2 means **x** approximately solves the least-squares problem
itn [*int*] Iteration number upon termination
r1norm [*float*] $\|\mathbf{r}\|_2^2$, where $\mathbf{r} = \mathbf{d} - \mathbf{Op}\mathbf{x}$
r2norm [*float*] $\sqrt{\mathbf{r}^T \mathbf{r} + \epsilon^2 \mathbf{x}^T \mathbf{x}}$. Equal to **r1norm** if $\epsilon = 0$

See also:

RegularizedInversion Regularized inversion

NormalEquationsInversion Normal equations inversion

Notes

Solve the following system of preconditioned equations given the operator **Op**, a preconditioner **P**, the data **d**

$$\mathbf{d} = \mathbf{Op}(\mathbf{P}\mathbf{p})$$

where **p** is the solution in the preconditioned space and $\mathbf{x} = \mathbf{P}\mathbf{p}$ is the solution in the original space.

Examples using *pylops.optimization.leastsquares.PreconditionedInversion*

- sphx_glr_gallery_plot_wavest.py
- 03. Solvers

Sparsity

<i>sparsity.IRLS</i> (Op, data, nouter[, threshR, ...])	Iteratively reweighted least squares.
<i>sparsity.OMP</i> (Op, data[, niter_outer, ...])	Orthogonal Matching Pursuit (OMP).
<i>sparsity.ISTA</i> (Op, data, niter[, eps, alpha, ...])	Iterative Shrinkage-Thresholding Algorithm (ISTA).

Continued on next page

Table 47 – continued from previous page

<code>sparsity.FISTA(Op, data, niter[, eps, ...])</code>	Fast Iterative Shrinkage-Thresholding Algorithm (FISTA).
<code>sparsity.SPGL1(Op, data[, SOp, tau, sigma, x0])</code>	Spectral Projected-Gradient for L1 norm.
<code>sparsity.SplitBregman(Op, RegsL1, data[, ...])</code>	Split Bregman for mixed L2-L1 norms.

pylops.optimization.sparsity.IRLS

`pylops.optimization.sparsity.IRLS` (*Op*, *data*, *nouter*, *threshR=False*, *epsR=1e-10*, *epsI=1e-10*, *x0=None*, *tolIRLS=1e-10*, *returnhistory=False*, *kind='data'*, ***kwargs_solver*)

Iteratively reweighted least squares.

Solve an optimization problem with *L1* cost function (data IRLS) or *L1* regularization term (model IRLS) given the operator *Op* and data *y*.

In the *data IRLS*, the cost function is minimized by iteratively solving a weighted least squares problem with the weight at iteration *i* being based on the data residual at iteration *i* – 1. This IRLS solver is robust to *outliers* since the *L1* norm given less weight to large residuals than *L2* norm does.

Similarly in the *model IRLS*, the weight at iteration *i* is based on the model at iteration *i* – 1. This IRLS solver inverts for a sparse model vector.

Parameters

Op [*pylops.LinearOperator*] Operator to invert

data [*numpy.ndarray*] Data

nouter [*int*] Number of outer iterations

threshR [*bool*, optional] Apply thresholding in creation of weight (True) or damping (False)

epsR [*float*, optional] Damping to be applied to residuals for weighting term

epsI [*float*, optional] Tikhonov damping

x0 [*numpy.ndarray*, optional] Initial guess

tolIRLS [*float*, optional] Tolerance. Stop outer iterations if difference between inverted model at subsequent iterations is smaller than *tolIRLS*

returnhistory [*bool*, optional] Return history of inverted model for each outer iteration of IRLS

kind [*str*, optional] Kind of solver (data or model)

****kwargs_solver** Arbitrary keyword arguments for *scipy.sparse.linalg.cg* solver for data IRLS and *scipy.sparse.linalg.lsqr* solver for model IRLS when using numpy data (or *pylops.optimization.solver.cg* and *pylops.optimization.solver.cgls* when using cupy data)

Returns

xinv [*numpy.ndarray*] Inverted model

nouter [*int*] Number of effective outer iterations

xinv_hist [*numpy.ndarray*, optional] History of inverted model

rw_hist [*numpy.ndarray*, optional] History of weights

Notes

Data IRLS solves the following optimization problem for the operator \mathbf{Op} and the data \mathbf{d} :

$$J = \|\mathbf{d} - \mathbf{Op}\mathbf{x}\|_1$$

by a set of outer iterations which require to repeatedly solve a weighted least squares problem of the form:

$$\mathbf{x}^{(i+1)} = \arg \min_{\mathbf{x}} \|\mathbf{d} - \mathbf{Op}\mathbf{x}\|_{2, \mathbf{R}^{(i)}}^2 + \epsilon_I^2 \|\mathbf{x}\|_2^2$$

where $\mathbf{R}^{(i)}$ is a diagonal weight matrix whose diagonal elements at iteration i are equal to the absolute inverses of the residual vector $\mathbf{r}^{(i)} = \mathbf{y} - \mathbf{Op}\mathbf{x}^{(i)}$ at iteration i . More specifically the j -th element of the diagonal of $\mathbf{R}^{(i)}$ is

$$R_{j,j}^{(i)} = \frac{1}{|r_j^{(i)}| + \epsilon_R}$$

or

$$R_{j,j}^{(i)} = \frac{1}{\max(|r_j^{(i)}|, \epsilon_R)}$$

depending on the choice `threshR`. In either case, ϵ_R is the user-defined stabilization/thresholding factor [1].

Similarly *model IRLS* solves the following optimization problem for the operator \mathbf{Op} and the data \mathbf{d} :

$$J = \|\mathbf{x}\|_1 \quad s.t. \quad \mathbf{d} = \mathbf{Op}\mathbf{x}$$

by a set of outer iterations which require to repeatedly solve a weighted least squares problem of the form [2]:

$$\mathbf{x}^{(i+1)} = \arg \min_{\mathbf{x}} \|\mathbf{x}\|_{2, \mathbf{R}^{(i)}}^2 \quad s.t. \quad \mathbf{d} = \mathbf{Op}\mathbf{x}$$

where $\mathbf{R}^{(i)}$ is a diagonal weight matrix whose diagonal elements at iteration i are equal to the absolutes of the model vector $\mathbf{x}^{(i)}$ at iteration i . More specifically the j -th element of the diagonal of $\mathbf{R}^{(i)}$ is

$$R_{j,j}^{(i)} = |x_j^{(i)}|$$

Examples using `pylops.optimization.sparsity.IRLS`

- `sphx_glr_gallery_plot_linearregr.py`
- `sphx_glr_gallery_plot_ista.py`
- `sphx_glr_gallery_plot_regr.py`

`pylops.optimization.sparsity.OMP`

`pylops.optimization.sparsity.OMP` (*Op*, *data*, *niter_outer*=10, *niter_inner*=40, *sigma*=0.0001, *normalizecols*=False, *show*=False)

Orthogonal Matching Pursuit (OMP).

Solve an optimization problem with L_0 regularization function given the operator \mathbf{Op} and data \mathbf{y} . The operator can be real or complex, and should ideally be either square $N = M$ or underdetermined $N < M$.

Parameters

Op [`pylops.LinearOperator`] Operator to invert

data [`numpy.ndarray`] Data

niter_outer [`int`, optional] Number of iterations of outer loop

niter_inner [`int`, optional] Number of iterations of inner loop. By choosing `niter_inner=0`, the Matching Pursuit (MP) algorithm is implemented.

sigma [`list`] Maximum L2 norm of residual. When smaller stop iterations.

normalizecols [`list`, optional] Normalize columns (`True`) or not (`False`). Note that this can be expensive as it requires applying the forward operator n_{cols} times to unit vectors (i.e., containing 1 at position j and zero otherwise); use only when the columns of the operator are expected to have highly varying norms.

show [`bool`, optional] Display iterations log

Returns

xinv [`numpy.ndarray`] Inverted model

iiter [`int`] Number of effective outer iterations

cost [`numpy.ndarray`, optional] History of cost function

See also:

ISTA Iterative Shrinkage-Thresholding Algorithm (ISTA).

FISTA Fast Iterative Shrinkage-Thresholding Algorithm (FISTA).

SPGL1 Spectral Projected-Gradient for L1 norm (SPGL1).

SplitBregman Split Bregman for mixed L2-L1 norms.

Notes

Solves the following optimization problem for the operator **Op** and the data **d**:

$$\|\mathbf{x}\|_0 \quad \text{subj.to} \quad \|\mathbf{Op}\mathbf{x} - \mathbf{b}\|_2^2 \leq \sigma^2,$$

using Orthogonal Matching Pursuit (OMP). This is a very simple iterative algorithm which applies the following step:

$$\begin{aligned} \Lambda_k &= \Lambda_{k-1} \cup \{\arg\max_j |\mathbf{Op}_j^H \mathbf{r}_k|\} \\ \mathbf{x}_k &= \arg\min_{\mathbf{x}} \|\mathbf{Op}_{\Lambda_k} \mathbf{x} - \mathbf{b}\|_2^2 \end{aligned}$$

Note that by choosing `niter_inner=0` the basic Matching Pursuit (MP) algorithm is implemented instead. In other words, instead of solving an optimization at each iteration to find the best \mathbf{x} for the currently selected basis functions, the vector \mathbf{x} is just updated at the new basis function by taking directly the value from the inner product $\mathbf{Op}_j^H \mathbf{r}_k$.

In this case it is highly recommended to provide a normalized basis function. If different basis have different norms, the solver is likely to diverge. Similar observations apply to OMP, even though mild unbalancing between the basis is generally properly handled.

Examples using `pylops.optimization.sparsity.OMP`

- `sphx_glr_gallery_plot_ista.py`

pylops.optimization.sparsity.ISTA

```
pylops.optimization.sparsity.ISTA(Op, data, niter, eps=0.1, alpha=None, eigsiter=None,
                                     eigstol=0, tol=1e-10, monitorres=False, returninfo=False,
                                     show=False, threshkind='soft', perc=None, call-
                                     back=None, decay=None, SOp=None, x0=None)
```

Iterative Shrinkage-Thresholding Algorithm (ISTA).

Solve an optimization problem with L_p , $p = 0, 1/2, 1$ regularization, given the operator Op and data y . The operator can be real or complex, and should ideally be either square $N = M$ or underdetermined $N < M$.

Parameters

Op [`pylops.LinearOperator`] Operator to invert

data [`numpy.ndarray`] Data

niter [`int`] Number of iterations

eps [`float`, optional] Sparsity damping

alpha [`float`, optional] Step size ($\alpha \leq 1/\lambda_{\max}(\text{Op}^H \text{Op})$ guarantees convergence. If `None`, the maximum eigenvalue is estimated and the optimal step size is chosen. If provided, the condition will not be checked internally).

eigsiter [`float`, optional] Number of iterations for eigenvalue estimation if `alpha=None`

eigstol [`float`, optional] Tolerance for eigenvalue estimation if `alpha=None`

tol [`float`, optional] Tolerance. Stop iterations if difference between inverted model at subsequent iterations is smaller than `tol`

monitorres [`bool`, optional] Monitor that residual is decreasing

returninfo [`bool`, optional] Return info of CG solver

show [`bool`, optional] Display iterations log

threshkind [`str`, optional] Kind of thresholding ('hard', 'soft', 'half', 'hard-percentile', 'soft-percentile', or 'half-percentile' - 'soft' used as default)

perc [`float`, optional] Percentile, as percentage of values to be kept by thresholding (to be provided when thresholding is soft-percentile or half-percentile)

callback [`callable`, optional] Function with signature (`callback(x)`) to call after each iteration where `x` is the current model vector

decay [`numpy.ndarray`, optional] Decay factor to be applied to thresholding during iterations

SOp [`pylops.LinearOperator`, optional] Regularization operator (use when solving the analysis problem)

Returns

xinv [`numpy.ndarray`] Inverted model

niter [`int`] Number of effective iterations

cost [`numpy.ndarray`, optional] History of cost function

Raises

NotImplementedError If `threshkind` is different from hard, soft, half, soft-percentile, or half-percentile

ValueError If `perc=None` when `threshkind` is soft-percentile or half-percentile

ValueError If `monitorres=True` and residual increases

See also:

OMP Orthogonal Matching Pursuit (OMP).

FISTA Fast Iterative Shrinkage-Thresholding Algorithm (FISTA).

SPGL1 Spectral Projected-Gradient for L1 norm (SPGL1).

SplitBregman Split Bregman for mixed L2-L1 norms.

Notes

Solves the following synthesis problem for the operator \mathbf{Op} and the data \mathbf{d} :

$$J = \|\mathbf{d} - \mathbf{Op}\mathbf{x}\|_2^2 + \epsilon \|\mathbf{x}\|_p$$

or the analysis problem:

$$J = \|\mathbf{d} - \mathbf{Op}\mathbf{x}\|_2^2 + \epsilon \|\mathbf{SOp}^H \mathbf{x}\|_p$$

if \mathbf{SOp} is provided. Note that in the first case, \mathbf{SOp} should be assimilated in the modelling operator (i.e., $\mathbf{Op} = \mathbf{GOp} * \mathbf{SOp}$).

The Iterative Shrinkage-Thresholding Algorithms (ISTA) [1] is used, where $p = 0, 1, 1/2$. This is a very simple iterative algorithm which applies the following step:

$$\mathbf{x}^{(i+1)} = T_{(\epsilon\alpha/2, p)}(\mathbf{x}^{(i)} + \alpha \mathbf{Op}^H (\mathbf{d} - \mathbf{Op}\mathbf{x}^{(i)}))$$

or

$$\mathbf{x}^{(i+1)} = \mathbf{SOp}(T_{(\epsilon\alpha/2, p)}(\mathbf{SOp}^H (\mathbf{x}^{(i)} + \alpha \mathbf{Op}^H (\mathbf{d} - \mathbf{Op}\mathbf{x}^{(i)}))))$$

where $\epsilon\alpha/2$ is the threshold and $T_{(\tau, p)}$ is the thresholding rule. The most common variant of ISTA uses the so-called soft-thresholding rule $T(\tau, p = 1)$. Alternatively an hard-thresholding rule is used in the case of $p=0$ or a half-thresholding rule is used in the case of $p=1/2$. Finally, percentile bases thresholds are also implemented: the damping factor is not used anymore and the threshold changes at every iteration based on the computed percentile.

Examples using `pylops.optimization.sparsity.ISTA`

- `sphx_glr_gallery_plot_ista.py`
- [03. Solvers](#)

`pylops.optimization.sparsity.FISTA`

```
pylops.optimization.sparsity.FISTA(Op, data, niter, eps=0.1, alpha=None, eigsiter=None,
                                   eigstol=0, tol=1e-10, returninfo=False, show=False,
                                   threshkind='soft', perc=None, callback=None, de-
                                   cay=None, SOp=None, x0=None)
```

Fast Iterative Shrinkage-Thresholding Algorithm (FISTA).

Solve an optimization problem with L_p , $p = 0, 1/2, 1$ regularization, given the operator \mathbf{Op} and data \mathbf{y} . The operator can be real or complex, and should ideally be either square $N = M$ or underdetermined $N < M$.

Parameters

Op [`pylops.LinearOperator`] Operator to invert

data [`numpy.ndarray`] Data

niter [`int`] Number of iterations

eps [`float`, optional] Sparsity damping

alpha [`float`, optional] Step size ($\alpha \leq 1/\lambda_{max}(\mathbf{Op}^H \mathbf{Op})$ guarantees convergence. If `None`, the maximum eigenvalue is estimated and the optimal step size is chosen. If provided, the condition will not be checked internally).

eigsiter [`int`, optional] Number of iterations for eigenvalue estimation if `alpha=None`

eigstol [`float`, optional] Tolerance for eigenvalue estimation if `alpha=None`

tol [`float`, optional] Tolerance. Stop iterations if difference between inverted model at subsequent iterations is smaller than `tol`

returninfo [`bool`, optional] Return info of FISTA solver

show [`bool`, optional] Display iterations log

threshkind [`str`, optional] Kind of thresholding ('hard', 'soft', 'half', 'soft-percentile', or 'half-percentile' - 'soft' used as default)

perc [`float`, optional] Percentile, as percentage of values to be kept by thresholding (to be provided when thresholding is soft-percentile or half-percentile)

callback [`callable`, optional] Function with signature (`callback(x)`) to call after each iteration where `x` is the current model vector

decay [`numpy.ndarray`, optional] Decay factor to be applied to thresholding during iterations

SOp [`pylops.LinearOperator`, optional] Regularization operator (use when solving the analysis problem)

x0: :obj:'numpy.ndarray', optional Initial guess

Returns

xinv [`numpy.ndarray`] Inverted model

niter [`int`] Number of effective iterations

cost [`numpy.ndarray`, optional] History of cost function

Raises

NotImplementedError If `threshkind` is different from hard, soft, half, soft-percentile, or half-percentile

ValueError If `perc=None` when `threshkind` is soft-percentile or half-percentile

See also:

OMP Orthogonal Matching Pursuit (OMP).

ISTA Iterative Shrinkage-Thresholding Algorithm (ISTA).

SPGL1 Spectral Projected-Gradient for L1 norm (SPGL1).

SplitBregman Split Bregman for mixed L2-L1 norms.

Notes

Solves the following synthesis problem for the operator \mathbf{Op} and the data \mathbf{d} :

$$J = \|\mathbf{d} - \mathbf{Op}\mathbf{x}\|_2^2 + \epsilon \|\mathbf{x}\|_p$$

or the analysis problem:

$$J = \|\mathbf{d} - \mathbf{Op}\mathbf{x}\|_2^2 + \epsilon \|\mathbf{SOp}^H \mathbf{x}\|_p$$

if \mathbf{SOp} is provided.

The Fast Iterative Shrinkage-Thresholding Algorithm (FISTA) [1] is used, where $p = 0, 1, 1/2$. This is a modified version of ISTA solver with improved convergence properties and limited additional computational cost. Similarly to the ISTA solver, the choice of the thresholding algorithm to apply at every iteration is based on the choice of p .

Examples using `pylops.optimization.sparsity.FISTA`

- `sphx_glr_gallery_plot_ista.py`
- *03. Solvers*
- *05. Image deblurring*
- *11. Radon filtering*
- *15. Least-squares migration*

`pylops.optimization.sparsity.SPGL1`

`pylops.optimization.sparsity.SPGL1` (*Op*, *data*, *SOp=None*, *tau=0*, *sigma=0*, *x0=None*,
***kwargs_spgl1*)

Spectral Projected-Gradient for L1 norm.

Solve a constrained system of equations given the operator \mathbf{Op} and a sparsifying transform \mathbf{SOp} aiming to retrieve a model that is sparse in the sparsifying domain.

This is a simple wrapper to `spgl1.spgl1` which is a porting of the well-known `SPGL1` MATLAB solver into Python. In order to be able to use this solver you need to have installed the `spgl1` library.

Parameters

Op [`pylops.LinearOperator`] Operator to invert

data [`numpy.ndarray`] Data

SOp [`pylops.LinearOperator`] Sparsifying transform

tau [`float`] Non-negative LASSO scalar. If different from 0, SPGL1 will solve LASSO problem

sigma [`list`] BPDN scalar. If different from 0, SPGL1 will solve BPDN problem

x0 [`numpy.ndarray`] Initial guess

****kwargs_spgl1** Arbitrary keyword arguments for `spgl1.spgl1` solver

Returns

xinv [`numpy.ndarray`] Inverted model in original domain.

pinv [`numpy.ndarray`] Inverted model in sparse domain.

info [`dict`] Dictionary with the following information:

`tau`, final value of tau (see sigma above)

`rnorm`, two-norm of the optimal residual

`rgap`, relative duality gap (an optimality measure)

`gnorm`, Lagrange multiplier of (LASSO)

stat, 1: found a BPDN solution, 2: found a BP solution; exit based on small gradient, 3: found a BP solution; exit based on small residual, 4: found a LASSO solution, 5: error, too many iterations, 6: error, linesearch failed, 7: error, found suboptimal BP solution, 8: error, too many matrix-vector products.

`niters`, number of iterations

`nProdA`, number of multiplications with A

`nProdAt`, number of multiplications with A'

`n_newton`, number of Newton steps

`time_project`, projection time (seconds)

`time_matprod`, matrix-vector multiplications time (seconds)

`time_total`, total solution time (seconds)

`niters_lsqr`, number of lsqr iterations (if `subspace_min=True`)

`xnorm1`, L1-norm model solution history through iterations

`rnorm2`, L2-norm residual history through iterations

`lambdaa`, Lagrange multiplier history through iterations

Raises

ModuleNotFoundError If the `spgl1` library is not installed

Notes

Solve different variations of sparsity-promoting inverse problem by imposing sparsity in the retrieved model [1].

The first problem is called *basis pursuit denoise (BPDN)* and its cost function is

$$\|\mathbf{x}\|_1 \quad \text{subj.to} \quad \|\mathbf{OpS}^H \mathbf{x} - \mathbf{b}\|_2^2 \leq \sigma,$$

while the second problem is the *l1-regularized least-squares or LASSO* problem and its cost function is

$$\|\mathbf{OpS}^H \mathbf{x} - \mathbf{b}\|_2^2 \quad \text{subj.to} \quad \|\mathbf{x}\|_1 \leq \tau$$

Examples using `pylops.optimization.sparsity.SPGL1`

- 03. Solvers

pylops.optimization.sparsity.SplitBregman

```
pylops.optimization.sparsity.SplitBregman(Op,      RegsL1,      data,      niter_outer=3,
                                             niter_inner=5,      RegsL2=None,
                                             dataregsL2=None, mu=1.0,  epsRL1s=None,
                                             epsRL2s=None, tol=1e-10, tau=1.0, x0=None,
                                             restart=False, show=False, **kwargs_lsqr)
```

Split Bregman for mixed L2-L1 norms.

Solve an unconstrained system of equations with mixed L2-L1 regularization terms given the operator `Op`, a list of L1 regularization terms `RegsL1`, and an optional list of L2 regularization terms `RegsL2`.

Parameters

- Op** [*pylops.LinearOperator*] Operator to invert
- RegsL1** [*list*] L1 regularization operators
- data** [*numpy.ndarray*] Data
- niter_outer** [*int*] Number of iterations of outer loop
- niter_inner** [*int*] Number of iterations of inner loop of first step of the Split Bregman algorithm. A small number of iterations is generally sufficient and for many applications optimal efficiency is obtained when only one iteration is performed.
- RegsL2** [*list*] Additional L2 regularization operators (if `None`, L2 regularization is not added to the problem)
- dataregsL2** [*list*, optional] L2 Regularization data (must have the same number of elements of `RegsL2` or equal to `None` to use a zero data for every regularization operator in `RegsL2`)
- mu** [*float*, optional] Data term damping
- epsRL1s** [*list*] L1 Regularization dampings (must have the same number of elements as `RegsL1`)
- epsRL2s** [*list*] L2 Regularization dampings (must have the same number of elements as `RegsL2`)
- tol** [*float*, optional] Tolerance. Stop outer iterations if difference between inverted model at subsequent iterations is smaller than `tol`
- tau** [*float*, optional] Scaling factor in the Bregman update (must be close to 1)
- x0** [*numpy.ndarray*, optional] Initial guess
- restart** [*bool*, optional] The unconstrained inverse problem in inner loop is initialized with the initial guess (`True`) or with the last estimate (`False`)
- show** [*bool*, optional] Display iterations log
- **kwargs_lsqr** Arbitrary keyword arguments for `scipy.sparse.linalg.lsqr` solver used to solve the first subproblem in the first step of the Split Bregman algorithm.

Returns

- xinv** [*numpy.ndarray*] Inverted model
- itn_out** [*int*] Iteration number of outer loop upon termination

Notes

Solve the following system of unconstrained, regularized equations given the operator \mathbf{Op} and a set of mixed norm (L2 and L1) regularization terms $\mathbf{R}_{L2,i}$ and $\mathbf{R}_{L1,i}$, respectively:

$$J = \mu/2 \|\mathbf{d} - \mathbf{Op}\mathbf{x}\|_2^2 + \sum_i \epsilon_{RL2,i}/2 \|\mathbf{d}_{\mathbf{R}_{L2,i}} - \mathbf{R}_{L2,i}\mathbf{x}\|_2^2 + \sum_i \|\mathbf{R}_{L1,i}\mathbf{x}\|_1$$

where μ and $\epsilon_{RL2,i}$ are the damping factors used to weight the different L2 regularization terms of the cost function.

The generalized Split-Bergman algorithm [1] is used to solve such cost function: the algorithm is composed of a sequence of unconstrained inverse problems and Bregman updates.

The original system of equations is initially converted into a constrained problem:

$$J = \mu/2 \|\mathbf{d} - \mathbf{Op}\mathbf{x}\|_2^2 + \sum_i \epsilon_{RL2,i}/2 \|\mathbf{d}_{\mathbf{R}_{L2,i}} - \mathbf{R}_{L2,i}\mathbf{x}\|_2^2 + \sum_i \|\mathbf{y}_i\|_1 \quad s.t. \quad \mathbf{y}_i = \mathbf{R}_{L1,i}\mathbf{x} \quad \forall i$$

and solved as follows:

$$(\mathbf{x}^{k+1}, \mathbf{y}_i^{k+1}) = \arg \min_{\mathbf{x}, \mathbf{y}_i} \|\mathbf{d} - \mathbf{Op}\mathbf{x}\|_2^2 + \sum_i \epsilon_{RL2,i}/2 \|\mathbf{d}_{\mathbf{R}_{L2,i}} - \mathbf{R}_{L2,i}\mathbf{x}\|_2^2 + \sum_i \|\mathbf{y}_i\|_1 + \sum_i \epsilon_{RL1,i}/2 \|\mathbf{y}_i - \mathbf{R}_{L1,i}\mathbf{x} - \mathbf{b}_i^k\|_2^2$$

$$\mathbf{b}_i^{k+1} = \mathbf{b}_i^k + (\mathbf{R}_{L1,i}\mathbf{x}^{k+1} - \mathbf{y}_i^{k+1})$$

The `scipy.sparse.linalg.lsqr` solver and a fast shrinkage algorithm are used within a inner loop to solve the first step. The entire procedure is repeated `niter_outer` times until convergence.

Examples using `pylops.optimization.sparsity.SplitBregman`

- `sphx_glr_gallery_plot_tvreg.py`
- *05. Image deblurring*
- *16. CT Scan Imaging*

3.7.3 Applications

Wave-Equation processing

<i>SeismicInterpolation</i> (data, nrec, iava[, ...])	Seismic interpolation (or regularization).
<i>Deghosting</i> (p, nt, nr, dt, dr, vel, zrec[, ...])	Wavefield deghosting.
<i>WavefieldDecomposition</i> (p, vz, nt, nr, dt, ...)	Up-down wavefield decomposition.
<i>MDD</i> (G, d[, dt, dr, nfm, wav, twosided, ...])	Multi-dimensional deconvolution.
<i>Marchenko</i> (R[, R1, dt, nt, dr, nfm, wav, ...])	Marchenko redatuming
<i>LSM</i> (z, x, t, srcs, recs, vel, wav, wavcenter)	Least-squares Migration (LSM).

pylops.waveeqprocessing.SeismicInterpolation

```
pylops.waveeqprocessing.SeismicInterpolation(data, nrec, iava, iava1=None,
                                                kind='fk', nffts=None, sampling=None,
                                                spataxis=None, spat1axis=None,
                                                taxis=None, paxis=None, plaxis=None,
                                                centeredh=True, nwins=None,
                                                nwin=None, nover=None, design=False,
                                                engine='numba', dottest=False,
                                                **kwargs_solver)
```

Seismic interpolation (or regularization).

Interpolate seismic data from irregular to regular spatial grid. Depending on the size of the input `data`, interpolation is either 2- or 3-dimensional. In case of 3-dimensional interpolation, data can be irregularly sampled in either one or both spatial directions.

Parameters

- data** [np.ndarray] Irregularly sampled seismic data of size $[n_{ry} (\times n_{rx} \times n_t)]$
- nrec** [int or tuple] Number of elements in the regularly sampled (reconstructed) spatial array, n_{Ry} for 2-dimensional data and (n_{Ry}, n_{Rx}) for 3-dimensional data
- iava** [list or numpy.ndarray] Integer (or floating) indices of locations of available samples in first dimension of regularly sampled spatial grid of interpolated signal. The `pylops.basicoperators.Restriction` operator is used in case of integer indices, while the `pylops.signalprocessing.Iterp` operator is used in case of floating indices.
- iava1** [list or numpy.ndarray, optional] Integer (or floating) indices of locations of available samples in second dimension of regularly sampled spatial grid of interpolated signal. Can be used only in case of 3-dimensional data.
- kind** [str, optional] Type of inversion: `fk` (default), `spatial`, `radon-linear`, `chirpradon-linear`, `radon-parabolic` or `radon-hyperbolic` and `sliding`
- nffts** [int or tuple, optional] `nffts` : tuple, optional Number of samples in Fourier Transform for each direction. Required if `kind='fk'`
- sampling** [tuple, optional] Sampling steps `dy` (, `dx`) and `dt`. Required if `kind='fk'` or `kind='radon-linear'`
- spataxis** [np.ndarray, optional] First spatial axis. Required for `kind='radon-linear'`, `kind='chirpradon-linear'`, `kind='radon-parabolic'`, `kind='radon-hyperbolic'`, can also be provided instead of `sampling` for `kind='fk'`
- spat1axis** [np.ndarray, optional] Second spatial axis. Required for `kind='radon-linear'`, `kind='chirpradon-linear'`, `kind='radon-parabolic'`, `kind='radon-hyperbolic'`, can also be provided instead of `sampling` for `kind='fk'`
- taxis** [np.ndarray, optional] Time axis. Required for `kind='radon-linear'`, `kind='chirpradon-linear'`, `kind='radon-parabolic'`, `kind='radon-hyperbolic'`, can also be provided instead of `sampling` for `kind='fk'`
- paxis** [np.ndarray, optional] First Radon axis. Required for `kind='radon-linear'`, `kind='chirpradon-linear'`, `kind='radon-parabolic'`,

`kind='radon-hyperbolic' and kind='sliding'`

plaxis [np.ndarray, optional] Second Radon axis. Required for `kind='radon-linear'`, `kind='chirpradon-linear'`, `kind='radon-parabolic'`, `kind='radon-hyperbolic'` and `kind='sliding'`

centeredh [bool, optional] Assume centered spatial axis (True) or not (False). Required for `kind='radon-linear'`, `kind='radon-parabolic'` and `kind='radon-hyperbolic'`

nwins [int or tuple, optional] Number of windows. Required for `kind='sliding'`

nwin [int or tuple, optional] Number of samples of window. Required for `kind='sliding'`

nover [int or tuple, optional] Number of samples of overlapping part of window. Required for `kind='sliding'`

design [bool, optional] Print number of sliding window (True) or not (False) when using `kind='sliding'`

engine [str, optional] Engine used for Radon computations (numpy/numba for Radon2D and Radon3D or numpy/fftw for ChirpRadon2D and ChirpRadon3D or)

dottest [bool, optional] Apply dot-test

****kwargs_solver** Arbitrary keyword arguments for `pylops.optimization.leastsquares.RegularizedInversion` solver if `kind='spatial'` or `pylops.optimization.sparsity.FISTA` solver otherwise

Returns

reccdata [np.ndarray] Reconstructed data of size $[n_{R_y} (\times n_{R_x} \times n_t)]$

recprec [np.ndarray] Reconstructed data in the sparse or preconditioned domain in case of `kind='fk'`, `kind='radon-linear'`, `kind='radon-parabolic'`, `kind='radon-hyperbolic'` and `kind='sliding'`

cost [np.ndarray] Cost function norm

Raises

KeyError If `kind` is neither `spatial`, `fl`, `radon-linear`, `radon-parabolic`, `radon-hyperbolic` nor `sliding`

Notes

The problem of seismic data interpolation (or regularization) can be formally written as

$$\mathbf{y} = \mathbf{R}\mathbf{x}$$

where a restriction or interpolation operator is applied along the spatial direction(s). Here $\mathbf{y} = [\mathbf{y}_{R1}^T, \mathbf{y}_{R2}^T, \dots, \mathbf{y}_{RNT}^T]^T$ where each vector \mathbf{y}_{Ri} contains all time samples recorded in the seismic data at the specific receiver R_i . Similarly, $\mathbf{x} = [\mathbf{x}_{r1}^T, \mathbf{x}_{r2}^T, \dots, \mathbf{x}_{rM}^T]^T$, contains all traces at the regularly and finely sampled receiver locations r_i .

Several alternative approaches can be taken to solve such a problem. They mostly differ in the choice of the regularization (or preconditioning) used to mitigate the ill-posedness of the problem:

- **spatial**: least-squares inversion in the original time-space domain with an additional spatial smoothing regularization term, corresponding to the cost function $J = ||\mathbf{y} - \mathbf{R}\mathbf{x}||_2 + \epsilon \nabla ||\mathbf{x}||_2$ where ∇ is a second order space derivative implemented via `pylops.basicoperators.SecondDerivative` in 2-dimensional case and `pylops.basicoperators.Laplacian` in 3-dimensional case
- **fk**: L1 inversion in frequency-wavenumber preconditioned domain corresponding to the cost function $J = ||\mathbf{y} - \mathbf{R}\mathbf{F}\mathbf{x}||_2$ where \mathbf{F} is frequency-wavenumber transform implemented via `pylops.signalprocessing.FFT2D` in 2-dimensional case and `pylops.signalprocessing.FFTND` in 3-dimensional case
- **radon-linear**: L1 inversion in linear Radon preconditioned domain using the same cost function as **fk** but with \mathbf{F} being a Radon transform implemented via `pylops.signalprocessing.Radon2D` in 2-dimensional case and `pylops.signalprocessing.Radon3D` in 3-dimensional case
- **radon-parabolic**: L1 inversion in parabolic Radon preconditioned domain
- **radon-hyperbolic**: L1 inversion in hyperbolic Radon preconditioned domain
- **sliding**: L1 inversion in sliding-linear Radon preconditioned domain using the same cost function as **fk** but with \mathbf{F} being a sliding Radon transform implemented via `pylops.signalprocessing.Sliding2D` in 2-dimensional case and `pylops.signalprocessing.Sliding3D` in 3-dimensional case

Examples using `pylops.waveeqprocessing.SeismicInterpolation`

- 12. *Seismic regularization*

`pylops.waveeqprocessing.Deghosting`

`pylops.waveeqprocessing.Deghosting`(*p*, *nt*, *nr*, *dt*, *dr*, *vel*, *zrec*, *pd*=None, *win*=None, *npad*=(11, 11), *ntaper*=(11, 11), *restriction*=None, *sp-transf*=None, *solver*=<function lsqr>, *dottest*=False, *dtype*='complex128', ***kwargs_solver*)

Wavefield deghosting.

Apply seismic wavefield decomposition from single-component (pressure) data. This process is also generally referred to as model-based deghosting.

Parameters

- p** [np.ndarray] Pressure data of of size $[n_{r_x}(\times n_{r_y}) \times n_t]$ (or $[n_{r_{x,sub}}(\times n_{r_{y,sub}}) \times n_t]$ in case a restriction operator is provided. Note that $n_{r_{x,sub}}$ (and $n_{r_{y,sub}}$) must agree with the size of the output of this operator)
- nt** [int] Number of samples along the time axis
- nr** [int or tuple] Number of samples along the receiver axis (or axes)
- dt** [float] Sampling along the time axis
- dr** [float or tuple] Sampling along the receiver array of the separated pressure constituents
- vel** [float] Velocity along the receiver array (must be constant)
- zrec** [float] Depth of receiver array
- pd** [np.ndarray, optional] Direct arrival to be subtracted from *p*
- win** [np.ndarray, optional] Time window to be applied to *p* to remove the direct arrival (if *pd*=None)

ntaper [`float` or `tuple`, optional] Number of samples of taper applied to propagator to avoid edge effects

npad [`float` or `tuple`, optional] Number of samples of padding applied to propagator to avoid edge effects angle

restriction [`pylops.LinearOperator`, optional] Restriction operator

sptransf [`pylops.LinearOperator`, optional] Sparsifying operator

solver [`float`, optional] Function handle of solver to be used if `kind='inverse'`

dottest [`bool`, optional] Apply dot-test

dtype [`str`, optional] Type of elements in input array. If `None`, directly inferred from `p`

****kwargs_solver** Arbitrary keyword arguments for chosen `solver`

Returns

pup [`np.ndarray`] Up-going wavefield

pdown [`np.ndarray`] Down-going wavefield

Notes

Up- and down-going components of seismic data ($p^-(x, t)$ and $p^+(x, t)$) can be estimated from single-component data ($p(x, t)$) using a ghost model.

The basic idea is that of using a one-way propagator in the f-k domain (also referred to as ghost model) to predict the down-going field from the up-going one (excluded the direct arrival and its source ghost referred here to as $p_d(x, t)$):

$$p^+ - p_d = e^{-jk_z 2z_{rec}} p^-$$

where k_z is the vertical wavenumber and z_{rec} is the depth of the array of receivers

In a matrix form we can thus write the total wavefield as:

$$\mathbf{p} - \mathbf{p}_d = (\mathbf{I} + \Phi) \mathbf{p}^-$$

where Φ is one-way propagator implemented via the `pylops.waveeqprocessing.PhaseShift` operator.

Examples using `pylops.waveeqprocessing.Deghosting`

- 13. *Deghosting*

`pylops.waveeqprocessing.WavefieldDecomposition`

`pylops.waveeqprocessing.WavefieldDecomposition` (`p`, `vz`, `nt`, `nr`, `dt`, `dr`, `rho`, `vel`, `nffts`=(`None`, `None`, `None`), `critical`=100.0, `ntaper`=10, `scaling`=1.0, `kind`='inverse', `restriction`=`None`, `sptransf`=`None`, `solver`=<function `lsqr`>, `dottest`=`False`, `dtype`='complex128', ****kwargs_solver**)

Up-down wavefield decomposition.

Apply seismic wavefield decomposition from multi-component (pressure and vertical particle velocity) data. This process is also generally referred to as data-based deghosting.

Parameters

- p** [np.ndarray] Pressure data of size $[n_{r_x} (\times n_{r_y}) \times n_t]$ (or $[n_{r_x, sub} (\times n_{r_y, sub}) \times n_t]$ in case a restriction operator is provided. Note that $n_{r_x, sub}$ (and $n_{r_y, sub}$) must agree with the size of the output of this operator)
- vz** [np.ndarray] Vertical particle velocity data of same size as pressure data
- nt** [int] Number of samples along the time axis
- nr** [int or tuple] Number of samples along the receiver axis (or axes)
- dt** [float] Sampling along the time axis
- dr** [float or tuple] Sampling along the receiver array (or axes)
- rho** [float] Density along the receiver array (must be constant)
- vel** [float] Velocity along the receiver array (must be constant)
- nffts** [tuple, optional] Number of samples along the wavenumber and frequency axes
- critical** [float, optional] Percentage of angles to retain in obliquity factor. For example, if critical=100 only angles below the critical angle $\frac{f(k_x)}{v}$ will be retained
- ntaper** [float, optional] Number of samples of taper applied to obliquity factor around critical angle
- kind** [str, optional] Type of separation: inverse (default) or analytical
- scaling** [float, optional] Scaling to apply to the operator (see Notes of `pylops.waveeqprocessing.wavedecomposition.UpDownComposition2D` for more details)
- restriction** [`pylops.LinearOperator`, optional] Restriction operator
- sptransf** [`pylops.LinearOperator`, optional] Sparsifying operator
- solver** [float, optional] Function handle of solver to be used if kind='inverse'
- dottest** [bool, optional] Apply dot-test
- dtype** [str, optional] Type of elements in input array.
- **kwargs_solver** Arbitrary keyword arguments for chosen solver

Returns

- pup** [np.ndarray] Up-going wavefield
- pdown** [np.ndarray] Down-going wavefield

Raises

- KeyError** If kind is neither analytical nor inverse

Notes

Up- and down-going components of seismic data ($p^-(x, t)$ and $p^+(x, t)$) can be estimated from multi-component data ($p(x, t)$ and $v_z(x, t)$) by computing the following expression [1]:

$$\begin{bmatrix} \mathbf{p}^+(k_x, \omega) \\ \mathbf{p}^-(k_x, \omega) \end{bmatrix} = \frac{1}{2} \begin{bmatrix} 1 & \frac{\omega \rho}{k_z} \\ 1 & -\frac{\omega \rho}{k_z} \end{bmatrix} \begin{bmatrix} \mathbf{p}(k_x, \omega) \\ \mathbf{v}_z(k_x, \omega) \end{bmatrix}$$

if kind='analytical' or alternatively by solving the equation in `ptcpy.waveeqprocessing.UpDownComposition2D` as an inverse problem, if kind='inverse'.

The latter approach has several advantages as data regularization can be included as part of the separation process allowing the input data to be aliased. This is obtained by solving the following problem:

$$\begin{bmatrix} \mathbf{p} \\ s * \mathbf{v}_z \end{bmatrix} = \begin{bmatrix} \mathbf{R}\mathbf{F} & 0 \\ 0 & s * \mathbf{R}\mathbf{F} \end{bmatrix} \mathbf{W} \begin{bmatrix} \mathbf{F}^H \mathbf{S} & 0 \\ 0 & \mathbf{F}^H \mathbf{S} \end{bmatrix} \mathbf{p}^\pm$$

where \mathbf{R} is a `ptcpy.basicoperators.Restriction` operator and \mathbf{S} is sparsifying transform operator (e.g., `ptcpy.signalprocessing.Radon2D`).

Examples using `pylops.waveeqprocessing.WavefieldDecomposition`

- 14. Seismic wavefield decomposition

`pylops.waveeqprocessing.MDD`

```
pylops.waveeqprocessing.MDD(G, d, dt=0.004, dr=1.0, nfmax=None, wav=None,
                             twosided=True, causality_precond=False, adjoint=False, psf=False,
                             dtype='float64', dottest=False, saveGt=True, add_negative=True,
                             smooth_precond=0, **kwargs_solver)
```

Multi-dimensional deconvolution.

Solve multi-dimensional deconvolution problem using `scipy.sparse.linalg.lsqr` iterative solver.

Parameters

- G** [`numpy.ndarray`] Multi-dimensional convolution kernel in time domain of size $[n_s \times n_r \times n_t]$ for `twosided=False` or `twosided=True` and `add_negative=True` (with only positive times) or size $[n_s \times n_r \times 2 * n_t - 1]$ for `twosided=True` and `add_negative=False` (with both positive and negative times)
- d** [`numpy.ndarray`] Data in time domain $[n_s(\times n_{vs}) \times n_t]$ if `twosided=False` or `twosided=True` and `add_negative=True` (with only positive times) or size $[n_s(\times n_{vs}) \times 2 * n_t - 1]$ if `twosided=True`
- dt** [`float`, optional] Sampling of time integration axis
- dr** [`float`, optional] Sampling of receiver integration axis
- nfmax** [`int`, optional] Index of max frequency to include in deconvolution process
- wav** [`numpy.ndarray`, optional] Wavelet to convolve to the inverted model and `psf` (must be centered around its index in the middle of the array). If `None`, the outputs of the inversion are returned directly.
- twosided** [`bool`, optional] MDC operator and data both negative and positive time (`True`) or only positive (`False`)
- add_negative** [`bool`, optional] Add negative side to MDC operator and data (`True`) or not (`False`)- operator and data are already provided with both positive and negative sides. To be used only with `twosided=True`.
- causality_precond** [`bool`, optional] Apply causality mask (`True`) or not (`False`)
- smooth_precond** [`int`, optional] Length of smoothing to apply to causality preconditioner
- adjoint** [`bool`, optional] Compute and return adjoint(s)
- psf** [`bool`, optional] Compute and return Point Spread Function (PSF) and its inverse
- dtype** [`bool`, optional] Type of elements in input array.

dottest [bool, optional] Apply dot-test

saveGt [bool, optional] Save G and G^H to speed up the computation of adjoint of `pylops.signalprocessing.Fredholm1` (True) or create G^H on-the-fly (False) Note that `saveGt=True` will be faster but double the amount of required memory

****kwargs_solver** Arbitrary keyword arguments for chosen solver (`scipy.sparse.linalg.cg` and `pylops.optimization.solver.cg` are used as default for numpy and cupy data, respectively)

Returns

minv [numpy.ndarray] Inverted model of size $[n_r(\times n_{vs}) \times n_t]$ for `twosided=False` or $[n_r(\times n_{vs}) \times 2 * n_t - 1]$ for `twosided=True`

madj [numpy.ndarray] Adjoint model of size $[n_r(\times n_{vs}) \times n_t]$ for `twosided=False` or $[n_r(\times n_{vs}) \times 2 * n_t - 1]$ for `twosided=True`

psfinv [numpy.ndarray] Inverted psf of size $[n_r \times n_r \times n_t]$ for `twosided=False` or $[n_r \times n_r \times 2 * n_t - 1]$ for `twosided=True`

psfadj [numpy.ndarray] Adjoint psf of size $[n_r \times n_r \times n_t]$ for `twosided=False` or $[n_r \times n_r \times 2 * n_t - 1]$ for `twosided=True`

See also:

[MDC](#) Multi-dimensional convolution

Notes

Multi-dimensional deconvolution (MDD) is a mathematical ill-solved problem, well-known in the image processing and geophysical community [1].

MDD aims at removing the effects of a Multi-dimensional Convolution (MDC) kernel or the so-called blurring operator or point-spread function (PSF) from a given data. It can be written as

$$\mathbf{d} = \mathbf{D}\mathbf{m}$$

or, equivalently, by means of its normal equation

$$\mathbf{m} = (\mathbf{D}^H \mathbf{D})^{-1} \mathbf{D}^H \mathbf{d}$$

where $\mathbf{D}^H \mathbf{D}$ is the PSF.

Examples using `pylops.waveeqprocessing.MDD`

- [09. Multi-Dimensional Deconvolution](#)

`pylops.waveeqprocessing.Marchenko`

```
class pylops.waveeqprocessing.Marchenko (R, Rl=None, dt=0.004, nt=None, dr=1.0, nf-  
max=None, wav=None, toff=0.0, nsmooth=10,  
dtype='float64', saveRt=True, prescaled=False)
```

Marchenko redatuming

Solve multi-dimensional Marchenko redatuming problem using `scipy.sparse.linalg.lsqr` iterative solver.

Parameters

- R** [`numpy.ndarray`] Multi-dimensional reflection response in time or frequency domain of size $[n_s \times n_r \times n_t / n_{fmax}]$. If provided in time, *R* should not be of complex type. Note that the reflection response should have already been multiplied by 2.
- R1** [`bool`, optional] *Deprecated*, will be removed in v2.0.0. Simply kept for back-compatibility with previous implementation
- dt** [`float`, optional] Sampling of time integration axis
- nt** [`float`, optional] Number of samples in time (not required if *R* is in time)
- dr** [`float`, optional] Sampling of receiver integration axis
- nfmax** [`int`, optional] Index of max frequency to include in deconvolution process
- wav** [`numpy.ndarray`, optional] Wavelet to apply to direct arrival when created using `trav`
- toff** [`float`, optional] Time-offset to apply to traveltimes
- nsmooth** [`int`, optional] Number of samples of smoothing operator to apply to window
- dtype** [`bool`, optional] Type of elements in input array.
- saveRt** [`bool`, optional] Save *R* and *R*^H to speed up the computation of adjoint of `pylops.signalprocessing.Fredholm1` (True) or create *R*^H on-the-fly (False) Note that `saveRt=True` will be faster but double the amount of required memory
- prescaled** [`bool`, optional] Apply scaling to *R* (False) or not (False) when performing spatial and temporal summations within the `pylops.waveeqprocessing.MDC` operator. In case `prescaled=True`, the *R* is assumed to have been pre-scaled by the user.

Raises

TypeError If *t* is not `numpy.ndarray`.

See also:

MDC Multi-dimensional convolution

MDD Multi-dimensional deconvolution

Notes

Marchenko redatuming is a method that allows to produce correct subsurface-to-surface responses given the availability of a reflection data and a macro-velocity model [1].

The Marchenko equations can be written in a compact matrix form [2] and solved by means of iterative solvers such as LSQR:

$$\begin{bmatrix} \Theta \mathbf{R} \mathbf{f}_d^+ \\ \mathbf{0} \end{bmatrix} = \mathbf{I} - \begin{bmatrix} \mathbf{0} & \Theta \mathbf{R} \\ \Theta \mathbf{R}^* & \mathbf{0} \end{bmatrix} \begin{bmatrix} \mathbf{f}^- \\ \mathbf{f}_m^+ \end{bmatrix}$$

Finally the subsurface Green's functions can be obtained applying the following operator to the retrieved focusing functions

$$\begin{bmatrix} -\mathbf{g}^- \\ \mathbf{g}^{+*} \end{bmatrix} = \mathbf{I} - \begin{bmatrix} \mathbf{0} & \mathbf{R} \\ \mathbf{R}^* & \mathbf{0} \end{bmatrix} \begin{bmatrix} \mathbf{f}^- \\ \mathbf{f}^+ \end{bmatrix}$$

Here **R** is the monopole-to-particle velocity seismic response (already multiplied by 2).

Attributes

ns [int] Number of samples along source axis

nr [int] Number of samples along receiver axis

shape [tuple] Operator shape

explicit [bool] Operator contains a matrix that can be solved explicitly (True) or not (False)

Methods

<code>__init__(R[, R1, dt, nt, dr, nfm, wav, ...])</code>	Initialize self.
<code>apply_multiplepoints(trav[, G0, nfft, rtm, ...])</code>	Marchenko redatuming for multiple points
<code>apply_onepoint(trav[, G0, nfft, rtm, ...])</code>	Marchenko redatuming for one point

apply_onepoint (*trav*, *G0=None*, *nfft=None*, *rtm=False*, *greens=False*, *dottest=False*, *fast=None*, *usematmul=False*, ***kwargs_solver*)
 Marchenko redatuming for one point

Solve the Marchenko redatuming inverse problem for a single point given its direct arrival traveltime curve (*trav*) and waveform (*G0*).

Parameters

trav [numpy.ndarray] Traveltime of first arrival from subsurface point to surface receivers of size $[n_r \times 1]$

G0 [numpy.ndarray, optional] Direct arrival in time domain of size $[n_r \times n_t]$ (if None, create arrival using *trav*)

nfft [int, optional] Number of samples in fft when creating the analytical direct wave

rtm [bool, optional] Compute and return rtm redatuming

greens [bool, optional] Compute and return Green's functions

dottest [bool, optional] Apply dot-test

fast [bool] *Deprecated*, will be removed in v2.0.0

usematmul [bool, optional] Use `numpy.matmul` (True) or for-loop with `numpy.dot` (False) in `pylops.signalprocessing.Fredholm1` operator. Refer to Fredholm1 documentation for details.

****kwargs_solver** Arbitrary keyword arguments for chosen solver (`scipy.sparse.linalg.lsqr` and `pylops.optimization.solver.cgls` are used as default for numpy and cupy *data*, respectively)

Returns

f1_inv_minus [numpy.ndarray] Inverted upgoing focusing function of size $[n_r \times n_t]$

f1_inv_plus [numpy.ndarray] Inverted downgoing focusing function of size $[n_r \times n_t]$

p0_minus [numpy.ndarray] Single-scattering standard redatuming upgoing Green's function of size $[n_r \times n_t]$

g_inv_minus [numpy.ndarray] Inverted upgoing Green's function of size $[n_r \times n_t]$

g_inv_plus [numpy.ndarray] Inverted downgoing Green's function of size $[n_r \times n_t]$

apply_multiplepoints (*trav*, *G0=None*, *nfft=None*, *rtm=False*, *greens=False*, *dottest=False*, *usematmul=False*, ***kwargs_solver*)

Marchenko redatuming for multiple points

Solve the Marchenko redatuming inverse problem for multiple points given their direct arrival traveltimes (*trav*) and waveforms (*G0*).

Parameters

trav [`numpy.ndarray`] Traveltime of first arrival from subsurface points to surface receivers of size $[n_r \times n_{vs}]$

G0 [`numpy.ndarray`, optional] Direct arrival in time domain of size $[n_r \times n_{vs} \times n_t]$ (if `None`, create arrival using *trav*)

nfft [`int`, optional] Number of samples in fft when creating the analytical direct wave

rtm [`bool`, optional] Compute and return rtm redatuming

greens [`bool`, optional] Compute and return Green's functions

dottest [`bool`, optional] Apply dot-test

usematmul [`bool`, optional] Use `numpy.matmul` (True) or for-loop with `numpy.dot` (False) in `pylops.signalprocessing.Fredholm1` operator. Refer to `Fredholm1` documentation for details.

****kwargs_solver** Arbitrary keyword arguments for chosen solver (`scipy.sparse.linalg.lsqr` and `pylops.optimization.solver.cgls` are used as default for `numpy` and `cupy` *data*, respectively)

Returns

f1_inv_minus [`numpy.ndarray`] Inverted upgoing focusing function of size $[n_r \times n_{vs} \times n_t]$

f1_inv_plus [`numpy.ndarray`] Inverted downgoing focusing function of size $[n_r \times n_{vs} \times n_t]$

p0_minus [`numpy.ndarray`] Single-scattering standard redatuming upgoing Green's function of size $[n_r \times n_{vs} \times n_t]$

g_inv_minus [`numpy.ndarray`] Inverted upgoing Green's function of size $[n_r \times n_{vs} \times n_t]$

g_inv_plus [`numpy.ndarray`] Inverted downgoing Green's function of size $[n_r \times n_{vs} \times n_t]$

Examples using `pylops.waveeqprocessing.Marchenko`

- 10. *Marchenko redatuming by inversion*

`pylops.waveeqprocessing.LSM`

class `pylops.waveeqprocessing.LSM` (*z*, *x*, *t*, *srcs*, *recs*, *vel*, *wav*, *wavcenter*, *y=None*, *mode='eikonal'*, *dottest=False*)

Least-squares Migration (LSM).

Solve seismic migration as inverse problem given smooth velocity model *vel* and an acquisition setup identified by sources (*src*) and receivers (*recs*)

Parameters

z [`numpy.ndarray`] Depth axis
x [`numpy.ndarray`] Spatial axis
t [`numpy.ndarray`] Time axis for data
srcs [`numpy.ndarray`] Sources in array of size $[2/3 \times n_s]$
recs [`numpy.ndarray`] Receivers in array of size $[2/3 \times n_r]$
vel [`numpy.ndarray` or `float`] Velocity model of size $[(n_y \times) n_x \times n_z]$ (or constant)
wav [`numpy.ndarray`] Wavelet
wavcenter [`int`] Index of wavelet center
y [`numpy.ndarray`] Additional spatial axis (for 3-dimensional problems)
mode [`numpy.ndarray`, optional] Computation mode (eikonal, analytic - only for constant velocity)
dottest [`bool`, optional] Apply dot-test

See also:

`pylops.waveeqprocessing.Demigration` Demigration operator

Notes

Inverting a demigration operator is generally referred in the literature as least-squares migration (LSM) as historically a least-squares cost function has been used for this purpose. In practice any other cost function could be used, for examples if `solver='pylops.optimization.sparsity.FISTA'` a sparse representation of reflectivity is produced as result of the inversion.

Finally, it is worth noting that in the first iteration of an iterative scheme aimed at inverting the demigration operator, a projection of the recorded data in the model domain is performed and an approximate (band-limited) image of the subsurface is created. This process is referred to in the literature as *migration*.

Attributes

Demop [`pylops.LinearOperator`] Demigration operator

Methods

<code>__init__(z, x, t, srcs, recs, vel, wav, ...)</code>	Initialize self.
<code>solve(d[, solver])</code>	Solve least-squares migration equations with chosen solver

solve (*d*, *solver*=<function lsqr>, ****kwargs_solver**)
 Solve least-squares migration equations with chosen solver

Parameters

d [`numpy.ndarray`] Input data of size $[n_s \times n_r \times n_t]$
solver [`func`, optional] Solver to be used for inversion
****kwargs_solver** Arbitrary keyword arguments for chosen solver

Returns

minv [np.ndarray] Inverted reflectivity model of size $[(n_y \times) n_x \times n_z]$

Examples using `pylops.waveeqprocessing.LSM`

- 15. *Least-squares migration*

Geophysical subsurface characterization

<code>poststack.PoststackInversion(data, wav[, ...])</code>	Post-stack linearized seismic inversion.
---	--

<code>prestack.PrestackInversion(data, theta, wav)</code>	Pre-stack linearized seismic inversion.
---	---

`pylops.avo.poststack.PoststackInversion`

`pylops.avo.poststack.PoststackInversion` (*data*, *wav*, *m0=None*, *explicit=False*, *simultaneous=False*, *epsI=None*, *epsR=None*, *dottest=False*, *epsRL1=None*, ***kwargs_solver*)

Post-stack linearized seismic inversion.

Invert post-stack seismic operator to retrieve an elastic parameter of choice from band-limited seismic post-stack data. Depending on the choice of input parameters, inversion can be trace-by-trace with explicit operator or global with either explicit or linear operator.

Parameters

data [np.ndarray] Band-limited seismic post-stack data of size $[n_{t0}(\times n_x \times n_y)]$

wav [np.ndarray] Wavelet in time domain (must have odd number of elements and centered to zero). If 1d, assume stationary wavelet for the entire time axis. If 2d of size $[n_{t0} \times n_h]$ use as non-stationary wavelet

m0 [np.ndarray, optional] Background model of size $[n_{t0}(\times n_x \times n_y)]$

explicit [bool, optional] Create a chained linear operator (False, preferred for large data) or a `MatrixMult` linear operator with dense matrix (True, preferred for small data)

simultaneous [bool, optional] Simultaneously invert entire data (True) or invert trace-by-trace (False) when using `explicit` operator (note that the entire data is always inverted when working with linear operator)

epsI [float, optional] Damping factor for Tikhonov regularization term

epsR [float, optional] Damping factor for additional Laplacian regularization term

dottest [bool, optional] Apply dot-test

epsRL1 [float, optional] Damping factor for additional blockiness regularization term

****kwargs_solver** Arbitrary keyword arguments for `scipy.linalg.lstsq` solver (if `explicit=True` and `epsR=None`) or `scipy.sparse.linalg.lsqr` solver (if `explicit=False` and/or `epsR` is not None)

Returns

minv [np.ndarray] Inverted model of size $[n_{t0}(\times n_x \times n_y)]$

datar [np.ndarray] Residual data (i.e., data - background data) of size $[n_{t0}(\times n_x \times n_y)]$

Notes

The cost function and solver used in the seismic post-stack inversion module depends on the choice of `explicit`, `simultaneous`, `epsI`, and `epsR` parameters:

- `explicit=True`, `epsI=None` and `epsR=None`: the explicit solver `scipy.linalg.lstsq` is used if `simultaneous=False` (or the iterative solver `scipy.sparse.linalg.lsqr` is used if `simultaneous=True`)
- `explicit=True` with `epsI` and `epsR=None`: the regularized normal equations $\mathbf{W}^T \mathbf{d} = (\mathbf{W}^T \mathbf{W} + \epsilon_I^2 \mathbf{I}) \mathbf{A} \mathbf{I}$ are instead fed into the `scipy.linalg.lstsq` solver if `simultaneous=False` (or the iterative solver `scipy.sparse.linalg.lsqr` if `simultaneous=True`)
- `explicit=False` and `epsR=None`: the iterative solver `scipy.sparse.linalg.lsqr` is used
- `explicit=False` with `epsR` and `epsRL1=None`: the iterative solver `pylops.optimization.leastsquares.RegularizedInversion` is used to solve the spatially regularized problem.
- `explicit=False` with `epsR` and `epsRL1`: the iterative solver `pylops.optimization.sparsity.SplitBregman` is used to solve the blockiness-promoting (in vertical direction) and spatially regularized (in additional horizontal directions) problem.

Note that the convergence of iterative solvers such as `scipy.sparse.linalg.lsqr` can be very slow for this type of operator. It is suggested to take a two steps approach with first a trace-by-trace inversion using the explicit operator, followed by a regularized global inversion using the outcome of the previous inversion as initial guess.

Examples using `pylops.avo.poststack.PoststackInversion`

- *07. Post-stack inversion*

`pylops.avo.prestack.PrestackInversion`

```
pylops.avo.prestack.PrestackInversion(data, theta, wav, m0=None, linearization='akirich',
                                     explicit=False, simultaneous=False, epsI=None,
                                     epsR=None, dottest=False, returnres=False,
                                     epsRL1=None, kind='centered', vsyp=0.5,
                                     **kwargs_solver)
```

Pre-stack linearized seismic inversion.

Invert pre-stack seismic operator to retrieve a set of elastic property profiles from band-limited seismic pre-stack data (i.e., angle gathers). Depending on the choice of input parameters, inversion can be trace-by-trace with explicit operator or global with either explicit or linear operator.

Parameters

data [np.ndarray] Band-limited seismic post-stack data of size $[(n_{lins} \times) n_{t0} \times n_{\theta} (\times n_x \times n_y)]$

theta [np.ndarray] Incident angles in degrees

wav [np.ndarray] Wavelet in time domain (must had odd number of elements and centered to zero)

m0 [np.ndarray, optional] Background model of size $[n_{t0} \times n_m (\times n_x \times n_y)]$

linearization [str or list, optional] choice of linearization, `akirich`: Aki-Richards, `fatti`: Fatti PS: PS or a combination of them (required only when `m0` is None).

explicit [`bool`, optional] Create a chained linear operator (`False`, preferred for large data) or a `MatrixMult` linear operator with dense matrix (`True`, preferred for small data)

simultaneous [`bool`, optional] Simultaneously invert entire data (`True`) or invert trace-by-trace (`False`) when using `explicit` operator (note that the entire data is always inverted when working with linear operator)

epsI [`float` or `list`, optional] Damping factor(s) for Tikhonov regularization term. If a list of n_m elements is provided, the regularization term will have different strenght for each elastic property

epsR [`float`, optional] Damping factor for additional Laplacian regularization term

dottest [`bool`, optional] Apply dot-test

returnres [`bool`, optional] Return residuals

epsRL1 [`float`, optional] Damping factor for additional blockiness regularization term

kind [`str`, optional] Derivative kind (`forward` or `centered`).

vsvp [`float` or `np.ndarray`] VS/VP ratio (constant or time/depth variant)

****kwargs_solver** Arbitrary keyword arguments for `scipy.linalg.lstsq` solver (if `explicit=True` and `epsR=None`) or `scipy.sparse.linalg.lsqr` solver (if `explicit=False` and/or `epsR` is not `None`)

Returns

minv [`np.ndarray`] Inverted model of size $[n_{t0} \times n_m (\times n_x \times n_y)]$

datar [`np.ndarray`] Residual data (i.e., data - background data) of size $[n_{t0} \times n_\theta (\times n_x \times n_y)]$

Notes

The different choices of cost functions and solvers used in the seismic pre-stack inversion module follow the same convention of the seismic post-stack inversion module.

Refer to `pylops.avo.poststack.PoststackInversion` for more details.

Examples using `pylops.avo.prestack.PrestackInversion`

- *08. Pre-stack (AVO) inversion*

3.8 PyLops Utilities

Alongside with its *Linear Operators* and *Solvers*, PyLops contains also a number of auxiliary routines performing universal tasks that are used by several operators or simply within one or more *Tutorials* for the preparation of input data and subsequent visualization of results.

3.8.1 Shared

Dot-test

<code>dottest(Op[, nr, nc, tol, complexflag, ...])</code>	Dot test.
---	-----------

pylops.utils.dottest

`pylops.utils.dottest` (*Op*, *nr=None*, *nc=None*, *tol=1e-06*, *complexflag=0*, *raiseerror=True*, *verb=False*, *backend='numpy'*)

Dot test.

Generate random vectors **u** and **v** and perform dot-test to verify the validity of forward and adjoint operators. This test can help to detect errors in the operator implementation.

Parameters

- Op** [*pylops.LinearOperator*] Linear operator to test.
- nr** [*int*] Number of rows of operator (i.e., elements in data)
- nc** [*int*] Number of columns of operator (i.e., elements in model)
- tol** [*float*, optional] Dottest tolerance
- complexflag** [*bool*, optional] generate random vectors with real (0) or complex numbers (1: only model, 2: only data, 3:both)
- raiseerror** [*bool*, optional] Raise error or simply return `False` when dottest fails
- verb** [*bool*, optional] Verbosity
- backend** [*str*, optional] Backend used for dot test computations (*numpy* or *cupy*). This parameter will be used to choose how to create the random vectors.

Raises

- ValueError** If dot-test is not verified within chosen tolerance.

Notes

A dot-test is mathematical tool used in the development of numerical linear operators.

More specifically, a correct implementation of forward and adjoint for a linear operator should verify the following *equality* within a numerical tolerance:

$$(\mathbf{Op} * \mathbf{u})^H * \mathbf{v} = \mathbf{u}^H * (\mathbf{Op}^H * \mathbf{v})$$

Examples using `pylops.utils.dottest`

- `sphx_glr_gallery_plot_seislet.py`
- *02. The Dot-Test*

Estimators

<code>trace_hutchinson(Op[, neval, batch_size, ...])</code>	Trace of linear operator using the Hutchinson method.
<code>trace_hutchpp(Op[, neval, sampler, backend])</code>	Trace of linear operator using the Hutch++ method.
<code>trace_nahutchpp(Op[, neval, sampler, cl, ...])</code>	Trace of linear operator using the NA-Hutch++ method.

pylops.utils.trace_hutchinson

`pylops.utils.trace_hutchinson` (*Op*, *neval=None*, *batch_size=None*, *sampler='rademacher'*,
backend='numpy')

Trace of linear operator using the Hutchinson method.

Returns an estimate of the trace of a linear operator using the Hutchinson method [1].

Parameters

neval [*int*, optional] Maximum number of matrix-vector products compute. Defaults to 10% of `shape[1]`.

batch_size [*int*, optional] Vectorize computations by sampling sketching matrices instead of vectors. Set this value to as high as permitted by memory, but there is no guarantee of speedup. Coerced to never exceed `neval`. When using **unitvector** as sampler, is coerced to not exceed `shape[1]`. Defaults to 100 or `neval`.

sampler [*str*, optional] Sample sketching matrices from the following distributions:

- **gaussian**: Mean zero, unit variance Gaussian.
- **rayleigh**: Sample from mean zero, unit variance Gaussian and normalize the columns.
- **rademacher**: Random sign.
- **unitvector**: Samples from the unit vectors \mathbf{e}_i without replacement.

backend [*str*, optional] Backend used to densify matrix (`numpy` or `cupy`). Note that this must be consistent with how the operator has been created.

Returns

trace [*self.dtype*] Operator trace.

Raises

ValueError If `neval` is smaller than 3.

NotImplementedError If the `sampler` is not one of the available samplers.

Notes

Let $m = \text{shape}[1]$ and $k = \text{neval}$. This algorithm estimates the trace via

$$\frac{1}{k} \sum_{i=1}^k \mathbf{z}_i^T \mathbf{O} \mathbf{p} \mathbf{z}_i$$

where vectors \mathbf{z}_i are sampled according to the sampling function. See [2] for a description of the variance and ϵ -approximation of different samplers.

Prefer the Rademacher sampler if the goal is to minimize variance, but the Gaussian for a better probability of approximating the correct value. Use the Unit Vector approach if you are sampling a large number of `neval` (compared to `shape[1]`), especially if the operator is highly-structured.

pylops.utils.trace_hutchpp

`pylops.utils.trace_hutchpp` (*Op*, *neval=None*, *sampler='rademacher'*, *backend='numpy'*)

Trace of linear operator using the Hutch++ method.

Returns an estimate of the trace of a linear operator using the Hutch++ method [1].

Parameters

neval [`int`, optional] Maximum number of matrix-vector products compute. Defaults to 10% of `shape[1]`.

sampler [`str`, optional] Sample sketching matrices from the following distributions:

- **gaussian**: Mean zero, unit variance Gaussian.
- **rayleigh**: Sample from mean zero, unit variance Gaussian and normalize the columns.
- **rademacher**: Random sign.

backend [`str`, optional] Backend used to densify matrix (`numpy` or `cupy`). Note that this must be consistent with how the operator has been created.

Returns

trace [`self.dtype`] Operator trace.

Raises

ValueError If `neval` is smaller than 3.

NotImplementedError If the `sampler` is not one of the available samplers.

Notes

This function follows Algorithm 1 of [1]. Let $m = \text{shape}[1]$ and $k = \text{neval}$.

1. Sample sketching matrices $\mathbf{S} \in \mathbb{R}^{m \times \lfloor k/3 \rfloor}$, and $\mathbf{G} \in \mathbb{R}^{m \times \lfloor k/3 \rfloor}$, from sub-Gaussian distributions.
2. Compute reduced QR decomposition of $\mathbf{O} \mathbf{p} \mathbf{S}$, retaining only \mathbf{Q} .
3. Return $\text{tr}(\mathbf{Q}^T \mathbf{O} \mathbf{p} \mathbf{Q}) + \frac{1}{\lfloor k/3 \rfloor} \text{tr}(\mathbf{G}^T (\mathbf{I} - \mathbf{Q} \mathbf{Q}^T) \mathbf{O} \mathbf{p} (\mathbf{I} - \mathbf{Q} \mathbf{Q}^T) \mathbf{G})$

Use the Rademacher sampler unless you know what you are doing.

pylops.utils.trace_nahutchpp

`pylops.utils.trace_nahutchpp` (*Op*, *neval=None*, *sampler='rademacher'*,
c1=0.16666666666666666, *c2=0.3333333333333333*, *backend='numpy'*)

Trace of linear operator using the NA-Hutch++ method.

Returns an estimate of the trace of a linear operator using the Non-Adaptive variant of Hutch++ method [1].

Parameters

neval [`int`, optional] Maximum number of matrix-vector products compute. Defaults to 10% of `shape[1]`.

sampler [`str`, optional] Sample sketching matrices from the following distributions:

- **gaussian**: Mean zero, unit variance Gaussian.
- **rayleigh**: Sample from mean zero, unit variance Gaussian and normalize the columns.
- **rademacher**: Random sign.

c1 [`float`, optional] Fraction of `neval` for sketching matrix \mathbf{S} .

c2 [`float`, optional] Fraction of `neval` for sketching matrix \mathbf{R} . Must be larger than `c2`, ideally by a factor of at least 2.

backend [`str`, optional] Backend used to densify matrix (`numpy` or `cupy`). Note that this must be consistent with how the operator has been created.

Returns

trace [`self.dtype`] Operator trace.

Raises

ValueError If `neval` not large enough to accomodate `c1` and `c2`.

NotImplementedError If the `sampler` is not one of the available samplers.

Notes

This function follows Algorithm 2 of [1]. Let $m = \text{shape}[1]$ and $k = \text{neval}$.

1. Fix constants c_1, c_2, c_3 such that $c_1 < c_2$ and $c_1 + c_2 + c_3 = 1$.
2. Sample sketching matrices $\mathbf{S} \in \mathbb{R}^{m \times c_1 k}$, $\mathbf{R} \in \mathbb{R}^{m \times c_2 k}$, and $\mathbf{G} \in \mathbb{R}^{m \times c_3 k}$ from sub-Gaussian distributions.
3. Compute $\mathbf{Z} = \mathbf{Op} \mathbf{R}$, $\mathbf{W} = \mathbf{Op} \mathbf{S}$, and $\mathbf{Y} = (\mathbf{S}^T \mathbf{Z})^+$, where $+$ denotes the Moore–Penrose inverse.
4. Return $\text{tr}(\mathbf{Y} \mathbf{W}^T \mathbf{Z}) + \frac{1}{c_3 k} [\text{tr}(\mathbf{G}^T \mathbf{Op} \mathbf{G}) - \text{tr}(\mathbf{G}^T \mathbf{Z} \mathbf{Y} \mathbf{W}^T \mathbf{G})]$

The default values for c_1 and c_2 are set to $1/6$ and $1/3$, respectively, but [1] suggests $1/4$ and $1/2$.

Use the Rademacher sampler unless you know what you are doing.

Scalability test

<code>scalability_test(Op, x[, workers, forward])</code>	Scalability test.
--	-------------------

pylops.utils.scalability_test

`pylops.utils.scalability_test` (*Op*, *x*, *workers*=[1, 2, 4], *forward*=True)
Scalability test.

Small auxiliary routine to test the performance of operators using `multiprocessing`. This helps identifying the maximum number of workers beyond which no performance gain is observed.

Parameters

Op [`pylops.LinearOperator`] Operator to test. It must allow for multiprocessing.

x [`numpy.ndarray`, optional] Input vector.

workers [`list`, optional] Number of workers to test out.

forward [`bool`, optional] Apply forward (True) or adjoint (False)

Returns

compute_times [`list`] Compute times as function of workers

speedup [`list`] Speedup as function of workers

Examples using `pylops.utils.scalability_test`

- `sphx_glr_gallery_plot_multiproc.py`

3.8.2 Others

Synthetics

<code>seismicevents.makeaxis(par)</code>	Create axes t, x, and y axes
<code>seismicevents.linear2d(x, t, v, t0, theta, ...)</code>	Linear 2D events
<code>seismicevents.parabolic2d(x, t, t0, px, pxx, ...)</code>	Parabolic 2D events
<code>seismicevents.hyperbolic2d(x, t, t0, vrms, ...)</code>	Hyperbolic 2D events
<code>seismicevents.linear3d(x, y, t, v, t0, ...)</code>	Linear 3D events
<code>seismicevents.hyperbolic3d(x, y, t, t0, ...)</code>	Hyperbolic 3D events

`pylops.utils.seismicevents.makeaxis`

`pylops.utils.seismicevents.makeaxis` (*par*)

Create axes t, x, and y axes

Create space and time axes from dictionary containing initial values (*ot, ox, oy*), sampling steps (*dt, dx, dy*) and number of elements (*nt, nx, ny*) for each axis

Parameters

par [dict] Dictionary containing initial values, sampling steps, and number of elements

Returns

t [numpy.ndarray] time axis

t2 [numpy.ndarray] double time axis (symmetric to zero)

x [numpy.ndarray] x axis

y [numpy.ndarray] y axis (None, if *oy, dy, ny* are not provided)

Examples

```
>>> par = {'ox':0, 'dx':2, 'nx':60,
>>>         'oy':0, 'dy':2, 'ny':100,
>>>         'ot':0, 'dt':4, 'nt':400}
>>> # Create axis
>>> t, t2, x, y = makeaxis(par)
```

Examples using `pylops.utils.seismicevents.makeaxis`

- `sphx_glr_gallery_plot_sliding.py`
- `sphx_glr_gallery_plot_patching.py`
- `sphx_glr_gallery_plot_chirpradon.py`

- sphx_glr_gallery_plot_mdc.py
- sphx_glr_gallery_plot_phaseshift.py
- sphx_glr_gallery_plot_seismicevents.py
- 09. *Multi-Dimensional Deconvolution*
- 11. *Radon filtering*
- 12. *Seismic regularization*
- 14. *Seismic wavefield decomposition*

pylops.utils.seismicevents.linear2d

pylops.utils.seismicevents.**linear2d**(*x, t, v, t0, theta, amp, wav*)

Linear 2D events

Create 2d linear events given propagation velocity, intercept time, angle, and amplitude of each event

Parameters

- x** [numpy.ndarray] space axis
- t** [numpy.ndarray] time axis
- v** [float] propagation velocity
- t0** [tuple or float] intercept time at $x = 0$ of each linear event
- theta** [tuple or float] angle (in degrees) of each linear event
- amp** [tuple or float] amplitude of each linear event
- wav** [numpy.ndarray] wavelet to be applied to data

Returns

- d** [numpy.ndarray] data without wavelet of size $[n_x \times n_t]$
- dwav** [numpy.ndarray] data with wavelet of size $[n_x \times n_t]$

Notes

Each event is created using the following relation:

$$t_i(x) = t_{0,i} + p_{x,i}x$$

where $p_{x,i} = \sin(\theta_i)/v$

Examples using pylops.utils.seismicevents.linear2d

- sphx_glr_gallery_plot_chirpradon.py
- sphx_glr_gallery_plot_seismicevents.py
- 11. *Radon filtering*
- 12. *Seismic regularization*

pylops.utils.seismicevents.parabolic2d

`pylops.utils.seismicevents.parabolic2d(x, t, t0, px, pxx, amp, wav)`

Parabolic 2D events

Create 2d parabolic events given intercept time, slowness, curvature, and amplitude of each event

Parameters

x [`numpy.ndarray`] space axis
t [`numpy.ndarray`] time axis
t0 [`tuple` or `float`] intercept time at $x = 0$ of each parabolic event
px [`tuple` or `float`] slowness of each parabolic event
pxx [`tuple` or `float`] curvature of each parabolic event
amp [`tuple` or `float`] amplitude of each parabolic event
wav [`numpy.ndarray`] wavelet to be applied to data

Returns

d [`numpy.ndarray`] data without wavelet of size $[n_x \times n_t]$
dwav [`numpy.ndarray`] data with wavelet of size $[n_x \times n_t]$

Notes

Each event is created using the following relation:

$$t_i(x) = t_{0,i} + p_{x,i}x + p_{xx,i}x^2$$

Examples using `pylops.utils.seismicevents.parabolic2d`

- `sphx_glr_gallery_plot_sliding.py`
- `sphx_glr_gallery_plot_patching.py`
- `sphx_glr_gallery_plot_seismicevents.py`
- *11. Radon filtering*

pylops.utils.seismicevents.hyperbolic2d

`pylops.utils.seismicevents.hyperbolic2d(x, t, t0, vrms, amp, wav)`

Hyperbolic 2D events

Create 2d hyperbolic events given intercept time, root-mean-square velocity, and amplitude of each event

Parameters

x [`numpy.ndarray`] space axis
t [`numpy.ndarray`] time axis
t0 [`tuple` or `float`] intercept time at $x = 0$ of each hyperbolic event
vrms [`tuple` or `float`] root-mean-square velocity of each hyperbolic event

amp [tuple or float] amplitude of each hyperbolic event

wav [numpy.ndarray] wavelet to be applied to data

Returns

d [numpy.ndarray] data without wavelet of size $[n_x \times n_t]$

dwav [numpy.ndarray] data with wavelet of size $[n_x \times n_t]$

Notes

Each event is created using the following relation:

$$t_i(x) = \sqrt{t_{0,i}^2 + x^2/v_{rms,i}^2}$$

Examples using `pylops.utils.seismicevents.hyperbolic2d`

- `sphx_glr_gallery_plot_mdc.py`
- `sphx_glr_gallery_plot_phaseshift.py`
- `sphx_glr_gallery_plot_seismicevents.py`
- *09. Multi-Dimensional Deconvolution*
- *14. Seismic wavefield decomposition*

`pylops.utils.seismicevents.linear3d`

`pylops.utils.seismicevents.linear3d(x, y, t, v, t0, theta, phi, amp, wav)`

Linear 3D events

Create 3d linear events given propagation velocity, intercept time, angles, and amplitude of each event.

Parameters

x [numpy.ndarray] space axis in x direction

y [numpy.ndarray] space axis in y direction

t [numpy.ndarray] time axis

v [float] propagation velocity

t0 [tuple or float] intercept time at $x = 0$ of each linear event

theta [tuple or float] angle in x direction (in degrees) of each linear event

phi [tuple or float] angle in y direction (in degrees) of each linear event

amp [tuple or float] amplitude of each linear event

wav [numpy.ndarray] wavelet to be applied to data

Returns

d [numpy.ndarray] data without wavelet of size $[n_y \times n_x \times n_t]$

dwav [numpy.ndarray] data with wavelet of size $[n_y \times n_x \times n_t]$

Notes

Each event is created using the following relation:

$$t_i(x, y) = t_{0,i} + p_{x,i}x + p_{y,i}y$$

where $p_{x,i} = \sin(\theta_i)\cos(\phi_i)/v$ and $p_{y,i} = \sin(\theta_i)\sin(\phi_i)/v$.

Examples using `pylops.utils.seismicevents.linear3d`

- `sphx_glr_gallery_plot_chirpradon.py`
- `sphx_glr_gallery_plot_seismicevents.py`

`pylops.utils.seismicevents.hyperbolic3d`

`pylops.utils.seismicevents.hyperbolic3d(x, y, t, t0, vrms_x, vrms_y, amp, wav)`
Hyperbolic 3D events

Create 3d hyperbolic events given intercept time, root-mean-square velocities, and amplitude of each event

Parameters

- x** [`numpy.ndarray`] space axis in x direction
- y** [`numpy.ndarray`] space axis in y direction
- t** [`numpy.ndarray`] time axis
- t0** [`tuple` or `float`] intercept time at $x = 0$ of each of hyperbolic event
- vrms_x** [`tuple` or `float`] root-mean-square velocity in x direction for each hyperbolic event
- vrms_y** [`tuple` or `float`] root-mean-square velocity in y direction for each hyperbolic event
- amp** [`tuple` or `float`] amplitude of each hyperbolic event
- wav** [`numpy.ndarray`] wavelet to be applied to data

Returns

- d** [`numpy.ndarray`] data without wavelet of size $[n_y \times n_x \times n_t]$
- dwav** [`numpy.ndarray`] data with wavelet of size $[n_y \times n_x \times n_t]$

Notes

Each event is created using the following relation:

$$t_i(x, y) = \sqrt{t_{0,i}^2 + x^2/v_{rmsx,i}^2 + y^2/v_{rmsy,i}^2}$$

Note that velocities do not have a physical meaning here (compared to the corresponding `pylops.utils.seismicevents.hyperbolic2d`), they rather simply control the curvature of the hyperboloid along the spatial axes.

Examples using `pylops.utils.seismicevents.hyperbolic3d`

- `sphx_glr_gallery_plot_sliding.py`
- `sphx_glr_gallery_plot_phaseshift.py`
- `sphx_glr_gallery_plot_seismicevents.py`

<code>marchenko.directwave(wav, trav, nt, dt[, ...])</code>	Analytical direct wave in acoustic media
---	--

`pylops.waveeqprocessing.marchenko.directwave`

`pylops.waveeqprocessing.marchenko.directwave` (*wav*, *trav*, *nt*, *dt*, *nfft=None*, *dist=None*, *kind='2d'*, *derivative=True*)

Analytical direct wave in acoustic media

Compute the analytical acoustic 2d or 3d Green's function in frequency domain given a wavelet *wav*, traveltime curve *trav* and distance *dist* (for 3d case only).

Parameters

wav [`numpy.ndarray`] Wavelet in time domain to apply to direct arrival when created using *trav*. Phase will be discarded resulting in a zero-phase wavelet with same amplitude spectrum as provided by *wav*

trav [`numpy.ndarray`] Traveltime of first arrival from subsurface point to surface receivers of size $[nr \times 1]$

nt [`float`, optional] Number of samples in time

dt [`float`, optional] Sampling in time

nfft [`int`, optional] Number of samples in fft time (if `None`, $nfft = nt$)

dist: :obj:'numpy.ndarray' Distance between subsurface point to surface receivers of size $[nr \times 1]$

kind [`str`, optional] 2-dimensional (2d) or 3-dimensional (3d)

derivative [`bool`, optional] Apply time derivative (`True`) or not (`False`)

Returns

direct [`numpy.ndarray`] Direct arrival in time domain of size $[nt \times nr]$

Notes

The analytical Green's function in 2D [1] is :

$$G^{2D}(\mathbf{r}) = -\frac{i}{4}H_0^{(1)}(k|\mathbf{r}|)$$

and in 3D [1] is:

$$G^{3D}(\mathbf{r}) = \frac{e^{-jk\mathbf{r}}}{4\pi\mathbf{r}}$$

Note that these Green's functions represent the acoustic response to a point source of volume injection. In case the response to a point source of volume injection rate is desired, a $j\omega$ scaling (which is equivalent to applying a first derivative in time domain) must be applied. Here this is accomplished by setting `derivative==True`.

Physical Sciences", Cambridge University Press, pp. 302, 2004.

Signal-processing

<code>signalprocessing.convmtx(h, n)</code>	Convolution matrix
<code>signalprocessing.nonstationary_convmtx(H, n)</code>	Convolution matrix from a bank of filters
<code>signalprocessing.slope_estimate(d, dz, dx[, ...])</code>	Local slope estimation

pylops.utils.signalprocessing.convmtx

`pylops.utils.signalprocessing.convmtx(h, n)`
Convolution matrix

Equivalent of [MATLAB's convmtx function](#). Makes a dense convolution matrix **C** such that the dot product `np.dot(C, x)` is the convolution of the filter h and the input signal x .

Parameters

- h** [np.ndarray] Convolution filter (1D array)
- n** [int] Number of columns (if $\text{len}(h) < n$) or rows (if $\text{len}(h) \geq n$) of convolution matrix

Returns

- C** [np.ndarray] Convolution matrix of size $\text{len}(h) + n - 1 \times n$ (if $\text{len}(h) < n$) or $n \times \text{len}(h) + n - 1$ (if $\text{len}(h) \geq n$)

pylops.utils.signalprocessing.nonstationary_convmtx

`pylops.utils.signalprocessing.nonstationary_convmtx(H, n, hc=0, pad=(0, 0))`
Convolution matrix from a bank of filters

Makes a dense convolution matrix **C** such that the dot product `np.dot(C, x)` is the nonstationary convolution of the bank of filters $H = [h_1, h_2, h_n]$ and the input signal x .

Parameters

- H** [np.ndarray] Convolution filters (2D array of shape $[n_{\text{filters}} \times n_h]$)
- n** [int] Number of columns of convolution matrix
- hc** [np.ndarray, optional] Index of center of first filter
- pad** [np.ndarray] Zero-padding to apply to the bank of filters before and after the provided values (use it to avoid wrap-around or pass filters with enough padding)

Returns

- C** [np.ndarray] Convolution matrix

pylops.utils.signalprocessing.slope_estimate

`pylops.utils.signalprocessing.slope_estimate(d, dz, dx, smooth=20)`
Local slope estimation

Local slopes are estimated using the *Structure Tensor* algorithm [1]. Note that slopes are returned as $\arctan(\theta)$ where θ is an angle defined in a RHS coordinate system with z axis pointing upward.

Parameters

- d** [np.ndarray] Input dataset of size $n_z \times n_x$
- dz** [float] Sampling in z-axis
- dx** [float] Sampling in x-axis
- smooth** [float, optional] Length of smoothing filter to be applied to the estimated gradients

Returns

- slopes** [np.ndarray] Estimated local slopes
- linearity** [np.ndarray] Estimated linearity

Notes

For each pixel of the input dataset **d** the local gradients $d\mathbf{d}/dz$ and $g_z = d\mathbf{d}/dx$ are computed and used to define the following three quantities: $g_{zz} = (d\mathbf{d}/dz)^2$, $g_{xx} = (d\mathbf{d}/dx)^2$, and $g_{zx} = d\mathbf{d}/dz * d\mathbf{d}/dx$. Such quantities are spatially smoothed and at each pixel their smoothed versions are arranged in a 2×2 matrix called the *smoothed gradient-square tensor*:

$$\mathbf{G} = \begin{bmatrix} g_{zz} & g_{zx} \\ g_{zx} & g_{xx} \end{bmatrix}$$

Local slopes can be expressed as $p = \arctan(\frac{\lambda_{max} - g_{xx}}{g_{zx}})$.

Examples using `pylops.utils.signalprocessing.slope_estimate`

- sphx_glr_gallery_plot_seislet.py
- sphx_glr_gallery_plot_slopeest.py

Tapers

<code>tapers.taper2d(nt, nmask, ntap[, tapertype])</code>	2D taper
<code>tapers.taper3d(nt, nmask, ntap[, tapertype])</code>	3D taper

`pylops.utils.tapers.taper2d`

`pylops.utils.tapers.taper2d(nt, nmask, ntap, tapertype='hanning')`
2D taper

Create 2d mask of size $[n_{mask} \times n_t]$ with tapering of size `ntap` along the first (and possibly second) dimensions

Parameters

- nt** [int] Number of samples along second dimension
- nmask** [int] Number of samples along first dimension
- ntap** [int or list] Number of samples of tapering at edges of first dimension (or both dimensions).
- tapertype** [str, optional] Type of taper (hanning, cosine, cosinesquare or None)

Returns

taper [numpy.ndarray] 2d mask with tapering along first dimension of size $[n_{mask} \times n_t]$

Examples using `pylops.utils.tapers.taper2d`

- sphx_glr_gallery_plot_phaseshift.py
- sphx_glr_gallery_plot_tapers.py

`pylops.utils.tapers.taper3d`

`pylops.utils.tapers.taper3d` (*nt*, *nmask*, *ntap*, *tapertype*='hanning')
3D taper

Create 2d mask of size $[n_{mask}[0] \times n_{mask}[1] \times n_t]$ with tapering of size *ntap* along the first and second dimension

Parameters

- nt** [int] Number of time samples of mask along third dimension
- nmask** [tuple] Number of space samples of mask along first dimension
- ntap** [tuple] Number of samples of tapering at edges of first dimension
- tapertype** [int] Type of taper (hanning, cosine, cosinesquare or None)

Returns

taper [numpy.ndarray] 2d mask with tapering along first dimension of size $[n_{mask,0} \times n_{mask,1} \times n_t]$

Examples using `pylops.utils.tapers.taper3d`

- sphx_glr_gallery_plot_mdc.py
- sphx_glr_gallery_plot_phaseshift.py
- sphx_glr_gallery_plot_tapers.py
- 09. Multi-Dimensional Deconvolution

Wavelets

<code>wavelets.ricker</code> (<i>t</i> , <i>f0</i>)	Ricker wavelet
<code>wavelets.gaussian</code> (<i>t</i> , <i>std</i>)	Gaussian wavelet

`pylops.utils.wavelets.ricker`

`pylops.utils.wavelets.ricker` (*t*, *f0*=10)
Ricker wavelet

Create a Ricker wavelet given time axis *t* and central frequency *f_0*

Parameters

- t** [numpy.ndarray] Time axis (positive part including zero sample)

f0 [`float`, optional] Central frequency

Returns

w [`numpy.ndarray`] Wavelet

t [`numpy.ndarray`] Symmetric time axis

wcenter [`int`] Index of center of wavelet

Examples using `pylops.utils.wavelets.ricker`

- `sphx_glr_gallery_plot_sliding.py`
- `sphx_glr_gallery_plot_patching.py`
- `sphx_glr_gallery_plot_avo.py`
- `sphx_glr_gallery_plot_chirpradon.py`
- `sphx_glr_gallery_plot_convolve.py`
- `sphx_glr_gallery_plot_ista.py`
- `sphx_glr_gallery_plot_mdc.py`
- `sphx_glr_gallery_plot_phaseshift.py`
- `sphx_glr_gallery_plot_prestack.py`
- `sphx_glr_gallery_plot_shift.py`
- `sphx_glr_gallery_plot_slopeest.py`
- `sphx_glr_gallery_plot_seismicevents.py`
- `sphx_glr_gallery_plot_wavest.py`
- *07. Post-stack inversion*
- *08. Pre-stack (AVO) inversion*
- *09. Multi-Dimensional Deconvolution*
- *11. Radon filtering*
- *12. Seismic regularization*
- *14. Seismic wavefield decomposition*
- *15. Least-squares migration*

`pylops.utils.wavelets.gaussian`

`pylops.utils.wavelets.gaussian` (*t*, *std=1*)

Gaussian wavelet

Create a Gaussian wavelet given time axis *t* and standard deviation *std* using `scipy.signal.windows.gaussian`.

Parameters

t [`numpy.ndarray`] Time axis (positive part including zero sample)

std [`float`, optional] Standard deviation of gaussian

Returns

w [numpy.ndarray] Wavelet

t [numpy.ndarray] Symmetric time axis

wcenter [int] Index of center of wavelet

Geophysical Reservoir characterization

<code>avo.zoeppritz_scattering(vp1, vs1, rho1, ...)</code>	Zoeppritz solution.
<code>avo.zoeppritz_element(vp1, vs1, rho1, vp0, ...)</code>	Single element of Zoeppritz solution.
<code>avo.zoeppritz_pp(vp1, vs1, rho1, vp0, vs0, ...)</code>	PP reflection coefficient from the Zoeppritz scattering matrix.
<code>avo.approx_zoeppritz_pp(vp1, vs1, rho1, vp0, ...)</code>	PP reflection coefficient from the approximate Zoeppritz equation.
<code>avo.akirichards(theta, vsvp[, n])</code>	Three terms Aki-Richards approximation.
<code>avo.fatti(theta, vsvp[, n])</code>	Three terms Fatti approximation.
<code>avo.ps(theta, vsvp[, n])</code>	PS reflection coefficient

pylops.avo.avo.zoeppritz_scattering

`pylops.avo.avo.zoeppritz_scattering(vp1, vs1, rho1, vp0, vs0, rho0, theta1)`
Zoeppritz solution.

Calculates the angle dependent p-wave reflectivity of an interface between two media for a set of incident angles.

Parameters

vp1 [float] P-wave velocity of the upper medium

vs1 [float] S-wave velocity of the upper medium

rho1 [float] Density of the upper medium

vp0 [float] P-wave velocity of the lower medium

vs0 [float] S-wave velocity of the lower medium

rho0 [float] Density of the lower medium

theta1 [np.ndarray or float] Incident angles in degrees

Returns

zoep [np.ndarray] 4×4 matrix representing the scattering matrix for the incident angle `theta1`

See also:

`zoeppritz_element` Single reflectivity element of Zoeppritz solution

`zoeppritz_pp` PP reflectivity element of Zoeppritz solution

pylops.avo.avo.zoeppritz_element

`pylops.avo.avo.zoeppritz_element` (*vp1*, *vs1*, *rho1*, *vp0*, *vs0*, *rho0*, *theta1*, *element*='PdPu')

Single element of Zoeppritz solution.

Simple wrapper to `pylops.avo.avo.scattering_matrix`, returning any mode reflection coefficient from the Zoeppritz scattering matrix for specific combination of incident and reflected wave and a set of incident angles

Parameters

vp1 [`float`] P-wave velocity of the upper medium

vs1 [`float`] S-wave velocity of the upper medium

rho1 [`float`] Density of the upper medium

vp0 [`float`] P-wave velocity of the lower medium

vs0 [`float`] S-wave velocity of the lower medium

rho0 [`float`] Density of the lower medium

theta1 [`np.ndarray` or `float`] Incident angles in degrees

element [`str`, optional] specific choice of incident and reflected wave combining any two of the following strings: Pd P-wave downgoing, Sd S-wave downgoing, Pu P-wave upgoing, Su S-wave upgoing (e.g., PdPu)

Returns

refl [`np.ndarray`] reflectivity values for all input angles for specific combination of incident and reflected wave.

See also:

[`zoeppritz_scattering`](#) Zoeppritz solution

[`zoeppritz_pp`](#) PP reflectivity element of Zoeppritz solution

pylops.avo.avo.zoeppritz_pp

`pylops.avo.avo.zoeppritz_pp` (*vp1*, *vs1*, *rho1*, *vp0*, *vs0*, *rho0*, *theta1*)

PP reflection coefficient from the Zoeppritz scattering matrix.

Simple wrapper to `pylops.avo.avo.scattering_matrix`, returning the PP reflection coefficient from the Zoeppritz scattering matrix for a set of incident angles

Parameters

vp1 [`float`] P-wave velocity of the upper medium

vs1 [`float`] S-wave velocity of the upper medium

rho1 [`float`] Density of the upper medium

vp0 [`float`] P-wave velocity of the lower medium

vs0 [`float`] S-wave velocity of the lower medium

rho0 [`float`] Density of the lower medium

theta1 [`np.ndarray` or `float`] Incident angles in degrees

Returns

PPrefl [np.ndarray] PP reflectivity values for all input angles.

See also:

[`zoeppritz_scattering`](#) Zoeppritz solution

[`zoeppritz_element`](#) Single reflectivity element of Zoeppritz solution

pylops.avo.avo.approx_zoeppritz_pp

`pylops.avo.avo.approx_zoeppritz_pp` (*vp1, vs1, rho1, vp0, vs0, rho0, theta1*)

PP reflection coefficient from the approximate Zoeppritz equation.

Approximate calculation of PP reflection from the Zoeppritz scattering matrix for a set of incident angles [1].

Parameters

vp1 [np.ndarray or list or tuple] P-wave velocity of the upper medium

vs1 [np.ndarray or list or tuple] S-wave velocity of the upper medium

rho1 [np.ndarray or list or tuple] Density of the upper medium

vp0 [np.ndarray or list or tuple] P-wave velocity of the lower medium

vs0 [np.ndarray or list or tuple] S-wave velocity of the lower medium

rho0 [np.ndarray or list or tuple] Density of the lower medium

theta1 [np.ndarray or float] Incident angles in degrees

Returns

PPrefl [np.ndarray] PP reflectivity values for all input angles.

See also:

[`zoeppritz_scattering`](#) Zoeppritz solution

[`zoeppritz_element`](#) Single reflectivity element of Zoeppritz solution

[`zoeppritz_pp`](#) PP reflectivity element of Zoeppritz solution

pylops.avo.avo.akirichards

`pylops.avo.avo.akirichards` (*theta, vsvp, n=1*)

Three terms Aki-Richards approximation.

Computes the coefficients of the of three terms Aki-Richards approximation for a set of angles and a constant or variable VS/VP ratio.

Parameters

theta [np.ndarray] Incident angles in degrees

vsvp [np.ndarray or float] VS/VP ratio

n [int, optional] number of samples (if vsvp is a scalare)

Returns

G1 [np.ndarray] first coefficient of three terms Aki-Richards approximation $[n_{\theta} \times n_{vsvp}]$

G2 [np.ndarray] second coefficient of three terms Aki-Richards approximation [$n_{theta} \times n_{vsvp}$]

G3 [np.ndarray] third coefficient of three terms Aki-Richards approximation [$n_{theta} \times n_{vsvp}$]

Notes

The three terms Aki-Richards approximation [1] is used to compute the reflection coefficient as linear combination of contrasts in V_P , V_S , and ρ . More specifically:

$$R(\theta) = G_1(\theta) \frac{\Delta V_P}{V_P} + G_2(\theta) \frac{\Delta V_S}{V_S} + G_3(\theta) \frac{\Delta \rho}{\bar{\rho}}$$

where $G_1(\theta) = \frac{1}{2\cos^2\theta}$, $G_2(\theta) = -4(V_S/V_P)^2 \sin^2\theta$, $G_3(\theta) = 0.5 - 2(V_S/V_P)^2 \sin^2\theta$, $\frac{\Delta V_P}{V_P} = 2 \frac{V_{P,2} - V_{P,1}}{V_{P,2} + V_{P,1}}$, $\frac{\Delta V_S}{V_S} = 2 \frac{V_{S,2} - V_{S,1}}{V_{S,2} + V_{S,1}}$, and $\frac{\Delta \rho}{\bar{\rho}} = 2 \frac{\rho_2 - \rho_1}{\rho_2 + \rho_1}$.

pylops.avo.avo.fatti

pylops.avo.avo.fatti(theta, vsvp, n=1)

Three terms Fatti approximation.

Computes the coefficients of the three terms Fatti approximation for a set of angles and a constant or variable VS/VP ratio.

Parameters

theta [np.ndarray] Incident angles in degrees

vsvp [np.ndarray or float] VS/VP ratio

n [int, optional] number of samples (if vsvp is a scalar)

Returns

G1 [np.ndarray] first coefficient of three terms Smith-Gidlow approximation [$n_{theta} \times n_{vsvp}$]

G2 [np.ndarray] second coefficient of three terms Smith-Gidlow approximation [$n_{theta} \times n_{vsvp}$]

G3 [np.ndarray] third coefficient of three terms Smith-Gidlow approximation [$n_{theta} \times n_{vsvp}$]

Notes

The three terms Fatti approximation [1] is used to compute the reflection coefficient as linear combination of contrasts in AI , SI , and ρ . More specifically:

$$R(\theta) = G_1(\theta) \frac{\Delta AI}{AI} + G_2(\theta) \frac{\Delta SI}{SI} + G_3(\theta) \frac{\Delta \rho}{\bar{\rho}}$$

where $G_1(\theta) = 0.5(1 + \tan^2\theta)$, $G_2(\theta) = -4(V_S/V_P)^2 \sin^2\theta$, $G_3(\theta) = 0.5(4(V_S/V_P)^2 \sin^2\theta - \tan^2\theta)$, $\frac{\Delta AI}{AI} = 2 \frac{AI_2 - AI_1}{AI_2 + AI_1}$, $\frac{\Delta SI}{SI} = 2 \frac{SI_2 - SI_1}{SI_2 + SI_1}$, $\frac{\Delta \rho}{\bar{\rho}} = 2 \frac{\rho_2 - \rho_1}{\rho_2 + \rho_1}$.

pylops.avo.avo.ps

`pylops.avo.avo.ps(theta, vsvp, n=1)`

PS reflection coefficient

Computes the coefficients for the PS approximation for a set of angles and a constant or variable VS/VP ratio.

Parameters

theta [np.ndarray] Incident angles in degrees

vsvp [np.ndarray or float] VS/VP ratio

n [int, optional] number of samples (if vsvp is a scalar)

Returns

G1 [np.ndarray] first coefficient for VP [$n_{theta} \times n_{vsvp}$]

G2 [np.ndarray] second coefficient for VS [$n_{theta} \times n_{vsvp}$]

G3 [np.ndarray] third coefficient for density [$n_{theta} \times n_{vsvp}$]

Notes

The approximation in [1] is used to compute the PS reflection coefficient as linear combination of contrasts in V_P , V_S , and ρ . More specifically:

$$R(\theta) = G_2(\theta) \frac{\Delta V_S}{\bar{V}_S} + G_3(\theta) \frac{\Delta \rho}{\bar{\rho}}$$

where $G_2(\theta) = \tan\theta/2[4(V_S/V_P)^2 \sin^2\theta - 4(V_S/V_P)\cos\theta\cos\phi]$, $G_3(\theta) = -\tan\theta/2[1 - 2(V_S/V_P)^2 \sin^2\theta + 2(V_S/V_P)\cos\theta\cos\phi]$, $\frac{\Delta V_S}{\bar{V}_S} = 2\frac{V_{S,2}-V_{S,1}}{V_{S,2}+V_{S,1}}$, and $\frac{\Delta \rho}{\bar{\rho}} = 2\frac{\rho_2-\rho_1}{\rho_2+\rho_1}$. Note that θ is the P-incidence angle whilst ϕ is the S-reflected angle which is computed using Snell's law and the average V_S/V_P ratio.

3.9 Implementing new operators

Users are welcome to create new operators and add them to the PyLops library.

In this tutorial, we will go through the key steps in the definition of an operator, using the `pylops.Diagonal` as an example. This is a very simple operator that applies a diagonal matrix to the model in forward mode and to the data in adjoint mode.

3.9.1 Creating the operator

The first thing we need to do is to create a new file with the name of the operator we would like to implement. Note that as the operator will be a class, we need to follow the UpperCaseCamelCase convention both for the class itself and for the filename.

Once we have created the file, we will start by importing the modules that will be needed by the operator. While this varies from operator to operator, you will always need to import the `pylops.LinearOperator` class, which will be used as *parent* class for any of our operators:

```
from pylops import LinearOperator
```

This class is a child of the `scipy.sparse.linalg.LinearOperator` class itself which implements the same methods of its parent class as well as an additional method for quick inversion: such method can be easily accessed by using `\` between the operator and the data (e.g., `A\y`).

After that we define our new object:

```
class Diagonal(LinearOperator):
```

followed by a `numpydoc` `docstring` (starting with `r"""` and ending with `"""`) containing the documentation of the operator. Such `docstring` should contain at least a short description of the operator, a `Parameters` section with a detailed description of the input parameters and a `Notes` section providing a mathematical explanation of the operator. Take a look at some of the core operators of PyLops to get a feeling of the level of details of the mathematical explanation.

We then need to create the `__init__` where the input parameters are passed and saved as members of our class. While the input parameters change from operator to operator, it is always required to create three members, the first called `shape` with a tuple containing the dimensions of the operator in the data and model space, the second called `dtype` with the data type object (`np.dtype`) of the model and data, and the third called `explicit` with a boolean (`True` or `False`) identifying if the operator can be inverted by a direct solver or requires an iterative solver. This member is `True` if the operator has also a member `A` that contains the matrix to be inverted like for example in the `pylops.MatrixMult` operator, and it will be `False` otherwise. In this case we have another member called `d` which is equal to the input vector containing the diagonal elements of the matrix we want to multiply to the model and data.

```
def __init__(self, d, dtype=None):
    self.d = d.flatten()
    self.shape = (len(self.d), len(self.d))
    self.dtype = np.dtype(dtype)
    self.explicit = False
```

We can then move onto writing the *forward mode* in the method `_matvec`. In other words, we will need to write the piece of code that will implement the following operation $y = Ax$. Such method is always composed of two inputs (the object itself `self` and the input model `x`). In our case the code to be added to the forward is very simple, we will just need to apply element-wise multiplication between the model `x` and the elements along the diagonal contained in the array `d`. We will finally need to `return` the result of this operation:

```
def _matvec(self, x):
    return self.d*x
```

Finally we need to implement the *adjoint mode* in the method `_rmatvec`. In other words, we will need to write the piece of code that will implement the following operation $x = A^H y$. Such method is also composed of two inputs (the object itself `self` and the input data `y`). In our case the code to be added to the forward is the same as the one from the forward (but this will obviously be different from operator to operator):

```
def _rmatvec(self, x):
    return self.d*x
```

And that's it, we have implemented our first linear operator!

3.9.2 Testing the operator

Being able to write an operator is not yet a guarantee of the fact that the operator is correct, or in other words that the adjoint code is actually the *adjoint* of the forward code. Luckily for us, a simple test can be performed to check the validity of forward and adjoint operators, the so called *dot-test*.

We can generate random vectors \mathbf{u} and \mathbf{v} and verify the the following *equality* within a numerical tolerance:

$$(\mathbf{A} * \mathbf{u})^H * \mathbf{v} = \mathbf{u}^H * (\mathbf{A}^H * \mathbf{v})$$

The method `pylops.utils.dottest` implements such a test for you, all you need to do is create a new test within an existing `test_*.py` file in the `pytests` folder (or in a new file).

Generally a test file will start with a number of dictionaries containing different parameters we would like to use in the testing of one or more operators. The test itself starts with a *decorator* that contains a list of all (or some) of dictionaries that will would like to use for our specific operator, followed by the definition of the test

```
@pytest.mark.parametrize("par", [(par1), (par2)])
def test_Diagonal(par):
```

At this point we can first of all create the operator and run the `pylops.utils.dottest` preceded by the `assert` command. Moreover, the forward and adjoint methods should tested towards expected outputs or even better, when the operator allows it (i.e., operator is invertible), a small inversion should be run and the inverted model tested towards the input model.

```
"""Dot-test and inversion for diagonal operator
"""
d = np.arange(par['nx']) + 1.

Dop = Diagonal(d)
assert dottest(Dop, par['nx'], par['nx'],
               complexflag=0 if par['imag'] == 1 else 3)

x = np.ones(par['nx'])
xlsqr = lsqr(Dop, Dop * x, damp=1e-20, iter_lim=300, show=0)[0]
assert_array_almost_equal(x, xlsqr, decimal=4)
```

3.9.3 Documenting the operator

Once the operator has been created, we can add it to the documentation of PyLops. To do so, simply add the name of the operator within the `index.rst` file in `docs/source/api` directory.

Moreover, in order to facilitate the user of your operator by other users, a simple example should be provided as part of the Sphinx-gallery of the documentation of the PyLops library. The directory `examples` contains several scripts that can be used as template.

3.9.4 Final checklist

Before submitting your new operator for review, use the following **checklist** to ensure that your code adheres to the guidelines of PyLops:

- you have created a new file containing a single class (or a function when the new operator is a simple combination of existing operators - see `pylops.Laplacian` for an example of such operator) and added to a new or existing directory within the `pylops` package.
- the new class contains at least `__init__`, `_matvec` and `_matvec` methods.
- the new class (or function) has a `numpydoc docstring` documenting at least the input `Parameters` and with a `Notes` section providing a mathematical explanation of the operator
- a new test has been added to an existing `test_*.py` file within the `pytests` folder. The test should verify that the new operator passes the `pylops.utils.dottest`. Moreover it is advisable to create a small toy

example where the operator is applied in forward mode and the resulting data is inverted using `\` from `pylops.LinearOperator`.

- the new operator is used within at least one *example* (in `examples` directory) or one *tutorial* (in `tutorials` directory).

3.10 Contributing

Contributions are welcome and greatly appreciated!

The best way to get in touch with the core developers and maintainers is to join the [PyLops slack channel](#) as well as open new *Issues* directly from the [github repo](#).

Moreover, take a look at the [Roadmap](#) page for a list of current ideas for improvements and additions to the PyLops library.

3.10.1 Types of Contributions

Report Bugs

Report bugs at <https://github.com/PyLops/pylops/issues>.

If you are playing with the PyLops library and find a bug, please report it including:

- Your operating system name and version.
- Any details about your Python environment.
- Detailed steps to reproduce the bug.

Propose New Operators or Features

Open an issue at <https://github.com/PyLops/pylops/issues> with tag *enhancement*.

If you are proposing a new operator or a new feature:

- Explain in detail how it should work.
- Keep the scope as narrow as possible, to make it easier to implement.

Implement Operators or Features

Look through the Git issues for operator or feature requests. Anything tagged with *enhancement* is open to whoever wants to implement it.

Add Examples or improve Documentation

Writing new operators is not the only way to get involved and contribute. Create examples with existing operators as well as improving the documentation of existing operators is as important as making new operators and very much encouraged.

3.10.2 Getting Started to contribute

Ready to contribute?

1. Fork the *PyLops* repo.
2. Clone your fork locally:

```
>> git clone https://github.com/your_name_here/pylops.git
```

3. Follow the installation instructions for *developers* that you find in *Installation* page. Ensure that you are able to *pass all the tests before moving forward*.
4. Add the main repository to the list of your remotes (this will be important to ensure you pull the latest changes before trying to merge your local changes):

```
>> git remote add upstream https://github.com/equinor/pylops
```

5. Create a branch for local development:

```
>> git checkout -b name-of-your-branch
```

Now you can make your changes locally.

6. When you're done making changes, check that your code follows the guidelines for *Implementing new operators* and that the both old and new tests pass successfully:

```
>> make tests
```

7. Commit your changes and push your branch to GitLab:

```
>> git add .  
>> git commit -m "Your detailed description of your changes."  
>> git push origin name-of-your-branch
```

Remember to add `-u` when pushing the branch for the first time.

8. Submit a pull request through the GitHub website.

3.10.3 Pull Request Guidelines

Before you submit a pull request, check that it meets these guidelines:

1. The pull request should include new tests for all the core routines that have been developed.
2. If the pull request adds functionality, the docs should be updated accordingly.
3. Ensure that the updated code passes all tests.

3.11 Changelog

3.11.1 Version 1.16.0

Released on: 11/12/2021

- Added *pylops.utils.estimators* module for trace estimation

- Added `x0` in `pylops.optimization.sparsity.ISTA` and `pylops.optimization.sparsity.FISTA` to handle non-zero initial guess
- Modified `pylops.optimization.sparsity.ISTA` and `pylops.optimization.sparsity.FISTA` to handle multiple right hand sides
- Modified creation of `haxis` in `pylops.signalprocessing.Radon2D` and `pylops.signalprocessing.Radon3D` to allow for uncentered spatial axes
- Fixed `_rmatvec` for explicit in `pylops.LinearOperator._ColumnLinearOperator`

3.11.2 Version 1.15.0

Released on: 23/10/2021

- Added `pylops.signalprocessing.Shift` operator.
- Added option to choose derivative kind in `pylops.avo.poststack.PoststackInversion` and `pylops.avo.prestack.PrestackInversion`.
- Improved efficiency of adjoint of `pylops.signalprocessing.Fredholm1` by applying complex conjugation to the vectors.
- Added `vsvp` to `pylops.avo.prestack.PrestackInversion` allowing to use user defined VS/VP ratio.
- Added `kind` to `pylops.basicoperators.CausalIntegration` allowing full, half, or trapezoidal integration.
- Fixed `_hardthreshold_percentile` in `pylops.optimization.sparsity` - [Issue #249](#).
- Fixed `r2norm` in `pylops.optimization.solver.cgls`.

3.11.3 Version 1.14.0

Released on: 09/07/2021

- Added `pylops.optimization.solver.lsqr` solver
- Added utility routine `pylops.utils.scalability_test` for scalability tests when using multiprocessing
- Added `pylops.avo.avo.ps` AVO modelling option and restructured `pylops.avo.prestack.PrestackLinearModelling` to allow passing any function handle that can perform AVO modelling apart from those directly available
- Added R-linear operators (when setting the property `clinear=False` of a linear operator). `pylops.basicoperators.Real`, `pylops.basicoperators.Imag`, and `pylops.basicoperators.Conj`
- Added possibility to run operators `pylops.basicoperators.HStack`, `pylops.basicoperators.VStack`, `pylops.basicoperators.Block`, `pylops.basicoperators.BlockDiag`, and `pylops.signalprocessing.Sliding3D` using multiprocessing
- Added `dtype` to vector `X` when using `scipy.sparse.linalg.lobpcg` in `eigs` method of `pylops.LinearOperator`
- Use `kind=forward` for FirstDerivative in `pylops.avo.poststack.PoststackInversion` inversion when dealing with L1 regularized inversion as it makes the inverse problem more stable (no ringing in solution)
- Changed `cost` in `pylops.optimization.solver.cg` and `pylops.optimization.solver.cgls` to be L2 norms of residuals

- Fixed `pylops.utils.dottest.dottest` for imaginary vectors and to ensure u and v vectors are of same dtype of the operator

3.11.4 Version 1.13.0

Released on: 26/03/2021

- Added `pylops.signalprocessing.Sliding1D` and `pylops.signalprocessing.Patch2D` operators
- Added `pylops.basicoperators.MemoizeOperator` operator
- Added decay and analysis option in `pylops.optimization.sparsity.ISTA` and `pylops.optimization.sparsity.FISTA` solvers
- Added `toreal` and `toimag` methods to `pylops.LinearOperator`
- Make `nr` and `nc` optional in `pylops.utils.dottest.dottest`
- Fixed complex check in `pylops.basicoperators.MatrixMult` when working with complex-valued cupy arrays
- Fixed bug in data reshaping in check in `pylops.avo.prestack.PrestackInversion`
- Fixed loading error when using old cupy and/or cusignal (see [Issue #201](#))

3.11.5 Version 1.12.0

Released on: 22/11/2020

- Modified all operators and solvers to work with cupy arrays
- Added `eigs` and `solver` submodules to `pylops.optimization`
- Added `deps` and `backend` submodules to `pylops.utils`
- Fixed bug in `pylops.signalprocessing.Convolve2D` and `pylops.signalprocessing.ConvolveND` when dealing with filters that have less dimensions than the input vector.

3.11.6 Version 1.11.1

Released on: 24/10/2020

- Fixed import of `pyfttw` when not available in `py:class:“pylops.signalprocessing.ChirpRadon3D”`

3.11.7 Version 1.11.0

Released on: 24/10/2020

- Added `pylops.signalprocessing.ChirpRadon2D` and `pylops.signalprocessing.ChirpRadon3D` operators.
- Fixed bug in the inferred dimensions for regularization data creation in `pylops.optimization.leastsquares.NormalEquationsInversion`, `pylops.optimization.leastsquares.RegularizedInversion`, and `pylops.optimization.sparsity.SplitBregman`.
- Changed dtype of `pylops.HStack` to allow automatic inference from dtypes of input operator.

- Modified dtype of `pylops.waveeqprocessing.Marchenko` operator to ensure that outputs of forward and adjoint are real arrays.
- Reverted to previous complex-friendly implementation of `pylops.optimization.sparsity._softthreshold` to avoid division by 0.

3.11.8 Version 1.10.0

Released on: 13/08/2020

- Added `tosparse` method to `pylops.LinearOperator`.
- Added `kind=linear` in `pylops.signalprocessing.Seislet` operator.
- Added `kind` to `pylops.FirstDerivative` operator to perform forward and backward (as well as centered) derivatives.
- Added `kind` to `pylops.optimization.sparsity.IRLS` solver to choose between data or model sparsity.
- Added possibility to use `scipy.sparse.linalg.lobpcg` in `pylops.LinearOperator.eigs` and `pylops.LinearOperator.cond`
- Added possibility to use `scipy.signal.oaconvolve` in `pylops.signalprocessing.Convolve1D`.
- Added `NRegs` to `pylops.optimization.leastsquares.NormalEquationsInversion` to allow providing regularization terms directly in the form of $H^T H$.

3.11.9 Version 1.9.1

Released on: 25/05/2020

- Changed internal behaviour of `pylops.sparsity.OMP` when `niter_inner=0`. Automatically reverts to Matching Pursuit algorithm.
- Changed handling of dtype in `pylops.signalprocessing.FFT` and `pylops.signalprocessing.FFT2D` to ensure that the type of the input vector is retained when applying forward and adjoint.
- Added `dtype` parameter to the FFT calls in the definition of the `pylops.waveeqprocessing.MDD` operation. This ensure that the type of the real part of `G` input is enforced to the output vectors of the forward and adjoint operations.

3.11.10 Version 1.9.0

Released on: 13/04/2020

- Added `pylops.waveeqprocessing.Deghosting` and `pylops.signalprocessing.Seislet` operators
- Added hard and half thresholds in `pylops.optimization.sparsity.ISTA` and `pylops.optimization.sparsity.FISTA` solvers
- Added prescaled input parameter to `pylops.waveeqprocessing.MDC` and `pylops.waveeqprocessing.Marchenko`
- Added sinc interpolation to `pylops.signalprocessing.Interp(kind == 'sinc')`

- Modified `pylops.waveeqprocessing.marchenko.directwave` to model analytical responses from both sources of volume injection (`derivative=False`) and source of volume injection rate (`derivative=True`)
- Added `pylops.LinearOperator.asoperator` method to `pylops.LinearOperator`
- Added `pylops.utils.signalprocessing.slope_estimate` function
- Fix bug in `pylops.signalprocessing.Radon2D` and `pylops.signalprocessing.Radon3D` when `onthe-fly=True` returning the same result as when `onthe-fly=False`

3.11.11 Version 1.8.0

Released on: 12/01/2020

- Added `pylops.LinearOperator.todense` method to `pylops.LinearOperator`
- Added `pylops.signalprocessing.Bilinear`, `pylops.signalprocessing.DWT`, and `pylops.signalprocessing.DWT2` operators
- Added `pylops.waveeqprocessing.PressureToVelocity`, `pylops.waveeqprocessing.UpDownComposition3Doperator`, and `pylops.waveeqprocessing.PhaseShift` operators
- Fix bug in `pylops.basicoperators.Kronecker` (see [Issue #125](#))

3.11.12 Version 1.7.0

Released on: 10/11/2019

- Added `pylops.Gradient`, `pylops.Sum`, `pylops.FirstDirectionalDerivative`, and `pylops.SecondDirectionalDerivative` operators
- Added `pylops.LinearOperator._ColumnLinearOperator` private operator
- Added possibility to directly mix Linear operators and numpy/scipy 2d arrays in `pylops.VStack` and `pylops.HStack` and `pylops.BlockDiag` operators
- Added `pylops.optimization.sparsity.OMP` solver

3.11.13 Version 1.6.0

Released on: 10/08/2019

- Added `pylops.signalprocessing.ConvolveND` operator
- Added `pylops.utils.signalprocessing.nonstationary_convmtx` to create matrix for non-stationary convolution
- Added possibility to perform seismic modelling (and inversion) with non-stationary wavelet in `pylops.avo.poststack.PoststackLinearModelling`
- Create private methods for `pylops.Block`, `pylops.avo.poststack.PoststackLinearModelling`, `pylops.waveeqprocessing.MDC` to allow calling different operators (e.g., from `pylops-distributed` or `pylops-gpu`) within the method

3.11.14 Version 1.5.0

Released on: 30/06/2019

- Added `conj` method to `pylops.LinearOperator`
- Added `pylops.Kronecker`, `pylops.Roll`, and `pylops.Transpose` operators
- Added `pylops.signalprocessing.Fredholm1` operator
- Added `pylops.optimization.sparsity.SPGL1` and `pylops.optimization.sparsity.SplitBregman` solvers
- Sped up `pylops.signalprocessing.Convolve1D` using `scipy.signal.fftconvolve` for multi-dimensional signals
- Changes in implementation of `pylops.waveeqprocessing.MDC` and `pylops.waveeqprocessing.Marchenko` to take advantage of primitives operators
- Added `epsRL1` option to `pylops.avo.poststack.PoststackInversion` and `pylops.avo.prestack.PrestackInversion` to include TV-regularization terms by means of `pylops.optimization.sparsity.SplitBregman` solver

3.11.15 Version 1.4.0

Released on: 01/05/2019

- Added numba engine to `pylops.Spread` and `pylops.signalprocessing.Radon2D` operators
- Added `pylops.signalprocessing.Radon3D` operator
- Added `pylops.signalprocessing.Sliding2D` and `pylops.signalprocessing.Sliding3D` operators
- Added `pylops.signalprocessing.FFTND` operator
- Added `pylops.signalprocessing.Radon3D` operator
- Added `niter` option to `pylops.LinearOperator.eigs` method
- Added `show` option to `pylops.optimization.sparsity.ISTA` and `pylops.optimization.sparsity.FISTA` solvers
- Added `pylops.waveeqprocessing.seismicinterpolation`, `pylops.waveeqprocessing.waveeqdecomposition` and `pylops.waveeqprocessing.lsm` submodules
- Added tests for engine in various operators
- Added documentation regarding usage of pylops Docker container

3.11.16 Version 1.3.0

Released on: 24/02/2019

- Added `fftw` engine to `pylops.signalprocessing.FFT` operator
- Added `pylops.optimization.sparsity.ISTA` and `pylops.optimization.sparsity.FISTA` sparse solvers
- Added possibility to broadcast (handle multi-dimensional arrays) to `pylops.Diagonal` and `pylops.Restriction` operators
- Added `pylops.signalprocessing.Interp` operator

- Added `pylops.Spread` operator
- Added `pylops.signalprocessing.Radon2D` operator

3.11.17 Version 1.2.0

Released on: 13/01/2019

- Added `pylops.LinearOperator.eigs` and `pylops.LinearOperator.cond` methods to estimate eigenvalues and conditioning number using scipy wrapping of `ARPACK`
- Modified default dtype for all operators to be `float64` (or `complex128`) to be consistent with default dtypes used by numpy (and scipy) for real and complex floating point numbers.
- Added `pylops.Flip` operator
- Added `pylops.Symmetrize` operator
- Added `pylops.Block` operator
- Added `pylops.Regression` operator performing polynomial regression and modified `pylops.LinearRegression` to be a simple wrapper of `pylops.Regression` when `order=1`
- Modified `pylops.MatrixMult` operator to work with both numpy ndarrays and scipy sparse matrices
- Added `pylops.avo.prestack.PrestackInversion` routine
- Added possibility to have a data weight via `Weight` input parameter to `pylops.optimization.leastsquares.NormalEquationsInversion` and `pylops.optimization.leastsquares.RegularizedInversion` solvers
- Added `pylops.optimization.sparsity.IRLS` solver

3.11.18 Version 1.1.0

Released on: 13/12/2018

- Added `pylops.CausalIntegration` operator

3.11.19 Version 1.0.1

Released on: 09/12/2018

- Changed module from `lops` to `pylops` for consistency with library name (and pip install).
- Removed quickplots from utilities and `matplotlib` from requirements of `PyLops`.

3.11.20 Version 1.0.0

Released on: 04/12/2018

- First official release.

3.12 Roadmap

This roadmap is aimed at providing an high-level overview on the bug fixes, improvements and new functionality that are planned for the PyLops library.

Any of the fixes/additions mentioned in the roadmap are directly linked to a *Github Issue* that provides more details onto the reason and initial thoughts for the implementation of such a fix/addition.

Striked tasks have been completed and related github issue closed with more details regarding how this task has been carried out.

3.12.1 Library structure

- Create a child repository and python library called `geolops` (just a suggestion) where geoscience-related operators and examples are moved across, keeping the core `pylops` library very generic and multi-purpose - [Issue #22](#).

3.12.2 Code cleaning

- Change all `np.flatten()` into `np.ravel()` - [Issue #24](#).
- Fix all `if: return ... else: ...` statements to enforce a single return with the same number of outputs - [Issue #26](#).
- Protected attributes and `@property` attributes in linear operator classes? - [Issue #27](#).

3.12.3 Code optimization

- Investigate speed-up given by decorating `_matvec` and `_rmatvec` methods with `numba @jit` and `@stencil` decorators - [Issue #23](#).
- Replace `np.fft.*` routines used in several submodules with double engine, numpy and pyFFTW - [Issue #20](#).

3.12.4 Modules

avo

- Add possibility to choose different damping factors for each elastic parameter to invert for in `pylops.avo.prestack.PrestackInversion` - [Issue #25](#).

basicoperators

- Create Kronecker operator - [Issue #28](#).
- Deal with edges in FirstDerivative and SecondDerivative operators - [Issue #34](#).

optimization

- Sparse solvers - [Issue #44](#).

signalprocessing

- Compare performance in FTT operator of performing `np.swap+np.fft.fft(..., axis=-1)` versus `np.fft.fft(..., axis=chosen)` - [Issue #33](#).
- Add Wavelet operator performing the wavelet transform - [Issue #21](#).
- Fredholm1 operator applying Fredholm integrals of first kind - [Issue #31](#).
- Fredholm2 operators applying Fredholm integrals of second kind - [Issue #31](#).

utils

Nothing so far

waveeqprocessing

- `numpy.matmul` as a way to speed up integral computation (i.e., inner for loop) in MDC operator - [Issue #32](#).
- NMO operator performing NMO modelling - [Issue #29](#).
- WavefieldDecomposition operator performing acoustic wavefield separation by inversion - [Issue #30](#).

3.13 Papers

This section lists various conference abstracts and papers using the PyLops framework:

- Vakalis, S.Chen, D., Yan, M., and Nanzer, J. A., *Image enhancement in active incoherent millimeter-wave imaging*. Passive and Active Millimeter-Wave Imaging XXIV 11745 [link](#) (2021).
- Li, X., Becker, T., Ravasi, M., Robertsson, J., and van Manen D.J., *Closed-aperture unbounded acoustics experimentation using multidimensional deconvolution*. The Journal of the Acoustical Society of America 149 (3), 1813-1828 [link](#) (2021).
- Kuijpers, D., Vasconcelos, I., and Putzky, P., *Reconstructing missing seismic data using Deep Learning*. arXiv, [link](#) (2021).
- Ravasi, M., and Birnie, C., *A Joint Inversion-Segmentation approach to Assisted Seismic Interpretation*. arXiv, [link](#) - [code](#) (2021).
- Haindl, C., Ravasi, M., and Broggini, F., *Handling gaps in acquisition geometries — Improving Marchenko-based imaging using sparsity-promoting inversion and joint inversion of time-lapse data*. Geophysics, 86 (2), S143-S154 [link](#) - [code](#) (2021).
- Ulrich, I. E., Zunino, A., Boehm, C., and Fichtner, A., *Sparsifying regularizations for stochastic sample average minimization in ultrasound computed tomography*. Medical Imaging 2021: Ultrasonic Imaging and Tomography. International Society for Optics and Photonics, [link](#) (2021).
- R Feng, R., Mejer Hansen, T., Grana, D., and Balling, N., *An unsupervised deep-learning method for porosity estimation based on poststack seismic data*. Geophysics, 85 (6), M97-M105. [link](#) (2020).
- Nightingale J. W., Hayes, R.G, et al., *PyAutoLens: Open-Source Strong Gravitational Lensing*, JOSS, [link](#) - [code](#) (2020).
- Zhang, M., *Marchenko Green's functions from compressive sensing acquisition* SEG Technical Program Expanded Abstracts, [link](#) (2020).

- Vargas, D., and Vasconcelos I., *Rayleigh-Marchenko Redatuming Using Scattered Fields in Highly Complex Media*, EAGE Technical Program Expanded Abstracts, [link](#) (2020).
- Ravasi, M., and Vasconcelos I., *Implementation of Large-Scale Integral Operators with Modern HPC Solutions*, EAGE Technical Program Expanded Abstracts, [link](#) - [code](#) (2020).
- Ruan, J., and Vasconcelos I., *Data-and prior-driven sampling and wavefield reconstruction for sparse, irregularly-sampled, higher-order gradient data*, SEG Technical Program Expanded Abstracts, [link](#) - [code](#) (2019).

3.14 Citing

When using `pylops` in scientific publications, please cite the following paper:

- Ravasi, M., and Vasconcelos I., *PyLops—A linear-operator Python library for scalable algebra and optimization*, Software X, (2020). [link](#).

3.15 Contributors

- Matteo Ravasi, [mrava87](#)
- Carlos da Costa, [cako](#)
- Dieter Werthmüller, [prisae](#)
- Tristan van Leeuwen, [TristanvanLeeuwen](#)
- Leonardo Uieda, [leouieda](#)
- Filippo Broggini, [filippo82](#)
- Tyler Hughes, [twhughes](#)
- Lyubov Skopintseva, [lskopintseva](#)
- Francesco Picetti, [fpicetti](#)
- Alan Richardson, [ar4](#)
- BurningKarl, [BurningKarl](#)
- Nick Luiken, [NickLuiken](#)

Bibliography

- [1] <http://www.caam.rice.edu/software/ARPACK/>
- [1] Fomel, S., Liu, Y., “Seislet transform and seislet frame”, *Geophysics*, 75, no. 3, V25-V38. 2010.
- [1] Andersson, F and Robertsson J. “Fast $\tau - p$ transforms by chirp modulation”, *Geophysics*, vol 84, NO.1, pp. A13-A17, 2019.
- [1] Andersson, F and Robertsson J. “Fast $\tau - p$ transforms by chirp modulation”, *Geophysics*, vol 84, NO.1, pp. A13-A17, 2019.
- [1] Wapenaar, K. “Reciprocity properties of one-way propagators”, *Geophysics*, vol. 63, pp. 1795-1798. 1998.
- [1] Wapenaar, K. “Reciprocity properties of one-way propagators”, *Geophysics*, vol. 63, pp. 1795-1798. 1998.
- [1] Wapenaar, K., van der Neut, J., Ruigrok, E., Draganov, D., Hunziker, J., Slob, E., Thorbecke, J., and Snieder, R., “Seismic interferometry by crosscorrelation and by multi-dimensional deconvolution: a systematic comparison”, *Geophysical Journal International*, vol. 185, pp. 1335-1364. 2011.
- [1] Paige, C. C., and Saunders, M. A. “LSQR: An algorithm for sparse linear equations and sparse least squares”, *ACM TOMS*, vol. 8, pp. 43-71, 1982.
- [1] https://en.wikipedia.org/wiki/Iteratively_reweighted_least_squares
- [2] Chartrand, R., and Yin, W. “Iteratively reweighted algorithms for compressive sensing”, *IEEE*. 2008.
- [1] Daubechies, I., Defrise, M., and De Mol, C., “An iterative thresholding algorithm for linear inverse problems with a sparsity constraint”, *Communications on pure and applied mathematics*, vol. 57, pp. 1413-1457. 2004.
- [1] Beck, A., and Teboulle, M., “A Fast Iterative Shrinkage-Thresholding Algorithm for Linear Inverse Problems”, *SIAM Journal on Imaging Sciences*, vol. 2, pp. 183-202. 2009.
- [1] van den Berg E., Friedlander M.P., “Probing the Pareto frontier for basis pursuit solutions”, *SIAM J. on Scientific Computing*, vol. 31(2), pp. 890-912. 2008.
- [1] Goldstein T. and Osher S., “The Split Bregman Method for L1-Regularized Problems”, *SIAM J. on Scientific Computing*, vol. 2(2), pp. 323-343. 2008.
- [1] Wapenaar, K. “Reciprocity properties of one-way propagators”, *Geophysics*, vol. 63, pp. 1795-1798. 1998.
- [1] Wapenaar, K., van der Neut, J., Ruigrok, E., Draganov, D., Hunziker, J., Slob, E., Thorbecke, J., and Snieder, R., “Seismic interferometry by crosscorrelation and by multi-dimensional deconvolution: a systematic comparison”, *Geophysical Journal International*, vol. 185, pp. 1335-1364. 2011.

- [1] Wapenaar, K., Thorbecke, J., Van der Neut, J., Broggini, F., Slob, E., and Snieder, R., “Marchenko imaging”, *Geophysics*, vol. 79, pp. WA39-WA57. 2014.
- [2] van der Neut, J., Vasconcelos, I., and Wapenaar, K. “On Green’s function retrieval by iterative substitution of the coupled Marchenko equations”, *Geophysical Journal International*, vol. 203, pp. 792-813. 2015.
- [1] Hutchinson, M. F. (1990). *A stochastic estimator of the trace of the influence matrix for laplacian smoothing splines*. *Communications in Statistics - Simulation and Computation*, 19(2), 433–450.
- [2] Avron, H., and Toledo, S. (2011). *Randomized algorithms for estimating the trace of an implicit symmetric positive semi-definite matrix*. *Journal of the ACM*, 58(2), 1–34.
- [1] Meyer, R. A., Musco, C., Musco, C., & Woodruff, D. P. (2021). *Hutch++: Optimal Stochastic Trace Estimation*. In *Symposium on Simplicity in Algorithms (SOSA)* (pp. 142–155). Philadelphia, PA: Society for Industrial and Applied Mathematics. [link](#)
- [1] Meyer, R. A., Musco, C., Musco, C., & Woodruff, D. P. (2021). *Hutch++: Optimal Stochastic Trace Estimation*. In *Symposium on Simplicity in Algorithms (SOSA)* (pp. 142–155). Philadelphia, PA: Society for Industrial and Applied Mathematics. [link](#)
- [1] Snieder, R. “A Guided Tour of Mathematical Methods for the
- [1] Van Vliet, L. J., Verbeek, P. W., “Estimators for orientation and anisotropy in digitized images”, *Journal ASCE Imaging Workshop*. 1995.
- [1] Dvorkin et al. *Seismic Reflections of Rock Properties*. Cambridge. 2014.
- [1] https://wiki.seg.org/wiki/AVO_equations
- [1] https://www.subsurfwiki.org/wiki/Fatti_equation
- [1] Xu, Y., and Bancroft, J.C., “Joint AVO analysis of PP and PS seismic data”, *CREWES Report*, vol. 9. 1997.

A

akirichards() (in module *pylops.avo.avo*), 249
 apply() (*pylops.Regression* method), 139
 apply_columns() (*pylops.LinearOperator* method), 119
 apply_multiplepoints() (*pylops.waveeqprocessing.Marchenko* method), 227
 apply_onepoint() (*pylops.waveeqprocessing.Marchenko* method), 227
 approx_zoeppritz_pp() (in module *pylops.avo.avo*), 249
 AVOLinearModelling (class in *pylops.avo.avo*), 197

B

Bilinear (class in *pylops.signalprocessing*), 167
 Block() (in module *pylops*), 147
 BlockDiag (class in *pylops*), 148

C

CausalIntegration (class in *pylops*), 141
 cg() (in module *pylops.optimization.solver*), 201
 cgls() (in module *pylops.optimization.solver*), 202
 ChirpRadon2D (class in *pylops.signalprocessing*), 182
 ChirpRadon3D (class in *pylops.signalprocessing*), 183
 cond() (*pylops.LinearOperator* method), 118
 Conj (class in *pylops*), 152
 conj() (*pylops.LinearOperator* method), 118
 convmtx() (in module *pylops.utils.signalprocessing*), 243
 Convolve1D (class in *pylops.signalprocessing*), 162
 Convolve2D() (in module *pylops.signalprocessing*), 163
 ConvolveND (class in *pylops.signalprocessing*), 165

D

Deghosting() (in module *pylops.waveeqprocessing*), 221

Demigration() (in module *pylops.waveeqprocessing*), 196

Diagonal (class in *pylops*), 128

directwave() (in module *pylops.waveeqprocessing.marchenko*), 242

div() (*pylops.LinearOperator* method), 116

dot() (*pylops.LinearOperator* method), 116

dottest() (in module *pylops.utils*), 233

DWT (class in *pylops.signalprocessing*), 174

DWT2D (class in *pylops.signalprocessing*), 175

E

eigs() (*pylops.LinearOperator* method), 117

F

fatti() (in module *pylops.avo.avo*), 250

FFT() (in module *pylops.signalprocessing*), 169

FFT2D (class in *pylops.signalprocessing*), 170

FFTND (class in *pylops.signalprocessing*), 172

FirstDerivative (class in *pylops*), 155

FirstDirectionalDerivative() (in module *pylops*), 160

FISTA() (in module *pylops.optimization.sparsity*), 213

Flip (class in *pylops*), 131

Fredholm1 (class in *pylops.signalprocessing*), 188

FunctionOperator (class in *pylops*), 121

G

gaussian() (in module *pylops.utils.wavelets*), 246

Gradient() (in module *pylops*), 159

H

HStack (class in *pylops*), 146

hyperbolic2d() (in module *pylops.utils.seismicvents*), 239

hyperbolic3d() (in module *pylops.utils.seismicvents*), 241

I

Identity (class in *pylops*), 125

Imag (class in pylops), 151
 Interp() (in module pylops.signalprocessing), 166
 inv() (pylops.MatrixMult method), 125
 IRLS() (in module pylops.optimization.sparsity), 209
 ISTA() (in module pylops.optimization.sparsity), 212

K

Kronecker (class in pylops), 149

L

Laplacian() (in module pylops), 158
 linear2d() (in module pylops.utils.seismicvents), 238
 linear3d() (in module pylops.utils.seismicvents), 240
 LinearOperator (class in pylops), 115
 LinearRegression() (in module pylops), 140
 LSM (class in pylops.waveeqprocessing), 228
 lsqr() (in module pylops.optimization.solver), 203

M

makeaxis() (in module pylops.utils.seismicvents), 237
 Marchenko (class in pylops.waveeqprocessing), 225
 mask() (pylops.Restriction method), 138
 matmat() (pylops.LinearOperator method), 116
 matrix() (pylops.Diagonal method), 129
 MatrixMult (class in pylops), 124
 matvec() (pylops.LinearOperator method), 115
 MDC() (in module pylops.waveeqprocessing), 193
 MDD() (in module pylops.waveeqprocessing), 224
 MemoizeOperator (class in pylops), 123

N

nonstationary_convmtx() (in module pylops.utils.signalprocessing), 243
 NormalEquationsInversion() (in module pylops.optimization.leastsquares), 205

O

OMP() (in module pylops.optimization.sparsity), 210

P

Pad (class in pylops), 133
 parabolic2d() (in module pylops.utils.seismicvents), 239
 Patch2D() (in module pylops.signalprocessing), 187
 PhaseShift() (in module pylops.waveeqprocessing), 195
 PoststackInversion() (in module pylops.avo.poststack), 230
 PoststackLinearModelling() (in module pylops.avo.poststack), 198

PreconditionedInversion() (in module pylops.optimization.leastsquares), 207
 PressureToVelocity() (in module pylops.waveeqprocessing), 189
 PrestackInversion() (in module pylops.avo.prestack), 231
 PrestackLinearModelling() (in module pylops.avo.prestack), 199
 PrestackWaveletModelling() (in module pylops.avo.prestack), 200
 ps() (in module pylops.avo.avo), 251

R

Radon2D() (in module pylops.signalprocessing), 179
 Radon3D() (in module pylops.signalprocessing), 180
 Real (class in pylops), 150
 Regression (class in pylops), 138
 RegularizedInversion() (in module pylops.optimization.leastsquares), 206
 Restriction (class in pylops), 136
 ricker() (in module pylops.utils.wavelets), 245
 rmatmat() (pylops.LinearOperator method), 116
 rmatvec() (pylops.LinearOperator method), 116
 Roll (class in pylops), 132

S

scalability_test() (in module pylops.utils), 236
 SecondDerivative (class in pylops), 157
 SecondDirectionalDerivative() (in module pylops), 160
 Seislet (class in pylops.signalprocessing), 176
 SeismicInterpolation() (in module pylops.waveeqprocessing), 219
 Shift() (in module pylops.signalprocessing), 173
 Sliding1D() (in module pylops.signalprocessing), 184
 Sliding2D() (in module pylops.signalprocessing), 185
 Sliding3D() (in module pylops.signalprocessing), 186
 slope_estimate() (in module pylops.utils.signalprocessing), 243
 Smoothing1D() (in module pylops), 153
 Smoothing2D() (in module pylops), 154
 solve() (pylops.waveeqprocessing.LSM method), 229
 SPGL1() (in module pylops.optimization.sparsity), 215
 SplitBregman() (in module pylops.optimization.sparsity), 217
 Spread (class in pylops), 142
 Sum (class in pylops), 134
 Symmetrize (class in pylops), 135

T

taper2d() (in module pylops.utils.tapers), 244

[taper3d\(\)](#) (*in module `pylops.utils.tapers`*), [245](#)
[todense\(\)](#) (*`pylops.Diagonal` method*), [129](#)
[todense\(\)](#) (*`pylops.LinearOperator` method*), [117](#)
[toimag\(\)](#) (*`pylops.LinearOperator` method*), [119](#)
[toreal\(\)](#) (*`pylops.LinearOperator` method*), [119](#)
[tosparse\(\)](#) (*`pylops.LinearOperator` method*), [117](#)
[trace\(\)](#) (*`pylops.LinearOperator` method*), [119](#)
[trace_hutchinson\(\)](#) (*in module `pylops.utils`*), [234](#)
[trace_hutchpp\(\)](#) (*in module `pylops.utils`*), [234](#)
[trace_nahutchpp\(\)](#) (*in module `pylops.utils`*), [235](#)
[Transpose](#) (*class in `pylops`*), [130](#)

U

[UpDownComposition2D\(\)](#) (*in module `pylops.waveeqprocessing`*), [191](#)
[UpDownComposition3D\(\)](#) (*in module `pylops.waveeqprocessing`*), [192](#)

V

[VStack](#) (*class in `pylops`*), [144](#)

W

[WavefieldDecomposition\(\)](#) (*in module `pylops.waveeqprocessing`*), [222](#)

Z

[Zero](#) (*class in `pylops`*), [127](#)
[zoeppritz_element\(\)](#) (*in module `pylops.avo.avo`*), [248](#)
[zoeppritz_pp\(\)](#) (*in module `pylops.avo.avo`*), [248](#)
[zoeppritz_scattering\(\)](#) (*in module `pylops.avo.avo`*), [247](#)